

字符从天而降

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript" FCTYPE="dynamicanimation8">
<!--
dynamicanimAttr = "dynamicanimation8"
  animateElements = new Array()
  currentElement = 0
  speed = 0
  stepsZoom = 8
  stepsWord = 8
  stepsFly = 12
  stepsSpiral = 16
  steps = stepsZoom
  step = 0
  outString = ""
  function dynAnimation8()
  {
    var ms = navigator.appVersion.indexOf("MSIE")
    ie4 = (ms>0) && (parseInt(navigator.appVersion.substring(ms+5, ms+6)) >= 4)
    if(!ie4)
    {
      if((navigator.appName == "Netscape") &&
        (parseInt(navigator.appVersion.substring(0, 1)) >= 4))
      {
        for (index=document.layers.length-1; index >= 0; index--)
        {
          layer=document.layers[index]
          if (layer.left==10000)
            layer.left=0
        }
      }
      return
    }
    for (index=document.all.length-1; index >= document.body.sourceIndex; index--)
    {
      el = document.all[index]
      animation = el.getAttribute(dynamicanimAttr, false)
      if(null != animation)
      {
        if(animation == "dropWord" || animation == "flyTopRightWord" || animation ==
"flyBottomRightWord")
        {
```

```

    ih = el.innerHTML
    outString = ""
    i1 = 0
    iend = ih.length
    while(true)
    {
        i2 = startWord(ih, i1)
        if(i2 == -1)
            i2 = iend
        outWord(ih, i1, i2, false, "")
        if(i2 == iend)
            break
        i1 = i2
        i2 = endWord(ih, i1)
        if(i2 == -1)
            i2 = iend
        outWord(ih, i1, i2, true, animation)
        if(i2 == iend)
            break
        i1 = i2
    }
    document.all[index].innerHTML = outString
    document.all[index].style.posLeft = 0
    document.all[index].setAttribute(dynamicanimAttr, null)
}
if(animation == "zoomIn" || animation == "zoomOut")
{
    ih = el.innerHTML
    outString = "<SPAN " + dynamicanimAttr + "=\"" + animation + "\" style=\"position:
relative; left: 10000px;\">"
    outString += ih
    outString += "</SPAN>"
    document.all[index].innerHTML = outString
    document.all[index].style.posLeft = 0
    document.all[index].setAttribute(dynamicanimAttr, null)
}
}
i = 0
for (index=document.body.sourceIndex; index < document.all.length; index++)
{
    el = document.all[index]
    animation = el.getAttribute(dynamicanimAttr, false)
    if (null != animation)

```

```

{
  if(animation == "flyLeft")
  {
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop = 0
  }
  else if(animation == "flyRight")
  {
    el.style.posLeft = 10000-offsetLeft(el)+document.body.offsetWidth
    el.style.posTop = 0
  }
  else if(animation == "flyTop" || animation == "dropWord")
  {
    el.style.posLeft = 0
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
  }
  else if(animation == "flyBottom")
  {
    el.style.posLeft = 0
    el.style.posTop
    =
document.body.scrollTop-offsetTop(el)+document.body.offsetHeight
  }
  else if(animation == "flyTopLeft")
  {
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
  }
  else if(animation == "flyTopRight" || animation == "flyTopRightWord")
  {
    el.style.posLeft = 10000-offsetLeft(el)+document.body.offsetWidth
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
  }
  else if(animation == "flyBottomLeft")
  {
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop
    =
document.body.scrollTop-offsetTop(el)+document.body.offsetHeight
  }
  else if(animation == "flyBottomRight" || animation == "flyBottomRightWord")
  {
    el.style.posLeft = 10000-offsetLeft(el)+document.body.offsetWidth
    el.style.posTop
    =
document.body.scrollTop-offsetTop(el)+document.body.offsetHeight
  }
}

```

```

else if(animation == "spiral")
{
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
}
else if(animation == "zoomIn")
{
    el.style.posLeft = 10000
    el.style.posTop = 0
}
else if(animation == "zoomOut")
{
    el.style.posLeft = 10000
    el.style.posTop = 0
}
else
{
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop = 0
}
el.initLeft = el.style.posLeft
el.initTop = el.style.posTop
animateElements[i++] = el
}
}
window.setTimeout("animate();", speed)
}
function offsetLeft(el)
{
    x = el.offsetLeft
    for (e = el.offsetParent; e; e = e.offsetParent)
        x += e.offsetLeft;
    return x
}
function offsetTop(el)
{
    y = el.offsetTop
    for (e = el.offsetParent; e; e = e.offsetParent)
        y += e.offsetTop;
    return y
}
function startWord(ih, i)
{
    for(tag = false; i < ih.length; i++)

```

```

    {
      c = ih.charAt(i)
      if(c == '<')
        tag = true
      if(!tag)
        return i
      if(c == '>')
        tag = false
    }
    return -1
  }
function endWord(ih, i)
{
  nonSpace = false
  space = false
  while(i < ih.length)
  {
    c = ih.charAt(i)
    if(c != ' ')
      nonSpace = true
    if(nonSpace && c == ' ')
      space = true
    if(c == '<')
      return i
    if(space && c != ' ')
      return i
    i++
  }
  return -1
}
function outWord(ih, i1, i2, dyn, anim)
{
  if(dyn)
    outString += "<SPAN " + dynamicanimAttr + "=\"" + anim + "\" style=\"position: relative;
left: 10000;\">>"
  outString += ih.substring(i1, i2)
  if(dyn)
    outString += "</SPAN>"
}
function animate()
{
  el = animateElements[currentElement]
  animation = el.getAttribute(dynamicanimAttr, false)
  step++
}

```

```

if(animation == "spiral")
{
  steps = stepsSpiral
  v = step/steps
  rf = 1.0 - v
  t = v * 2.0*Math.PI
  rx = Math.max(Math.abs(el.initLeft), 200)
  ry = Math.max(Math.abs(el.initTop), 200)
  el.style.posLeft = Math.ceil(-rf*Math.cos(t)*rx)
  el.style.posTop = Math.ceil(-rf*Math.sin(t)*ry)
}
else if(animation == "zoomIn")
{
  steps = stepsZoom
  el.style.fontSize = Math.ceil(50+50*step/steps) + "%"
  el.style.posLeft = 0
}
else if(animation == "zoomOut")
{
  steps = stepsZoom
  el.style.fontSize = Math.ceil(100+200*(steps-step)/steps) + "%"
  el.style.posLeft = 0
}
else
{
  steps = stepsFly
  if(animation == "dropWord" || animation == "flyTopRightWord" || animation ==
"flyBottomRightWord")
    steps = stepsWord
  dl = el.initLeft / steps
  dt = el.initTop / steps
  el.style.posLeft = el.style.posLeft - dl
  el.style.posTop = el.style.posTop - dt
}
if (step >= steps)
{
  el.style.posLeft = 0
  el.style.posTop = 0
  currentElement++
  step = 0
}
if(currentElement < animateElements.length)
  window.setTimeout("animate();", speed)
}

```

```
//-->
```

```
</SCRIPT>
```

第二步:把如下代码加入<body>区域中(也就是在页面中调用脚本)

```
<p dynamicanimation8="dropWord"
style="position: relative !important; left: 10000 !important" align="center"><font size="3"
color="#ee00FF">很好玩吧!有没有吓一跳?<font size="7"><b><font face="Arial,
Helvetica, sans-serif" color="#FF0000">YES!
</font></b></font></font></p>
```

第三步:把<body>改为

```
<body bgcolor="#ffffff" onload="dynAnimation8()">
```

打字机式字符输出

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
<!--

    var layers = document.layers, style = document.all, both = layers || style, idme=908601;
    if (layers) { layerRef = 'document.layers'; styleRef = ''; } if (style) { layerRef = 'document.all';
styleRef = '.style'; }

    function writeOnText(obj, str) {
        if (layers) with (document[obj]) { document.open(); document.write(str);
document.close(); }
        if (style) eval(obj+'.innerHTML= str');
    }
    //以下是输出的内容,自己修改即可。
    var dispStr = new Array(
        "<font color=red size=3>欢迎光临精彩 JavaScript 世界 ...</font><br><font
color=green size=3>你知道怎样在你的网页中做一个很酷的网页菜单吗?</font><br><font
color=red size=3>你知道怎样让你的网页背景向上或向下移动吗?</font><br><font color=blue
size=3>你知道怎样在你的主页中任意位置显示一个时钟吗?</font><br><font color=red
size=3>你知道怎样在主页中做特效文字吗?</font><br><font color=black size=3>你知道怎样
做一个很 cool 的日历吗?</font>"
    );

    var overMe=0;
```

```

function txtTyper(str, idx, idObj, spObj, clr1, clr2, delay, plysnd) {
    var tmp0 = tmp1 = "", skip = 0;
    if (both && idx <= str.length) {
        if (str.charAt(idx) == '<') { while (str.charAt(idx) != '>') idx++; idx++; }
        if (str.charAt(idx) == '&' && str.charAt(idx+1) != ' ') { while (str.charAt(idx) != ';')
idx++; idx++; }
        tmp0 = str.slice(0,idx);
        tmp1 = str.charAt(idx++);

        if (overMe==0 && plysnd==1) {
            if (navigator.plugins[0]) {
                if (navigator.plugins["LiveAudio"][0].type=="audio/basic" &&
navigator.javaEnabled()) {
                    document.embeds[0].stop();
                    setTimeout("document.embeds[0].play(false)",100); }
                } else if (document.all) {
                    ding.Stop();
                    setTimeout("ding.Run()",100);
                }
                overMe=1;
            } else overMe=0;

            writeOnText(idObj, "<span class="+spObj+"><font
color="+clr1+">" +tmp0+"</font><font color="+clr2+">" +tmp1+"</font></span>");
            setTimeout("txtTyper("+str+", "+idx+", "+idObj+", "+spObj+", "+clr1+", "+clr2+",
"+delay+", "+plysnd+")",delay);
        }
    }

    function init() {
        txtTyper(dispStr[0], 0, 'ttl0', 'ttl1', '#339933', '#99FF33', 50, 0);
    }

    // -->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```
<DIV class=ttl1 id=ttl0><SPAN class=ttl1></SPAN></DIV>
```

第三步:把<body>改为

```
<body bgcolor="#ffffff" onload="onload=init()">
```


滚动显示的 LOGO

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
```

```
<!--
```

```
var scrollerwidth=88
```

```
var scrollerheight=31
```

```
var scrollerbgcolor='white'
```

```
//每个图间暂停 3 秒。
```

```
var pausebetweenimages=3000
```

//边界下面的行，如果希望 logo 都是带连接的，只要加上<a>标签即可。

```
var slideimages=new Array()
```

```
slideimages[0]='<A href=http://bhysj.163.net/ target=_blank><IMG alt= 痴人可不是傻子  
border=0 height=31 src=chir.gif width=88></A>'
```

```
slideimages[1]='<A href=http://wjader.126.com target=_blank><IMG alt= 紫巾苑 border=0  
height=31 src=zjlogo.gif width=88></A>'
```

```
slideimages[2]='<A href=http://hanyu2000.yeah.net/ target=_blank><IMG alt= 碧空流云  
border=0 height=31 src=bhlogo.gif width=88></A>'
```

```
slideimages[3]='<A href=http://tdyn.126.com target=_blank><IMG alt= 天地有你 border=0  
height=31 src=tdyn.gif width=88></A>'
```

```
slideimages[4]='<A href=http://teach.t500.net target=_blank><IMG alt= 教师之家欢迎你  
border=0 height=31 src=home2.gif width=88></A>'
```

```
//尽管填加更多的。
```

```
if (slideimages.length>1)
```

```
  i=2
```

```
  else
```

```
  i=0
```

```
function move1(whichlayer){
```

```
  tlayer=eval(whichlayer)
```

```
  if (tlayer.top>0&&tlayer.top<=5){
```

```
    tlayer.top=0
```

```
    setTimeout("move1(tlayer)",pausebetweenimages)
```

```
    setTimeout("move2(document.main.document.second)",pausebetweenimages)
```

```
  return
```

```
  }
```

```
  if (tlayer.top>=tlayer.document.height*-1){
```

```
    tlayer.top-=5
```

```
    setTimeout("move1(tlayer)",100)
```

```

}
else{
tlayer.top=scrollerheight
tlayer.document.write(slideimages[i])
tlayer.document.close()
if (i==slideimages.length-1)
i=0
else
i++
}
}

function move2(whichlayer){
tlayer2=eval(whichlayer)
if (tlayer2.top>0&&tlayer2.top<=5){
tlayer2.top=0
setTimeout("move2(tlayer2)",pausebetweenimages)
setTimeout("move1(document.main.document.first)",pausebetweenimages)
return
}
if (tlayer2.top>=tlayer2.document.height*-1){
tlayer2.top-=5
setTimeout("move2(tlayer2)",100)
}
else{
tlayer2.top=scrollerheight
tlayer2.document.write(slideimages[i])
tlayer2.document.close()
if (i==slideimages.length-1)
i=0
else
i++
}
}

function move3(whichdiv){
tdiv=eval(whichdiv)
if (tdiv.style.pixelTop>0&&tdiv.style.pixelTop<=5){
tdiv.style.pixelTop=0
setTimeout("move3(tdiv)",pausebetweenimages)
setTimeout("move4(second2)",pausebetweenimages)
return
}
if (tdiv.style.pixelTop>=tdiv.offsetHeight*-1){

```

```

tdiv.style.pixelTop-=5
setTimeout("move3(tdiv)",100)
}
else{
tdiv.style.pixelTop=scrollerheight
tdiv.innerHTML=slideimages[i]
if (i==slideimages.length-1)
i=0
else
i++
}
}

```

```

function move4(whichdiv){
tdiv2=eval(whichdiv)
if (tdiv2.style.pixelTop>0&&tdiv2.style.pixelTop<=5){
tdiv2.style.pixelTop=0
setTimeout("move4(tdiv2)",pausebetweenimages)
setTimeout("move3(first2)",pausebetweenimages)
return
}
if (tdiv2.style.pixelTop>=tdiv2.offsetHeight*-1){
tdiv2.style.pixelTop-=5
setTimeout("move4(second2)",100)
}
else{
tdiv2.style.pixelTop=scrollerheight
tdiv2.innerHTML=slideimages[i]
if (i==slideimages.length-1)
i=0
else
i++
}
}

```

```

function startscroll(){
if (document.all){
move3(first2)
second2.style.top=scrollerheight
}
else if (document.layers){
move1(document.main.document.first)
document.main.document.second.top=scrollerheight+5
document.main.document.second.visibility='show'

```

```
}  
}
```

```
window.onload=startscroll
```

```
//-->
```

```
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<ilayer          id="main"          width=&{ scrollerwidth};          height=&{ scrollerheight};  
bgcolor=&{ scrollerbgcolor};>  
<layer id="first" left=0 top=1 width=&{ scrollerwidth};>  
<script language="JavaScript1.2">  
if (document.layers)  
document.write(slideimages[0])  
</script>  
</layer>  
<layer id="second" left=0 top=0 width=&{ scrollerwidth}; visibility=hide>  
<script language="JavaScript1.2">  
if (document.layers)  
document.write(slideimages[1])  
</script>  
</layer>  
</ilayer>  
<p>  
<SCRIPT language="JavaScript">  
<!--  
if (document.all){  
document.writeln('<span                                id="main2"  
style="position:relative;width:'+scrollerwidth+';height:'+scrollerheight+';overflow:hidden;background-color:'+scrollerbgcolor+'">')  
document.writeln('<div  
style="position:absolute;width:'+scrollerwidth+';height:'+scrollerheight+';clip:rect(0  
' +scrollerwidth+' '+scrollerheight+' 0);left:0;top:0">')  
document.writeln('<div                                id="first2"  
style="position:absolute;width:'+scrollerwidth+';left:0;top:1;">')  
document.write(slideimages[0])  
document.writeln('</div>')  
document.writeln('<div                                id="second2"  
style="position:absolute;width:'+scrollerwidth+';left:0;top:0">')
```

```
document.write(slideimages[1])
document.writeln('</div>')
document.writeln('</div>')
document.writeln('</span>')
}
//-->
```

```
</SCRIPT>
```

文本自动滚屏

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function selectScroller(n) {
optlist = document.scrollform.scroller;
optlist[optlist.length] = new Option(optlist[0].text, "", false, false);
optlist[0] = null;
optlist.selectedIndex = -1;
n = (n + 1) % optlist.length;
// change the speed below: 1000 = 1 second.
setTimeout("selectScroller("+n+")",2000);
}
// End -->
</script>
```

第二步:把如下代码加入<body>区域中

```
<form name="scrollform">
<select name="scroller" size=8>
<option>This select option list will
<option>scroll text by copying
<option>the top line to the bottom
<option>line before deleting the
<option>top line. This moves the
<option>options up one line and
<option>gives the impression of
<option>scrolling.
<option>
<option>You can leave as many
<option>blank lines as you feel
<option>necessary to give the
<option>look of begining and
```

```
<option>ending.  
<option>  
<option>This script was written  
<option>in response to those  
<option>who wanted a news  
<option>scroller to work within  
<option>a table's cell and for  
<option>those who want old  
<option>browsers to also see  
<option>a scroller on the page.  
<option>  
<option>This select option list will  
<option>scroll text by copying  
<option>the top line to the bottom  
<option>line before deleting the  
<option>top line. This moves the  
<option>options up one line and  
<option>gives the impression of  
<option>scrolling.  
<option>  
<option>You can leave as many  
<option>blank lines as you feel  
<option>necessary to give the  
<option>look of beginning and  
<option>ending.  
<option>  
<option>This script was written  
<option>in response to those  
<option>who wanted a news  
<option>scroller to work within  
<option>a table's cell and for  
<option>those who want old  
<option>browsers to also see  
<option>a scroller on the page.  
<option>  
<option>yobo42@hotmail.com  
</select>  
</form>
```

第三步:把<body>改为

```
<BODY OnLoad="selectScroller(0);">
```

在文本框中控制别人输入字数

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
maxLen = 130; // max number of characters allowed

function checkMaxInput(form) {
if (form.message.value.length > maxLen) // if too long... trim it!
form.message.value = form.message.value.substring(0, maxLen);
// otherwise, update 'characters left' counter
else form.remLen.value = maxLen - form.message.value.length;
}
// End -->
</script>
```

第二步:把如下代码加入<body>区域中

```
<form name=myform action="YOUR-SCRIPT.CGI">
<font size="1" face="arial, helvetica, sans-serif"> ( You may enter up to 125 characters. )<br>
<textarea name=message wrap=physical cols=28 rows=4
onKeyDown="checkMaxInput(this.form)" onKeyUp="checkMaxInput(this.form)"></textarea>
<br>
<input readonly type=text name=remLen size=3 maxlength=3 value="130"> characters
left</font>
</form>
```

文本上下弹跳

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
<!--

done = 0;
step = 4

function anim(yp,yk)
{
if(document.layers) document.layers["napis"].top=yp;
else document.all["napis"].style.top=yp;

if(yp>yk) step = -4
if(yp<60) step = 4

setTimeout('anim('+yp+step+')','+yk+')', 10);
}
```

```

function start()
{
  if(done) return
  done = 1;

  if(navigator.appName=="Netscape") {
    document.napis.left=innerWidth/2 - 145;
    anim(60,innerHeight - 60)
  }
  else {
    napis.style.left=280;
    anim(60,document.body.offsetHeight - 60)
  }
}

}

</script>
<div id="napis"
style="position: absolute; top: 159px; width: 400px; height: 78px; left: 215px"><font
size="5"><b>上下不停弹跳的文本</b></font></div>
<script language="JavaScript">
<!--
  setTimeout('start()',10);
</script>

```

特酷消隐字体

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
```

```
<!--
```

```
var thissize=20
```

```
var textfont="隶书"
```

```
var textcolor= new Array()
```

```
textcolor[0]="000000"
```

```
textcolor[1]="000000"
```

```
textcolor[2]="000000"
```

```
textcolor[3]="111111"
```

```
textcolor[4]="222222"
```

```
textcolor[5]="333333"
```



```
textcolor[6]="444444"  
textcolor[7]="555555"  
textcolor[8]="666666"  
textcolor[9]="777777"  
textcolor[10]="888888"  
textcolor[11]="999999"  
textcolor[12]="aaaaaa"  
textcolor[13]="bbbbbb"  
textcolor[14]="cccccc"  
textcolor[15]="dddddd"  
textcolor[16]="eeeeee"  
textcolor[17]="ffffff"  
textcolor[18]="ffffff"
```

```
var message = new Array()  
message[0]="欢迎光临超级 JAVA 酷"  
message[1]="请多停留一会"  
message[2]="你会有更多的收获"  
message[3]="请再次光临"  
i_message=0
```

```
var i_strength=0  
var i_message=0  
var timer
```

```
function glowtext() {  
if(document.all) {  
if (i_strength <=17) {  
glowdiv.innerHTML=message[i_message]  
document.all.glowdiv.style.filter="glow(color="+textcolor[i_strength]+", strength=4)"  
i_strength++  
timer=setTimeout("glowtext()",100)  
}  
else {  
clearTimeout(timer)  
setTimeout("deglowtext()",1500)  
}  
}  
}
```

```
function deglowtext() {  
if(document.all) {  
if (i_strength >=0) {  
glowdiv.innerHTML=message[i_message]
```

```

document.all.glowdiv.style.filter="glow(color="+textcolor[i_strength]+", strength=4)"
i_strength--
timer=setTimeout("deglowtext()",100)
}
else {
clearTimeout(timer)
i_message++
if (i_message>=message.length) {i_message=0}
i_strength=0
intermezzo()
}
}
}

function intermezzo() {
glowdiv.innerHTML=""
setTimeout("glowtext()",1000)
}

//-->

</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<div id="glowdiv" style="position:absolute;visibility:visible;width:600px;text-align:center;
top:185px;left:70px;font-family:隶书;font-size:30pt;color:000000"></div>

```

第三步:把<body>区中内容改为

```

<body bgcolor="#ffffff" onLoad="glowtext()">

```

文本框栏目介绍

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var messages = new Array(6);
messages[0] = "";
messages[1] = "Have you ever seen anything like this before?";
messages[2] = "Can you imagine how you could use it on your site?";
messages[3] = "It's great for sharing lots of information.";
messages[4] = "And doesn't take up much space! ";
messages[5] = "So, get the code and put it on your site!";
function messageReveal() {

```

```

var messageindex = document.messageForm.messagePick.selectedIndex
document.messageForm.messageField.value = messages[messageindex];
}
// End -->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<form name="messageForm">
<select name="messagePick" OnChange="messageReveal()">
<option value="0">The Menu Message
<option>Seen this before?
<option>Possible uses?
<option>Shares Information
<option>Saves space
<option>Get the code!
</select>
<br><p>
<textarea name="messageField" rows=6 cols=50 wrap=virtual></textarea>
</form>

```

旋转变换文字

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT language=javascript>
//luxiaoqing
Phrase="欢迎你的光临"
Balises=""
Taille=40;
Midx=100;
Decal=0.5;
Nb=Phrase.length;
y=-10000;
for (x=0;x<Nb;x++){
  Balises=Balises + '<DIV Id=L' + x + ' STYLE="width:3;font-family: Courier
New;font-weight:bold;position:absolute;top:40;left:50;z-index:0">' + Phrase.charAt(x) + '</DIV>'
}
document.write (Balises);
Time=window.setInterval("Alors()",10);
Alpha=5;
I_Alpha=0.05;

function Alors(){
  Alpha=Alpha-I_Alpha;

```

```
for (x=0;x<Nb;x++){
    Alpha1=Alpha+Decal*x;
    Cosine=Math.cos(Alpha1);
    Ob=document.all("L"+x);
    Ob.style.posLeft=Midx+100*Math.sin(Alpha1)+50;
    Ob.style.zIndex=20*Cosine;
    Ob.style.fontSize=Taille+25*Cosine;
    Ob.style.color="rgb("+ (27+Cosine*80+50) + ","+ (127+Cosine*80+50) + ",0)";
}
}
```

</SCRIPT>

特酷的文本输出

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style>
```

```
<!--
```

```
@media screen{
```

```
    fx\;TYPEWRITER { behavior:url(lu.htc);
```

```
        height: 15pt;
```

```
    }
```

```
}
```

```
td { font-size: 9pt}
```

```
.heading1 { font-family: "Arial", "Helvetica", "sans-serif"; font-size: 18pt; color: #990099}
```

```
-->
```

```
</style>
```

第二步:把如下代码加入<body>区域中

```
<p><fx:typewriter speed="100"> 欢迎光临怀柔网网站，请多提意见。  
http://www.hrwn.cnE-mail:webmaster@hrwn.cn</fx:typewriter></p>
```

第三步:建立一个名为 lu.htc 的文件，内容如下。(注意要在文本窗口中编辑好!)

```
<EVENT id=typewriter name=typewriter />
```

```
<ATTACH event=onload for=window handler=startTyping />
```

```
<method name=typeIt />
```

```
<property name=speed />
```

```
<script language="javascript">
```

```
// 声明变量
```

```
var counter=0;
```

```
var buffer1;
```

```
var buffer2;
```

```
var bufLength;
```

```
var typing;
```

```
if (!speed) { var speed=100}
```

```
function startTyping(){
```

```
buffer1 = element.innerText;

element.innerText="";

buffer2 = "";

bufLength = buffer1.length;

typing = window.setInterval(uniqueID+".typeIt()",speed);

}

function typeIt(){

    buffer2 = buffer2 + buffer1.substring(counter,counter+1);

    element.innerText = buffer2;

    counter = counter + 1;

    if (counter == bufLength){clearInterval(typing)}

}

</script>
```

页面自动滚屏效果

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
```

```
<!--
```

```
function scrollit(){
for (I=1; I<=500; I++){
parent.scroll(1,I)
}
}
```

```
//-->
```

</SCRIPT>

第二步:把如下代码加入<body>区域中

```
<div id="glowdiv" style="position:absolute;visibility:visible;width:600px;text-align:center;
top:185px;left:70px;font-family:隶书;font-size:30pt;color:000000"></div>
```

第三步:把<body>区中内容改为

```
<body bgcolor="#ffffff" onload="scrollit()">
```

炽热的文字特效 (IE)

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style>
```

```
<!--
```

```
#glowtext{
```

```
filter:glow(color=red,strength=2);
```

```
width:100%;
```

```
}
```

```
-->
```

```
</style>
```

```
<script language="JavaScript1.2">
```

```
function glowit(which){
```

```
if (document.all.glowtext[which].filters[0].strength==2)
```

```
document.all.glowtext[which].filters[0].strength=1
```

```
else
```

```
document.all.glowtext[which].filters[0].strength=2
```

```
}

function glowit2(which){

if (document.all.glowtext.filters[0].strength==2)

document.all.glowtext.filters[0].strength=1

else

document.all.glowtext.filters[0].strength=2

}

function startglowing(){

if (document.all.glowtext&&glowtext.length){

for (i=0;i<glowtext.length;i++)

eval('setInterval("glowit('+i+')",150)')

}

else if (glowtext)

setInterval("glowit2(0)",150)

}

if (document.all)

window.onload=startglowing

</script>
```

第二步:把如下代码加入<body>区域中

```
<span id="glowtext">任意文字</span>
```

鼠标响应文字变色

脚本说明:

把如下代码加入<body>区域中

```
<font face="arial" size=3 onMouseOver="this.style.backgroundColor = 'red';"  
onMouseOut="this.style.backgroundColor = 'yellow';">欢迎光临怀柔网网站</font>
```

隐藏显示字符脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">  
<!--  
  
//if explorer (4.x)  
  
if (document.all) {  
  
    layerRef='document.all'  
  
    styleRef='.style.'  
  
}  
  
//else if netscape (4.x)  
  
else if (document.layers) {  
  
    layerRef='document.layers'  
  
    styleRef='.'  
  
}  
  
else{  
  
    alert("你使用的浏览器可能看不到效果。")  
  
}
```

```
function show(){  
  
    eval(layerRef+["divTest"]+styleRef+'visibility="visible"')  
  
}  
  
function hide(){  
  
    eval(layerRef+["divTest"]+styleRef+'visibility="hidden"')  
  
}  
  
//-->
```

</SCRIPT>

第二步:把如下代码加入<body>区域中

```
<p align="center"><br>
```

```
    <a href="javascript:hide('divText.html')"> 隐 藏 字 符 </a> <a  
href="javascript:show('divText.html')">显示字符</a>
```

```
<p align="center">
```

```
<div id="divTest" style="position:absolute; left:168px; width:440px; height:32px; top:210px;  
visibility: hidden">
```

```
    <p align="center">对不起,代码不能随便看的,如果你真的想要,请与我联系!</a></p>
```

鼠标响应图片变化

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="Javascript">
```

```
img1=new Array(2);
```

```
img1[0]=new Image; img1[0].src="image/img-01.jpg";  
img1[1]=new Image; img1[1].src="image/img-02.jpg";  
img1[2]=new Image; img1[2].src="image/img-03.jpg";
```

```
img2=new Array(2);  
img2[0]=new Image; img2[0].src="image/img-01-a.jpg";  
img2[1]=new Image; img2[1].src="image/img-02-a.jpg";  
img2[2]=new Image; img2[2].src="image/img-03-a.jpg";
```

```
function show(n)  
{  
if (n==0) document.P0.src=img2[0].src;  
if (n==1) document.P1.src=img2[1].src;  
if (n==2) document.P2.src=img2[2].src;  
  
}
```

```
function hide(n)  
{  
if (n==0) document.P0.src=img1[0].src;  
if (n==1) document.P1.src=img1[1].src;  
if (n==2) document.P2.src=img1[2].src;  
  
}
```

```
</SCRIPT>
```

```
<A HREF="cool/music_cool.htm" ONMOUSEOVER="show(0);"  
ONMOUSEOUT="hide(0);"><IMG SRC="image/img-01.jpg" ALT="给我留言" NAME="P0"  
BORDER=0 HEIGHT=33 WIDTH=100></a><br>  
<A HREF="cool/music_cool.htm" ONMOUSEOVER="show(1);"  
ONMOUSEOUT="hide(1);"><IMG SRC="image/img-02.jpg" ALT="给我留言" NAME="P1"  
BORDER=0 HEIGHT=33 WIDTH=100></a><br>  
<A HREF="cool/music_cool.htm" ONMOUSEOVER="show(2);"  
ONMOUSEOUT="hide(2);"><IMG SRC="image/img-03.jpg" ALT="给我留言" NAME="P2"  
BORDER=0 HEIGHT=33 WIDTH=100></a><br>
```

星星满天闪烁

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language=javascript1.2>
<!--
hexa = new Array(16);
for(var i = 0; i < 10; i++) hexa[i] = i;
hexa[10]="a";
hexa[11]="b";
hexa[12]="c";
hexa[13]="d";
hexa[14]="e";
hexa[15]="f";
function hex(i)
{
if (i < 0) return "00";
else if (i > 255) return "ff";
else return "" + hexa[Math.floor(i/16)] + hexa[i%16];
}
function setbgColor(r, g, b)
{
var hr = hex(r);
var hg = hex(g);
var hb = hex(b);
document.bgColor = "#"+hr+hg+hb;
}
function fade(sr, sg, sb, er, eg, eb, step)
{
for(var i = 0; i <= step; i++)
{
setbgColor( Math.floor(sr * ((step-i)/step) + er * (i/step)),
Math.floor(sg * ((step-i)/step) + eg * (i/step)), Math.floor(sb *
((step-i)/step) + eb * (i/step)));
}
}

//-->
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<SCRIPT language=javascript1.2>
<!--
for(i=1;i<=10;i++)
{
```

```

document.write("<div
                                                    id=\"star\"+i+\"\"
style=\"position:absolute;top:80%;left:\"+(Math.floor(Math.random()*5)+9*(i-1))+\"%;width:21;he
ight:21;visibility:hidden;\"><dd><img
                                                    src=\"star.gif\"
                                                    WIDTH=\"21\"
HEIGHT=\"21\"></dd></div>");
}
function randommove()
{
    for(i=1;i<=10;i++)
        eval("star"+i+".style.top=get_top()");
}

function get_top()
{
    var t,t2;
    t=Math.floor(Math.random()*380);
    t2=t.toString()+"px";
    return(t2);
}
function set_visible()
{
    for(i=1;i<=10;i++)
        eval("star"+i+".style.visibility=\"visible\"");
    banner.style.visibility="visible";
    friends.style.visibility="visible";
    high(pic);
}

function bar_show()
{
    bar.style.visibility="visible";
}

function start_it()
{
    fade(255,255,255, 0,0,0, 50);
    setInterval("randommove()",1000);
    set_visible();
    setTimeout("bar_show()",2000);
}

function end_it()
{
    banner.style.visibility="hidden";
    friends.style.visibility="hidden";
    pic.style.visibility="hidden";
    fade(0,0,0,255,255,255,10);
}

```

```
}  
-->  
</SCRIPT>
```

第三步:把<body>改为

```
<BODY aLink=#ffffff bgColor=#ffffff link=#ffffff onload=start_it()  
onunload=end_it() text=#ffffff topMargin=0 vLink=#ffffff>
```

打开页面颜色渐变

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT Language="JavaScript">  
<!-- 屏幕变色程序 -->  
function BgColor()  
{  
var x = 0, step = 1  
while( x <= 0xffffff)  
    {  
document.bgColor = x  
x += step  
step <<= 8  
if( step >= 0x1000000) step = 1  
}  
}  
BgColor()  
</Script>
```

第二步:把<body>中的内容改为:

```
<body bgcolor="#ffffff" onLoad="BgColor()">
```

页面打开特效

脚本说明:

把如下代码加入<body>区域中:

```
<script language=JavaScript>  
var mylocation="time3.htm"  
var winheight=100  
var winsize=100  
var x=5  
function go(){  
win2=window.open("", "", "scrollbars")  
win2.location=mylocation  
if (!document.layers&&!document.all){
```

```

win2.location=mylocation
return}
win2.resizeTo(100,100)
win2.moveTo(0,0)
go2()}
function go2(){
if (winheight>=screen.availHeight-3)
x=0
win2.resizeBy(5,x)
winheight+=5
winsize+=5
if (winsize>=screen.width-5){
win2.location=mylocation
winheight=100
winsize=100
x=5
return}
setTimeout("go2()",50)
}
</script>
<a href="javascript:go()">打特殊页面</a>

```

英文名字变日文

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Original: Momoko Sakura -->
```

```
<!-- Modified By: Ronnie T. Moore, Editor -->
```

```
<!-- This script and many more are available free online at -->
```

```
<!-- The JavaScript Source!! http://javascript.internet.com -->
```

```
<!-- Begin
```

```
function isvowel(v) {
```

```
if ((v == "a") || (v == "e") || (v == "i") || (v == "o") || (v == "u")) {
```

```
return true;
```

```
}
```

```
else {
```

```
return false;
```

```
}
```

```
}
```

```
function toJapanese(inp) {
```

```
name1 = inp;
```

```
otp = "";
```

```

cnt = 0;
k = "";
l = "";
inp = inp.toLowerCase();
while (cnt <= inp.length - 1) {
k = inp.charAt(cnt);
if ((cnt + 1) > (inp.length - 1)) {
l = "u";
}
else {
l = inp.charAt(cnt+1);
}
if ((k == " ") || (k == "-") || (k == "")) {
otp = otp + k;
cnt += 1;
}
if ((l == "y") && (!isvowel(k))) {
l = "i";
}
if (k == "x") {
if (cnt == 0) {
k = "z";
}
else {
k = "k";
}
}
if (k == "g") {
if ((l == "e") || (l == "i") || (l == "y")) {
k = "j";
}
else {
if (isvowel(l)) {
otp = otp + k + l;
cnt += 2;
}
else {
otp = otp + k + "u";
cnt += 1;
}
}
}
if (k == "j") {
if ((l == "a") || (l == "u") || (l == "o")) {

```



```

otp = otp + k + 1;
cnt +=2;
}
if ((l == "e") || (l == "i")) {
otp = otp + "ji";
cnt += 2;
}
}
if (k == "y") {
if ((l == "a") || (l == "u") || (l == "o")) {
otp = otp + k + 1;
cnt += 2;
}
else {
k = "i";
}
}
if (k == "m") {
if (isvowel(l)) {
otp = otp + k + 1;
cnt += 2;
}
else {
if ((l == "b") || (l == "m") || (l == "p")) {
otp = otp + "n";
cnt += 1;
}
else {
otp = otp + "mu";
cnt += 1;
}
}
}
if (isvowel(k) || ((k == "n") && (!isvowel(l)))) {
otp = otp + k;
cnt = cnt + 1;
}
if (k == "q") {
k = "k";
}
if (k == "v") {
k = "b";
}
if (k == "l") {

```

```

k = "r";}
if (k == "c") {
if (l == "h") {
otp = otp + "chi";
cnt += 3;
}
else {
if ((l == "e") || (l == "i") || (l == "y")) {
k = "s";
}
else {
k = "k";
}
}
}
if (k == "w") {
if ((l == "a") || (l == "o")) {
otp = otp + k + l;
cnt += 2;
}
else {
if ((l == "i") || (l == "e")) {
otp = otp + "u" + l;
cnt += 2;
}
else {
k = "b";
}
}
}
if ((k == "b") || (k == "k") || (k == "r")) {
if (isvowel(l)) {
otp = otp + k + l;
cnt += 2;
}
else {
otp = otp + k + "u";
cnt += 1;
}
}
if (k == "d") {
if ((l == "i") || (l == "a") || (l == "e")) {
otp = otp + "de";
cnt += 2;
}
}

```

```

}
if ((l == "u" || l == "o")) {
    otp = otp + "do";
    cnt += 2;
}
if (!isvowel(l)) {
    otp = otp + "de";
    cnt += 1;
}
}
if (k == "f") {
    otp = otp + "fu";
    cnt += 1;
    if (isvowel(l)) {
        cnt += 1;
    }
}
if (k == "h") {
    if (l == "u") {
        otp = otp + "fu";
        cnt += 2;
    }
    else {
        if (isvowel(l)) {
            otp = otp + k + l;
            cnt += 2;
        }
        else {
            otp = otp + "fu";
            cnt += 1;
        }
    }
}
if (k == "z") {
    if (l == "i") {
        k = "j";
    }
    else {
        if (isvowel(l)) {
            otp = otp + k + l;
            cnt += 2;
        }
        else {
            otp = otp + "zu";

```

```

cnt += 1;
    }
}
}
if (k == "n") {
if (isvowel(l)) {
otp = otp + k + 1;
cnt += 2;
    }
}
if (k == "p") {
if (l == "h") {
otp = otp + "fu";
cnt += 2;
    }
if (isvowel(l)) {
otp = otp + k + 1;
cnt += 2;
    }
else {
otp = otp + "pu";
cnt += 1;
    }
}
if (k == "s") {
if ((l == "i") || (l == "h")) {
otp = otp + "shi";
cnt += 2;
if (l == "h") {
cnt += 1;
    }
}
else {
if (isvowel(l)) {
otp = otp + k + 1;
cnt += 2;
    }
else {
otp = otp + "su";
cnt += 1;
    }
}
}
if (k == "t") {

```

```

if ((l == "a" || l == "e" || l == "o")) {
otp = otp + k + l;
cnt += 2;
}
if ((l == "u" || (!isvowel(l) && !(l == "h")))) {
otp = otp + "tsu";
cnt += 1;
if (l == "u") {
cnt += 1;
}
if ((l == "s") && (inp.charAt(cnt + 1) == "u")) {
cnt += 2;
}
}
if (l == "i") {
otp = otp + "chi";
cnt += 2;
}
if (l == "h") {
otp = otp + "fu";
cnt += 3;
}
}
name2 = "" + otp.charAt(0).toUpperCase();
for (j = 1; j <= otp.length - 1; j++) {
name2 += otp.charAt(j);
}
alert(name1 + " is pronounced in Japanese as: \"" + name2 + "\"");
}
// End -->
</script>

```

第二步:把如下代码加入<body>区域中

```

<form>
Your Name: <input type=text name="personname" size=15>
<input type=button value="Show Japanese Name!"
onClick="toJapanese(this.form.personname.value);">
</form>

```

页面上下滚动

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style type="text/css">
#item {position:absolute; visibility:hidden; left:0px}
</style>
```

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Begin
var isNS=(document.layers);
var _all=(isNS)? " : 'all.' ;
var _style=(isNS)? " : '.style' ;
var _visible=(isNS)? 'show' : 'visible';
var w_x, w_y, item, okscroll=false, godown;
function init(){
item=eval('document.'+_all+'item'+_style);
getwindowsize();
item.visibility=_visible;
scrollpage();
}
function getwindowsize() {
w_x=(isNS)? window.innerWidth-5 : document.body.clientWidth;
w_y=(isNS)? window.innerHeight : document.body.clientHeight;
(isNS)? item.clip.width=42: item.width=42;
(isNS)? item.clip.height=20 : item.height=20;
moveitem();
}
function resizeNS() {
setTimeout('document.location.reload()',400);
}
function moveitem() {
if (isNS) {
item.moveTo((pageXOffset+w_x-70),(w_y+pageYOffset-50))
}else{
item.pixelLeft=document.body.scrollLeft+w_x-70;
item.pixelTop=w_y+document.body.scrollTop-50;
}
}
window.onload=init;
(isNS) ? window.onresize=resizeNS : window.onresize=getwindowsize ;
function scrollpage() {
status = "";
if (okscroll) {
if (godown) {
```

```

(isNS)? window.scrollBy(0,4) : window.scrollBy(0,4) ;
} else {
(isNS)? window.scrollBy(0,-4) : window.scrollBy(0,-4) ;
}
}
moveitem();
setTimeout('scrollpage()', 40);
}
// End -->
</script>

```

第二步:把如下代码加入<body>区域中

```

<div id="item">
<a href="javascript:void(0)" onMouseover="okscroll=true; godown=true"
onMouseout="okscroll=false"></a><a
href="javascript:void(0)"
onMouseover="okscroll=true; godown=false" onMouseout="okscroll=false"></a>
</div>

```

页面缩小特效

脚本说明：

第一步:把如下代码加入<head>区域中:

```

<style>
<!--
.intro{
position:absolute;
left:0;
top:0;
layer-background-color:white;
background-color:white;
border:0.1px solid white
}
-->
</style>

```

第二步:把<body>中加入如下代码：

<!--如下代码必须紧接着<body>写！-->

```
<div id="i1" class="intro"></div>
<script language="JavaScript1.2">
```

```
//尝试改变速度
```

```
var speed=5
if (document.layers){
var reference=window.innerWidth/window.innerHeight
var temp=eval("document.i1.clip")
temp.left=temp.top=0
temp.right=window.innerWidth
temp.bottom=window.innerHeight
}
else if (document.all){
var reference=document.body.clientWidth/document.body.clientHeight
var rightclip,leftclip,topclip,bottomclip
var temp=document.all.i1.style
topclip=leftclip=0
rightclip=temp.width=document.body.clientWidth
bottomclip=temp.height=document.body.clientHeight
}
```

```
function doit(){
window.scrollTo(0,0)
if (document.layers){
if (temp.left>window.innerWidth/2)
clearInterval(stopit)
temp.left+=reference*speed
temp.top+=speed
temp.right-=reference*speed
temp.bottom-=speed
}
else if (document.all){
if (leftclip>document.body.clientWidth/2)
clearInterval(stopit)
temp.clip="rect( "+topclip+" "+rightclip+" "+bottomclip+" "+leftclip+" )"
leftclip+=reference*speed
topclip+=speed
rightclip-=reference*speed
bottomclip-=speed
}
}
stopit=setInterval("doit()",100)
```


</script>

左右页面分开

```
<script
language="JavaScript1.2">

var speed=20
var temp=new Array()
var temp2=new Array()
if (document.layers){
for (i=1;i<=2;i++){
temp[i]=eval("document.i"+i+".clip")
temp2[i]=eval("document.i"+i)
temp[i].width=window.innerWidth/2
temp[i].height=window.innerHeight
temp2[i].left=(i-1)*temp[i].width
}
}
else if (document.all){
var clipright=document.body.clientWidth/2,clipleft=0
for (i=1;i<=2;i++){
temp[i]=eval("document.all.i"+i+".style")
temp[i].width=document.body.clientWidth/2
temp[i].height=document.body.offsetHeight
temp[i].left=(i-1)*parseInt(temp[i].width)
}
}

function openit(){
window.scrollTo(0,0)
if (document.layers){
temp[1].right-=speed
temp[2].left+=speed
if (temp[2].left>window.innerWidth/2)
clearInterval(stopit)
}
else if (document.all){
clipright-=speed
temp[1].clip="rect(0 "+clipright+" auto 0)"
clipleft+=speed
temp[2].clip="rect(0 auto auto "+clipleft+)"
if (clipright<=0)
```

```
clearInterval(stopit)
}
}

function gogo(){
stopit=setInterval("openit()",100)
}
gogo()

</script>
```

图片满天飞舞

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="JavaScript">
<!--//
```

//设置下面一些参数，小球移动速度 1-50，数值大速度快；

```
var ballWidth = 40;
```

```
var ballHeight = 40;
```

```
var BallSpeed = 10;
```

```
var maxBallSpeed = 50;
```

```
var xMax;
```

```
var yMax;
```

```
var xPos = 0;
```

```
var yPos = 0;
```

```
var xDir = 'right'; //水平方向向右移动
```

```
var yDir = 'down'; //垂直方向向下移动
```

```
var superbballRunning = true;
```

```
var tempBallSpeed;
```

```
var currentBallSrc;
```

```
var newXDir;
```

```
var newYDir;
```

```
function initializeBall() {
```

```
    if (document.all) {
```

```
        xMax = document.body.clientWidth
```

```
        yMax = document.body.clientHeight
```

```
        document.all("superball").style.visibility = "visible";
```

```
    }
```

```
    else if (document.layers) {
```

```
        xMax = window.innerWidth;
```

```
        yMax = window.innerHeight;
        document.layers["superball"].visibility = "show";
    }
    setTimeout('moveBall()',400);
}
```

```
function moveBall() {
    if (superballRunning == true) {
        calculatePosition();
        if (document.all) {
            document.all("superball").style.left = xPos + document.body.scrollLeft;
            document.all("superball").style.top = yPos + document.body.scrollTop;
        }
        else if (document.layers) {
            document.layers["superball"].left = xPos + pageXOffset;
            document.layers["superball"].top = yPos + pageYOffset;
        }
        setTimeout('moveBall()',30);
    }
}
```

```
function calculatePosition() {
    if (xDir == "right") {
        if (xPos > (xMax - ballWidth - BallSpeed)) {
            xDir = "left";
        }
    }
    else if (xDir == "left") {
        if (xPos < (0 + BallSpeed)) {
            xDir = "right";
        }
    }
    if (yDir == "down") {
        if (yPos > (yMax - ballHeight - BallSpeed)) {
            yDir = "up";
        }
    }
    else if (yDir == "up") {
        if (yPos < (0 + BallSpeed)) {
            yDir = "down";
        }
    }
    if (xDir == "right") {
        xPos = xPos + BallSpeed;
```

```

    }
    else if (xDir == "left") {
        xPos = xPos - BallSpeed;
    }
    else {
        xPos = xPos;
    }
    if (yDir == "down") {
        yPos = yPos + BallSpeed;
    }
    else if (yDir == "up") {
        yPos = yPos - BallSpeed;
    }
    else {
        yPos = yPos;
    }
}

if (document.all||document.layers)
window.onload = initializeBall;
window.onresize = new Function("window.location.reload()");

// -->
</script>
<style type="text/css">

#superball {
position:absolute;
left:0;
top:0;
visibility:hide;
visibility:hidden;
width:40;
height:40;
}

</style>

```

第二步:把如下代码加入区域中 :

```

<span id="superball"><a href="http://www.javascript2000.com"></a></span>

```

页面掉下去

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- This script and many more are available free online at -->
<!-- The JavaScript Source!! http://www.javascript2000.com -->

<!-- Begin
function moveWin() {
for (var i = 1; i < 1001; i++)
window.moveBy(1, 1);
window.moveBy(-1000, -1000);
}
// End -->
</script>
```

第二步:把如下代码加入区域中 :

```
<form>
<input type=button value="Slide to Yahoo"
onClick="moveWin();window.location.href='http://www.yahoo.com';">
</form>
<br>
<a href="http://www.excite.com"; onClick="moveWin()">Slide to Excite</a>
```

页面向右滚屏

脚本说明 :

把如下代码加入<body>区域中:

```
<SCRIPT Language="JavaScript">
<!--

function scrollit(){
    for (H=0; H<=4500; H++){
        parent.scroll(H,0)
    }
}
//-->
</SCRIPT>
<input type=button value="Push and follow me!" onClick="scrollit()">
<FONT SIZE="+4">.....i..love..javascript..very..much!</FONT>
```

禁止图片下载的脚本

脚本说明:

把如下代码加入<body>区域中

```
<A HREF="javascript:void(0)" onmouseover="alert('对不起,图片不能随便下载!')"><IMG SRC="j2.gif" Align="center" Border="0" width="99" height="50"></A>
```

图片隐现效果的脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT language="JavaScript">
```

```
<!--
```

```
function makevisible(cur,which){
```

```
if (which==0)
```

```
cur.filters.alpha.opacity=100
```

```
else
```

```
cur.filters.alpha.opacity=20
```

```
}
```

```
//-->
```

```
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```

```

随机显示图片脚本

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT language="JavaScript"><!--
```

```
today=new Date();
```

```
jran=today.getTime();
```

```
function rnd() {
```

```
    ia=9301;
```

```
    ic=49297;
```

```
    im=233280;
```

```
    jran = (jran*ia+ic) % im;
```

```
    return jran/(im*1.0);
```

```
};
```

```
function rand(number) {
```

```
    return Math.ceil(rnd()*number);
```

```
};
```

```
document.write("<CENTER>");
```

```
for(i=1;i<=1;i++) {
```

```
    myNum=(rand(10)); //改成你要随机显示的图片数 ;
```

```
    if(myNum == 1) document.write("<img src='back.jpg'>");
```

```
if(myNum == 2) document.write("<img src='j2.gif'>"); //图片路径 , 可用 http://
```

```
if(myNum == 3) document.write("<img src='email.gif'>");
```

```
if(myNum == 4) document.write("<img src='arrow.gif'>");
```

```
if(myNum == 5) document.write("<img src='j2.gif'>");
```

```
if(myNum == 6) document.write("<img src='email.gif'>");
```

```
if(myNum == 7) document.write("<img src='arrow.gif'>");
```

```
if(myNum == 8) document.write("<img src='j2.gif'>");
```

```
if(myNum == 9) document.write("<img src='back.jpg'>");
```

```
if(myNum == 10) document.write("<img src='email.gif'>");
```

```
    else {
```

```
document.write();
```

```
    }
```

```
};
```

```
document.write("</CENTER>");
```

```
//-->
```

```
</SCRIPT>
```

图片变形扭曲脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```

```

```
<script language="JavaScript">
```

```
var b = 1;
```

```
var c = true;
```

```
function fade(){
```

```
if(document.all);
```

```
if(c == true) {
```

```
  b++;
```

```
  }
```

```
if(b==100) {
```

```
  b--;
```

```
  c = false
```

```
  }
```

```
if(b==10) {
```

```
  b++;
```

```
  c = true;
```

```
  }
```

```
if(c == false) {
```

```
  b--;
```

```
  }
```

```
  u.width=150 + b;
```

```
  u.height=125 - b;
```

```
  setTimeout("fade()",50);
```

```
  }
```

```
</script>
```

第二步:把<body>区域中改为

```
<body bgcolor="#ffffff" onLoad="fade()">
```


雪景

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript1.2">
<!-- Begin
var no = 12; // number of hearts
var speed = 10; // smaller number moves the hearts faster
var heart = "5.gif";
var flag;
var ns4up = (document.layers) ? 1 : 0; // browser sniffer
var ie4up = (document.all) ? 1 : 0;

var dx, xp, yp; // coordinate and position variables
var am, stx, sty; // amplitude and step variables
var i, doc_width = 800, doc_height = 600;
if (ns4up) {
doc_width = self.innerWidth;
doc_height = self.innerHeight;
} else if (ie4up) {
doc_width = document.body.clientWidth;
doc_height = document.body.clientHeight;
}
dx = new Array();
xp = new Array();
yp = new Array();
amx = new Array();
amy = new Array();
stx = new Array();
sty = new Array();
flag = new Array();
for (i = 0; i < no; ++ i) {
dx[i] = 0; // set coordinate variables
xp[i] = Math.random()*(doc_width-30)+10; // set position variables
yp[i] = Math.random()*doc_height;
amy[i] = 12+ Math.random()*20; // set amplitude variables
amx[i] = 10+ Math.random()*40;
stx[i] = 0.02 + Math.random()/10; // set step variables
sty[i] = 0.7 + Math.random(); // set step variables
flag[i] = (Math.random())>0.5?1:0;
if (ns4up) { // set layers
if (i == 0) {
document.write("<layer name=\"dot"+ i +"\" left=\"15\" ");
document.write("top=\"15\" visibility=\"show\"><img src=\"");
```

```

document.write(heart+ "\" border=\"0\"></layer>");
} else {
document.write("<layer name=\"dot"+ i + "\" left=\"15\" ");
document.write("top=\"15\" visibility=\"show\"><img src=\"");
document.write(heart+ "\" border=\"0\"></layer>");
}
} else
if (ie4up) {
if (i == 0) {
document.write("<div id=\"dot"+ i + "\" style=\"POSITION: ");
document.write("absolute; Z-INDEX: "+ i +"; VISIBILITY: ");
document.write("visible; TOP: 15px; LEFT: 15px;\"><img src=\"");
document.write(heart+ "\" border=\"0\"></div>");
} else {
document.write("<div id=\"dot"+ i + "\" style=\"POSITION: ");
document.write("absolute; Z-INDEX: "+ i +"; VISIBILITY: ");
document.write("visible; TOP: 15px; LEFT: 15px;\"><img src=\"");
document.write(heart+ "\" border=\"0\"></div>");
}
}
}

function snowNS() { // Netscape main animation function
for (i = 0; i < no; ++ i) { // iterate for every dot
if (yp[i] > doc_height-50) {
xp[i] = 10+ Math.random()*(doc_width-amx[i]-30);
yp[i] = 0;
flag[i]=(Math.random()<0.5)?1:0;
stx[i] = 0.02 + Math.random()/10;
sty[i] = 0.7 + Math.random();
doc_width = self.innerWidth;
doc_height = self.innerHeight;
}
if (flag[i])
dx[i] += stx[i];
else
dx[i] -= stx[i];
if (Math.abs(dx[i]) > Math.PI) {
yp[i]+=Math.abs(amy[i]*dx[i]);
xp[i]+=amx[i]*dx[i];
dx[i]=0;
flag[i]=!flag[i];
}
document.layers["dot"+i].top = yp[i] + amy[i]*(Math.abs(Math.sin(dx[i])+dx[i]));

```

```

document.layers["dot"+i].left = xp[i] + amx[i]*dx[i];

}
setTimeout("snowNS()", speed);
}

function snowIE() { // IE main animation function
for (i = 0; i < no; ++ i) { // iterate for every dot
if (yp[i] > doc_height-50) {
xp[i] = 10+ Math.random()*(doc_width-amx[i]-30);
yp[i] = 0;
stx[i] = 0.02 + Math.random()/10;
sty[i] = 0.7 + Math.random();
flag[i]=(Math.random()<0.5)?1:0;
doc_width = document.body.clientWidth;
doc_height = document.body.clientHeight;
}
if (flag[i])
dx[i] += stx[i];
else
dx[i] -= stx[i];
if (Math.abs(dx[i]) > Math.PI) {
yp[i]+=Math.abs(amy[i]*dx[i]);
xp[i]+=amx[i]*dx[i];
dx[i]=0;
flag[i]=!flag[i];
}

document.all["dot"+i].style.pixelTop = yp[i] + amy[i]*(Math.abs(Math.sin(dx[i])+dx[i]));
document.all["dot"+i].style.pixelLeft = xp[i] + amx[i]*dx[i];
}
setTimeout("snowIE()", speed);
}

if (ns4up) {
snowNS();
} else if (ie4up) {
snowIE();
}
// End -->
</script>

```

图片渐渐出现脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT FOR=window EVENT=onLoad LANGUAGE=vbscript>
  image1.filters.item(0).apply()
  image1.filters.item(0).transition = 12
  image1.Style.visibility = ""
  image1.filters(0).play(2.0)
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```

```

相片选择器脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<Script Language="JavaScript">
<!-- Begin
function display_image(form) {
selectionname = form.imagename.options[form.imagename.selectedIndex].text;
selection = form.imagename.options[form.imagename.selectedIndex].value;
PreView          =          window.open("",          "Preview",
"toolbar=0,location=0,directories=0,status=0,menubar=0,scrollbars=0,resizable=0,copyhistory=0,
width=360,height=440 left=0 top=0");
PreView.document.open();
PreView.document.write("<HTML><HEAD>");
PreView.document.write("<TITLE>Preview</TITLE>");
PreView.document.write("</HEAD><BODY BGCOLOR=FFFFFF TEXT=000000>");
PreView.document.write("<FORM><CENTER><B><FONT SIZE=+1>" +
selectionname + "</FONT></B><HR>");
PreView.document.write("<IMG HSPACE=0 VSPACE=0 " +
"SRC=" + selection + ">");
PreView.document.write("<HR><FORM><INPUT TYPE='button' VALUE='关闭窗口' " +
"onClick='window.close()'></FORM>");
PreView.document.write("</CENTER>");
PreView.document.write("</BODY></HTML>");
PreView.document.close();
}
// End -->
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<FORM>
<select NAME="imagenam" onChange="display_image(this.form)">
<option value="" SELECTED>请选择相片
<option value="hhy1.jpg">相片一
<option value="hhy2.jpg">相片二
<option value="hhy3.jpg">相片三
<option value="hhy4.jpg">相片四
<option value="hhy5.jpg">相片五
<option value="hhy6.jpg">相片六
<option value="hhy7.jpg">相片七

</select>
</FORM>
```

图形循环渐显脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```

<script language="JavaScript">
```

```
var b = 1;
var c = true;
```

```
function fade(){
if(document.all);
```

```
if(c == true) {
b++;
}
if(b==100) {
b--;
c = false
}
```

```
if(b==10) {
b++;
c = true;
}
```

```
if(c == false) {
b--;
}
u.filters.alpha.opacity=0 + b;
```

```
setTimeout("fade()",50);  
}  
</script>
```

第二步:把<body>区域改为

```
<body bgcolor="#ffffff" onLoad="fade()">
```

图形左右晃动脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

```
step = 0;  
obj = new Image();  
  
function anim(xp,xk,smer) //smer = direction  
{  
  obj.style.left = x;  
  
  x += step*smer;  
  
  if (x>=(xk+xp)/2) {  
    if (smer == 1) step--;  
    else step++;  
  }  
  else {  
    if (smer == 1) step++;  
    else step--;  
  }  
  
  if (x >= xk) {  
    x = xk;  
    smer = -1;  
  }  
  
  if (x <= xp) {  
    x = xp;  
    smer = 1;  
  }  
  // if (smer > 2) smer = 3;  
  setTimeout('anim('+xp+', '+xk+', '+smer+)', 50);  
}
```

```

function moveLR(objID,movingarea_width,c)
{

    if (navigator.appName=="Netscape") window_width = window.innerWidth;
        else window_width = document.body.offsetWidth;

    obj = document.images[objID];
    image_width = obj.width;

    x1 = obj.style.left;
    x = Number(x1.substring(0,x1.length-2));    // 30px -> 30

    if (c == 0) {

        if (movingarea_width == 0) {
            right_margin = window_width - image_width;
            anim(x,right_margin,1);
        }
        else {
            right_margin = x + movingarea_width - image_width;
            if (movingarea_width < x + image_width) window.alert("No space for moving!");
                else anim(x,right_margin,1);
        }
    }
    else {
        if (movingarea_width == 0) right_margin = window_width - image_width;
            else {
                x = Math.round((window_width-movingarea_width)/2);
                right_margin = Math.round((window_width+movingarea_width)/2)-image_width;
            }
        anim(x,right_margin,1);
    }
}

//-->
</SCRIPT>

```

第二步:在<body>区域加入如下代码

```

<SCRIPT LANGUAGE="JavaScript">
<!--
    setTimeout("moveLR('picture',300,1)",10);
//-->
</SCRIPT>
```

图形选择脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">

<!--

image1= new Image();

image1.src = "image1.gif";

image2= new Image();

image2.src = "image2.gif";

image3= new Image();

image3.src = "image3.gif";

function imgchange(){

    var imageNum = document.form.selImage.selectedIndex + 1;

    fname = eval("image" + imageNum + ".src")

    document.img.src = fname

}

//-->

</SCRIPT>
```


第二步:在<body>区域加入如下代码

```
<FORM name="form">  
  
<SELECT NAME="selImage" size=1>  
  
<OPTION>Image 1  
  
<OPTION>Image 2  
  
<OPTION>Image 3  
  
</SELECT>  
  
<INPUT type="button" value="View" onClick="imgchange()">  
  
</FORM>  
  
<IMG SRC="image1.gif" NAME="img">
```

图片翻滚导航

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script>  
<!--//  
  
//定义图片的宽度和高度，所有的图片要有相同的尺寸；  
var imgwidth=400  
var imgheight=60  
  
//下面定义了包含 2 个图片的数组，数组的下标从 0 开始，你可以增加任意的图片，按照顺序增加即可，注意相应增加数组下标。  
var imgname=new Array()  
imgname[0]="imggum1.jpg"  
imgname[1]="imggum2.jpg"  
  
//下面定义图片的 url，如果不需要 url，将连接值设置为"#”；
```

```

var imgurl=new Array()

imgurl[0]="http://java2000.126.com"
imgurl[1]="#"

// 先预读图片，不要修改这里；
var imgpreload=new Array()
for (i=0;i<=imgname.length-1;i++) {
    imgpreload[i]=new Image()
    imgpreload[i].src=imgname[i]
}

var pause=2000

//图片的显示速度，数值小速度快；
var speed=20

//下面的参数也会影响图片显示的速度，数值小速度快；代表 2 个图片的显示间隔。
var step=10

//不要修改下面的代码；
var i_loop=0
var i_image=0

function stretchimage() {
    if (i_loop<=imgwidth) {
        if (document.all) {
            imgcontainer.innerHTML="<a href='"+imgurl[i_image]+' target='_blank'><img
width='"+i_loop+"' height='"+imgheight+"' src='"+imgname[i_image]+' border='0'></a>"
        }
        i_loop=i_loop+step
        var timer=setTimeout("stretchimage()",speed)
    }
    else {
        i_loop=imgwidth
        clearTimeout(timer)
        imgcontainer.innerHTML="<a href='"+imgurl[i_image]+' target='_blank'><img
src='"+imgname[i_image]+' border='0'></a>"
        var timer=setTimeout("shrinkimage()",pause)
    }
}

function shrinkimage() {

```

```

    if (i_loop>=0) {
        if (document.all) {
            imgcontainer.innerHTML="<a href='"+imgurl[i_image]+'"' target='_blank'><img
width='"+i_loop+"' height='"+imgheight+"' src='"+imgname[i_image]+'"' border='0'></a>"
            }
            i_loop=i_loop-step
            var timer=setTimeout("shrinkimage()",speed)
        }
        else {
            i_loop=0
            clearTimeout(timer)
            changeimage()
        }
    }
}

function changeimage() {
    i_image++
    if (i_image>=imgname.length) {i_image=0}
    if (document.layers) {
        document.imgcontainer.document.write("<a href='"+imgurl[i_image]+'"'
target='_blank'><img src='"+imgname[i_image]+'"' border='0'></a>")
        document.imgcontainer.document.close()
    }
    stretchimage()
}

// -->
</script>
<style>
.containerstyle {
    position:absolute;
    left:100px;
    top:10px;
}
</style>

```

第二步:把如下代码加入<body>区域中

```
<span id="imgcontainer" class="containerstyle"></span>
```

第三步:把<body>区中的内容发言为:

```
<body bgcolor="#ffffff" onLoad="stretchimage()">
```

图片定期消失

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script LANGUAGE="JavaScript">
<!--
function isNew(maxdays, addDate){

    var oldDate = new Date(addDate);
    var newDate = new Date();
    var maxdaysold = maxdays*24*60*60*1000;
    var psj=0;

    if ((newDate.getTime()-oldDate.getTime()) <= maxdaysold) {
        document.write("<img src=pic.jpg width=400 height=40 ALIGN=MIDDLE
Alt='New'>");
    }

}
}
//-->
</script>
<script LANGUAGE="JavaScript">
<!--
isNew(7,"05/14/2000")
//-->
</script>
```

自由控制图片下载

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT>

x=false;
old="";

function conmuta() {
if (x) {
document.GIFanim.src=old;
document.anim.boton.value="Stop Download";
x=false;

}
else {
```

```

old=document.GIFanim.src;
document.GIFanim.src="test.gif";
document.anim.boton.value="continue Download";
x=true;
}
}
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<table align=right>
<tr><td>

<tr><td>
<form name="anim">
<input name="boton" type="button" value="Stop Download" onClick="conmuta()">
</form>
</table>

```

自由设定图片大小

脚本说明:

第一步:把如下代码加入<body>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function ViewImage(form) {
ix = form.width.value;
iy = form.height.value;
ifile = form.url.value;
NS = (document.layers) ? 1 : 0;
localurl = ifile.indexOf("http://") == -1;
if (NS && localurl) ifile = "file:/" + ifile;
var win;
var sWidth;
var sHeight;
win
window.open("", "", "width="+ix+",height="+iy+",menubar=no,toolbar=no,top=100,left=100");
if (NS) {
sWidth = win.innerWidth;
sHeight = win.innerHeight;
} else {
sWidth = win.document.body.clientWidth;
sHeight = win.document.body.clientHeight;
}
win.document.open();
=

```

```

win.document.write("<html><head></head><body onBlur=this.close();>");
win.document.write('<div
style="position:absolute;width:'+ix+'px;height:'+iy+'px;left:0px;top:0px">');
win.document.write("</div></body></html>");
win.document.close();
}
// End -->
</script>

```

第二步：把<body>区域改为

```

<form name=imageform>
<input name=url type=file size=40>
<p>
Height: <input name=height type=text value="200" size=3>
Width: <input name=width type=text value="150" size=3>
<p>
<input type=button value="View Image" onClick="ViewImage(this.form);">

```

图片响应鼠标变换

脚本说明:

第一步:把如下代码加入<body>区域中

```

<center>
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var rand1 = 0;
var useRand = 0;

images = new Array;
images[1] = new Image();
images[1].src = "image1.gif";
images[2] = new Image();
images[2].src = "image2.gif";
images[3] = new Image();
images[3].src = "image3.gif";
images[4] = new Image();
images[4].src = "image4.gif";

function swapPic() {
var imgnum = images.length - 1;
do {
var randnum = Math.random();

```

```

rand1 = Math.round((imgnum - 1) * randnum) + 1;
} while (rand1 == useRand);
useRand = rand1;
document.randimg.src = images[useRand].src;
}
// End -->
</script>
<a onClick="swapPic();"></a><br>
<font face="Verdana" size="-2">click image to change</font>
</center>

```

第二步:把<body>区域中内容改为:

```
<body bgcolor="#ffffff" OnLoad="swapPic()">
```

图片自由运动

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var isNS = ((navigator.appName == "Netscape") && (parseInt(navigator.appVersion) >= 4));
var _all = "";
var _style = "";
var wwidth, wheight;
var ydir = '++';
var xdir = '++';
var id1, id2, id3;
var x = 1;
var y = 1;
var x1, y1;
if(!isNS) {
_all='all.';
_style='.style';
}
function getwindowsize() {
clearTimeout(id1);
clearTimeout(id2);
clearTimeout(id3);
if (isNS) {
wwidth = window.innerWidth - 55;
wheight = window.innerHeight - 50;
} else {
wwidth = document.body.clientWidth - 55;
wheight = document.body.clientHeight - 50;
}
}

```

```

id3 = setTimeout('randomdir()', 20000);
animate();
}
function randomdir() {
if (Math.floor(Math.random()*2)) {
(Math.floor(Math.random()*2)) ? xdir='--': xdir='++';
} else {
(Math.floor(Math.random()*2)) ? ydir='--': ydir='++';
}
id2 = setTimeout('randomdir()', 20000);
}
function animate() {
eval('x'+xdir);
eval('y'+ydir);
if (isNS) {
pic1.moveTo((x+pageXOffset),(y+pageYOffset))
} else {
pic1.pixelLeft = x+document.body.scrollLeft;
pic1.pixelTop = y+document.body.scrollTop;
}
if (isNS) {
if (pic1.top <= 5+pageYOffset) ydir = '++';
if (pic1.top >= wheight+pageYOffset) ydir = '--';
if (pic1.left >= wwidth+pageXOffset) xdir = '--';
if (pic1.left <= 5+pageXOffset) xdir = '++';
} else {
if (pic1.pixelTop <= 5+document.body.scrollTop) ydir = '++';
if (pic1.pixelTop >= wheight+document.body.scrollTop) ydir = '--';
if (pic1.pixelLeft >= wwidth+document.body.scrollLeft) xdir = '--';
if (pic1.pixelLeft <= 5+document.body.scrollLeft) xdir = '++';
}
id1 = setTimeout('animate()', 30);
}
// End -->
</script>

```

第二步:在<body>区中加入如下代码

```

<div id="pic1" style="position:absolute; visibility:visible; left:0px; top:0px; z-index:-1">

</div>

<script language="javascript">
var pic1=eval('document.'+_all+'pic1'+_style);
</script>

```


第三步:把<body>区中内容改为:

```
<body bgcolor="#ffffff" OnLoad="getwindowsize()" OnResize="getwindowsize()">
```

图片大小变换

脚本说明:

把如下代码加入<body>区域中

```
<span id="s1" style = "width : 100">  
<a href="index.shtml"  
onmouseover="img1.style.width='95';"  
onmouseout="img1.style.width= '67';">  
<Img src="link1.gif" id="img1">  
</a>  
</span>
```

图片随意移动

脚本说明:

第一步:把如下代码加入<body>区域中

```
<style type="text/css">  
    #plane1 { position:absolute; left:290; top:170; width:121; z-index:0}  
    #plane2 { position:absolute; left:400; top:250; width:118; z-index:0}  
</style>  
<SCRIPT LANGUAGE="JavaScript">  
//Modified by the CoffeeCup HTML Editor++  
//http://www.coffeecup.com  
// Global variables for platform branching  
var isNav, isIE  
if (parseInt(navigator.appVersion) >= 4) {  
    if (navigator.appName == "Netscape") {  
        isNav = true  
    } else {  
        isIE = true  
    }  
}  
  
// ***Begin CSS custom API Functions***  
// Set zIndex property  
function setZIndex(obj, zOrder) {  
    obj.zIndex = zOrder  
}  
// Position an object at a specific pixel coordinate  
function shiftTo(obj, x, y) {  
    if (isNav) {
```

```

        obj.moveTo(x,y)
    } else {
        obj.pixelLeft = x
        obj.pixelTop = y
    }
}
// ***End API Functions***

// Global holds reference to selected element
var selectedObj
// Globals hold location of click relative to element
var offsetX, offsetY

// Find out which element has been clicked on
function setSelectedElem(evt) {
    if (isNav) {
        // declare local var for use in upcoming loop
        var testObj
        // make copies of event coords for use in upcoming loop
        var clickX = evt.pageX
        var clickY = evt.pageY
        // loop through all layers (starting with frontmost layer)
        // to find if the event coordinates are in the layer
        for (var i = document.layers.length - 1; i >= 0; i--) {
            testObj = document.layers[i]
            if ((clickX > testObj.left) &&
                (clickX < testObj.left + testObj.clip.width) &&
                (clickY > testObj.top) &&
                (clickY < testObj.top + testObj.clip.height)) {
                // if so, then set the global to the layer, bring it
                // forward, and get outa here
                selectedObj = testObj
                setZIndex(selectedObj, 100)
                return
            }
        }
    } else {
        // use IE event model to get the targeted element
        var imgObj = window.event.srcElement
        // make sure it's one of our planes
        if (imgObj.parentElement.id.indexOf("plane") != -1) {
            // then set the global to the style property of the element,
            // bring it forward, and say adios
            selectedObj = imgObj.parentElement.style
        }
    }
}

```

```

        setZIndex(selectedObj,100)
        return
    }
}
// the user probably clicked on the background
selectedObj = null
return
}
// Drag an element
function dragIt(evt) {
    // operate only if a plane is selected
    if (selectedObj) {
        if (isNav) {
            shiftTo(selectedObj, (evt.pageX - offsetX), (evt.pageY - offsetY))
        } else {
            shiftTo(selectedObj, (window.event.clientX - offsetX), (window.event.clientY -
offsetY))
            // prevent further system response to dragging in IE
            return false
        }
    }
}
// Set globals to connect with selected element
function engage(evt) {
    setSelectedElem(evt)
    if (selectedObj) {
        // set globals that remember where the click is in relation to the
        // top left corner of the element so we can keep the element-to-cursor
        // relationship constant throughout the drag
        if (isNav) {
            offsetX = evt.pageX - selectedObj.left
            offsetY = evt.pageY - selectedObj.top
        } else {
            offsetX = window.event.offsetX
            offsetY = window.event.offsetY
        }
    }
    // block mouseDown event from forcing Mac to display
    // contextual menu.
    return false
}
// Restore elements and globals to initial values
function release(evt) {
    if (selectedObj) {

```

```

        setZIndex(selectedObj, 0)
        selectedObj = null
    }
}
// Turn on event capture for Navigator
function setNavEventCapture() {
    if (isNav) {
        document.captureEvents(Event.MOUSEDOWN | Event.MOUSEMOVE |
Event.MOUSEUP)
    }
}
// Assign event handlers used by both Navigator and IE (called by onLoad)
function init() {
    if (isNav) {
        setNavEventCapture()
    }
    // assign functions to each of the events (works for both Navigator and IE)
    document.onmousedown = engage
    document.onmousemove = dragIt
    document.onmouseup = release
}
</SCRIPT>

```

```

<DIV ID=plane1><IMG NAME="planePic1" SRC="clock1.jpg" BORDER=0></DIV>
<DIV ID=plane2><IMG NAME="planePic1" SRC="clock2.jpg" BORDER=0></DIV>

```

第二步:把<body>区域中内容改为:

```
<body bgcolor="#ffffff" onLoad="init()">
```

自动显示图片属性

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function checkImage(loc) {
loc = "Wc232358f98b75.html" + loc;
windowprops = 'menubar=0,toolbar=0,status=0,location=0';
popupWindow = open(loc, 'previewWin', windowprops);
if (popupWindow.opener == null)
popupWindow.opener = self;
}
// End -->
</script>

```

第二步:把如下代码加入<body>区域中

```
<form name=dimform>
请输入你所要显示的图片的路径:<br>
<input type=text name=url size=40 value="http://">
<input type=button value="OK" onClick="checkImage(this.form.url.value);">
<p>
检测结果:<p>
宽度 = <input type=text name=width><br>
高度 = <input type=text name=height>
</form>
```

第三步:新建 image-popup.html 的文件，其代码如下:

```
<HTML>
<HEAD>
<SCRIPT LANGUAGE="JavaScript1.1">
<!-- Begin
imageerror = 0;
function allDone() {
width = (!imageerror) ? document.images[0].width : "error";
height = (!imageerror) ? document.images[0].height : "error";
opener.document.dimform.width.value = width;
opener.document.dimform.height.value = height;
timerID = window.setTimeout('window.close();', 2000);
}
function complain() {
imageerror = 1;
alert('Error loading that image. Please correct the image URL and try again. ');
timerID = window.setTimeout('window.close();', 2000);}
// End -->
</SCRIPT>
</HEAD>
<BODY onLoad="allDone();">
<script language="JavaScript">
<!-- Begin
query = location.search;
url = query.substring(1, query.length);
document.write("");
```

```
// End -->
</script>
<P>
Loading image.... Reading dimensions....
</BODY>
</HTML>
```

图片循环显现

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var interval = 2.5; // delay between rotating images (in seconds)
var random_display = 1; // 0 = no, 1 = yes
interval *= 1000;

var image_index = 0;
image_list = new Array();
image_list[image_index++] = new imageItem("01.jpg");
image_list[image_index++] = new imageItem("02.jpg");
image_list[image_index++] = new imageItem("03.jpg");
image_list[image_index++] = new imageItem("04.jpg");
var number_of_image = image_list.length;
function imageItem(image_location) {
this.image_item = new Image();
this.image_item.src = image_location;
}
function get_ImageItemLocation(imageObj) {
return(imageObj.image_item.src)
}
function generate(x, y) {
var range = y - x + 1;
return Math.floor(Math.random() * range) + x;
}
function getNextImage() {
if (random_display) {
image_index = generate(0, number_of_image-1);
}
else {
image_index = (image_index+1) % number_of_image;
}
var new_image = get_ImageItemLocation(image_list[image_index]);
return(new_image);
}
```

```
function rotateImage(place) {
var new_image = getNextImage();
document[place].src = new_image;
var recur_call = "rotateImage('"+place+"')";
setTimeout(recur_call, interval);
}
// End -->
</script>
```

第二步:把<body>中加入如下代码 :

```

```

第三步 : 把<body>中内容改为 :

```
<body bgcolor="#ffffff" OnLoad="rotateImage('rImage')">
```

图片变化效果

脚本说明:

把如下代码加入<body>区域中

```
<a name="logoAnchor"> </a>
<div id="logo" style="position:absolute;visibility:visible;">

</div>
```

```
<SCRIPT LANGUAGE="JavaScript1.2">
<!-- Begin
function BrowserCheck() {
var b = navigator.appName;
if (b == "Netscape") this.b = "NS";
else if (b == "Microsoft Internet Explorer") this.b = "IE";
else this.b = b;
this.v = parseInt(navigator.appVersion);
this.NS = (this.b == "NS" && this.v >= 4);
this.NS4 = (this.b == "NS" && this.v == 4);
this.NS5 = (this.b == "NS" && this.v == 5);
this.IE = (this.b == "IE" && this.v >= 4);
this.IE4 = (navigator.userAgent.indexOf('MSIE 4') > 0);
this.IE5 = (navigator.userAgent.indexOf('MSIE 5') > 0);
if (this.IE5 || this.NS5) this.VER5 = true;
```

```

if (this.IE4 || this.NS4) this.VER4 = true;
this.oldVer = (! this.VER5 && ! this.VER4) ? true : false;
this.min = (this.NS || this.IE);
}
is = new BrowserCheck()
var myLogo = (is.NS4) ? document.layers["logo"] : document.all["logo"].style;
var logoWidth = (is.NS4) ? document.logo.document.logoIm.width : document.logoIm.width;
var logoHeight = (is.NS4) ? document.logo.document.logoIm.height : document.logoIm.height;
var halfHeight = logoHeight / 2;
var windowWidth = (is.NS4) ? window.innerWidth - 16 : document.body.offsetWidth - 20;
var halfWidth = logoWidth / 2;
var cliplogoHeightor = (is.NS4) ?
'myLogo.clip.top = 0;' +
'myLogo.clip.right = right;' +
'myLogo.clip.bottom = logoHeight;' +
'myLogo.clip.left = left;'
:
'str="rect(0 " + right + " " + logoHeight + " " + left + ")";' +
'myLogo.clip = str;'
var clipLogoVert = (is.NS4) ?
'myLogo.clip.top = up;' +
'myLogo.clip.right = logoWidth;' +
'myLogo.clip.bottom = dn;' +
'myLogo.clip.left = 0;'
:
'str="rect(" + up + " " + logoWidth + " " + dn + " 0)";' +
'myLogo.clip = str;'
var right = logoWidth, left = 0;
var cnt = 0, up = halfHeight, dn = halfHeight, upDown;
var logoWidth, logoHeight;
// ----- User modifiable variables -----

//if useAnchorPosition is true logo will be positioned where you put the "logoAnchor"
//set to false to center logo - also set myLogo.top to desired position

var useAnchorPosition = false; // set to false to set your own logo position below
if (! useAnchorPosition) {
myLogo.left = ((windowWidth / 2) - (logoWidth / 2)); // centers logo - comment out if using
line below
//myLogo.left = 100; // remove '/' to set left position
myLogo.top = 200; // sets logo top
}
var scrollInc = 5; // sets # of pixels to scroll in 1 time frame
var scrollSpeed = 10; // sets the scroll speed

```



```
// -----  
function scrollLogo() {  
  if (cnt == 0) {  
    up-- ; dn++;  
    if (up < -10) {  
      right = logoWidth;  
      left = 0;  
      upDown = -scrollInc;  
      cnt++;  
    }  
    eval(clipLogoVert);  
  }  
  if (cnt == 1) {  
    right += upDown;  
    left -= upDown;  
    if (right < halfWidth-40) {  
      right = halfWidth;  
      left = halfWidth;  
      upDown = scrollInc;  
      cnt++;  
    }  
    eval(cliplogoHeightor);  
  }  
  if (cnt == 2) {  
    right += upDown;  
    left -= upDown;  
    if (right > logoWidth+20) {  
      right = logoWidth;  
      left = 0;  
      up = 0;  
      dn = logoHeight;  
      cnt++;  
    }  
    eval(cliplogoHeightor);  
  }  
  if (cnt == 3) {  
    up++;  
    dn--;  
    if (dn < halfHeight - 10) {  
      up = halfHeight;  
      dn = halfHeight;  
      right = logoWidth;  
      left = 0;  
      upDown = scrollInc;  
    }  
  }  
}
```

```

cnt = 0;
}
eval(clipLogoVert)
}
setTimeout("scrollLogo()", scrollSpeed);
}
if (! is.oldVer)window.onload = init;
function init() {
positionLogo();
scrollLogo();
}
var L, T;
var pos = (is.NS4) ? pos = document.anchors['logoAnchor'] : document.all['logoAnchor'];
var posStr = (is.NS4) ? 'L = pos.x ; T = pos.y' : 'L = pos.offsetLeft; T = pos.offsetTop';
function positionLogo() {
if (! useAnchorPosition) return;
eval(posStr);
myLogo.top = T;
myLogo.left = L;
}
// End -->
</script>
</td>
</tr>
</table>

```

随机显示 banner

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```

<!-- Begin
var how_many_ads = 3;
var now = new Date()
var sec = now.getSeconds()
var ad = sec % how_many_ads;
ad +=1;
if (ad==1) {
txt="The World's Largest Online Bookstore, Amazon.com";
url="http://www.amazon.com";
alt="amazon.com";
banner="http://imageserv.imgis.com/images/Ad12669St1Sz1Sq1_Ban1.gif";
width="468";

```

```

height="60";
}
if (ad==2) {
txt="Palm III by 3Com, in stock!";
url="http://cybershop.com/";
alt="cybershop.com";
banner="http://imageserv.imgis.com/images/Ad13189St1Sz1Sq5_Ban10.gif";
width="468";
height="60";
}
if (ad==3) {
txt="Find it at GoTo.com";
url="http://www.goto.com";
alt="goto.com";
banner="http://imageserv.imgis.com/images/Ad13700St1Sz1Sq1_Ban1.gif";
width="468";
height="60";
}
document.write('<center>');
document.write('<a href=\"' + url + '\" target=\"_top\">');
document.write('<img src=\"' + banner + '\" width=');
document.write(width + ' height=' + height + ');');
document.write('alt=\"' + alt + '\" border=0><br>');
document.write('<small>' + txt + '</small></a>');
document.write('</center>');
// End -->
</SCRIPT>

```

鼠标驱动图片变化

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT language="JavaScript">
<!-- Begin
function movepic(img_name,img_src) {
document[img_name].src=img_src;
}
// End -->
</SCRIPT>
<A HREF="http://javascript.internet.com"
onmouseover="movepic('button','crab.gif)"
onmouseout="movepic('button','profits.gif)">
<IMG NAME="button" SRC="profits.gif" ALT="Image"></A>

```

图片不停闪烁

脚本说明:

第一步:把如下代码加入<body>区域中

```
<DIV ID="soccer" STYLE="position:absolute; left:150; top:0">
<a href="http://图片的链接.com" target="_blank">
<IMG SRC="minutes1.gif" border="0"></a>
</DIV>
<SCRIPT LANGUAGE="JavaScript">
var msec = 500; //改变时间得到不同的闪烁间隔;
var counter = 0;
function soccerOnload() {
setTimeout("blink()", msec);
}
function blink() {
soccer.style.visibility =
(soccer.style.visibility == "hidden") ? "visible" : "hidden";
counter +=1;
setTimeout("blink()", msec);
}
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" ONLOAD="soccerOnload()">
```

图片跟随鼠标

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
var newtop=0
var newleft=0
if (navigator.appName == "Netscape") {
    layerStyleRef="layer.";
    layerRef="document.layers";
    styleSwitch="";
}
else
{
    layerStyleRef="layer.style.";
    layerRef="document.all";
    styleSwitch=".style";
}

function doMouseMove() {
```

```

layerName = 'iit'

eval('var curElement='+layerRef+'[''+layerName+'']')
eval(layerRef+'[''+layerName+'']+styleSwitch+'.visibility="hidden"')
eval('curElement'+styleSwitch+'.visibility="visible"')
eval('newleft=document.body.clientWidth-curElement'+styleSwitch+'.pixelWidth')
eval('newtop=document.body.clientHeight-curElement'+styleSwitch+'.pixelHeight')
eval('height=curElement'+styleSwitch+'.height')
eval('width=curElement'+styleSwitch+'.width')
width=parseInt(width)
height=parseInt(height)
if (event.clientX > (document.body.clientWidth - 5 - width))
{
newleft=document.body.clientWidth + document.body.scrollLeft - 5 - width
}
else
{
newleft=document.body.scrollLeft + event.clientX
}
eval('curElement'+styleSwitch+'.pixelLeft=newleft')

if (event.clientY > (document.body.clientHeight - 5 - height))
{
newtop=document.body.clientHeight + document.body.scrollTop - 5 - height
}
else
{
newtop=document.body.scrollTop + event.clientY
}
eval('curElement'+styleSwitch+'.pixelTop=newtop')
}

```

```
document.onmousemove = doMouseMove;
```

```
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```

<script language="javascript">
  if (navigator.appName == "Netscape") {

  }
  else
  {
    document.write('<div ID=OuterDiv>')
  }

```

```
document.write('')
document.write('</div>')
}
</script>
```

鼠标放上去打开新页面

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT Language="JavaScript">function winopen ()
{msg=open("update.htm","NewWindow","toolbar=no,location=no,directories=no,status=no,menu
bar=no,scrollbars=no,resizable=no,copyhistory=yes,width=400,height=260");}</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<a href="" onMouseOver="winopen(); return true;"><IMG SRC="shu.gif" border="0"></a>
```

脚本说明:

把如下代码加入<head>区域中

```
<script language="javascript">
function click() {
if (event.button==1) { //改成 button==2 为禁止右键
alert('对不起,禁止使用此功能.')
}
}
document.onmousedown=click
</script>
```

禁用鼠标左右键

脚本说明:

把如下代码加入 <head>区域中

```
<script language="javascript">
function click() {
if (event.button==1) { //改成 button==2为禁止右键
alert('对不起,禁止使用此功能.')
}
}
document.onmousedown=click
</script>
```

脚本说明:

把如下代码加入 <head>区域中

```

<script language="javascript">
function click() {
if (event.button==1) { //改成 button==2为禁止右键
alert( '对不起 禁止使用此功能 .' )
}
}
document.onmousedown=click
</script>

```

鼠标控制窗口开关

脚本说明：

第一步 把如下代码加入 <head>区域中 (你可以对链接及说明作相应修改)

```

<SCRIPT Language="JavaScript">function winopen()
{msg1=open("update.htm", "Homepage", "toolbar=no, location=no, directories=no, status=no, menubar=no, scrol lbars=no, resizable=no, copyhistory=no, width=200, height=250");}</script>

```

第二步 把如下代码加入 <body>区域中

```

<SCRIPT Language="JavaScript">function winopen1()
{msg1=open("sh3.htm", "Homepage", "toolbar=no, location=no, directories=no, status=no, menubar=no, scrol lbars=no, resizable=no, copyhistory=no, width=200, height=250");}</script>
<a href="" onmouseover="winopen1(); return true;" onmouseout="msg1.close();">update</a>

```

鼠标点击效果

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<SCRIPT LANGUAGE="JavaScript1.2">
<!-- Begin
var ver = navigator.appVersion;
var dcm = document.getElementById ? 1 : 0;
var ie5 = (ver.indexOf("MSIE 5") > -1 && dcm) ? 1 : 0;
var n = (document.layers);
var ie = (document.all);

var sparksAflyin = 0;
var totalSparks = 0;
var sparksOn = 1;
function initMouseEvents() {
document.onmousedown = mouseDown;
if (n) document.captureEvents(Event.MOUSEDOWN | Event.MOUSEMOVE);
}
function mouseDown(e) {
if (sparksOn) {
var mousex = (n) ? e.pageX : event.x+document.body.scrollLeft;

```

```

var mouseY = (n) ? e.pageY : event.y+document.body.scrollTop;
if (!sparksAflyin) {
for (var k = 0; k <= 9; k++)
    eval('SHOW("sDiv'+k+'")');
sparksAflyin = 1;
totalSparks = 0;
for(i = 0; i <= 9; i++)
eval('moveTo('+i+',0,'#mousex+', '#mousey+')');
    }
}
function moveTo(i, j, mousex, mousey){
if (j < eval('anim_'+i+'_x.length') ){
var tempx = eval('anim_'+i+'_x[j]'+mousex');
var tempy = eval('anim_'+i+'_y[j]'+mousey');
if (ie) {
if(tempy+30 > (document.body.offsetHeight+document.body.scrollTop))
tempy = document.body.offsetHeight+document.body.scrollTop-30;
if(tempx+30 > (document.body.offsetWidth+document.body.scrollLeft))
tempx = document.body.offsetWidth+document.body.scrollLeft-30;
eval('document.all.sDiv'+i+'.style.left = tempx;');
eval('document.all.sDiv'+i+'.style.top = tempy;');
}
if (n) {
eval('document.layers.sDiv'+i+'.left = tempx;');
eval('document.layers.sDiv'+i+'.top = tempy;');
}
j++;
// timeout: 50 = fireworks speed, larger number = slower speed
setTimeout("moveTo("+i+", "+j+", "#mousex+", "#mousey+"", 50)
}
else {
eval('HIDE("sDiv'+i+'")');
totalSparks++;
}
if (totalSparks == 10) {
sparksAflyin = 0;
totalSparks = 0;
}
}
function SHOW(divName){
if (document.all)
eval('document.all.'+divName+'.style.visibility = "visible";');
else if (document.layers)

```



```

eval('document.layers["'+divName+'"].visibility = "visible";');
}
function HIDE(divName){
if (document.all)
eval('document.all.'+divName+'.style.visibility = "hidden";');
else if (document.layers)
eval('document.layers["'+divName+'"].visibility = "hide";');
}
anim_0_x=new Array(20,20,10,0,0,0,0,0,0,0,0);
anim_0_y=new Array(-20,-40,-60,-80,-60,-40,-20,0,20,40,60,80);
anim_1_x=new Array(20,20,17,36,60,78,90,92,93,98,108,120,133,152,181);
anim_1_y=new Array(-20,-20,-33,-38,-38,-27,-2,25,51,84,113,141,162,212,253);
anim_2_x=new Array(20,20,2,3,4,5,6,7,8,9,10,12,13,15,18);
anim_2_y=new Array(-20,-20,-33,-38,-38,-27,-2,25,51,84,113,141,162,212,253);
anim_3_x=new Array(-20,-20,-2,-1,7,10,18,35,60,102,94,94,93,97,108,111,117,127);
anim_3_y=new
Array(-20,-25,-64,-89,-104,-150,-173,-197,-213,-199,-151,-101,-66,-17,27,87,140,189);
anim_4_x=new
Array(-20,-20,-10,-39,-30,-69,-64,-138,-154,-200,-181,-209,-191,-207,-203,-213,-202,-221,-21
1);
anim_4_y=new
Array(-20,-20,-28,-51,-79,-100,-135,-154,-193,-183,-149,-134,-89,-60,8,51,107,157,201);
anim_5_x=new
Array(-20,-29,-51,-72,-105,-133,-164,-189,-209,-229,-247,-270,-279,-282,-283,-283,-285,-286,
-288);
anim_5_y=new
Array(-20,-55,-86,-116,-154,-183,-205,-217,-217,-198,-169,-120,-44,-8,40,87,144,190,248);
anim_6_x=new Array(-20,-20,-7,14,44,79,143,186,217,226,234,244,250,259,265,274);
anim_6_y=new Array(-20,-21,-72,-113,-139,-166,-188,-181,-126,-68,-3,54,134,187,215,257);
anim_7_x=new
Array(20,20,-3,-9,-13,-27,-33,-44,-54,-66,-77,-95,-107,-136,-150,-160,-164,-168,-171,-172,-1
72,-176,-175);
anim_7_y=new
Array(-20,-26,-43,-63,-89,-116,-145,-169,-201,-222,-240,-253,-254,-245,-220,-195,-160,-124,-
81,-53,-26,19,68);
anim_8_x=new
Array(-20,20,-35,39,0,45,-1,24,-15,14,-20,35,-18,38,-11,16,49,64,81,93,100,103,109);
anim_8_y=new
Array(-20,-20,-32,-42,-62,-76,-89,-107,-132,-147,-173,-180,-192,-209,-236,-193,-119,-73,-24,
51,95,130,188);
anim_9_x=new Array(-20,-51,-89,-110,-165,-191,-228,-240,-259,-271,-277,-281,-287);
anim_9_y=new Array(-20,-20,-35,-37,-34,-16,10,47,105,150,189,227,273);
// End -->
</script>

```

第二步 把 <body>改为

```
<body bgcolor="#ffffff" OnLoad="initMouseEvent()">
```

第三步 在 <body>区域中加入如下代码

```
<div id="sparks">
<div id="sDiv0" style="position:absolute; visibility: hidden;"><font face="arial black"
color="red">a</font></div>
<div id="sDiv1" style="position:absolute; visibility: hidden;"><font face="arial black"
color="yellow">b</font></div>
<div id="sDiv2" style="position:absolute; visibility: hidden;"><font face="arial black"
color="blue">c</font></div>
<div id="sDiv3" style="position:absolute; visibility: hidden;"><font face="arial black"
color="red">d</font></div>
<div id="sDiv4" style="position:absolute; visibility: hidden;"><font face="arial black"
color="orange">e</font></div>
<div id="sDiv5" style="position:absolute; visibility: hidden;"><font face="arial black"
color="white">f</font></div>
<div id="sDiv6" style="position:absolute; visibility: hidden;"><font face="arial black"
color="green">g</font></div>
<div id="sDiv7" style="position:absolute; visibility: hidden;"><font face="arial black"
color="skyblue">h</font></div>
<div id="sDiv8" style="position:absolute; visibility: hidden;"><font face="arial black"
color="yellow">i</font></div>
<div id="sDiv9" style="position:absolute; visibility: hidden;"><font face="arial black"
color="white">j</font></div>
</div>
```

禁用右键并自动导航

脚本说明：

把如下代码加入 <body>区域中

```
<script language="JavaScript">
if (navigator.appName.indexOf("Internet Explorer") != -1)
    document.onmousedown = noSourceExplorer;
function noSourceExplorer()
{
    if (event.button == 2 | event.button == 3)
    {
        alert("禁止右键 .. 去 yahoo!");
        location.replace("http://www.yahoo.com");
    }
}
```

```
    }  
  }  
</script>
```

鼠标激活警告框

脚本说明：

把如下代码加入 <body>区域中

```
<a href="" onMouseOver="alert('本站域名 :http://www.hrw.cn');return true;">记住本站域名 </a>
```

鼠标跟踪器

脚本说明：

把如下代码加入 <body>区域中

```
<SCRIPT language="JavaScript">  
<!--  
B=document.all;  
C=document.layers;  
T1=new  
Array("trail1.gif",38,35,"trail2.gif",30,31,"trail3.gif",28,26,"trail4.gif",22,21,"trail5.gif",16,16)  
nos=parseInt(T1.length/3)  
rate=50  
ie5fix1=0;  
ie5fix2=0;  
for (i=0;i<nos;i++){  
  createContainer("CLR"+i,i*10,i*10,i*3+1,i*3+2,"","<img src='"+T1[i*3]+"' width='"+T1[(i*3+1)]+"' height='"+T1[(i*3+2)]+"' border=0>")  
  function createContainer(N,Xp,Yp,W,H,At,HT,Cp,St){  
    with (document){  
      write((!B) ? "<layer id='"+N+"' left="+Xp+" top="+Yp+" width="+W+" height="+H : "<div id='"+N+"' style='position:absolute;left:"+Xp+"; top:"+Yp+"; width:"+W+"; height:"+H+"; ");  
      if(St){  
        if (C)  
          write(" style=");  
        write(St+";' ");  
      }  
      else write((B)?"'": "");  
      write((At) ? At+">" : ">");  
      write((HT) ? HT : "");  
      if (!Cp)  
        closeContainer(N)  
    }  
  }  
  function closeContainer(){  
    document.write((B)?"</div>":"</layer>")
```

```

}
function getXpos(N){
return (B) ? parseInt(B[N].style.left) : C[N].left
}
function getYpos(N){
return (B) ? parseInt(B[N].style.top) : C[N].top
}

function moveContainer(N,DX,DY){
c=(B) ? B[N].style :C[N];c.left=DX;c.top=DY
}
function cycle(){
//if (IE5)
if (document.all&&window.print){
ie5fix1=document.body.scrollLeft;
ie5fix2=document.body.scrollTop;
}
for (i=0;i<(nos-1);i++){
moveContainer("QR"+i,getXpos("QR"+(i+1)),getYpos("QR"+(i+1)))
}
}
function newPos(e){
moveContainer("QR"+(nos-1),(B)?event.clientX+ie5fix1:e.pageX+2,(B)?event.clientY+ie5fix2:e.
pageY+2
)
}
if(document.layers)
document.captureEvents(Event.MOUSEMOVE)
document.onmousemove=newPos
setInterval("cycle()",rate)

//-->

</SCRIPT>

```

右键自动链接页面

脚本说明：

把如下代码加入 <body>区域中

```
<script language=JavaScript>
```

```
if (navigator.appName.indexOf("Internet Explorer") != -1)
```

```
    document.onmousedown = noSourceExplorer;
```

```
function noSourceExplorer()
```

```
{
```

```
    if (event.button == 2 | event.button == 3)
```

```
    {
```

```
        alert("现在正在打开怀柔网首页");
```

```
        location.replace("Upper1/default.htm");
```

```
    }
```

```
}
```

```
</script>
```

跟随鼠标的星星

脚本说明：

把如下代码加入 <body>区域中

```
<script>
```

```
/*
```

```
Scrolling Image Map/Text Link Tooltip Script-
```

```
Special Thanks to: Rob(http://rob.yeah.net)
```

```
Miss Ann(http://annworld.126.com)
```

```
*/
```

```
if (!document.layers&&!document.all)
```

```
event="test"
```

```
function showtip2(current,e,text){
```

```
if (document.all&&document.readyState=="complete"){
```

```
document.all.tooltip2.innerHTML='<marquee style="border:1px solid black">'+text+'</marquee>'
```

```
document.all.tooltip2.style.pixelLeft=event.clientX+document.body.scrollLeft+10
```

```
document.all.tooltip2.style.pixelTop=event.clientY+document.body.scrollTop+10
```

```

document.all.tooltip2.style.visibility="visible"
}

else if (document.layers){
document.tooltip2.document.nstip.document.write('<b>'+text+'</b>')
document.tooltip2.document.nstip.document.close()
document.tooltip2.document.nstip.left=0
currentscroll=setInterval("scrolltip()",100)
document.tooltip2.left=e.pageX+10
document.tooltip2.top=e.pageY+10
document.tooltip2.visibility="show"
}
}
function hidetip2(){
if (document.all)
document.all.tooltip2.style.visibility="hidden"
else if (document.layers){
clearInterval(currentscroll)
document.tooltip2.visibility="hidden"
}
}

function scrolltip(){
if (document.tooltip2.document.nstip.left>=-document.tooltip2.document.nstip.document.width)
document.tooltip2.document.nstip.left-=5
else
document.tooltip2.document.nstip.left=150
}
</script>
<script language="JavaScript">
function YY_Layerfx(yyleft,yytop,yfmx,yfny,yydiv,yyblder,yyloop,yyto,yycnt,yystep)
{ //v1.2
//copyright (c)1999 Yarrat, Jaro von Flocken
if ((document.layers)||(document.all)){
with (Math) {ynextx= eval(yfmx)}
with (Math) {ynexty= eval(yfny)}
yycnt=(yyloop && yynt>=yystep*yyblder)?0:yynt+yystep;
if (document.layers){
eval(yydiv+".top="+ynexty+yytop)
eval(yydiv+".left="+ynextx+yyleft)
}
if (document.all){
eval("yydiv=yydiv.replace(/.layers/gi, '.all')");
eval(yydiv+".style.pixelTop="+ynexty+yytop);
}
}
}

```

```

        eval(yydiv+".style.pixelLeft="+(ynnextx+yyleft));
    }

    argStr='YY_Layerfx('+yyleft+', '+yytop+', "'+yyfnx+'", "'+yyfny+'", "'+yydiv+'", '+yyblder+', '+y
yloop+', '+yyto+', '+yycnt+', '+yystep+')';
    if (yycnt<=yystep*yyblder){eval(yydiv+".yyto=setTimeout(argStr,yyto)};
}

}

function YY_Mbusetrace(evt) { //v1.2 copyright (c)1999 Yaromat
    if (yyns4)
        {if (evt.pageX) {yy_ml=evt.pageX; yy_mt=evt.pageY;} }
    else{
        yy_ml=(event.clientX + document.body.scrollLeft);
        yy_mt=(event.clientY + document.body.scrollTop);
    }
    if (yy_tracescript)eval(yy_tracescript)
}
</script>
<script language="JavaScript">
function PopWin()
{
    var PopWin =
window.open("new.htm", "PopWin", "toolbar=no, directories=no, scrollbar=yes, height=350, width=400
");
}
</script>
<div id="tooltip2"
style="position:absolute;visibility:hidden;clip:rect(0 150 50
0);width:150px;background-color:lightyellow">
    <layer name="nstip" width="1000px" bgcolor="lightyellow"> </layer>
</div>
<div id="yyd0"
style="position:absolute; left:10px; top:50px; width:3px; height:3px; z-index:1;
background-color: #19636c; layer-background-color: #19636c; border: 1px none #000000; clip:
rect(0 3 3 0)"></div>
<div
id="yyd1"
style="position:absolute; left:20px; top:50px; width:3px; height:3px; z-index:1;
background-color: #708574; layer-background-color: #708574; border: 1px none #000000; clip:
rect(0 3 3 0)"></div>
<div
id="yyd2"

```

```

style="position:absolute; left:30px; top:50px; width:3px; height:3px; z-index:1;
background-color: #379bbf; layer-background-color: #379bbf; border: 1px none #000000; clip:
rect(0 3 3 0)"></div>
  <div
id="yyd3"
style="position:absolute; left:40px; top:50px; width:3px; height:3px; z-index:1;
background-color: #25184c; layer-background-color: #25184c; border: 1px none #000000; clip:
rect(0 3 3 0)"></div>
  <div
id="yyd4"
style="position:absolute; left:50px; top:50px; width:3px; height:3px; z-index:1;
background-color: #31bd3c; layer-background-color: #31bd3c; border: 1px none #000000; clip:
rect(0 3 3 0)"></div>
  <div
id="yyd5"
style="position:absolute; left:60px; top:50px; width:3px; height:3px; z-index:1;
background-color: #c11efd; layer-background-color: #c11efd; border: 1px none #000000; clip:
rect(0 3 3 0)"></div>
  <script>
var yyns4=window.Event?true:false; var yy_mt = 0; var yy_ml = 0;
document.onmousemove = YY_Mbuserace;
yy_tracescript = '';

if (yyns4){ document.captureEvents(Event.MOUSEMOVE);
  YY_Mbuserace('',',',document.YY_Mbuserace1')}

YY_Layerfx(0,0,'yy_ml+cos((15*sin(yycnt/39.83007847812662))+0)*150*(sin(10+yycnt/20)+0.2)*co
s(yycnt/20)', 'yy_mt+sin((15*sin(yycnt/34.224861639800686))+0)*150*(sin(10+yycnt/20)+0.2)*cos
(yycnt/20)', 'document.layers[\`yyd0\`]',2000,true,80,0,1);

YY_Layerfx(0,0,'yy_ml+cos((15*sin(yycnt/27.66510707209673))+30)*150*(sin(10+yycnt/20)+0.2)*c
os(yycnt/20)', 'yy_mt+sin((15*sin(yycnt/9.240632767417667))+30)*150*(sin(10+yycnt/20)+0.2)*co
s(yycnt/20)', 'document.layers[\`yyd1\`]',2000,true,80,0,1);

YY_Layerfx(0,0,'yy_ml+cos((15*sin(yycnt/16.45318944579641))+60)*150*(sin(10+yycnt/20)+0.2)*c
os(yycnt/20)', 'yy_mt+sin((15*sin(yycnt/16.0564452288292))+60)*150*(sin(10+yycnt/20)+0.2)*cos
(yycnt/20)', 'document.layers[\`yyd2\`]',2000,true,80,0,1);

YY_Layerfx(0,0,'yy_ml+cos((15*sin(yycnt/6.95348954836835))+90)*150*(sin(10+yycnt/20)+0.2)*co
s(yycnt/20)', 'yy_mt+sin((15*sin(yycnt/44.13697049887155))+90)*150*(sin(10+yycnt/20)+0.2)*cos
(yycnt/20)', 'document.layers[\`yyd3\`]',2000,true,80,0,1);

```



```
YY_Layerfx(0,0,'yy_ml+cos((15*sin(yycnt/33.90077294583733))+120)*150*(sin(10+yycnt/20)+0.2)*  
cos(yycnt/20)', 'yy_mt+sin((15*sin(yycnt/2.2378828869411587))+120)*150*(sin(10+yycnt/20)+0.2)  
*cos(yycnt/20)', 'document.layers[\`yyd4\`]', 2000, true, 80, 0, 1);
```

```
YY_Layerfx(0,0,'yy_ml+cos((15*sin(yycnt/37.858312521039835))+150)*150*(sin(10+yycnt/20)+0.2)  
*cos(yycnt/20)', 'yy_mt+sin((15*sin(yycnt/18.083839795990098))+150)*150*(sin(10+yycnt/20)+0.2)  
)*cos(yycnt/20)', 'document.layers[\`yyd5\`]', 2000, true, 80, 0, 1);
```

```
</script>
```

```
<script>
```

```
/*
```

```
Scrolling Image Map/Text Link Tooltip Script-
```

```
Special Thanks to: Rob(http://rob.yeah.net)
```

```
Miss Ann(http://annworld.126.com)
```

```
*/
```

```
if (!document.layers&&!document.all)
```

```
event="test"
```

```
function showtip2(current,e,text){
```

```
if (document.all&&document.readyState=="complete"){
```

```
document.all.tooltip2.innerHTML=<marquee style="border:1px solid black">'+text+'</marquee>
```

```
document.all.tooltip2.style.pixelLeft=event.clientX+document.body.scrollLeft+10
```

```
document.all.tooltip2.style.pixelTop=event.clientY+document.body.scrollTop+10
```

```
document.all.tooltip2.style.visibility="visible"
```

```
}
```

```
else if (document.layers){
```

```
document.tooltip2.document.nstip.document.write('<b>'+text+'</b>')
```

```
document.tooltip2.document.nstip.document.close()
```

```
document.tooltip2.document.nstip.left=0
```

```
currentscroll=setInterval("scrolltip()", 100)
```

```
document.tooltip2.left=e.pageX+10
```

```
document.tooltip2.top=e.pageY+10
```

```
document.tooltip2.visibility="show"
```

```
}
```

```
}
```

```
function hidetip2(){
```

```
if (document.all)
```

```
document.all.tooltip2.style.visibility="hidden"
```

```
else if (document.layers){
```

```
clearInterval(currentscroll)
```

```
document.tooltip2.visibility="hidden"
```

```
}
```

```
}
```

```

function scrollTip(){
if (document.tooltip2.document.nstip.left>=-document.tooltip2.document.nstip.document.width)
document.tooltip2.document.nstip.left-=5
else
document.tooltip2.document.nstip.left=150
}
</script>
<script language="JavaScript">
function YY_Layerfx(yyleft,yytop,yfmx,yfny,yydiv,yyblder,yyloop,yyto,yycnt,yystep)
{ //v1.2
//copyright (c)1999 Yarmat, Jaro von Flocken
if ((document.layers)||(document.all)){
with (Math) {ynextx= eval(yfmx)}
with (Math) {ynexty= eval(yfny)}
yycnt=(yyloop && yynt=>yynt*yyblder)?0:yynt+yystep;
if (document.layers){
eval(yydiv+".top="+(ynexty+yytop))
eval(yydiv+".left="+(ynextx+yleft))
}
if (document.all){
eval("yydiv=yydiv.replace(/.layers/gi, '.all')");
eval(yydiv+".style.pixelTop="+(ynexty+yytop));
eval(yydiv+".style.pixelLeft="+(ynextx+yleft));
}
}

argStr='YY_Layerfx('+yleft+', '+yytop+', '+yfmx+', '+yfny+', '+yydiv+', '+yyblder+', '+yyloop+', '+yyto+', '+yycnt+', '+yynt+')';
if (yynt<=>yynt*yyblder){eval(yydiv+".yyto=setTimeout(argStr,yyto)};
}

}

function YY_Mbusetrace(evt) { //v1.2 copyright (c)1999 Yarmat
if (yyns4)
{if (evt.pageX) {yy_ml=evt.pageX; yy_mt=evt.pageY;} }
else{
yy_ml=(event.clientX + document.body.scrollLeft);
yy_mt=(event.clientY + document.body.scrollTop);
}
if (yy_tracescript)eval(yy_tracescript)
}
</script>
<script language="JavaScript">
function PopWin()

```

```
{
  var PopWin =
window.open("new.htm", "PopWin", "toolbar=no, directories=no, scrollbars=yes, height=350, width=400");
}
</script>
```

右键打开收藏夹

脚本说明：

把如下代码加入 <body>区域中

```
<script language=JavaScript1.2>

if (document.all)

document.body.onmousedown=new Function("if
(event.button==2||event.button==3)window.external.addFavorite('Upper1/default.htm', '怀柔网
')")

</script>
```

字符围绕鼠标

脚本说明：

把如下代码加入 <head>区域中

```
<SCRIPT language=javascript>
<!--//This is a JS program for Sword Jin's JoyFM homepage.All rights reserved.
var cx=0;
var cy=0;
var val=0;
function locate()
{   cx=window.event.x;
    cy=window.event.y;

}
document.onmousemove=locate;
function follow(i)
{   var x;
    if(i<4)x=cx-50+i*10;
    else x=cx-25+i*10;
    var y=cy-20+Math.floor(Math.random()*40);
    w=eval("word"+i);
```

```

    with(w.style)
    {
        left=x.toString()+"px";
        top=y.toString()+"px";
    }
}
function show(i)
{
    var w=eval("word"+i);
    with(w.style)
    {
        visibility="visible";
        s=parseInt(fontSize);
        if(s>=200)s-=100;
        else if(s>90&&s<=100)
        {
            s-=85;
            clearInterval(val);
            if(i<5)val=setInterval("show("+(i+1)+")",20);
        }
        fontSize=s;
    }
}
}
function start()
{
    for(i=1;i<=5;i++)
    {
        val=setInterval("show(1)",20);
        setInterval("follow("+i+")",100);
    }
}
}

//-->
</SCRIPT>
<SCRIPT language=javascript>
    var word=new Array(5);
    word[1]="J";word[2]="o";word[3]="y";word[4]="F";word[5]="m";
    for(i=1;i<=5;i++)
        document.write("<div id='word'+i+' '
style='width:20px;height:20px;position:absolute;font-size:1000;visibility:hidden'><font
face='Forte' color='#00FF00'>"+word[i]+"</font></div>");start();

</SCRIPT>

```

各种形状的鼠标

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<table width="53%" border="0">
  <tr>
    <td width="51%" height="25">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:hand">style="cursor:hand"</a></b></font></div>
    </td>
    <td width="49%" valign="top" height="25">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:crosshair">style="cursor:crosshair"</a></b></font></div>
    </td>
  </tr>
  <tr>
    <td width="51%" height="29" valign="top">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:text">style="cursor:text"</a></b></font></div>
    </td>
    <td width="49%" valign="top" height="29">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:wait">style="cursor:wait"</a></b></font></div>
    </td>
  </tr>
  <tr>
    <td width="51%" height="29" valign="top">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:move">style="cursor:move"</a></b></font></div>
    </td>
    <td width="49%" valign="top" height="29">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:help">style="cursor:help"</a></b></font></div>
    </td>
  </tr>
  <tr>
    <td width="51%" height="29" valign="top">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:e-resize">style="cursor:e-resize"</a></b></font></div>
    </td>
    <td width="49%" valign="top" height="29">
      <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b><a
href="cursor.htm" style="cursor:n-resize">style="cursor:n-resize"</a></b></font></div>
    </td>
  </tr>
```

```

</tr>
<tr>
  <td width="51%" height="29" valign="top">
    <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b>a
href="cursor.htm" style="cursor:nw-resize">style="cursor:nw-resize"</a></b></font></div>
  </td>
  <td width="49%" valign="top" height="29">
    <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b>a
href="cursor.htm" style="cursor:w-resize">style="cursor:w-resize"</a></b></font></div>
  </td>
</tr>
<tr>
  <td width="51%" height="29" valign="top">
    <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b>a
href="cursor.htm" style="cursor:s-resize">style="cursor:s-resize"</a></b></font></div>
  </td>
  <td width="49%" valign="top" height="29">
    <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b>a
href="cursor.htm" style="cursor:se-resize">style="cursor:se-resize"</a></b></font></div>
  </td>
</tr>
<tr>
  <td width="51%" height="29" valign="top">
    <div align="left"><font face="Arial, Helvetica, sans-serif" size="2"><b>a
href="cursor.htm" style="cursor:sw-resize">style="cursor:sw-resize"</a></b></font></div>
  </td>
  <td width="49%" valign="top" height="29">
    <div align="left"></div>
  </td>
</tr>
</table>

```

跟随鼠标的字符

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<style type="text/css">
```

```
.spanstyle {
```

```

  COLOR: #ffd8ff; FONT-FAMILY: 宋体; FONT-SIZE: 10pt; POSITION: absolute; TOP: -50px;
  VISIBILITY: visible

```

```
}

</style>

<script>

var x,y

var step=18

var flag=0

// Your snappy message. Important: the space at the end of the sentence!!!

var message=" 怀柔网欢迎你的光临!"

message=message.split("")

var xpos=new Array()

for (i=0;i<=message.length-1;i++) {

    xpos[i]=-50

}

var ypos=new Array()

for (i=0;i<=message.length-1;i++) {

    ypos[i]=-200

}

function handlerMM(e){

    x = (document.layers) ? e.pageX : document.body.scrollLeft+event.clientX

    y = (document.layers) ? e.pageY : document.body.scrollTop+event.clientY
```

```

flag=1

}

function makesnake() {

if (flag==1 && document.all) {

    for (i=message.length-1; i>=1; i--) {

        xpos[i]=xpos[i-1]+step

        ypos[i]=ypos[i-1]

    }

    xpos[0]=x+step

    ypos[0]=y

    for (i=0; i<message.length-1; i++) {

        var thisspan = eval("span"+(i)+".style")

        thisspan.posLeft=xpos[i]

        thisspan.posTop=ypos[i]

    }

}

else if (flag==1 && document.layers) {

    for (i=message.length-1; i>=1; i--) {

        xpos[i]=xpos[i-1]+step

```



```
        ypos[i]=ypos[i-1]

    }

    xpos[0]=x+step

    ypos[0]=y

    for (i=0; i<=message.length-1; i++) {

        var thisspan = eval("document.span"+i)

        thisspan.left=xpos[i]

        thisspan.top=ypos[i]

    }

}

var timer=setTimeout("makesnake()",30)

}

</script>
```

第二步 把如下代码加入 <body>区域中

```
<script>
```

```
<!-- Beginning of JavaScript -
```

```
for (i=0; i<=message.length-1; i++) {
```

```

        document.write("<span id='span"+i+"' class='spanstyle'>")

document.write(message[i])

        document.write("</span>")

}

if (document.layers){

document.captureEvents(Event.MOUSEMOVE);

}

document.onmousemove = handlerMM;

// - End of JavaScript - -->

</script>

```

第三步 把 <body>改为

```
<body bgcolor="#ffffff" onload="makesnake()">
```

非图片鼠标跟踪器

脚本说明：

第一步：把如下代码加入 <body>区域中

```
<STYLE TYPE="text/css">
<!--
```

```

BODY{
overflow:scroll;
overflow-x:hidden;
}

.s1
{
position : absolute;
font-size : 12pt;
color : blue;
visibility: hidden;

```

```

}

.s2
{
  position : absolute;
  font-size : 20pt;
  color    : red;
  visibility : hidden;
}

.s3
{
  position : absolute;
  font-size : 16pt;
  color    : gold;
  visibility : hidden;
}

.s4
{
  position : absolute;
  font-size : 14pt;
  color    : lime;
  visibility : hidden;
}
-->
</STYLE>

```

第二步：把如下代码加入 <body>区域中

```

<DIV ID="div1" CLASS="s1">*</DIV>
<DIV ID="div2" CLASS="s2">*</DIV>
<DIV ID="div3" CLASS="s3">*</DIV>
<DIV ID="div4" CLASS="s4">*</DIV>

```

```

<script language="javascript" type="text/javascript" class="s5">

```

```

var nav = (document.layers);
var tmr = null;
var spd = 50;
var x = 0;
var x_offset = 5;
var y = 0;

```

```
var y_offset = 15;
```

```
if(nav) document.captureEvents(Event.MOUSEMOVE);  
document.onmousemove = get_mouse;
```

```
function get_mouse(e)  
{  
  x = (nav) ? e.pageX : event.clientX+document.body.scrollLeft;  
  y = (nav) ? e.pageY : event.clientY+document.body.scrollTop;  
  x += x_offset;  
  y += y_offset;  
  beam(1);  
}
```

```
function beam(n)  
{  
  if(n<5)  
  {  
    if(nav)  
    {  
      eval("document.div"+n+".top="+y);  
      eval("document.div"+n+".left="+x);  
      eval("document.div"+n+".visibility='visible'");  
    }  
    else  
    {  
      eval("div"+n+".style.top="+y);  
      eval("div"+n+".style.left="+x);  
      eval("div"+n+".style.visibility='visible'");  
    }  
    n++;  
    tmr=setTimeout("beam("+n+")",spd);  
  }  
  else  
  {  
    clearTimeout(tmr);  
    fade(4);  
  }  
}
```

```
function fade(n)  
{  
  if(n>0)  
  {
```

```
    if(nav)eval("document.div"+n+".visibility='hidden'");
    else eval("div"+n+".style.visibility='hidden'");
    n--;
    tmr=setTimeout("fade("+n+")",spd);
  }
  else clearTimeout(tmr);
}

// -->
</script>
```

显示链接特征

脚本说明：

第一步 把如下代码加入 <head>区域中：

```
<SCRIPT language=javascript>

function mOver(){

document.all.tags("A").item(0).style.textDecorat ion="none";

}

</SCRIPT>
```

```
<STYLE type=text/css>A:hover {

COLOR: orange

}

</STYLE>
```

```
<STYLE type=text/css>A:hover {

CURSOR: ne-resize

}


```

```
A {  
  
    TEXT-DECORATION: none  
  
}  
  
</STYLE>
```

第二步 把如下代码加入 <body>区域中：

```
<A href="Upper1/default.htm" 怀柔网 </A>
```

改变链接属性

脚本说明：

把如下代码加入 <body>区域中

```
<a href="home.html" style="color:navy"  
onmouseover="this.style.fontWeight='bold';"  
onmouseout="this.style.fontWeight='normal';">IE Users highlight  
this and it will turn bold! </a>
```

显示鼠标坐标

脚本说明：

第一步 把如下代码加入 <body>区域中：

```
<SCRIPT LANGUAGE="JavaScript">  
if (navigator.appName == 'Netscape')  
{  
    document.captureEvents(Event.MOUSEMOVE);  
    document.onmousemove = netscapeMouseMove;  
}  
  
function netscapeMouseMove(e) {  
    if (e.screenX != document.test.x.value && e.screenY != document.test.y.value)  
    {  
        document.test.x.value = e.screenX;  
        document.test.y.value = e.screenY;  
    }  
}  
  
function microsoftMouseMove() {  
    if (window.event.x != document.test.x.value && window.event.y != document.test.y.value)  
    {  
        document.test.x.value = window.event.x;
```

```

document.test.y.value = window.event.y;
}
}
</SCRIPT>
<FORM NAME="test">
X: <INPUT TYPE="TEXT" NAME="x" SIZE="4"> Y: <INPUT
TYPE="TEXT" NAME="y" SIZE="4">
</FORM>

```

第二步：把 <body>中内容改为：

```
<body bgcolor="#ffffff" onmouseover="microsoftMouseMove()">
```

随鼠标的彩色字符

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<STYLE>.spanstyle {
COLOR: #0066ff; FONT-FAMILY: 隶书; FONT-SIZE: 14pt; FONT-WEIGHT: normal; POSITION: absolute;
TOP: -50px; VISIBILITY: visible
}
</STYLE>

```

第二步 把如下代码加入 <body>区域中

```

<SCRIPT language=javascript>
var message=欢迎光临 javascript精彩世界 !";
var x,y;
var step=12;
var flag=0;

message=message.split("");
var xpos=new Array();
for (i=0;i<=message.length-1;i++) {
    xpos[i]=-50;
}

var ypos=new Array();
for (i=0;i<=message.length-1;i++) {
    ypos[i]=-50;
}

function handlerMM(e) {
    x = (document.layers) ? e.pageX : document.body.scrollLeft+event.clientX+10;
    y = (document.layers) ? e.pageY : document.body.scrollTop+event.clientY;
    flag=1;
}

```

```

function makesnake() {
    if (flag==1 && document.all) {
        for (i=message.length-1; i>=1; i--) {
            xpos[i]=xpos[i-1]+step;
            ypos[i]=ypos[i-1];
        }
        xpos[0]=x+step;
        ypos[0]=y;

        for (i=0; i<=message.length-1; i++) {
            var thisspan = eval("span"+(i)+".style");
            thisspan.posLeft=xpos[i];
            thisspan.posTop=ypos[i];
            thisspan.color=Math.random() * 255 * 255 * 255 + Math.random() * 255 * 255
+ Math.random() * 255;
        }
    }
    else if (flag==1 && document.layers) {
        for (i=message.length-1; i>=1; i--) {
            xpos[i]=xpos[i-1]+step;
            ypos[i]=ypos[i-1];
        }
        xpos[0]=x+step;
        ypos[0]=y;

        for (i=0; i<message.length-1; i++) {
            var thisspan = eval("document.span"+i);
            thisspan.left=xpos[i];
            thisspan.top=ypos[i];
            thisspan.color=Math.random() * 255 * 255 * 255 + Math.random() * 255 * 255
+ Math.random() * 255;
        }
    }
}
</SCRIPT>

```

```

<SCRIPT language=javascript>
for (i=0;i<=message.length-1;i++) {
    document.write("<span id='span'+i+' ' class='spanstyle'>");
    document.write(message[i]);
    document.write("</span>");
}

```



```

    if (document.layers) {
        document.captureEvents(Event.MOUSEMOVE);
    }
    document.onmousemove = handlerMM;
</SCRIPT>

```

```

<SCRIPT language=javascript>
function pageonload() {
    makesnake();
    window.setTimeout("pageonload();", 2);
}
</SCRIPT>

```

第三步 把 <body>改为

```
<body bgcolor="#ffffff" onload=javascript:pageonload(>
```

间隔状态栏跑马灯

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<SCRIPT language="JavaScript">
<!--
function scrollit(seed) {
var m1 = "HI: 你好! ";
var m2 = "欢迎访问南京有线电视台网站 ";
var m3 = "请多提意见,谢谢! ";
var m4 = "E-MAIL:webmaster@hrw.cn";
var m5 = "Upper1/default.htm";
var msg=m1+m2+m3+m4+m5;
var out = " ";
var c = 1;
if (seed > 100) {
seed--;
cmd="scrollit("+seed+)";
timerTwo=window.setTimeout(cmd,100);
}
else if (seed <= 100 && seed > 0) {
for (c=0 ; c < seed ; c++) {
out+=" ";
}
out+=msg;
seed--;
window.status=out;
cmd="scrollit("+seed+)";

```

```

timerTwo=window.setTimeout(cmd,100);
}
else if (seed <= 0) {
if (-seed < msg.length) {
out+=msg.substring(-seed,msg.length);
seed--;
window.status=out;
cmd="scrollit("+seed+")";
timerTwo=window.setTimeout(cmd,100);
}
else {
window.status=" ";
timerTwo=window.setTimeout("scrollit(100)",75);
}
}
}
}
}
}

```

```
//-->
```

```
</SCRIPT>
```

第二步 把如下代码加入 <body>区域中

```
<body background=bag.gif onLoad="scrollit(100)">
```

文字从右弹出

脚本说明：

把如下代码加入 <head>区域中

```
<script language="JavaScript">
```

```
var MESSAGE = " 欢迎来到怀柔网网站，请多提意见。谢谢！ "
```

```
var POSITION = 150
```

```
var DELAY = 10
```

```
var scroll = new statusMessageObject()
```

```
function statusMessageObject(p,d) {
```

```

this.msg = MESSAGE

this.out = " "

this.pos = POSITION

this.delay = DELAY

this.i = 0

this.reset = clearMessage}

function clearMessage() {

    this.pos = POSITION}

function scroller() {

    for (scroll.i = 0; scroll.i < scroll.pos; scroll.i++) {

        scroll.out += " "}

    if (scroll.pos >= 0)

        scroll.out += scroll.msg

    else scroll.out = scroll.msg.substring(-scroll.pos,scroll.msg.length)

    window.status = scroll.out

    scroll.out = " "

    scroll.pos--

    if (scroll.pos < -(scroll.msg.length)) {

        scroll.reset()}

    setTimeout ('scroller()',scroll.delay)}

function snapIn(jumpSpaces,position) {

    var msg = scroll.msg

```

```

var out = ""

for (var i=0; i<position; i++)

    {out += msg.charAt(i)}

for (i=1; i<jumpSpaces; i++)

    {out += " "}

out += msg.charAt(position)

window.status = out

if (jumpSpaces <= 1) {

    position++

    if (msg.charAt(position) == ' ')

        {position++ }

    jumpSpaces = 100-position

} else if (jumpSpaces > 3)

    {jumpSpaces *= .75}

else

    {jumpSpaces--}

if (position != msg.length) {

    var cmd = "snapIn(" + jumpSpaces + "," + position + ")";

    scrollID = window.setTimeout(cmd,scroll.delay);

} else {    window.status=""

    jumpSpaces=0

    position=0

```

```
cmd = "snapIn(" + jumpSpaces + "," + position + ")";  
  
scrollID = window.setTimeout(cmd,scroll.delay);  
  
return false }  
  
return true}  
  
snapIn(100,0);  
  
</script>
```

文字从左依次弹出

脚本说明：

把如下代码加入 <head>区域中

```
<script language="JavaScript">  
  
var msg = "欢迎来到怀柔网网站，请多提意见。谢谢！" ;  
  
var interval = 120  
  
var spaceLen = 120;  
  
var space10=" ";  
  
var seq=0;  
  
function Scroll() {  
  
len = msg.length;  
  
window.status = msg.substring(0, seq+1);  
  
seq++;  
  
if ( seq >= len ) {  
  
seq = 0;
```

```
window.status = '';  
  
window.setTimeout("Scroll()", interval );  
  
}  
  
else  
  
window.setTimeout("Scroll()", interval );  
  
}  
  
Scroll();  
  
</script>
```

文字从右到左移动

脚本说明：

把如下代码加入 <head>区域中

```
<script>  
  
<!-- Beginning of JavaScript Applet -----  
  
function scrollIt_r2l(seed)  
  
{ var m1 = "欢迎来到怀柔网网站，请多提意见。谢谢！" ;  
  
var m2 = " " ;  
  
var msg=m1+m2;  
  
var out = " " ;  
  
var c = 1;  
  
var speed = 120;  
  
if (seed > 100)  
  
{  
seed-=2;
```

```

        var cmd="scrollit_r2l(" + seed + ")";

        timerTwo=window.setTimeout(cmd,speed);}

else if (seed <= 100 && seed > 0)

{
        for (c=0 ; c < seed ; c++)

                {      out+=" ";}

        out+=msg;      seed-=2;

var cmd="scrollit_r2l(" + seed + ")";

window.status=out;

timerTwo=window.setTimeout(cmd,speed); }

        else if (seed <= 0)

{
        if (-seed < msg.length)

                {

                        out+=msg.substring(-seed,msg.length);

                        seed-=2;

                        var cmd="scrollit_r2l(" + seed + ")";

                        window.status=out;

                        timerTwo=window.setTimeout(cmd,speed);}

        else {      window.status=" ";

                timerTwo=window.setTimeout("scrollit_r2l(100)",speed);

}

}

}

```

```
scrollIt_r2l(100);
```

```
// -- End of JavaScript code -->
```

```
</script>
```

文字快速依次弹出

脚本说明：

把如下代码加入 <head>区域中

```
<script language="JavaScript">
```

```
<!--
```

```
function statusMessageObject(p,d) {
```

```
    this.msg = MESSAGE
```

```
    this.out = " "
```

```
    this.pos = POSITION
```

```
    this.delay = DELAY
```

```
    this.i      = 0
```

```
    this.reset = clearMessage
```

```
}
```

```
function clearMessage() {
```

```
    this.pos = POSITION
```

```
}
```

```
var POSITION = 100
```

```
var DELAY   = 4
```

```
var MESSAGE = "欢迎来到怀柔网网站，请多提意见。谢谢！"
```



```

var scroll = new statusMessageObject()

function scroller() {

  for (scroll.i = 0; scroll.i < scroll.pos; scroll.i++) {

    scroll.out += " "

  }

  if (scroll.pos >= 0)

    scroll.out += scroll.msg

  else scroll.out = scroll.msg.substring(-scroll.pos,scroll.msg.length)

  window.status = scroll.out

  scroll.out = " "

  scroll.pos--

  if (scroll.pos < -(scroll.msg.length)) {

    scroll.reset()

  }

  setTimeout ('scroller()',scroll.delay)

}

function snapIn(jumpSpaces,position) {

  var msg = scroll.msg

  var out = ""

  for (var i=0; i<position; i++)

    {out += msg.charAt(i)}

  for (i=1;i<jumpSpaces;i++)

```

```
{out += " "}  
  
out += msg.charAt(position)  
  
window.status = out  
  
if (jumpSpaces <= 1) {  
  
    position++  
  
    if (msg.charAt(position) == ' ')  
  
        {position++ }  
  
    jumpSpaces = 100-position  
  
} else if (jumpSpaces > 3)  
  
    {jumpSpaces *= .75}  
  
else  
  
    {jumpSpaces--}  
  
if (position != msg.length) {  
  
    var cmd = "snapIn(" + jumpSpaces + "," + position + ")";  
  
    scrollID = window.setTimeout(cmd,scrollID.delay);  
  
} else {  
  
    window.status=""  
  
    jumpSpaces=0  
  
    position=0  
  
    cmd = "snapIn(" + jumpSpaces + "," + position + ")";  
  
    scrollID = window.setTimeout(cmd,scrollID.delay);  
  
    return false
```

```
}  
  
    return true  
  
}  
  
snapIn(100,0);  
  
// -->  
  
</script>
```

文字组合弹出

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<script language="javascript">  
  
<!-- Hide this script from old browsers -->  
  
var speed = 10  
  
var pause = 1500  
  
var timerID = null  
  
var bannerRunning = false  
  
var ar = new Array()  
  
ar[0] = "欢迎来到怀柔网网站！  "  
  
ar[1] = "欢迎光临网页特效专栏  "  
  
ar[2] = "请多提意见，谢谢！  "  
  
var message = 0
```

```
var state = ""

clearState()

function stopBanner() {

    if (bannerRunning)

        clearTimeout(timerID)

    bannerRunning = false

}

function startBanner() {

    stopBanner()

    showBanner()

}

function clearState() {

    state = ""

    for (var i = 0; i < ar[message].length; ++i) {

        state += "0"

    }

}

function showBanner() {

    if (getString()) {

        message++

        if (ar.length <= message)
```

```

        message = 0

        clearState()

        timerID = setTimeout("showBanner()", pause)

        bannerRunning = true
    } else {

        var str = ""

        for (var j = 0; j < state.length; ++j) {

            str += (state.charAt(j) == "1") ? ar[message].charAt(j) : " "

        }

        window.status = str

        timerID = setTimeout("showBanner()", speed)

        bannerRunning = true

    }

}

function getString() {

    var full = true

    for (var j = 0; j < state.length; ++j) {

        if (state.charAt(j) == 0)

            full = false

    }

    if (full)

        return true

```

```
while (1) {  
  
    var num = getRandom(ar [message]. length)  
  
    if (state.charAt(num) == "0")  
  
        break  
  
}  
  
state = state.substring(0, num) + "1" + state.substring(num + 1, state.length)  
  
return false  
  
}  
  
function getRandom(max) {  
  
    return Math.round((max - 1) * Math.random())  
  
}  
  
// -- End Hiding Here -->  
  
</script>
```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" onLoad="startBanner()">
```

文字不停闪烁

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<script language="">
```

```
<!--
```

```
var yourwords = "欢迎光临怀柔网网站 !!!";
```

```
var speed = 700;

var control = 1;

function flash()

{

    if (control == 1)

        {

            window.status=yourwords;

            control=0;

        }

    else

        {

            window.status="";

            control=1;

        }

    setTimeout("flash()",speed);

}

// -->

</script>
```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" onLoad="flash()">
```

状态栏显示链接

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<script language="JavaScript">
<!--
function MM_displayStatusMsg(msgStr) { //v1.0
    status=msgStr;
    document.MM_returnValue = true;
}
//-->
</script>
```

第二步 把如下代码加入 <body>区域中

```
<a href="http://www.yahoo.com"
onMouseOver="MM_displayStatusMsg( '中文雅虎搜索引擎!!! ');
return document.MM_returnValue"><font color="#0000FF">中文雅虎 </font></a><br>
<br>
<a href="http://www.163.net"
onMouseOver="MM_displayStatusMsg( '中国人气最旺的中文网站 ' );
return document.MM_returnValue"><font color="#0000FF">网易 </font></a> <br>
<br>
<a href="http://www.sina.com.cn"
onMouseOver="MM_displayStatusMsg( '最好最全的新闻网站 ' );
return document.MM_returnValue"><font color="#0000FF">新浪网 </font></a>
```

title显示日期

脚本说明：

把如下代码加入 <body>区域中：

```
<script language="JavaScript1.2">
<!--hide
var ismMonth = new
Array("1月 ", "2月 ", "3月 ", "4月 ", "5月 ", "6月 ", "7月 ", "8月 ", "9月 ", "10月 ", "11月 ", "12月 ");
var ismDay = new
Array("星期日 ", "星期一 ", "星期二 ", "星期三 ", "星期四 ", "星期五 ", "星期六 ", "星期日 ");
today = new Date ();
Year=today.getYear();
Date=today.getDate();
if (document.all)
document.title="今天是： "+Year+"年 "+ismMonth[today.getMonth()+Date]+"日
"+ismDay[today.getDay()]
//--hide-->
</script>
```

文字来回出现

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">

<!-- Begin

var Message="欢迎光临怀柔网精彩 JavaScript集锦!!";

var place=1;

function scrollIn() {

window.status=Message.substring(0, place);

if (place >= Message.length) {

place=1;

window.setTimeout("scrollOut()", 300);

} else {

place++;

window.setTimeout("scrollIn()", 50);

}

}

function scrollOut() {

window.status=Message.substring(place, Message.length);

if (place >= Message.length) {

place=1;

window.setTimeout("scrollIn()", 100);

} else {

place++;
```

```
window.setTimeout("scrollOut()", 50);

    }

}

// End -->

</SCRIPT>
```

第二步 把 <body>中的内容改为：

```
<body bgcolor="#ffffff" onLoad="scrollIn()">
```

文字慢慢出现

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- hide script from old browsers
var phrase = "精彩 javascript特效光临你的光临!!! ";
var lenPhrase = phrase.length;
var phraseOut = "";
var pause = 25;
var i=0;
var j=0;
var animateWidth = 20;
var position=animateWidth;
function stack() {
    if (phrase.charAt(i) != " ") {
        phraseOut = "";
        for (j=0; j<i; j++) {
            phraseOut += phrase.charAt(j);
        }
        for (j=i; j<position; j++) {
            phraseOut += " ";
        }
        phraseOut += phrase.charAt(i);
        for (j=position; j<animateWidth; j++) {
            phraseOut += " ";
        }
        window.status = phraseOut;
```

```

        if (position == i) {
            animateWidth++;
            position = animateWidth;
            i++;
        }
        else {
            position--;
        }
    }
    else {
        i++
    }
    if (i<lenPhrase) {
        setTimeout("stack()",pause);
    }
}
// end hiding contents -->
</SCRIPT>

```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" OnLoad="stack()">
```

状态栏特殊效果

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<script language="JavaScript">
```

```

<!-- Funny text script by Bart Jellema
var hellotext="网页特效欢迎你 "
var thetext=""
var started=false
var step=0
var times=1

function welcomeText()
{
    times--
    if (times==0)
    {
        if (started==false)
        {
            started = true;
            window.status = hellotext;

```

```

        setTimeout("anim()",1);
    }
    thetext = helloertext;
}
}

```

```

function showstatustext(txt)
{
    thetext = txt;
    setTimeout("welcometext()",4000)
    times++
}

```

```

function anim()
{
    step++
    if (step==7) {step=1}
    if (step==1) {window.status='>==='+thetext+'===<'}
    if (step==2) {window.status='>=>'+thetext+'==<<'}
    if (step==3) {window.status='>>=>'+thetext+'<<<'}
    if (step==4) {window.status='=>>'+thetext+'<<<'}
    if (step==5) {window.status='=>=>'+thetext+'<<='}
    if (step==6) {window.status='=>=>'+thetext+'<=='}
    setTimeout("anim()",200);
}

```

</script>

第二步 把 <body>中的内容改为：

```

<body bgcolor="#ffffff" onLoad="welcometext()">
</textarea>
<SCRIPT LANGUAGE="JavaScript">

```

<!-- hide

```

function goHist(a)

```

```

{

```

```

    history.go(a);

```

```

}

```

```
//-->

</script>

<FORM METHOD="post">
<INPUT TYPE="button" VALUE="返回" onClick="goHist(-1)" style="background-color: #8000FF; color:
rgb(255,255,255)">
</form>
</center>
<br>
<br>
</body>
</html>
```

文字从中间出现

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">

<!-- escondamos
//texto a mostrarse
var mensaje=" *** Aqui puede usted colocar el mensaje que quiera";
mensaje+=" y esperar hasta que los usuarios se aburran de leerlo. ***";

//fraccion a mostrarse
var ancho=50;

//rutina de mensaje deslizando
function desliza(){
window.status=mensaje.substring(0,ancho);
mensaje+=mensaje.substring(0,1);
mensaje=mensaje.substring(1,mensaje.length);
setTimeout("desliza()",200);
}

// basta de esconder -->

</SCRIPT>
```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" onLoad="desliza(); return true;">
```

文字分解出现

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- hide from old browsers
```

```
var str=""
```

```
var direction="left"
```

```
function createArray(n)
```

```
{  
    for (var i = 0; i < n; i++) {this[i] = 0}  
    return this  
}
```

```
var js_mult1=3141
```

```
var js_mult2=5821
```

```
var js_m1=100000000
```

```
var js_m2=10000
```

```
var js_iseed=0
```

```
var js_iseed1=0
```

```
var js_iseed2=0
```

```
function random(n)
```

```
{  
    if (js_iseed == 0)  
    {  
        now = new Date()  
        js_iseed = now.getHours() + now.getMinutes() * 60  
            + now.getSeconds() * 3600  
    }  
    js_iseed1 = js_iseed / js_m2  
    js_iseed2 = js_iseed % js_m2  
    var tmp = (((js_iseed2 * js_mult1 + js_iseed1 * js_mult2) % js_m2) *  
        js_m2 + (js_iseed2 * js_mult2)) % js_m1  
    js_iseed = (tmp + 1) % js_m1  
    return (Math.floor((js_iseed/js_m1) * n))  
}
```

```
msgArray = createArray(5)
```

```

msgArray[0] = "欢迎你的光临 ,网页特效站欢迎你 "
msgArray[1] = "网页特效站欢迎你 ,网页特效站欢迎你 "
msgArray[2] = "记得要经常来呀 ,网页特效站欢迎你 "
msgArray[3] = "你可以给我写信 ,网页特效站欢迎你 "
msgArray[4] = "也可以给我留言 ,网页特效站欢迎你 "

msg = ""
dmsg = ""

function ddMessage()
{
    if (msg == dmsg) // reset and delay
    {

        msg = msgArray[random(5)]

        dmsg = ""
        for (var ii = 0; ii < msg.length; ii++) dmsg += " "

        JSCTimeOutID = window.setTimeout('ddMessage()',100)
        return true
    }

    // pick a character
    var ii = random(msg.length)

    var astr = dmsg.substring(0, ii)
    var bstr = msg.substring(ii, ii+1)
    var cstr = dmsg.substring(ii+1, dmsg.length)

    dmsg = astr+bstr+cstr
    window.status = dmsg

    JSCTimeOutID = window.setTimeout('ddMessage()',50)

    return true
}

```

```
<!-- done hiding -->
```

```
</SCRIPT>
```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" onload="JSCTimeOut ID = window.setTimeout('doMessage()',500);">
```

输入字符出现在状态栏

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<script language="JavaScript">
```

```
Ret = prompt( '你这里输入什么，在状态栏上就会显示什么 ', "something")
```

```
var temp
```

```
var f =
```

```
"
```

```
"
```

```
var f = f + (Ret)
```

```
var speedtogo = 50
```

```
var counter
```

```
function scrollon() {
```

```
    temp = f.substring(0,1);
```

```
    f += temp
```

```
    f = f.substring(1,100);
```

```
    window.status = f.substring(0,100);
```

```
    counter = setTimeout("scrollon()",speedtogo);
```

```
}
```

```
</script>
```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" onLoad="scrollon()">
```

文字多处出现

脚本说明：

把如下代码加入 <body>区域中

```
<SCRIPT language="javascript">

var scroll = true;
var num = 0;
function scrollStatus() {

    var statusText = "";
    var statusChars = new Array(' ', 'S', 'c', 'r', 'i', 'p', 't', ' ', 'B', 'y', ' ', 'P',
'y', 'r', 'o', 'B', 'r', 'i', 'a', 'n', '@', 'h', 'o', 't', 'm', 'a', 'i', 'l', '.', 'c', 'o',
'm');

    for (var l = 0; l < 1; l++) {
        for (var a = num; a < statusChars.length; a++)
            statusText += statusChars[a];
        for (var b = 0; b < num; b++)
            statusText += statusChars[b];
    }
    window.status = statusText;
    num++;
    if (num >= statusChars.length)
        num = 0;
    if (scroll) {
        setTimeout("scrollStatus()", 100);
    }
}

scrollStatus();
```

```
</SCRIPT>
<form name="form1">
<input name="stopIt" type="button" value="Stop Scrolling"
onClick="    if (scroll == false)
                scroll = true;
            else
                scroll = false;
            scrollStatus();
            scrollButton();"
">
</form>
```

```
<SCRIPT language="javascript">
```

```
var num = 0;
scrollButton();
```

```

function scrollButton() {
    var buttonChars = new Array('S', 't', 'o', 'p', ' ', 'S', 'c', 'r', 'o', 'l', 'l', 'i',
'n', 'g', ' ', ' ', ' ');
    var buttonText = "";
    for (var a = num; a < buttonChars.length; a++)
        buttonText += buttonChars[a];
    for (var b = 0; b < num; b++)
        buttonText += buttonChars[b];
    num++;
    if (num >= buttonChars.length)
        num = 0;
    document.form1.stopIt.value = buttonText;
    if (scroll) {
        setTimeout("scrollButton();", 100);
    }
}

```

</SCRIPT>

Title特效

脚本说明：

第一步 把如下代码加入 <body>区域中

```

<script language=javascript >
var text=document.title
var timerID

```

```

function newtext() {

    clearTimeout(timerID)

    document.title=text.substring(1, text.length)+text.substring(0,1)

    text=document.title.substring(0, text.length)

    timerID = setTimeout("newtext()", 100)

}

</script>

```

第二步 把如下代码加入 <body>区域中

```

<body bgcolor="#ffffff" onload="newtext()">

```

调节文字显示速度

脚本说明：

第一步 把如下代码加入 <body>区域中

```
<script language="javascript">
tid = 0;
pause = 0;
var to;
var bcount;
var tcount;

function bannerArray() {
    this.length = 54;
    this[1] = "                W";
    this[2] = "                Wé";
    this[3] = "                Wél";
    this[4] = "                Wélc";
    this[5] = "                Wélco";
    this[6] = "                Wélcóm";
    this[7] = "                Wélcómé";
    this[8] = "                Wélcómé ";
    this[9] = "                Wélcómé t";
    this[10] = "                Wélcómé to";
    this[11] = "                Wélcómé to ";
    this[12] = "                Wélcómé to I";
    this[13] = "                Wélcómé to IM";
    this[14] = "                Wélcómé to IMA";
    this[15] = "                Wélcómé to IMA S";
    this[16] = "                Wélcómé to IMA ST";
    this[17] = "                Wélcómé to IMA STU";
    this[18] = "                Wélcómé to IMA STUD";
    this[19] = "                Wélcómé to IMA STUDI ";
    this[20] = "                Wélcómé to IMA STUDIO";
    this[21] = "                Wélcómé to IMA STUDIOS";
    this[22] = "                Wélcómé to IMA STUDIOS'";
    this[23] = "                Wélcómé to IMA STUDIOS' Si";
    this[24] = "                Wélcómé to IMA STUDIOS' Sit";
    this[25] = "                Wélcómé to IMA STUDIOS' Site!";
    this[26] = "                ";
    this[27] = "                Wélcómé to IMA STUDIOS' Site! ";
    this[28] = "                ";
    this[29] = "                Wélcómé to IMA STUDIOS' Site! ";
    this[30] = "                Wélcómé to IMA STUDIOS' Site! ";
    this[31] = "                Wélcómé to IMA STUDIOS' Site! ";
}
```

```

this[32] = "elcome to IMA STUDIOS' Site! ";
this[33] = "lcome to IMA STUDIOS' Site! ";
this[34] = "come to IMA STUDIOS' Site! ";
this[35] = "ome to IMA STUDIOS' Site! ";
this[36] = "me to IMA STUDIOS' Site!";
this[37] = "e to IMA STUDIOS' Site! ";
this[38] = "to IMA STUDIOS' Site!";
this[39] = "o IMA STUDIOS' Site! ";
this[40] = " IMA STUDIOS' Site!";
this[41] = " MA STUDIOS' Site!";
this[42] = "A STUDIOS' Site ";
this[43] = "STUDIOS' Site!";
this[44] = "TUDIOS' Site!";
this[45] = "UDIOS' Site!";
this[46] = "DIOS' Site!";
this[47] = "'IOS' Site!";
this[48] = "OS' Site!";
this[49] = " S' Site!";
this[50] = "' Site!";
this[51] = " Site!";
this[52] = "ite!";
this[53] = "te!";
this[54] = " e!";
return this
}

```

```

function MakeArray(n) {
    this.length = n;
    return this
}

```

```

banner = new bannerArray();
IMAbanner = 1;

```

```

function banner1(n) {
    tid=window.setTimeout("banner1(IMAbanner)",to);
    f.result.value = banner[IMAbanner];
    window.status = banner[IMAbanner];
    IMAbanner = IMAbanner + 1;
    if (IMAbanner == 55) {
        IMAbanner = 1;
    }
}

```

```
        window.clearTimeout(tid);
        tid=window.setTimeout("banner1()", to);
    }
}
```

```
function start(x) {
    f=x;
    to=60;
    banner1(x);
}
```

```
function pausing(x) {
    if (pause == 0) {
        pause = 1;
        f.P.value = "Paused";
        window.clearTimeout(tid);
    }
    else {
        pause = 0;
        f.P.value = " ";
        banner1(x);
    }
}
```

```
function speedup() {
    if (to != 0) {
        to = to-30;
    }
}
```

```
function slowdown() {
    to = to+30;
}
```

```
function refr() {
    to = 90;
    IMAbanner = 1;
}
```

```
function cleartids() {
    window.clearTimeout(tid);
}
```

```
</script>
```

```
<form name="banner">
<input type="button" name="加速" value="加速" onClick="speedup()">
<input type="button" name="减速" value="减速" onClick="slowdown()">
<input type="button" name="暂停" value="暂停" onclick="pausing(this.form)">
<input type="text" name="P" size=6>
<input type="text" name="result" size=28>
<input type="reset" name="复原" value="复原" onclick="refr()">
</form>
```

第二步 把如下代码加入 <body>区域中

```
<body bgcolor="#ffffff" onload="start(document.forms[0])" onunload="cleartids()">
```

状态栏显示标准时钟

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT language="JavaScript">
```

```
function doClock() {

    window.setTimeout( "doClock()", 1000 );

    today = new Date();

    self.status = today.toString();

}
```

```
</SCRIPT>
```

第二步 把 <body>中的内容改为：

```
<body bgcolor="#ffffff" onLoad="doClock()">
```

控制他人进入相应页面脚本

脚本说明：

第一步 把如下代码加入首页 (本例为 password1.htm)的 <head>区域中

```
<SCRIPT LANGUAGE="javascript">
<!-- Hide
var new_window = null;
function password() {
new_window = window.open('password2.htm', 'pass', 'width=350,height=150,resizable=1');//你可以改变链接和窗口大小
}
//-->
</SCRIPT>
```

第二步 在首页 (本例为 password1.htm)的 <body>区域中加入 (用来调用输入密码页)

```
<A HREF="javascript:password()">这里 </A>
```

第三步 在 password2.htm(你可以自己随着设定 页面 <head>中加入

```
<SCRIPT LANGUAGE="JavaScript">
<!--Hide
function goForit() {
    var location;
    var password;
    password=this.document.testform.inputbox.value
    location=password + ".htm"
    fetch(location)
    theKeeper=window.close()
}
function fetch(location) {
    var root;
    if (opener.closed)
{root=window.open('', 'toolbar=yes, location=yes, status=yes, menubar=yes, scrollbars=yes, resizable=yes, copyhistory=no');
    root.location.href = location;
} else {
    opener.location.href = location;
}
}
//-->
</SCRIPT>
```

第四步 在 password2.htm(你可以自己随着设定 页面 <body>中加入

```
<CENTER>
<FONT SIZE=3>输入密码, 然后按 submit进入密码页 (即进入相应的 time1.htm页面中 )</FONT>
<FORM NAME="test form">
```

```
<INPUT TYPE="text" NAME="inputbox" VALUE="" size=20>
<INPUT TYPE="button" NAME="button" Value="Submit" onClick="goForit(this.form)"></FORM>
</FONT><p>
密码为：time1
</CENTER>
```

输入密码后才能进入页面

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Hide
al="`1234567890-=-!@#$/^&*()_+qwer"
+"tyuiop[]QWERTYUIOP{}|asdfghjkl;A"
+"SDFGHJKL:zxcvbm,./ZXCVBNM<>?";
ab1="";
bctr=0;
function ckPwd(){
  tst=document.isn.username.value
  +"*"+document.isn.passwrld.value+"*";
  ls=document.pd.pe.value;
  a=eval(ls.substring(0,2))-91;
  ls=ls.substring(2,ls.length);
  nls="";
  flg=0;
  while (ls.length>12){
    ab=eval(ls.substring(0,2))-89;
    ab1=(ab1=="?"?" "+ab:ab1);
    oab1=ab1;
    ls=ls.substring(2,ls.length);
    for (var i=0;i<ab;i++){
      nr=eval(ls.substring(0,2))-a;
      ls=ls.substring(2,ls.length);
      nls+=al.charAt(nr);
    }
    nls+="*";
    if (nls.indexOf(tst)>-1){
      ls="";
      flg=1;
    }
  }
  if (flg==1){
    tstOk();
  }
  else{
```



```

bctr++;
if (bctr>3){
    location.href="nopass.htm";
}
else{
    alert('对不起 用户名 密码错误 .'
    +" 你已试登录 "+bctr+"次 .");
}
}
}

function tstOk(){
    ab1=ab1+" "+a;
    alert("正确, 开始登录!");
    location.href='\\c3a8e458b281.htm'+ab1;
}

// End Hiding -->
</SCRIPT>

```

第二步 把如下代码加入 <body>区域中

```

<FORM NAME="pd">
<!-- Paste the element from the pseudo-encrypter here -->
<!-- Paste this element into your script -->
<INPUT TYPE='hidden' NAME='pe'
VALUE='9393693658789606190557772053938953313395586858685868976834793758313033975834793758313
033 '>
</FORM>

```

```

<FORM NAME="isn">
<TABLE BORDER=2 CELLPADDING=5 CELLSPACING=0 BGCOLOR=BLUE>
<TR><TD COLSPAN=2 ALIGN=CENTER><FONT SIZE=4 COLOR=WHITE FACE="楷体_GB2312"><B>请您输入
</B></FONT></TD></TR>
<TR><TD><FONT SIZE=3 COLOR=WHITE><B>UserName:</B></FONT></TD>
<TD><INPUT TYPE="text" NAME="username" VALUE="" SIZE=10</TD></TR>
<TR><TD><FONT SIZE=3 COLOR=WHITE><B>Password:</B></FONT></TD>
<TD><INPUT TYPE="password" NAME="passwd" VALUE="" SIZE=10</TD></TR>
<TR><TD COLSPAN=2 ALIGN=CENTER><INPUT TYPE="button" NAME="btn" VALUE=" 登录 "
onClick="ckPwd();return false;"></TD></TR>
</TABLE></FORM>

```

```
<TABLE BORDER=1 WIDTH=486>
```

```
<TR><TD COLSPAN=3 ALIGN=CENTER><FONT FACE="楷体_GB2312"><B>你可以使用如下号  
码 :</B></FONT></TD></TR>
```

```
<TR><TD><FONT FACE="helvetica,arial,geneva">User Name:John<BR>Password: 4$3gb/a</TD>  
<TD><FONT FACE="helvetica,arial,geneva">User Name: Mary<BR>Password: hHHHk</TD>  
<TD><FONT FACE="helvetica,arial,geneva">User Name: Humphrey<BR>Password: humphrey</TD></TR>  
</TABLE>
```

输入正确进入密码保护页

脚本说明：

把如下代码加入 <body>区域中：

```
<SCRIPT LANGUAGE="JavaScript">  
function password() {  
var testV = 1;  
var pass1 = prompt( '请输入密码 (密码是 welcome):','');  
while (testV < 3) {  
if (!pass1)  
history.go(-1);  
if (pass1 == "welcome") {  
alert( '密码正确!');  
break;  
}  
testV+=1;  
var pass1 =  
prompt( '密码错误 请重新输入:');  
}  
if (pass1!="password" & testV ==3)  
history.go(-1);  
return " ";  
}  
document.write(password());  
</SCRIPT>
```

密码保护页面 (一)

脚本说明：

第一步 把如下代码加入的 <head>区域中

```
<script language="JavaScript">  
  
<!--  
function hidden(){  
var location=document.input.password.value + ".htm";  
this.location.href = location;  
}  
</script>
```

```
// -- End Hiding Here
```

```
// -->
```

```
</script>
```

第二步 在 <body>区域中加入

```
<form name="input">
```

```
<table>
```

```
<tr>
```

```
<td>Password:<p><input type="text" size="25" name="password"></p>
```

```
<p><input type="button" value="Enter" onclick="hidden()"></td>
```

```
</tr>
```

```
</table>
```

```
<table width="196">
```

```
</table>
```

```
</form>
```

在线考试脚本 (一)

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

```
function scorequiz(fom) {
```

```
    list=0
```

```
    if(fom.Q1.value!=null && fom.Q1.value!="") {list=list+1}
```

```
    if(fom.Q2.value!=null && fom.Q2.value!="") {list=list+1}
```

```
    if(fom.Q3.value!=null && fom.Q3.value!="") {list=list+1}
```

```
    if(fom.Q4.value!=null && fom.Q4.value!="") {list=list+1}
```

```
    if(fom.Q5.value!=null && fom.Q5.value!="") {list=list+1}
```

```
    if(fom.Q6.value!=null && fom.Q6.value!="") {list=list+1}
```

```
    if(fom.Q7.value!=null && fom.Q7.value!="") {list=list+1}
```

```
    if(fom.Q8.value!=null && fom.Q8.value!="") {list=list+1}
```

```
    if(fom.Q9.value!=null && fom.Q9.value!="") {list=list+1}
```

```
    if(fom.Q10.value!=null && fom.Q10.value!="") {list=list+1}
```

```
    fom.SCORE.value =eval(list)
```

```
        if (fom.SCORE.value<=8){
```

```
            ok="不及格！"
```

```
    }
```

```
function clearquiz(fom) {
```

```

list=0
form.Q1.value="?"
form.Q2.value="?"
form.Q3.value="?"
form.Q4.value="?"
form.Q5.value="?"
form.Q6.value="?"
form.Q7.value="?"
form.Q8.value="?"
form.Q9.value="?"
form.Q10.value="?"
form.SCORE.value =eval(list)
}

function msg() {
  alert("感谢参加测试，您的成绩已经将 mail给 Webmaster。 ")
}
// -->

</SCRIPT>

```

第二步 把如下代码加入 <body>区域中

```

<table width="75%" border="0" align="center">
  <tr>
    <td>
      <form name="quiz1"
action ="mailto:xiaoqinglu@263.net?subject=测试结果反馈 " method="post" enctype="text/plain"
onLoad="clearquiz(this.form)" onSubmit="msg()">
        您的姓名 :
        <input type="Text" name="Name" value="" class="pt9">
        <br>
        <hr>
        1. Internet上使用的网络协议是 : _____
        <ol>
          <input type="radio" name="Q1" value="*TCP/IP" onClick=Q1.value="*">
            TCP/IP<br>
          <input type="radio" name="Q1" value="X.25" onClick=Q1.value="X.25">
            X.25<br>
          <input type="radio" name="Q1" value="NetBEUI" onClick=Q1.value="NetBEUI">
            NetBEUI<br>
        </ol>
        2. 我们通过 _____长距离连接两台计算机使它们通讯。

```

```
<ol>
  <input type="radio" name="Q2" value="LAN" onClick=Q2.value="A">
  LAN<br>
  <input type="radio" name="Q2" value="*WAN" onClick=Q2.value="*">
  WAN<br>
  <input type="radio" name="Q2" value="WAIS" onClick=Q2.value="C">
  WAIS<br>
</ol>
```

3. HUB是指：_____

```
<ol>
  <input type="radio" name="Q3" value="网关 " onClick=Q3.value="网关 ">
  网关 <br>
  <input type="radio" name="Q3" value="网桥 " onClick=Q3.value="网桥 ">
  网桥 <br>
  <input type="radio" name="Q3" value="路由器 " onClick=Q3.value="路由器 ">
  路由器 <br>
  <input type="radio" name="Q3" value="*集线器 " onClick=Q3.value="*">
  集线器 <br>
</ol>
```

4. 56K MODEM的传输速度为：_____

```
<ol>
  <input type="radio" name="Q4" value="56Kbytes" onClick=Q4.value="A">
  每秒传输 56K bytes的数据。 <br>
  <input type="radio" name="Q4" value="*56kbps" onClick=Q4.value="*">
  每秒传输 56k bits的数据。 <br>
</ol>
```

5. Gateway是指：_____

```
<ol>
  <input type="radio" name="Q5" value="*网关 " onClick=Q5.value="*">
  网关 <br>
  <input type="radio" name="Q5" value="网桥 " onClick=Q5.value="B">
  网桥 <br>
  <input type="radio" name="Q5" value="路由器 " onClick=Q5.value="C">
  路由器 <br>
  <input type="radio" name="Q5" value="集线器 " onClick=Q5.value="D">
  集线器 <br>
</ol>
```

6. Http默认的端口是：_____

```
<ol>
  <input type="radio" name="Q6" value="8080" onClick=Q6.value="A">
  8080<br>
  <input type="radio" name="Q6" value="*80" onClick=Q6.value="*">
  80<br>
  <input type="radio" name="Q6" value="25" onClick=Q6.value="25">
```

25

7. JavaScript是一种类似于 C+的语言，比较难掌握： _____

<input type="radio" name="Q7" value="True" onClick=Q7.value="T">

True

<input type="radio" name="Q7" value="*False" onClick=Q7.value="*">

False

8. JAVA是 _____ 公司的产品：

<input type="radio" name="Q8" value="Microsoft" onClick=Q8.value="A">

Microsoft

<input type="radio" name="Q8" value="Novell" onClick=Q8.value="B">

Novell

<input type="radio" name="Q8" value="*SUN" onClick=Q8.value="*">

SUN

9. CGI通过 _____ 收集用户填写的表单信息：

<input type="radio" name="Q9" value="Form" onClick=Q9.value="A">

Fom

<input type="radio" name="Q9" value="环境变量 " onClick=Q9.value="*">

环境变量

<input type="radio" name="Q9" value="javascripts脚本 " onClick=Q9.value="C">

javascripts脚本

10. 服务器响应 "404 error"的含义是： _____

<input type="radio" name="Q10" value="*文件不存在 " onClick=Q10.value="*">

文件不存在

<input type="radio" name="Q10" value="Server error" onClick=Q10.value="B">

服务器错误

<input type="radio" name="Q10" value="Client error" onClick=Q10.value="C">

浏览器错误

<hr>

<input type="button" name="submit" value="开始评分 " onClick=scorequiz(this.fom)
class="pt9">

<input type="reset" name="reset" value="重新测试 " onClick=clearquiz(this.fom)
class="pt9">

<input type="submit" value="将成绩 MAIL给管理员 " onClick=scorequiz(this.fom)
name="submit" class="pt9">


```

        <br>
        你的考试成绩 :
        <input name="SCORE" type="text" class="pt9">
    </form>
</td>
</tr>
</table>

```

在线考试脚本 (二)

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<script language="JavaScript">

var Total_Question = 4    // 修改这里与题目数量一致

var msg = ""

// 正确答案
var Solution = new Array(Total_Question)
Solution[0] = "TCP/IP"
Solution[1] = "集线器 "
Solution[2] = "SUN"
Solution[3] = "Microsoft"
//

function GetSelectedButton(ButtonGroup)
{
    for (var x=0; x < ButtonGroup.length; x++)
        if (ButtonGroup[x].checked) return x
    return 0
}

function ReportScore(correct)
{
    var SedWin =
        window.open("", "scorewin", "scrollbars,width=300,height=220")
    var MustHave1 = "<HTML><HEAD><TITLE>测验成绩报告 </TITLE></HEAD><BODY>"
    var Percent = "<H2>测验成绩 : "+Math.round(correct/Total_Question*100)
        + "</H2><HR>"
    lastscore=Math.round(correct/Total_Question*100)
    if (lastscore == "100"){
        msg = MustHave1 +Percent + "<font color='red'>恭喜,全部答对了! </font><p>" +msg + "<input
type='button' value='close' onclick=javascript:window.close()></BODY></HTML>"}
    else {

```

```

    msg = MustHave1 +Percent + "<font color='red'>正确答案 : </font><p>" + msg + "<input
type='button' value='close' onclick=javascript:window.close()></BODY></HTML>"
}
    SedWin.document.write(msg)
    msg = "" //清空 msg
}

function Grade()
{
    var correct = 0
    var wrong = 0
    for (number=0; number < Total_Question; number++)
    {
        var fom = document.foms[number] // Question #
        var i = GetSelectedButton(fom.q1)
        if (fom.q1[i].value == "1")
        { correct++ }
        else
        { wrong++
            msg += "Question "+(number+1)+". "
                +Solution[number]+"<BR>"
        }
    }
    ReportScore(correct)
}

</script>

```

第二步 把如下代码加入 <body>区域中

```

<table width="79%" border="0" align="center">
<tr>
<td>
<form>
三个非常简单的问题 : <p>
(1) Internet上使用的网络协议是 : _____
<br>
<input type="radio" name="q1" value="0" checked>X.25
<input type="radio" name="q1" value="1">TCP/ IP
<input type="radio" name="q1" value="0">NetBEUI
<br><br> </form>

```



```
<form>
(2)HUB是指： _____
<br>
<input type="radio" name="q1" value="0" checked>网桥
<input type="radio" name="q1" value="1">集线器
<input type="radio" name="q1" value="0">网关
<input type="radio" name="q1" value="0">路由器
<br><Br> </form>
```

```
<form>
(3)JAVA是哪个公司的产品： _____
<br>
<input type="radio" name="q1" value="0" checked>Novell
<input type="radio" name="q1" value="0">Microsoft
<input type="radio" name="q1" value="1">SUN
<br><Br> </form>
```

```
<form>
(4)IIS(Internet Infomation Server)是哪个公司的产品： _____
<br>
<input type="radio" name="q1" value="0" checked>Novell
<input type="radio" name="q1" value="1">Microsoft
<input type="radio" name="q1" value="0">Netscape
<br><Br> </form>
```

```
<form>
  <div align="center">
    <input type="button" name="Submit" value="看看成绩 "
onClick="Grade()" class="pt9">
  </div>
</form>
</td>
</tr>
</table>
```

在线考试脚本 (三)

脚本说明：

把如下代码加入 <body>区域中

```
<script>
  <!-- hide
  var ans = new Array;
  var done = new Array;
  var score = 0;
```

```
// LOSER! Don't read the answers!
ans[1] = "c";
ans[2] = "a";
ans[3] = "b";
ans[4] = "b";
ans[5] = "d";
ans[6] = "c";
ans[7] = "c";
ans[8] = "c";
ans[9] = "d";
ans[10] = "a";
function Engine(question, answer) {
    if (answer != ans[question]) {
        if (!done[question]) {
            done[question] = -1;
            alert("你选错了, 你答对了 " + score + "个 ");
        }

        else {

            alert("你已经选过这个了!");
        }

    }

    else {

        if (!done[question]) {

            done[question] = -1;

            score++;

            alert("恭喜你, 你答对了 " + score + "个 ");
        }

        else {

            alert("你已经回答过这个了!");
        }

    }

}
```

```

    }
}

function NextLevel () {
    if (score > 10) {
        alert("你作弊了吧!");
    }
    if (score >= 7 && score <= 9) {
        alert("你答的不错!!!")
        //self.location="GameQuiz2.htm"
    }
    else {
        alert("你还要继续努力!!!")
    }
}

//-->

</script>

<form>

<b>1. WARM-UP: Who created the famous <i>WarCraft 2</i>?</b><p>

<input type=radio value="a" onClick="Engine(1, this.value)">Sierra On-Line<br>

<input type=radio value="b" onClick="Engine(1, this.value)">BlueByte<br>

```

<input type=radio value="c" onClick="Engine(1, this.value)">Blizzard Entertainment

<input type=radio value="d" onClick="Engine(1, this.value)">Microsoft<p>

2. This famous 3D shooter claimed <i>PC Gamer's</i> Game of 1994 Award.<p>

<input type=radio value="a" onClick="Engine(2, this.value)">Doom

<input type=radio value="b" onClick="Engine(2, this.value)">Hexen

<input type=radio value="c" onClick="Engine(2, this.value)">Descent

<input type=radio value="d" onClick="Engine(2, this.value)">Wolfenstein 3D<p>

3. The first intergalactic combat game. Name it.<p>

<input type=radio value="a" onClick="Engine(3, this.value)">Master of Orion

<input type=radio value="b" onClick="Engine(3, this.value)">Star Control

<input type=radio value="c" onClick="Engine(3, this.value)">StarCraft

<input type=radio value="d" onClick="Engine(3, this.value)">Star Trek<p>

4. The game ever to contain graphics was this classic by Roberta Williams.<p>

<input type=radio value="a" onClick="Engine(4, this.value)">King's Quest

<input type=radio value="b" onClick="Engine(4, this.value)">Mystery House

<input type=radio value="c" onClick="Engine(4, this.value)">Time Zone

<input type=radio value="d" onClick="Engine(4, this.value)">Mission: Asteriod<p>

5. The first real-time strategy game was: <p>

WarCraft: Orcs & Humans

Command & Conquer

Dune

Dune 2<p>

6. In PC Gamer, Quake won these 'of-the-year' awards (1996): <p>

Best Game, Best Action Game

Best Action Game, Best
Multiplayer

Best Sound Effects, Best
Multiplayer

All of the above<p>

7. The best selling game of all time is: <p>

WarCraft 2

C&C: Red Alert

Sim City

King's Quest 5<p>

8. This is a turn-based strategy game: <p>

C&C: Red Alert

Might and Magic 3

Heroes of Might and Magic


```
<input type=radio value="d" onClick="Engine(8, this.value)">Daggerfall: The Elder Scrolls<p>
```

```
<b>9. PC Gamer's <i>Best Game of the 1996</i> went to: </b><p>
```

```
<input type=radio value="a" onClick="Engine(9, this.value)">C&C: Red Alert<br>
```

```
<input type=radio value="b" onClick="Engine(9, this.value)">Tomb Raider<br>
```

```
<input type=radio value="c" onClick="Engine(9, this.value)">Quake<br>
```

```
<input type=radio value="d" onClick="Engine(9, this.value)">Civilization 2<p>
```

```
<b>10. Blizzard's new release, <i>Diablo</i> is a: </b><p>
```

```
<input type=radio value="a" onClick="Engine(10, this.value)">Role Playing Game<br>
```

```
<input type=radio value="b" onClick="Engine(10, this.value)">2D Action Game<br>
```

```
<input type=radio value="c" onClick="Engine(10, this.value)">3D Action Game<br>
```

```
<input type=radio value="d" onClick="Engine(10, this.value)">Simulation<p>
```

```
<center>
```

```
<input type=button onClick="NextLevel()" value="Advance to next level">
```

```
</center>
```

```
</form>
```

在线测试脚本 (四)

脚本说明：

把如下代码加入 <body>区域中

```
<SCRIPT language=JavaScript><!--
```

```
function getResult(form) {
```

```
var score = 0

if (form.Q01[0].checked) { score += -1 }
if (form.Q01[1].checked) { score += 3 }

if (form.Q02[0].checked) { score += -1 }
if (form.Q02[1].checked) { score += 0 }
if (form.Q02[2].checked) { score += 3 }

if (form.Q03[0].checked) { score += 3 }
if (form.Q03[1].checked) { score += 0 }

if (form.Q04[0].checked) { score += 3 }
if (form.Q04[1].checked) { score += 0 }
if (form.Q04[2].checked) { score += -1 }

if (form.Q05[0].checked) { score += -1 }
if (form.Q05[1].checked) { score += 3 }

if (form.Q06[0].checked) { score += 3 }
if (form.Q06[1].checked) { score += -1 }

if (form.Q07[0].checked) { score += 3 }
if (form.Q07[1].checked) { score += 0 }

if (form.Q08[0].checked) { score += 3 }
if (form.Q08[1].checked) { score += 0 }

if (form.Q09[0].checked) { score += 3 }
if (form.Q09[1].checked) { score += -1 }

if (form.Q10[0].checked) { score += 3 }
if (form.Q10[1].checked) { score += -1 }

score1=score*100/30
if (score1 > 60) { alert('恭喜恭喜！你的成功率是 '+score1+'好兆头，不是吗？ ')}
if (score1 > 30 && score1 <61) { alert('你的成功率是 '+score1+'。怎么办 加把劲吧！ ')}
if (score1 < 31 ) { alert('你的成功率只有 '+score1+'。你还是放弃吧 ...') }
}

// --></SCRIPT>

<P><FONT color=#ff8000 size=4><STRONG>你的恋爱成功率 </STRONG></FONT></P>
```

```

<FORM name=pt1>
<OL>
  <LI>与情人相处，能否直接询问对方是不是爱你？
  <P><INPUT CHECKED name=Q01 type=radio value=1>能 <INPUT name=Q01 type=radio
  value=2>不能 </P>
  <LI>恋爱结婚主要是解决：
  <P><INPUT CHECKED name=Q02 type=radio value=1>性欲 <INPUT name=Q02 type=radio
  value=2>生活 <INPUT name=Q02 type=radio value=3>亲密伴侣 </P>
  <LI>从恋爱到结婚时间是否需要长一点？
  <P><INPUT CHECKED name=Q03 type=radio value=1>要 <INPUT name=Q03 type=radio
  value=2>不要 </P>
  <LI>嫉妒是什么信号？
  <P><INPUT CHECKED name=Q04 type=radio value=1>爱 <INPUT name=Q04 type=radio
  value=2>不安 <INPUT name=Q04 type=radio value=3>竞争 </P>
  <LI>可以在情人面前与别的异性过于亲热吗？
  <P><INPUT CHECKED name=Q05 type=radio value=1>可以 <INPUT name=Q05 type=radio
  value=2>不可以 </P>
  <LI>能同时和两个人要好吗？
  <P><INPUT CHECKED name=Q06 type=radio value=1>不能 <INPUT name=Q06 type=radio
  value=2>能 </P>
  <LI>许多人对婚后生活满怀奢望，结果常常落空，是这样吗？
  <P><INPUT CHECKED name=Q07 type=radio value=1>是 <INPUT name=Q07 type=radio
  value=2>不是 </P>
  <LI>哪种人最经不起失恋和孤寂之苦，女人还是男人？
  <P><INPUT CHECKED name=Q08 type=radio value=1>女人 <INPUT name=Q08 type=radio
  value=2>男人 </P>
  <LI>忠贞是搞好婚姻的重要原则吗？
  <P><INPUT CHECKED name=Q09 type=radio value=1>是 <INPUT name=Q09 type=radio
  value=2>不是 <BR></P>
<LI>忠贞是搞好婚姻的重要原则吗？
  <P><INPUT CHECKED name=Q10 type=radio value=1>是 <INPUT name=Q10 type=radio
  value=2>不是 <BR></P>
</LI></OL>
<P> <INPUT name=finish onclick=getResult(this.fom) type=button value=EQ解码 > <INPUT
  type=reset value=" RESET "></P></FORM>

```

在线测试脚本 (五)

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<SCRIPT language=JavaScript>
function processForm(fom){
var xf=xf1=0;
hc=new Array(20);
var roll_call=hc.length;

```



```
for (i=roll_call;i>0;i--)
{hc[i-1]=1};
//loops through the radio buttons finding out which one is selected
if (fom.c1[1].checked==1) hc[0]=2;
if (fom.c1[2].checked==1) hc[0]=3;
if (fom.c1[3].checked==1) hc[0]=4;
if (fom.c2[1].checked==1) hc[1]=2;
if (fom.c2[2].checked==1) hc[1]=3;
if (fom.c2[3].checked==1) hc[1]=4;
if (fom.c3[1].checked==1) hc[2]=2;
if (fom.c3[2].checked==1) hc[2]=3;
if (fom.c3[3].checked==1) hc[2]=4;
if (fom.c4[1].checked==1) hc[3]=2;
if (fom.c4[2].checked==1) hc[3]=3;
if (fom.c4[3].checked==1) hc[3]=4;
if (fom.c5[0].checked==1) hc[4]=4;
if (fom.c5[1].checked==1) hc[4]=3;
if (fom.c5[2].checked==1) hc[4]=2;
if (fom.c6[1].checked==1) hc[5]=2;
if (fom.c6[2].checked==1) hc[5]=3;
if (fom.c6[3].checked==1) hc[5]=4;
if (fom.c7[1].checked==1) hc[6]=2;
if (fom.c7[2].checked==1) hc[6]=3;
if (fom.c7[3].checked==1) hc[6]=4;
if (fom.c8[1].checked==1) hc[7]=2;
if (fom.c8[2].checked==1) hc[7]=3;
if (fom.c8[3].checked==1) hc[7]=4;
if (fom.c9[0].checked==1) hc[8]=4;
if (fom.c9[1].checked==1) hc[8]=3;
if (fom.c9[2].checked==1) hc[8]=2;
if (fom.c10[1].checked==1) hc[9]=2;
if (fom.c10[2].checked==1) hc[9]=3;
if (fom.c10[3].checked==1) hc[9]=4;
if (fom.c11[1].checked==1) hc[10]=2;
if (fom.c11[2].checked==1) hc[10]=3;
if (fom.c11[3].checked==1) hc[10]=4;
if (fom.c12[1].checked==1) hc[11]=2;
if (fom.c12[2].checked==1) hc[11]=3;
if (fom.c12[3].checked==1) hc[11]=4;
if (fom.c13[0].checked==1) hc[12]=4;
if (fom.c13[1].checked==1) hc[12]=3;
if (fom.c13[2].checked==1) hc[12]=2;
if (fom.c14[1].checked==1) hc[13]=2;
if (fom.c14[2].checked==1) hc[13]=3;
```

```

if (fom.c14[3].checked==1) hc[13]=4;
if (fom.c15[1].checked==1) hc[14]=2;
if (fom.c15[2].checked==1) hc[14]=3;
if (fom.c15[3].checked==1) hc[14]=4;
if (fom.c16[1].checked==1) hc[15]=2;
if (fom.c16[2].checked==1) hc[15]=3;
if (fom.c16[3].checked==1) hc[15]=4;
if (fom.c17[0].checked==1) hc[16]=4;
if (fom.c17[1].checked==1) hc[16]=3;
if (fom.c17[2].checked==1) hc[16]=2;
if (fom.c18[1].checked==1) hc[17]=2;
if (fom.c18[2].checked==1) hc[17]=3;
if (fom.c18[3].checked==1) hc[17]=4;
if (fom.c19[0].checked==1) hc[18]=4;
if (fom.c19[1].checked==1) hc[18]=3;
if (fom.c19[2].checked==1) hc[18]=2;
if (fom.c20[1].checked==1) hc[19]=2;
if (fom.c20[2].checked==1) hc[19]=3;
if (fom.c20[3].checked==1) hc[19]=4;
for (i=roll_call;i>0;i--)
{xf+=hc[i-1]};
xf1=Math.ceil(xf*1.25);
fom.answer.value="你的得分为 "+xf1+"分 ";
}</SCRIPT>

```

第二步 把如下代码加入 <body>区域中

```

<TABLE border=0 cellPadding=4 cellSpacing=0 height=79 width=500>
  <TBODY>
    <TR>
      <TD align=middle height=46 width=519<SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 6pt">
          </SPAN><FONT
            color=#0000ff><STRONG><SPAN
              style="FONT-FAMILY: 宋体 ; FONT-SIZE: 12pt; LINE-HEIGHT: 15px">你有焦虑情绪吗?
            </SPAN></STRONG></FONT><SPAN
              style="FONT-FAMILY: 宋体 ; FONT-SIZE: 6pt">
                </SPAN></TD></TR>
    <TR>
      <TD height=18 width=519<SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">仔细阅读每一题，然后根据你
        最近一个星期的实际感觉，选择适合的答案。 </SPAN></TD></TR></TBODY></TABLE></DIV>
<FORM name=see>
<DIV align=left>

```

```
<TABLE border=0 cellPadding=10 cellSpacing=0 height=388 width=517>
  <TBODY>
    <TR>
      <TD height=1 width=517><SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">1 觉得比平常容易紧张和着急。 <BR><INPUT
        name=c1 type=radio value=1>没有或很少时间。 <BR><INPUT name=c1 type=radio
        value=3>小部分时间。 <BR><INPUT name=c1 type=radio value=5>相当多时间。 <BR><INPUT
        name=c1 type=radio value=V1>绝大部分或全部时间。 </SPAN></TD></TR>
    <TR>
      <TD height=1 width=517><SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">2 无缘无故感到害怕。
<BR><INPUT
        name=c2 type=radio value=11>没有或很少时间。 <BR><INPUT name=c2 type=radio
        value=31>小部分时间。 <BR><INPUT name=c2 type=radio value=51>相当多时间。 <BR><INPUT
        name=c2 type=radio value=V2>绝大部分或全部时间。 </SPAN></TD></TR>
    <TR>
      <TD height=1 width=517><SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">3 容易心里烦乱或觉得惊慌。
<BR><INPUT
        name=c3 type=radio value=12>没有或很少时间。 <BR><INPUT name=c3 type=radio
        value=32>小部分时间。 <BR><INPUT name=c3 type=radio value=52>相当多时间。 <BR><INPUT
        name=c3 type=radio value=V3>绝大部分或全部时间。 </SPAN></TD></TR>
    <TR>
      <TD height=35 width=517><SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">4 觉得可能将要发疯。
<BR><INPUT
        name=c4 type=radio value=13>没有或很少时间。 <BR><INPUT name=c4 type=radio
        value=33>小部分时间。 <BR><INPUT name=c4 type=radio value=53>相当多时间。 <BR><INPUT
        name=c4 type=radio value=V4>绝大部分或全部时间。 </SPAN></TD></TR>
    <TR>
      <TD height=35 width=517><SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">5 觉得一切都很好，也不会
发生什么不幸。 <BR><INPUT
        name=c5 type=radio value=14>没有或很少时间。 <BR><INPUT name=c5 type=radio
        value=34>小部分时间。 <BR><INPUT name=c5 type=radio value=54>相当多时间。 <BR><INPUT
        name=c5 type=radio value=V5>绝大部分或全部时间。 </SPAN></TD></TR>
    <TR>
      <TD height=35 width=517><SPAN
        style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">6 手脚发抖打颤。 <BR><INPUT
        name=c6 type=radio value=15>没有或很少时间。 <BR><INPUT name=c6 type=radio
        value=35>小部分时间。 <BR><INPUT name=c6 type=radio value=55>相当多时间。 <BR><INPUT
        name=c6 type=radio value=V6>绝大部分或全部时间。 </SPAN></TD></TR>
  <TR>
```

```
<TD height=35 width=517><SPAN
  style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">7 因为头痛、头颈痛和背痛
而苦恼。 <BR><INPUT
  name=c7 type=radio value=16>没有或很少时间。 <BR><INPUT name=c7 type=radio
  value=36>小部分时间。 <BR><INPUT name=c7 type=radio value=56>相当多时间。 <BR><INPUT
  name=c7 type=radio value=V7>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
  <TD height=35 width=517><SPAN
    style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">8 感觉容易衰弱和疲乏。
<BR><INPUT
  name=c8 type=radio value=17>没有或很少时间。 <BR><INPUT name=c8 type=radio
  value=37>小部分时间。 <BR><INPUT name=c8 type=radio value=57>相当多时间。 <BR><INPUT
  name=c8 type=radio value=V8>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
  <TD height=35 width=517><SPAN
    style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">9 觉得心平气和，并且容易
安静地坐着。 <BR><INPUT
  name=c9 type=radio value=18>没有或很少时间。 <BR><INPUT name=c9 type=radio
  value=38>小部分时间。 <BR><INPUT name=c9 type=radio value=58>相当多时间。 <BR><INPUT
  name=c9 type=radio value=V9>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
  <TD height=35 width=517><SPAN
    style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">10 觉得心跳得很快。
<BR><INPUT
  name=c10 type=radio value=19>没有或很少时间。 <BR><INPUT name=c10 type=radio
  value=39>小部分时间。 <BR><INPUT name=c10 type=radio value=59>相当多时间。 <BR><INPUT
  name=c10 type=radio value=V10>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
  <TD height=35 width=517><SPAN
    style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">11 因为一阵阵头晕而苦恼。
<BR><INPUT
  name=c11 type=radio value=110>没有或很少时间。 <BR><INPUT name=c11 type=radio
  value=310>小部分时间。 <BR><INPUT name=c11 type=radio value=510>相当多时间。 <BR><INPUT
  name=c11 type=radio value=V11>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
  <TD height=35 width=517><SPAN
    style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">12 有晕倒发作，或觉得要晕
倒似的。 <BR><INPUT
  name=c12 type=radio value=111>没有或很少时间。 <BR><INPUT name=c12 type=radio
  value=311>小部分时间。 <BR><INPUT name=c12 type=radio value=511>相当多时间。 <BR><INPUT
  name=c12 type=radio value=V12>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
  <TD height=35 width=517><SPAN
```

13 吸气呼气都感到很容易。

没有或很少时间。 小部分时间。 相当多时间。 绝大部分或全部时间。

14 手脚麻木和刺痛。

没有或很少时间。 小部分时间。 相当多时间。 绝大部分或全部时间。

15 因为胃痛和消化不良而苦恼。

没有或很少时间。 小部分时间。 相当多时间。 绝大部分或全部时间。

16 常常要小便。

没有或很少时间。 小部分时间。 相当多时间。 绝大部分或全部时间。

17 手常常是干燥温暖的。

没有或很少时间。 小部分时间。 相当多时间。 绝大部分或全部时间。

18 脸红发热。

没有或很少时间。 小部分时间。 相当多时间。 绝大部分或全部时间。

19 容易入睡并且一夜睡得很好。

没有或很少时间。

```

value=318>小部分时间。 <BR><INPUT name=c19 type=radio value=518>相当多时间。 <BR><INPUT
name=c19 type=radio value=V19>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
<TD height=35 width=517><SPAN
style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px">20 作恶梦。 <BR><INPUT
name=c20 type=radio value=119>没有或很少时间。 <BR><INPUT name=c20 type=radio
value=319>小部分时间。 <BR><INPUT name=c20 type=radio value=519>相当多时间。 <BR><INPUT
name=c20 type=radio value=V20>绝大部分或全部时间。 </SPAN></TD></TR>
<TR>
<TD align=middle height=25 width=517><SPAN
style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px"><INPUT
onclick=processFom(this.fom) style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt" type=button value=
都选择完了，结果怎样 ?><INPUT
name=answer
style="COLOR: rgb(255,0,0); FONT-FAMILY: 宋体 ; FONT-SIZE:
9pt"></SPAN></TD></TR></TBODY></TABLE></DIV></FORM>
<DIV align=left>
<TABLE border=0 cellPadding=4 cellSpacing=0 height=22 width=500>
<TBODY>
<TR>
<TD height=22 width=520><SPAN
style="FONT-FAMILY: 宋体 ; FONT-SIZE: 9pt; LINE-HEIGHT: 15px"><FONT
color=#ff0000>说明
</FONT>你焦虑评定的分界值是 50分，分值越高，焦虑倾向越明显。
</SPAN></TD></TR></TBODY></TABLE>

```

在线测试脚本 (六)

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT language=JavaScript>
<!--
function processForm(form){
if (form.c1[0].checked==1) form.answer.value="把双手放在胸口前往往给人一种害羞、紧张、自我保护的感觉。选择这个姿势的男性就是喜欢这种含羞答答、在紧张时不自觉地手足无措，稍具气质及矜持的女性。";
if (form.c1[1].checked==1) form.answer.value="两手垂下给人一种自然、顺从的感觉。选择这个姿势的男性会喜欢不造作、不刻意掩饰自己及带点天真的女性。";
if (form.c1[2].checked==1) form.answer.value="两手张开给人一种接纳、包容的感觉。选择这个姿势的男性会倾向喜欢较年长、或是能给予他像母亲的爱般温暖的女性。";
}
//-->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```
<TABLE border=0 cellPadding=4 cellSpacing=0 height=78 width=500>
  <TBODY>
    <TR>
      <TD align=middle height=38 width=561><SPAN
        style="FONT-SIZE: 6pt">          </SPAN><SPAN
          style="FONT-SIZE: 12pt"><STRONG>哪一类型女仔最吸引你</STRONG></SPAN><SPAN
            style="FONT-SIZE: 6pt">          </SPAN></TD></TR></TBODY></TABLE></DIV>
<FORM name=see>
<DIV align=left>
<TABLE border=0 cellPadding=10 cellSpacing=0 height=223 width=517>
  <TBODY>
    <TR>
      <TD height=1 width=517>
        <DIV align=left>
          <P>假如圣母玛莉亚赤裸站在你面前，你认为她的双手会放在那儿？</P></DIV>
          <DIV align=left>
            <P><INPUT name=c1 type=radio value=1>放在胸口前。<BR><INPUT name=c1 type=radio
              value=3>两手垂下。<BR><INPUT name=c1 type=radio value=V1>两手张开成 V 字形。
            </P></DIV></TD></TR>
          <TR>
            <TD align=middle height=27 width=517><INPUT onclick=processForm(this.form) style="FONT-FAMILY: 宋体;
              FONT-SIZE: 9pt" type=button value=已选好，看看结论!></TD></TR>
          <TR>
            <TD align=middle height=-12 width=517><TEXTAREA cols=47 name=answer rows=5 style="COLOR:
              rgb(255,0,0); FONT-FAMILY: 宋 体 ; FONT-SIZE: 9pt; LINE-HEIGHT:
              15px"></TEXTAREA></TD></TR></TBODY></TABLE>
```

自由控制打开的窗口

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
closetime = 0; // Close window after __ number of seconds?
// 0 = do not close, anything else = number of seconds

function Start(URL, WIDTH, HEIGHT) {
windowprops = "left=50,top=50,width=" + WIDTH + ",height=" + HEIGHT;
preview = window.open(URL, "preview", windowprops);
if (closetime) setTimeout("preview.close();", closetime*1000);
}

function doPopup() {

url = "1.htm"; // change to your popup page URL

width = 267; // width of window in pixels
height = 103; // height of window in pixels
delay = 5; // time in seconds before popup opens
timer = setTimeout("Start(url, width, height)", delay*1000);
}
// End -->
</script>
```

第二步:把<body>区域中内容改为

```
<BODY OnLoad="doPopup();">
```

记录页面修改时间

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
<!--hide script from old browsers
document.write("This page has been updated: " + document.lastModified + "")
// end hiding -->
</script>
```

检测浏览器去过站点

脚本说明:

把如下代码加入<body>区域中

```
<script>
```



```
var times=history.length;
document.write('此浏览器已经去过'+times+'个站了。');
</script>
```

离开时显示信息

脚本说明:

把<body>区域中改为:

```
<body bgcolor="#ffffff" onUnload="window.alert('谢谢你的光临!欢迎下次再来!')">
```

弹出窗口自动关闭

脚本说明:

第一步:把如下代码加入 <head>区域中

```
<script language="JavaScript">
<!--
var gt = unescape('%3e');
var popup = null;
var over = "Launch Pop-up Navigator";
popup = window.open("", 'popupnav', 'width=225,height=235,resizable=1,scrollbars=auto');
if (popup != null) {
if (popup.opener == null) {
popup.opener = self;
}
popup.location.href = 'tan.htm';
}
// -->
</script>
```

第二步:新建 tan.htm 文件(注意要与上面的对应!)

第三步:在新建文件中加入如下代码(注意两个文件要在同一目录下)

```
<script language="JavaScript">
```

```
function closeit() {
```

```
setTimeout("self.close()",10000)
```

```
}
```

```
</script>
```

离开页面弹出窗口

脚本说明:

第一步：把如下代码加入<head>区域中

```
<script LANGUAGE="JavaScript">
```

```
<!-- Begin  
function leave() {  
window.open('tan1.htm',"', 'toolbar=no,menubar=no,location=no,height=225,width=235');  
}  
// End -->  
</script>
```

第二步：把<body>区域中内容改为:

```
<body bgcolor="#ffffff" onUnload="leave()">
```

进入时显示信息

脚本说明:

把<body>区域中改为:

```
<body bgcolor="#ffffff" onLoad="window.alert('欢迎光临怀柔网\n\n 本站有网页特效,影音空间\n\n 还有许多其它栏目\n\n 网址 http://www.hrw.cn\n\nE-mail: webmaster@hrw.cn')">
```

离开启动收藏夹

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="javascript">
```

```
function bookmark(){
```

```
window.external.AddFavorite('Upper1/default.htm', '怀柔网')
```

```
}
```

```
</script>
```

第二步:把<body>中内容改为:

```
<body bgcolor="#ffffff" onunload="bookmark()">
```

链接确认按钮

脚本说明:

把如下代码加入<body>区域中

```
<script language="">

function winconfirm(){

    question = confirm("你确认要到 “ 怀柔网 ” 吗?")

    if (question != "0"){

        window.open("Upper1/default.htm")

    }

}

</script>

<a href="javascript:winconfirm()">怀柔网</a>
```

点击加入收藏夹

脚本说明:

把如下代码加入<body>区域中

```
<a href="javascript:window.external.AddFavorite('Upper1/default.htm', '怀柔网')">点击加入收藏夹</a>
```

记录页面更新时间

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
<!--hide script from old browsers
document.write("本页最后更新日期: <br>" + document.lastModified + "")// end hiding -->
</script>
```

打开硬盘驱动器

脚本说明:

把如下代码加入<body>区域中

```
<form action="file:///c/"><input type="submit" value="c:\ drive"></form>
<p>
<form action="file:///a/"><input type="submit" value="a:\ drive"></form>
<p>
<form action="file:///b/"><input type="submit" value="b:\ drive"></form>
<p>
<form action="file:///d/"><input type="submit" value="d:\ drive"></form>
```

```
<p>
<form action="file:///e/"><input type="submit" value="e:\ drive"></form>
```

设置默认首页

脚本说明:

把如下代码加入<body>区域中

```
<span style="float:right" onclick="var
strHref=window.location.href;this.style.behavior='url(#default#homepage)';this.setHomePage('ht
tp://www.hrw.cn');" style="CURSOR: hand"><br>将本站设为首页</a></span>
```

输入框测试警告

脚本说明:

第一步：把如下代码加入<head>区域中

```
<script language="JavaScript">
<!-- Hide
```

```
function test1(form) {
    if (form.text1.value == "")
        alert("您没写上任何东西，请再输入一次 !")
    else {
        alert("嗨 "+form.text1.value+"! 您已输入完成 !");
    }
}
```

```
function test2(form) {
    if (form.text2.value == "" ||
        form.text2.value.indexOf('@', 0) == -1)
        alert("这不是正确的 e-mail address! 请再输入一次 !");
    else alert("您已输入完成 !");
}
// -->
</script>
```

第二步：在<body>中加入如下代码：

```
<form name="first">
Enter your name:<br>
<input type="text" name="text1">
<input type="button" name="button1" value="输入测试" onClick="test1(this.form)">
<P>
Enter your e-mail address:<br>
<input type="text" name="text2">
<input type="button" name="button2" value="输入测试" onClick="test2(this.form)">
```

链接弹出警告框

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script>function winconfirm(){ question = confirm("确实要用新窗口打开聊天室站点吗?")
    if (question != "0"){ window.open("chat.htm", "NewWin", "status=yes, height=200,
width=400") } }</script>
```

第二步:在<body>中加入:

```
<a href="" onClick="winconfirm(); return false;">这里</a>
```

关闭窗口链接

脚本说明:

把如下代码加入<body>区域中

```
<a href="javascript:window.close()"><br>
关闭窗口</a>
```

显示器分辨率检测

脚本说明:

把如下代码加入<body>区域中:

```
<script language="JavaScript1.2">
<!--
var correctwidth=1024
var correctheight=768
if (screen.width!=correctwidth||screen.height!=correctheight)
document.write(" 本站最佳分辨率: "+correctwidth+"*"+correctheight+"。 你当前的分辨率
是:"+screen.width+"*"+screen.height+"。 设置合适的分辨率才能取得最佳的显示效果!")
//-->
</script>
```

按分辨率导航

脚本说明:

第一步:把如下代码加入<head>区域中(你可以对链接及说明作相应修改)

```
<script LANGUAGE="JavaScript">

<!-- Begin
function redirectPage() {
var url640x480 = "http://www.163.com/";
var url800x600 = "http://www.sohu.com/";
var url1024x768 = "http://www.yoursite.com/";
if ((screen.width == 640) && (screen.height == 480))
window.location.href= url640x480;
```

```
else if ((screen.width == 800) && (screen.height == 600))
window.location.href= url800x600;
else if ((screen.width == 1024) && (screen.height == 768))
window.location.href= url1024x768;
else window.location.href= url640x480;
}
// End -->
</script>
```

第二步:把如下代码加入<body>区域中

```
<form>
<input type=button value="进入符合分辨率的页面" onClick="redirectPage()">
</form>
```

定制打开的窗口

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="JavaScript">
<!--
function win() {
var h= document.winfrm.hig.value
var w= document.winfrm.wid.value
testWindow=window.open("about:blank",'testwin','toolbar=no,location=no,directories=no,menubar=no,scrollbars=no,resizable=no,width='+ w + ',height='+ h +");
testWindow.document.writeln("<head><title>测试窗口</title></head>");
testWindow.document.writeln("<body bgcolor=#ffffcc>");
testWindow.document.writeln("该窗口已经按照你要求的大小打开了！<p>");
testWindow.document.writeln("如何使用就在于你的创意了！</body>");
testWindow.document.writeln("");
}
// -->
</script>
```

第二步:把如下代码加入<body>区域中

```
<form name="winfrm">
窗口宽度:
<input type="text" name="wid" maxlength="3">
<br>
窗口高度:
<input type="text" name="hig" maxlength="3">
<br>
<input type="button" name="s" value="开始测试" onClick="win()" class="yk9">
</form>
```

控制窗口打开日期

脚本说明:

第一步：把如下代码加入<head>区域中

```
<script language="JavaScript">
```

```
<!--
```

```
window.open("hi.htm", "", "scrollbars=no,resizable,height=150,width=200")
```

```
//-->
```

```
</script>
```

第二步：新建 hi.htm 文件，其内容为如下代码:

```
<html>
```

```
<head>
```

```
<script language="javascript">
```

```
function openOrClose() {
```

```
var beginDateAndTime="200006250000" //起始时间,格式为：年,月,日,时,秒
```

```
var endDateAndTime="200008310000" //结束时间(本例设定在 2000 年才弹出)
```

```
var aTime = new Date()
```

```
var thisYear = aTime.getYear()
```

```
var thisMonth = aTime.getMonth() + 1
```

```
var thisDate = aTime.getDate()
```

```
var thisHour = aTime.getHours()
```

```
var thisMinute = aTime.getMinutes()
```

```
var thisDateAndTime = (thisYear*100000000)+(thisMonth*1000000)+(thisDate*10000)+(thisHour*100)+thisMinute
```

```
if (thisDateAndTime <= beginDateAndTime || thisDateAndTime >= endDateAndTime) {
```

```
self.close()

}

}

</script>
</head>
<body onload=openOrClose() bgcolor="#fef4d9">
<center>本窗口只在 2000 年 7 月份打开
<br>你可以任意更改时间设置
</center>
```

打开窗口居中

脚本说明:

把如下代码加入<body>区域中

```
<input type="button" value="怀柔网" onClick="window.open('Upper1/default.htm', 'Sample',
'toolbar=no,location=no,directories=no,status=no,menubar=no,scrollbars=no,resizable=yes,copyhi
story=yes,width=490,height=320,left=0,top=0')" name="Input">
```

输入框控制

脚本说明:

第一步:把如下代码加入<body>区域中

```
<form onSubmit="return false;">
```

这里不允许输入如下字符: (像 !@#%\$^&* 等)


```
<textarea rows=2 cols=20 name=comments onKeyPress="if ((event.keyCode > 32 &&
event.keyCode < 48) || (event.keyCode > 57 && event.keyCode < 65) || (event.keyCode > 90 &&
event.keyCode < 97)) event.returnValue = false;"></textarea>
```

```
<br>
```

```
<br>
```

这里不能输入引号:


```
<input type=text name=txtEmail onKeyPress="if (event.keyCode==34 || event.keyCode==39)
event.returnValue = false;">
```

```
<br>
```

```
<br>
```

这里只能输入数字:


```
<input type=text name=txtPostalCode onKeyPress="if (event.keyCode < 45 || event.keyCode > 57)
event.returnValue = false;">
```

```
</form>
```

查看输入框内容

脚本说明:

第一步:把如下代码加入<head>区域中


```
<script language="javascript">
function testtrim(){
var theform=document.trimform;
trimedname = theform.name.value;
var trimmed_name = trimmedname.replace(" ", "");
alert ("您输入的内容是:\"\" + trimmed_name + "\"");
return false; //视具体的使用情况决定是否用该句;
}
</script>
```

第二步:把如下代码加入区域中

```
<form method="post" action="" onsubmit="return testtrim()" name="trimform">
<input type="text" name="name">
<input type="submit" name="Submit" value="查看输入内容" class="font">
</form>
```

显示所有链接

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript1.2">

<!--

function extractlinks(){

var links=document.all.tags("A")

var total=links.length

var win2=window.open("", "", "menubar,scrollbars,toolbar")

win2.document.write("<font size='2'>一共有"+total+"个连接</font><br>")

for (i=0;i<total;i++){

win2.document.write("<font size='2'>"+links[i].outerHTML+"</font><br>")

}

}
```

```
}
```

```
//-->
```

```
</script>
```

```
<input type="button" onClick="extractlinks()" value="显示所有的连接">
```

限时载入页面

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JAVASCRIPT">
```

```
setTimeout("document.location.href='Upper1/default.htm'",2000);
```

```
</SCRIPT>
```

输入框神秘消失

脚本说明 :

把如下代码加入<body>区域中:

```
<SCRIPT>
```

```
if (document.layers) {
```

```
    document.writeln ('<STYLE>');
```

```
    document.writeln ('    .changeable { position: relative; }');
```

```
    document.writeln ('</STYLE>');
```

```
}
```

```
</SCRIPT>
```

```
<SCRIPT>
```

```
function setElement (id, html) {
```

```
    if (document.layers) {
```

```
        var l = document[id];
```

```
        if (!l.overLayer) {
```

```
            l.overLayer = new Layer(l.clip.width);
```

```
            l.overLayer.left = l.pageX;
```

```
            l.overLayer.top = l.pageY;
```

```
            l.visibility = 'hide';
```

```
            l.overLayer.visibility = 'show';
```

```
        }
```

```
        l.overLayer.document.open();
```

```
        l.overLayer.document.write(html);
```

```
        l.overLayer.document.close();
```

```
    }
```

```
    else if (document.all) {
```

```
        document.all[id].innerHTML = html;
```

```

    }
}
function changeNow() {
var user = document.aForm.user.value
document.aForm.aField.value = "Welcome "+user+"";
setElement ('someParagraph', document.aForm.aField.value);
}
var nw = "";
document.write('<FORM NAME="aForm">');
document.write('<INPUT TYPE="hidden" NAME="aField" VALUE="">');
document.write('<SPAN ID="someParagraph" CLASS="changeable">');
document.write('<input type=text name=user size=5> <INPUT TYPE="button" VALUE="ok"
ONCLICK="changeNow();">');
document.write('</SPAN></form>');
</SCRIPT>

```

检测访问来源

脚本说明：

把如下代码加入<body>区域中：

你来自:


```
<SCRIPT LANGUAGE="JAVASCRIPT">
```

```
var where = document.referrer
```

```
if (where == "") { document.write("a bookmark or by typing in my URL") }
```

```
else { document.write(where) }
```

```
</SCRIPT>
```

```
</FONT><P>
```

回退的页面数

脚本说明：

把如下代码加入<body>区域中：

```
<a href="javascript:history.go(-1)">1</a>
```

```
<a href="javascript:history.go(-2)">2</a>
```

```
<a href="javascript:history.go(-3)">3</a>
```

```
<a href="javascript:history.go(-4)">4</a>
```

```
<a href="javascript:history.go(-5)">5</a>
```

```
<a href="javascript:history.go(-6)">6</a>
```

```
<a href="javascript:history.go(-7)">7</a>
```

```
<a href="javascript:history.go(-8)">8</a>
```

```
<a href="javascript:history.go(-9)">9</a>
```

```
<a href="javascript:history.go(-10)">10</a>
```

倒计时载入页面

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<META HTTP-EQUIV="REFRESH" CONTENT="11; URL=14.htm">
```

第二步:把<body>中加入如下代码：

```
<META HTTP-EQUIV="REFRESH" CONTENT="11; URL=14.htm">
```

```
<script language="JavaScript">
```

```
startday = new Date();  
clockStart = startday.getTime();
```

```
function initStopwatch()
```

```
{  
    var myTime = new Date();  
        var timeNow = myTime.getTime();  
        var timeDiff = timeNow - clockStart;  
        this.diffSecs = timeDiff/1000;  
        return(this.diffSecs);  
}
```

```
function getSecs()
```

```
{  
    var mySecs = initStopwatch();  
    var mySecs1 = ""+mySecs;  
    mySecs1 = mySecs1.substring(0,mySecs1.indexOf(".")) + " secs.";  
    document.form1.timespent.value = mySecs1  
    window.setTimeout('getSecs()',1000);  
}
```

```
</script>
```

```
<center>
```

This page will change in 10 seconds:

```
<form name=form1><input size=9 name=timespent></form>
```

```
</center>
```

第三步：把<body>中内容改为：

```
<body bgcolor="#ffffff" onLoad="window.setTimeout('getSecs()',1)">
```

自由打开窗口

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT LANGUAGE="JAVASCRIPT">
```

```
<!-- hide
```

```
function customize(form) {
```

```
    var address = document.form1.url.value;
```

```
    var op_tool   = (document.form1.tool.checked == true) ? 1 : 0;
```

```
    var op_loc_box = (document.form1.loc_box.checked == true) ? 1 : 0;
```

```
    var op_dir    = (document.form1.dir.checked == true) ? 1 : 0;
```

```
    var op_stat   = (document.form1.stat.checked == true) ? 1 : 0;
```

```
    var op_menu   = (document.form1.menu.checked == true) ? 1 : 0;
```

```
    var op_scroll = (document.form1.scroll.checked == true) ? 1 : 0;
```

```
    var op_resize = (document.form1.resize.checked == true) ? 1 : 0;
```

```
    var op_wid    = document.form1.wid.value;
```

```
    var op_heigh  = document.form1.heigh.value;
```

```
    var option = "toolbar=" + op_tool + ",location=" + op_loc_box + ",directories="
```

```
+ op_dir +                ",status="      + op_stat
+                ",menubar="    + op_menu +                ",scrollbars="
+ op_scroll +                ",resizeable="  + op_resize
+                ",width="
+ op_wid +                ",height="    + op_heigh;

var win3 = window.open("", "what_I_want", option);

var win4 = window.open(address, "what_I_want");

}
```

```
function clear(form){

    document.form1.wid.value="";

    document.form1.heigh.value="";

}
```

```
// done hiding -->
```

```
</SCRIPT>
```

```
<TABLE cellpadding=5 border><TR><TD><PRE>
```

```
<FORM name=form1  ACTION="javascript:" METHOD="POST">
```

```
<INPUT TYPE="text" NAME="url" value="http://www.hrw.cn" >: URL
```

```
<INPUT TYPE="checkbox" NAME="tool">: Toolbar
```

```
<INPUT TYPE="checkbox" NAME="loc_box">: Location
```

<INPUT TYPE="checkbox" NAME="dir">: Directories

<INPUT TYPE="checkbox" NAME="stat">: Status

<INPUT TYPE="checkbox" NAME="menu">: Menubar

<INPUT TYPE="checkbox" NAME="scroll">: Scrollbars

<INPUT TYPE="checkbox" NAME="resize">: Resizable

<INPUT TYPE="text" NAME="wid" value=>: Width

<INPUT TYPE="text" NAME="heigh" value=>: Height

<CENTER>

<INPUT TYPE="button" VALUE="=ENTER=" OnClick="customize(this.form)">

<INPUT TYPE="reset" VALUE="=RESET=" onClick="clear(this.form)">

</PRE></TD></TR></TABLE>

</FORM>

检测 IE所装插件

脚本说明：

把如下代码加入<body>区域中:

```
<script language="JavaScript">
<!-- Hide this script from old browsers --
  var num_of_plugins = navigator.plugins.length;
for (var i=0; i < num_of_plugins; i++) {
  var list_number=i+1;
  document.write("<font color=red>Plug-in No." + list_number + "-
</font>" + navigator.plugins[i].name+ " <br>[Location: " + navigator.plugins[i].filename + "]<p>");
  }
if (list_number>15)
  alert("\n 哇!你有 " + list_number + " 种外挂程序!")
else
  alert ("\n 多找一些外挂程序吧! 你只有 " + list_number + " 种外挂程序,有点逊!")
// -- End Hiding Here -->
</script>
```

检测点链接速度

脚本说明：

把如下代码加入<body>区域中:

```
<script>
tim=1
setInterval("tim++",100)
b=1

var autourl=new Array()
autourl[1]="www.hrw.cn"
autourl[2]="javacool.3322.net"
autourl[3]="www.sina.com.cn"
autourl[4]="www.nuaa.edu.cn"
autourl[5]="www.cctv.com"

function butt(){
document.write("<form name=autof>")
for(var i=1;i<autourl.length;i++)document.write("<input type=text name=txt"+i+" size=10 value=
测试中.....> =》 <input type=text name=url"+i+" size=40> =》 <input type=button value=GO
onclick=window.open(this.form.url"+i+"."+value)><br>")
document.write("<input type=submit value=刷新></form>")
}
butt()
function auto(url){
document.forms[0]["url"+b].value=url
if(tim>200)
{ document.forms[0]["txt"+b].value="链接超时"}
else
{ document.forms[0]["txt"+b].value="时间"+tim/10+"秒"}
b++
}
function          run(){for(var          i=1;i<autourl.length;i++)document.write("<img
src=http://"+autourl[i]+"/"+Math.random()+""          width=1          height=1
onerror=auto('http://'+autourl[i]+'')>")}
run()</script>
```

检测健康程度

脚本说明：

把如下代码加入<body>区域中:

```
<script LANGUAGE="JAVASCRIPT">
```

```
<!-- hide this script tag's contents from old browsers
```

```
function ClearForm(form){
```

```
    form.weight.value = "";
```



```

form.height.value = "";

form.bmi.value = "";

form.my_comment.value = "";

}

function bmi(weight, height) {

    bmindx=weight/eval(height*height);

    return bmindx;

}

function checkform(form) {

    if (form.weight.value==null||form.weight.value.length==0

        || form.height.value==null||form.height.value.length==0){

        alert("\nPlease complete the form first");

        return false;

    }

    else if (parseFloat(form.height.value) <= 0||

        parseFloat(form.height.value) >=500||

        parseFloat(form.weight.value) <= 0||

        parseFloat(form.weight.value) >=500){

        alert("\nReally know what you're doing? \nPlease enter values again. \nWeight

in kilos and \nheight in cm");

        ClearForm(form);

```

```
        return false;
    }

    return true;
}

function computeform(form) {

    if (checkform(form)) {

        yourbmi=Math.round(bmi(form.weight.value, form.height.value/100));

        form.bmi.value=yourbmi;

        if (yourbmi >30) {

            form.my_comment.value="不要在闹了!!!";

        }

        else if (yourbmi >28 && yourbmi <=30) {

            form.my_comment.value="您是猪吗?";

        }

        else if (yourbmi >23 && yourbmi <=28) {

            form.my_comment.value="两头猪也没有你重吧?";

        }

        else if (yourbmi >21 && yourbmi <=23) {

            form.my_comment.value="您现在是偏胖,应该注意饮食!";

        }

        else if (yourbmi >=19 && yourbmi <=21) {

            form.my_comment.value="哇!!!您太苗条了! 是标准身材";
```

```

    }

    else if (yourbmi >=18 && yourbmi <19) {

        form.my_comment.value="您是不是营养不良?????";

    }

    else if (yourbmi >=17 && yourbmi <18) {

        form.my_comment.value="这个不是骨头吗?????";

    }

    else if (yourbmi <17) {

        form.my_comment.value="按照生物学来说这种生物是不能生存的";

    }

}

return;

}

// -- done hiding from old browsers -->

</script>

<form NAME="BMI" method="POST">
  <table border="1">
    <tr>
      <td><font color="red"><div align="center"><center><p>体重</font> (kg)</td>
      <td align="center"><font color="red"><div align="center"><center><p>身 高
</font>(cm)</td>
      <td align="center"><font color="blue"><div align="center"><center><p>健 康 值
</font></td>
      <td align="center"><font color="blue"><div align="center"><center><p>电脑对您的评
价</font></td>

```

```

</tr>
<tr align="center">
  <td><input          TYPE="TEXT"          NAME="weight"          SIZE="6"
onFocus="this.form.weight.value=""></td>
  <td><input          TYPE="TEXT"          NAME="height"          SIZE="6"
onFocus="this.form.height.value=""></td>
  <td><input TYPE="TEXT" NAME="bmi" SIZE="5"></td>
  <td><input TYPE="TEXT" NAME="my_comment" size="40"></td>
</tr>
</table>
<div align="center"><center><p><input TYPE="button" VALUE="确定"
onClick="computeform(this.form)"> <input TYPE="reset" VALUE="取消"
onClick="ClearForm(this.form)"> </p>
</center></div>
</form>

```

页面中打开窗口

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- hide from old browsers
```

```
function PopIt(label, msg){
  // Set up Page Colors & Table
  var s1 =      "<TITLE>Information!</TITLE>" +
  "<BODY BGCOLOR='ffffff'><TABLE BORDER=0><TR>" +
  "<TD WIDTH=90% HEIGHT=90 VALIGN=TOP ALIGN=LEFT>" +
  "<FONT SIZE=4>"
  var s2 = "<FONT COLOR='FF0000'><B>"+label+"</B></FONT><P>"
  var s3 =      "</TD><TD WIDTH=10%> </TD></TR><TR><TD> </TD>"+
  "<TD VALIGN=TOP ALIGN=RIGHT>"+
  "<FORM><INPUT TYPE='BUTTON' VALUE='Okay'" +
  "onClick='self.close()'>" +
  "</FORM></TD></TR></TABLE></BODY>"
  popup = window.open("", "popDialog", "height=160,width=300,scrollbars=no")
  popup.document.write(s1+s2+msg+s3)
  popup.document.close()
}

```

```
function popHelp(){
  PopIt('PopIt', 'This function allows you to ' +
  'create a popup window.')
}

```

```
<!-- done hiding -->
```

```
</SCRIPT>
<FORM>
<INPUT TYPE="BUTTON" VALUE="Pop-Up" onClick="popHelp()">
</FORM>
```

特殊的 Bookmark

脚本说明：

把如下代码加入<body>区域中：

```
<a href="javascript:void(0);" onClick='window.external.AddFavorite(location.href,
document.title);'>加入收藏夹</a>
```

窗口打开关闭程序

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT>
function close_nagwin(){
var popupURL = "1.htm";
popup =
window.open(popupURL,"TripodPopup", 'toolbar=0,location=0,directories=0,status=0,menubar=0,
scrollbars=0,resizable=0,width=0,height=0');

popup.close()}

close_nagwin();

</SCRIPT>
```

随机显示一些数字

脚本说明：

把如下代码加入<body>区域中：

```
<script language="javascript">

function Quickpick()
{
var ball

for( ball = 0; ball < 5; ball++)
{
this[ball] = parseInt((Math.random() *
Math.pow(10,16)) % 49) + 1;

for(var list = 0; list < ball; list++)
```

```

        {
            if(this[list] == this[ball])
            {
                list = ball;
                ball--;
            }
        }
    }
    this[ball] = parseInt((Math.random() * Math.pow(10,16)) % 42) + 1;
    return this;
}

```

</script>

<script language="javascript">

```

    var idx;
    var powerball = new Array(6);

    powerball = this.Quickpick();

    document.write("<center>");
    document.write("<font      size=+2>POWER</font><font      size=+2
color=#C00000>BALL</font><br>");
    document.write("<hr width=400><font size=+2>");
    for(idx = 0; idx < 5; idx++)
        document.write(powerball[idx] + " - ")
    document.write("</font><font color=#D00000 size=+2>" + powerball[idx] +
"</font>");
    document.write("</center>");

```

</script>

页面自动打开

脚本说明：

把<body>中的内容改为

```

<body                                bgcolor="#ffffff"
OnLoad="if(parent.frames.length==0)top.location='Upper1/default.htm';">

```

进入弹出收藏夹

脚本说明:

第一步:把如下代码加入<body>区域中

```

<SCRIPT LANGUAGE="JavaScript">

```

```

<!-- Begin

```

```

var expDays = 7;

url = "http://www.javascript2000.com/";
title = "网页制作特效";

// Cookie code from The JavaScript Source
function GetCookie (name) {
var arg = name + "=";
var alen = arg.length;
var clen = document.cookie.length;
var i = 0;
while (i < clen) {
var j = i + alen;
if (document.cookie.substring(i, j) == arg)
return getCookieVal (j);
i = document.cookie.indexOf(" ", i) + 1;
if (i == 0) break;
}
return null;
}
function SetCookie (name, value) {
var argv = SetCookie.arguments;
var argc = SetCookie.arguments.length;
var expires = (argc > 2) ? argv[2] : null;
var path = (argc > 3) ? argv[3] : null;
var domain = (argc > 4) ? argv[4] : null;
var secure = (argc > 5) ? argv[5] : false;
document.cookie = name + "=" + escape (value) +
((expires == null) ? "" : ("; expires=" + expires.toGMTString())) +
((path == null) ? "" : ("; path=" + path)) +
((domain == null) ? "" : ("; domain=" + domain)) +
((secure == true) ? "; secure" : "");
}
function DeleteCookie (name) {
var exp = new Date();
exp.setTime (exp.getTime() - 1);
var cval = GetCookie (name);
document.cookie = name + "=" + cval + "; expires=" + exp.toGMTString();
}
var exp = new Date();
exp.setTime(exp.getTime() + (expDays*24*60*60*1000));
function amt(){
var count = GetCookie('count')
if(count == null) {

```

```

SetCookie('count','1')
return 1
}
else {
var newcount = parseInt(count) + 1;
DeleteCookie('count')
SetCookie('count',newcount,exp)
return count
}
}
function getCookieVal(offset) {
var endstr = document.cookie.indexOf(";", offset);
if (endstr == -1)
endstr = document.cookie.length;
return unescape(document.cookie.substring(offset, endstr));
}

function checkCount() {
var count = GetCookie('count');
if (count == null) {
count=1;
SetCookie('count', count, exp);

if ((navigator.appName == "Microsoft Internet Explorer") && (parseInt(navigator.appVersion) >=
4)) {
window.external.AddFavorite (url,title);
}
else {
var msg = "Don't forget to bookmark us!";
if(navigator.appName == "Netscape") msg += " (CTRL-D)";
alert(msg);
}
}
else {
count++;
SetCookie('count', count, exp);
}
}
checkCount();
// End -->
</script>

```

自动显示是否更新

脚本说明:

把如下代码加入<body>区域中

```
<TABLE border=2 cellspacing=0 cellpadding=3>
<TR><TD bgcolor="#000044">
<FONT color="#4400ff" face=georgia,arial size=+1>
<CENTER>
<SCRIPT LANGUAGE="JavaScript">
<!--
document.write(document.title);
//-->
</SCRIPT>
</TD></TR>
<TR><TD bgcolor="#440000">
<FONT size=-1 color="#ff0000" face="trebuchet MS","arial">
<FONT color="#ff8800">Born on:</font>
```

September 25, 1997

```
<br>
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function getCookieVal (offset) {
var endstr = document.cookie.indexOf (";", offset);
if (endstr == -1)
endstr = document.cookie.length;
return unescape(document.cookie.substring(offset, endstr));
}
function GetCookie (name) {
var arg = name + "=";
var alen = arg.length;
var clen = document.cookie.length;
var i = 0;
while (i < clen) {
var j = i + alen;
if (document.cookie.substring(i, j) == arg)
return getCookieVal (j);
i = document.cookie.indexOf(" ", i) + 1;
if (i == 0) break;
}
return null;
}
function SetCookie (name, value) {
```

```

var argv = SetCookie.arguments;
var argc = SetCookie.arguments.length;
var expires = (argc > 2) ? argv[2] : null;
var path = (argc > 3) ? argv[3] : null;
var domain = (argc > 4) ? argv[4] : null;
var secure = (argc > 5) ? argv[5] : false;
document.cookie = name + "=" + escape (value) +
((expires == null) ? "" : ("; expires=" + expires.toGMTString())) +
((path == null) ? "" : ("; path=" + path)) +
((domain == null) ? "" : ("; domain=" + domain)) +
((secure == true) ? "; secure" : "");
}
function DeleteCookie(name) {
var exp = new Date();
FixCookieDate (exp);
exp.setTime (exp.getTime() - 1);
var cval = GetCookie (name);
if (cval != null)
document.cookie = name + "=" + cval + "; expires=" + exp.toGMTString();
}
var cookie_date=new Date(document.lastModified);
var expdate = new Date();
expdate.setTime(expdate.getTime()+(5*24*60*60*1000));
document.write("<Font color=ff8800>" + "Last updated: " + "</font>" +document.lastModified);
document.write("");
if (!(cookie_date == GetCookie("cookie_date"))){
SetCookie("cookie_date",cookie_date,expdate);
document.write("<font color='yellow'><br>Site has changed since last visit!</font><br>");
}
// End -->
</SCRIPT>
</FONT>
</TD></TR>
</TABLE>
</CENTER>

```

浏览器详细报告

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT>
```

```
<!-- Begin
```

```
function whatBrowser() {
```

```
document.Browser.Name.value=navigator.appName;
```

```

document.Browser.Version.value=navigator.appVersion;
document.Browser.Code.value=navigator.appCodeName;
document.Browser.Agent.value=navigator.userAgent;
}
// End -->
</SCRIPT>
<TABLE BORDER>
<FORM NAME="Browser">
<TR>
<TD> Browser Name: </TD>
<TD> <INPUT TYPE="txt" NAME="Name" Size="45"></TD>
</TR>
<TR>
<TD> Browser Version: </TD>
<TD> <INPUT TYPE="txt" NAME="Version" Size="45"></TD>
</TR>
<TR>
<TD> Browser Code Name: </TD>
<TD> <INPUT TYPE="txt" NAME="Code" Size="45"></TD>
</TR>
<TR>
<TD> User-Agent: </TD>
<TD> <INPUT TYPE="txt" NAME="Agent" Size="45"></TD>
</TR>
</FORM>
</TABLE>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="whatBrowser()>
```

第二列 时间日期类

时钟显示在任意指定位置

脚本说明：

第一步:把如下代码加入<body>区域中:

```

<span id=liveclock style=position:absolute;left:250px;top:122px;; width: 109px; height: 15px>
</span> （这里可以调整时钟的方位。调用脚本时去掉括号中内容）
<SCRIPT language=javascript>
<!--

```

```

function show5(){if(!document.layers&&!document.all)
return
var Digital=new Date()
var hours=Digital.getHours()
var minutes=Digital.getMinutes()
var seconds=Digital.getSeconds()
var dn="AM"
if(hours>12){dn="PM"
hours=hours-12
}if(hours==0)
hours=12
if(minutes<=9)
minutes="0"+minutes
if(seconds<=9)
seconds="0"+seconds
//change font size here to your desire
myclock="<font          size='5'          face='Arial'><b><font          size='1'>Current
Time:</font></br>" +hours+":"+minutes+":"
+seconds+" "+dn+"</b></font>"
if(document.layers){document.layers.liveclock.document.write(myclock)
document.layers.liveclock.document.close()
}else if(document.all)
liveclock.innerHTML=myclock
setTimeout("show5()",1000)
}
//>
</SCRIPT>

```

第二步:把<body>中的内容改为

```
<body bgcolor="#ffffff" ONLOAD=show5()>
```

倒计时代码生成器

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language=javascript>
```

```
<!--
```

```

function          generate(form){for(var
q=0;q<12;q++){if(document.me.m.options[document.me.m.selectedIndex].value==q){var
m2=q+1
}var txt='<!-- 分三步完成全部脚本:\r\n\r\n'
+' 1. 将第一部分粘贴到 HTML 的 HEAD 区\r\n'
+' 2. 将 OnLoad 事件加入 BODY 标签内\r\n'
+' 3. 将最后一部分代码加入 BODY 区 -->\r\n\r\n'

```

```

+<!-- 第一步: 将如下代码粘贴到 HTML 的 HEAD 区-->\r\n\r\n'
+<HEAD>\r\n\r\n<SCRIPT LANGUAGE="JavaScript">\r\n\r\n'
+<!-- Begin\r\n'
+'var Temp2;\n'
+'var timerID = null;\n'
+'var timerRunning = false;\n'
+'function arry() {\n'
+'this.length = 12;\n'
+'this[0] = 31;\n'
+'this[1] = 28;\n'
+'this[2] = 31;\n'
+'this[3] = 30;\n'
+'this[4] = 31;\n'
+'this[5] = 30;\n'
+'this[6] = 31;\n'
+'this[7] = 31;\n'
+'this[8] = 30;\n'
+'this[9] = 31;\n'
+'this[10] = 30;\n'
+'this[11] = 31;\n'
+'}\n'
+'var date = new arry();\n'
+'\n'
+'function stopclock() {\n'
+'if(timerRunning)\n'
+'clearTimeout(timerID);\n'
+'timerRunning = false;\n'
+'}\n'
+'\n'
+'function startclock() {\n'
+'stopclock();\n'
+'showtime();\n'
+'}\n'
+'\n'
+'function showtime() {\n'
+'now = new Date();\n'
+'var CurMonth = now.getMonth();\n'
+'var CurDate = now.getDate();\n'
+'var CurYear = now.getFullYear();\n'
+'now = null;\n'
+'if (+document.me.d.options[document.me.d.selectedIndex].value+ < CurDate) {\n'
+'CurDate -= date[CurMonth]; CurMonth++;\n'
+'}\n'
+'if (+document.me.m.options[document.me.m.selectedIndex].value+ < CurMonth) {\n'

```

```

+CurMonth -= 12; CurYear++;\n'
+}')\n'
+\n'
+'var Yearleft = '+document.me.y.options[document.me.y.selectedIndex].value+' - CurYear;\n'
+'var Monthleft = '+document.me.m.options[document.me.m.selectedIndex].value+' - CurMonth;\n'
+'var Dateleft = '+document.me.d.options[document.me.d.selectedIndex].value+' - CurDate;\n'
+\n'
+'document.dateform.a.value = Yearleft;\n'
+'document.dateform.b.value = Monthleft;\n'
+'document.dateform.c.value = Dateleft;\n'
+\n'
+'timerID = setTimeout("showtime()",1000);\n'
+'timerRunning = true;\n'
+}')\n'
+'/\n End -->\n</script>\n'
+'</H'+EAD>\n\n'
+'<!-- 第二步：将 OnLoad 事件加入 BODY 标签内 -->\n\n'
+'<BO'+DY Onload="startclock()">\n\n'
+'<!-- 第三步：将最后一部分代码加入 BODY 区 -->\n\n'
+'<form name=dateform>距离'
+m2+''+document.me.d.options[document.me.d.selectedIndex].value+'/'
+document.me.y.options[document.me.y.selectedIndex].value
+'还有\n'
+'<input type=text name=a size=2 value="">年\n'
+'<input type=text name=b size=2 value="">月\n'
+'<input type=text name=c size=2 value="">天\n'
+'</fo'+rm>\n\n'
+'<+!-- 代码长度: 1.95 KB --+>'
);}document.mail.source.value=txt;document.mail.source2.value=txt;}
//-->
</SCRIPT>

```

第二步:把如下代码加入区域中：

```

<center>
<table border=5 bordercolor=blue borderlight=green>
<tr><td align=center><font size=5 color=red face="Arial, Helvetica, sans-serif"><strong>下面框
中为脚本显示区</strong></font></td></tr>
<tr><td align=center><form name=me> <p><select name=m size=1> <option value=0>January
</option> <option value=1>February </option> <option value=2>March </option> <option
value=3>April </option> <option value=4>May </option> <option value=5>June </option>

```

```

<option value=6>July </option> <option value=7>August </option> <option value=8>September
</option> <option value=9>October </option> <option value=10>November </option> <option
value=11>December </option> </select> <select name=d size=1> <option value=1>1 </option>
<option value=2>2 </option> <option value=3>3 </option> <option value=4>4 </option> <option
value=5>5 </option> <option value=6>6 </option> <option value=7>7 </option> <option
value=8>8 </option> <option value=9>9 </option> <option value=10>10 </option> <option
value=11>11 </option> <option value=12>12 </option> <option value=13>13 </option> <option
value=14>14 </option> <option value=15>15 </option> <option value=16>16 </option> <option
value=17>17 </option> <option value=18>18 </option> <option value=19>19 </option> <option
value=20>20 </option> <option value=21>21 </option> <option value=22>22 </option> <option
value=23>23 </option> <option value=24>24 </option> <option value=25>25 </option> <option
value=26>26 </option> <option value=27>27 </option> <option value=28>28 </option> <option
value=29>29 </option> <option value=30>30 </option> <option value=31>31 </option>
</select><select name=y size=1> <option value=1999>1999 </option> <option value=2000>2000
</option> <option value=2001>2001 </option> <option value=2002>2002 </option> <option
value=2003>2003 </option> <option value=2004>2004 </option> <option value=2005>2005
</option> <option value=2006>2006 </option> <option value=2007>2007 </option> <option
value=2008>2008 </option> <option value=2009>2009 </option> </select><br> <input
type=button onclick=generate() value=生成代码 class=yk9><input type=button value=返回
onClick=history.go(-1) name=button class=yk9><p></p></form><form name=mail> <input
type=hidden name=scriptname value="Countdown Creator"><input type=hidden name=source2
value><table bgcolor=dedfdf border=1 cellpadding=1 width=396> <tr> <td align=center
height=218><textarea name=source rows=12 cols=55 class=yk9></textarea><br> <br> </td>
</td> </tr> </table></form></td></tr></table>

```

八种风格的时间日期

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT language=javascript author=luxiaoqing><!--
function initArray(){for(i=0;i<initArray.arguments.length;i++)
this[i]=initArray.arguments[i];}var isnMonths=new initArray("1月","2月","3月","4月","5月","6
月","7月","8月","9月","10月","11月","12月");var isnDays=new initArray("星期日","星期一","
星期二","星期三","星期四","星期五","星期六","星期日");today=new
Date();hrs=today.getHours();min=today.getMinutes();sec=today.getSeconds();clckh=""+((hrs>12)
?hrs-12:hrs);
clckm=((min<10)?"0:"")+min;clcks=((sec<10)?"0:"")+sec;clck=(hrs>=12)?"下午":"上午";var
stnr="";var ns="0123456789";var a="";

//-->

```

```
</SCRIPT>
```

第二步:把如下代码加入区域中

```

<SCRIPT language=javascript><!--
function getFullYear(d){//d is a date object

```

```

yr=d.getYear();if(yr<1000)
yr+=1900;return yr;}document.write("<table width=486>");//don't delete this line

/* 每一段代表一种风格,不需要的删除即可*/

document.write("<TR><TD VALIGN=TOP><P> 风 格 一 <P></TD><TD
VALIGN=TOP>"+isnDays[today.getDay()]
+"," +isnMonths[today.getMonth()+""+today.getDate()+"日,"
+getFullYear(today)+" 年 <P>");document.write("<TR><TD VALIGN=TOP> 风格 二
<P></TD><TD VALIGN=TOP>"+clckh+":"+clckm
+": "+clcks+""+clck+"<P></TD></TR>");document.write("<TR><TD VALIGN=TOP> 风格 三
<P></TD><TD VALIGN=TOP>"+isnDays[today.getDay()+"," +isnMonths[today.getMonth()+""
+today.getDate()+"日," +getFullYear(today)+"年 " +clckh+":"+clckm+":"+
+clcks+""+clck+"<P></TD></TR>");document.write("<TR><TD VALIGN=TOP> 风格 四
<P></TD><TD VALIGN=TOP>"+(today.getMonth()+1)+"/"+today.getDate()+""
+(getFullYear(today)+"").substring(2,4)+"<P></TD></TR>");document.write("<TR><TD
VALIGN=TOP> 风 格 五 :<P></TD><TD
VALIGN=TOP>"+hrs+":"+clckm+":"+clcks+"<P></TD></TR>");document.write("<TR><TD
VALIGN=TOP> 风 格 六 :<P></TD><TD>"+today+"<P></TD></TR>");document.write("<TR><TD VALIGN=TOP>
风格 七 <P></TD><TD>"+navigator.appName+"<P></TD></TR>");document.write("<TR><TD
VALIGN=TOP> 风 格 八 :<P></TD><TD
VALIGN=TOP>"+navigator.appVersion+"<P></TD></TR>");document.write("</table>"); //
don't delete this line
//-->
</SCRIPT>

```

显示登陆时间

脚本说明:

把如下代码加入<body>区域中

```

<form name=forms> <font size=3><CENTER><div align=center><p></font><font color=red
size=3>您在本站逗留了</font><font color=#80FF80><br> <input type=text name=input1
size=10></font></p></div></center></font><SCRIPT language=javascript><!--

```

```

var sec=0;var min=0;var hou=0;flag=0;idt=window.setTimeout("update()",1000);function
update(){sec++;if(sec==60){sec=0;min+=1;}if(min==60){min=0;hou+=1;}if((min>0)&&(flag==
0)){window.alert("您刚刚来了 1 分钟!可别急着走开,还有好多好东东等着您呢!--站长

```



```
");flag=1;}
```

```
document.forms.input1.value=hou+" 时 "+min+" 分 "+sec+" 秒  
";idt=window.setTimeout("update();",1000);}
```

```
//-->
```

```
</SCRIPT></form>
```

日历生成器

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<SCRIPT LANGUAGE="JavaScript">  
<!-- Begin  
var dDate = new Date();  
var dCurMonth = dDate.getMonth();  
var dCurDayOfMonth = dDate.getDate();  
var dCurYear = dDate.getFullYear();  
var objPrevElement = new Object();  
  
function fToggleColor(myElement) {  
var toggleColor = "#ff0000";  
if (myElement.id == "calDateText") {  
if (myElement.color == toggleColor) {  
myElement.color = "";  
} else {  
myElement.color = toggleColor;  
}  
} else if (myElement.id == "calCell") {  
for (var i in myElement.children) {  
if (myElement.children[i].id == "calDateText") {  
if (myElement.children[i].color == toggleColor) {  
myElement.children[i].color = "";  
} else {  
myElement.children[i].color = toggleColor;  
}  
}  
}  
}  
}  
}
```

```

function fSetSelectedDay(myElement){
if (myElement.id == "calCell") {
if (!isNaN(parseInt(myElement.children["calDateText"].innerText))) {
myElement.bgColor = "#c0c0c0";
objPrevElement.bgColor = "";
document.all.calSelectedDate.value = parseInt(myElement.children["calDateText"].innerText);
objPrevElement = myElement;
    }
}
}
function fGetDaysInMonth(iMonth, iYear) {
var dPrevDate = new Date(iYear, iMonth, 0);
return dPrevDate.getDate();
}
function fBuildCal(iYear, iMonth, iDayStyle) {
var aMonth = new Array();
aMonth[0] = new Array(7);
aMonth[1] = new Array(7);
aMonth[2] = new Array(7);
aMonth[3] = new Array(7);
aMonth[4] = new Array(7);
aMonth[5] = new Array(7);
aMonth[6] = new Array(7);
var dCalDate = new Date(iYear, iMonth-1, 1);
var iDayOfFirst = dCalDate.getDay();
var iDaysInMonth = fGetDaysInMonth(iMonth, iYear);
var iVarDate = 1;
var i, d, w;
if (iDayStyle == 2) {
aMonth[0][0] = "Sunday";
aMonth[0][1] = "Monday";
aMonth[0][2] = "Tuesday";
aMonth[0][3] = "Wednesday";
aMonth[0][4] = "Thursday";
aMonth[0][5] = "Friday";
aMonth[0][6] = "Saturday";
} else if (iDayStyle == 1) {
aMonth[0][0] = "Sun";
aMonth[0][1] = "Mon";
aMonth[0][2] = "Tue";
aMonth[0][3] = "Wed";
aMonth[0][4] = "Thu";
aMonth[0][5] = "Fri";
aMonth[0][6] = "Sat";
}
}

```

```

} else {
aMonth[0][0] = "Su";
aMonth[0][1] = "Mo";
aMonth[0][2] = "Tu";
aMonth[0][3] = "We";
aMonth[0][4] = "Th";
aMonth[0][5] = "Fr";
aMonth[0][6] = "Sa";
}
for (d = iDayOfFirst; d < 7; d++) {
aMonth[1][d] = iVarDate;
iVarDate++;
}
for (w = 2; w < 7; w++) {
for (d = 0; d < 7; d++) {
if (iVarDate <= iDaysInMonth) {
aMonth[w][d] = iVarDate;
iVarDate++;
}
}
}
return aMonth;
}

function fDrawCal(iYear, iMonth, iCellWidth, iCellHeight, sDateTextSize, sDateTextWeight,
iDayStyle) {
var myMonth;
myMonth = fBuildCal(iYear, iMonth, iDayStyle);
document.write("<table border='1'>")
document.write("<tr>");
document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'>" + myMonth[0][0] +
"</td>");
document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'>" + myMonth[0][1] +
"</td>");
document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'>" + myMonth[0][2] +
"</td>");
document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'>" + myMonth[0][3] +
"</td>");
document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'>" + myMonth[0][4] +
"</td>");

```

```

document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'" + myMonth[0][5] +
"</td>");
document.write("<td align='center'
style='FONT-FAMILY:Arial;FONT-SIZE:12px;FONT-WEIGHT: bold'" + myMonth[0][6] +
"</td>");
document.write("</tr>");
for (w = 1; w < 7; w++) {
document.write("<tr>")
for (d = 0; d < 7; d++) {
document.write("<td align='left' valign='top' width='" + iCellWidth + "' height='" + iCellHeight +
" id=calCell style='CURSOR:Hand' onMouseOver='fToggleColor(this)'
onMouseOut='fToggleColor(this)' onclick=fSetSelectedDay(this)'>");
if (!isNaN(myMonth[w][d])) {
document.write("<font id=calDateText onMouseOver='fToggleColor(this)'
style='CURSOR:Hand;FONT-FAMILY:Arial;FONT-SIZE:" + sDateTextSize +
";FONT-WEIGHT:" + sDateTextWeight + "' onMouseOut='fToggleColor(this)'
onclick=fSetSelectedDay(this)'>" + myMonth[w][d] + "</font>");
} else {
document.write("<font id=calDateText onMouseOver='fToggleColor(this)'
style='CURSOR:Hand;FONT-FAMILY:Arial;FONT-SIZE:" + sDateTextSize +
";FONT-WEIGHT:" + sDateTextWeight + "' onMouseOut='fToggleColor(this)'
onclick=fSetSelectedDay(this)'>&nbsp;&nbsp;&nbsp;</font>");
}
document.write("</td>")
}
document.write("</tr>");
}
document.write("</table>")
}
function fUpdateCal(iYear, iMonth) {
myMonth = fBuildCal(iYear, iMonth);
objPrevElement.bgColor = "";
document.all.calSelectedDate.value = "";
for (w = 1; w < 7; w++) {
for (d = 0; d < 7; d++) {
if (!isNaN(myMonth[w][d])) {
calDateText[((7*w)+d)-7].innerText = myMonth[w][d];
} else {
calDateText[((7*w)+d)-7].innerText = " ";
}
}
}
}
}

```

```
// End -->
</script>
```

第二步:把如下代码加入<body>区域中:

```
<script language="JavaScript" for=window event=onload>
<!-- Begin
var dCurDate = new Date();
frmCalendarSample.tbSelMonth.options[dCurDate.getMonth()].selected = true;
for (i = 0; i < frmCalendarSample.tbSelYear.length; i++)
if (frmCalendarSample.tbSelYear.options[i].value == dCurDate.getFullYear())
frmCalendarSample.tbSelYear.options[i].selected = true;
// End -->
</script>
```

```
<form name="frmCalendarSample" method="post" action="">
<input type="hidden" name="calSelectedDate" value="">
```

```
<table border="1">
<tr>
<td>
<select name="tbSelMonth" onchange='fUpdateCal(frmCalendarSample.tbSelYear.value,
frmCalendarSample.tbSelMonth.value)'>
<option value="1">January</option>
<option value="2">February</option>
<option value="3">March</option>
<option value="4">April</option>
<option value="5">May</option>
<option value="6">June</option>
<option value="7">July</option>
<option value="8">August</option>
<option value="9">September</option>
<option value="10">October</option>
<option value="11">November</option>
<option value="12">December</option>
</select>
```

```
<select name="tbSelYear" onchange='fUpdateCal(frmCalendarSample.tbSelYear.value,
frmCalendarSample.tbSelMonth.value)'>
<option value="1998">1998</option>
<option value="1999">1999</option>
<option value="2000">2000</option>
<option value="2001">2001</option>
<option value="2002">2002</option>
<option value="2003">2003</option>
```

```
<option value="2004">2004</option>
</select>
</td>
</tr>
<tr>
<td>
<script language="JavaScript">
var dCurDate = new Date();
fDrawCal(dCurDate.getFullYear(), dCurDate.getMonth()+1, 30, 30, "12px", "bold", 1);
</script>
</td>
</tr>
</table>
</form>
```

退出时显示访问时间

脚本说明:

第一步：把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="Javascipt">
<!-- Begin
pageOpen = new Date();

function bye() {
pageClose = new Date();
minutes = (pageClose.getMinutes() - pageOpen.getMinutes());
seconds = (pageClose.getSeconds() - pageOpen.getSeconds());
time = (seconds + (minutes * 60));
if (time == 1) {
time = (time + " second");
}
else {
time = (time + " seconds");
}
alert('您在这儿呆了' + time + '欢迎再来!');
}
// End -->
</SCRIPT>
```

第二步：把<body>区域改为

```
<body bgcolor="#ffffff" onUnload="bye()">
```

一款特酷的时钟

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<script language="javascript1.1">
```

```
<!--
```

```
/*
```

Live clock script credit: Website Abstraction (www.wsabstract.com).

Your free JavaScripts archieve, with over 200+ free JavaScripts.

This script may be freely used as long as credit remains intact.

```
*/
```

```
var dn
```

```
c1=new Image(); c1.src="c1.gif"
```

```
c2=new Image(); c2.src="c2.gif"
```

```
c3=new Image(); c3.src="c3.gif"
```

```
c4=new Image(); c4.src="c4.gif"
```

```
c5=new Image(); c5.src="c5.gif"
```

```
c6=new Image(); c6.src="c6.gif"
```

```
c7=new Image(); c7.src="c7.gif"
```

```
c8=new Image(); c8.src="c8.gif"
```

```
c9=new Image(); c9.src="c9.gif"
```

```
c0=new Image(); c0.src="c0.gif"
```

```
cb=new Image(); cb.src="cb.gif"
```

```
cam=new Image(); cam.src="cam.gif"
```

```
cpm=new Image(); cpm.src="cpm.gif"
```

```
function extract(h,m,s,type){
```

```
if (!document.images)

return

if (h<=9){

document.images.a.src=cb.src

document.images.b.src=eval("c"+h+".src")

}

else {

document.images.a.src=eval("c"+Math.floor(h/10)+".src")

document.images.b.src=eval("c"+(h%10)+".src")

}

if (m<=9){

document.images.d.src=c0.src

document.images.e.src=eval("c"+m+".src")

}

else {

document.images.d.src=eval("c"+Math.floor(m/10)+".src")

document.images.e.src=eval("c"+(m%10)+".src")

}

if (s<=9){

document.g.src=c0.src

document.images.h.src=eval("c"+s+".src")

}
```



```
else {

document.images.g.src=eval("c"+Math.floor(s/10)+".src")

document.images.h.src=eval("c"+(s%10)+".src")

}

if (dn=="AM") document.j.src=cam.src

else document.images.j.src=cpm.src

}

function show3(){

if (!document.images)

return

var Digital=new Date()

var hours=Digital.getHours()

var minutes=Digital.getMinutes()

var seconds=Digital.getSeconds()

dn="AM"

if ((hours>=12)&&(minutes>=1)||(hours>=13)){

dn="PM"

hours=hours-12

}

if (hours==0)

hours=12

extract(hours,minutes,seconds,dn)
```

```
setTimeout("show3()",1000)
```

```
}
```

```
//-->
```

```
</script>
```

第二步:把<body>中加入如下代码 :

```

```

第三步 : 把<body>中内容改为 :

```
<body bgcolor="#ffffff" onLoad="show3()">
```

全中文日期显示

脚本说明 :

把如下代码加入<body>区域中:

```
<script language="JavaScript">
```

```
function number(index1){
```

```
var numberstring="一二三四五六七八九十";
```

```
if(index1 ==0) {document.write("十")}
```

```
if(index1 < 10){
```

```
document.write(numberstring.substring(0+(index1-1),index1))}
```

```
else if(index1 < 20 ){
```

```
document.write("十"+numberstring.substring(0+(index1-11),(index1-10)))}
```

```
else if(index1 < 30 ){
```

```
document.write("二十"+numberstring.substring(0+(index1-21),(index1-20)))}
```

```
else{
```

```
document.write("三十"+numberstring.substring(0+(index1-31),(index1-30)))}
```

```
}
```

```
var today1 = new Date()
```

```
var month = today1.getMonth()+1
```

```
var date = today1.getDate()
```

```
var day = today1.getDay()
```

```
document.write("公元二零零零年")
```

```
number(month)
```

```
document.write("月")
```

```
number(date)
document.write("日")
</script>
```

纯 JavaScript 时钟

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<SCRIPT language=javascript>
<!--
pX=400;pY=200
obs = new Array(13)
function ob () {
  for (i=0; i<13; i++) {
    if (document.all) obs[i]=new Array (eval('ob'+i).style,-100,-100)
    else obs[i] = new Array (eval('document.ob'+i),-100,-100)
  }
}
function cl(a,b,c){
  if (document.all) {
    if (a!=0) b+=-1
    eval('c'+a+'.style.pixelTop='+pY+(c))
    eval('c'+a+'.style.pixelLeft='+pX+(b))
  }
  else{
    if (a!=0) b+=10
    eval('document.c'+a+'.top='+pY+(c))
    eval('document.c'+a+'.left='+pX+(b))
  }
}
if (document.all) c0.style.pixelLeft=26
}

function runClock() {
  for (i=0; i<13; i++) {
    obs[i][0].left=obs[i][1]+pX
    obs[i][0].top=obs[i][2]+pY
  }
}

var lastsec
function timer() {
  time = new Date ()
  sec = time.getSeconds()
  if (sec!=lastsec) {
```

```

lastsec = sec
sec=Math.PI*sec/30
min=Math.PI*time.getMinutes()/30
hr =Math.PI*((time.getHours()*60)+time.getMinutes())/360
for (i=1;i<6;i++) {
    obs[i][1] = Math.sin(sec) * (44 - (i-1)*11)-16;
    if (document.layers)obs[i][1]+=10;
    obs[i][2] = -Math.cos(sec) * (44 - (i-1)*11)-27;
}
for (i=6;i<10;i++) {
    obs[i][1] = Math.sin(min) * (40 - (i-6)*10)-16;
    if (document.layers)obs[i][1]+=10;
    obs[i][2] = -Math.cos(min) * (40 - (i-6)*10)-27;
}
for (i=10;i<13;i++) {
    obs[i][1] = Math.sin(hr) * (37 - (i-10)*11)-16;
    if (document.layers)obs[i][1]+=10;
    obs[i][2] = -Math.cos(hr) * (37 - (i-10)*11)-27;
}
}

function setNum(){

cl (0,-67,-65);
cl (1,10,-51);
cl (2,28,-33);
cl (3,35,-8);
cl (4,28,17);
cl (5,10,35);
cl (6,-15,42);
cl (7,-40,35);
cl (8,-58,17);
cl (9,-65,-8);
cl (10,-58,-33);
cl (11,-40,-51);
cl (12,-16,-56);

}

//-->

</SCRIPT>

```

第二步:把<body>中加入如下代码 :

```
<div id="c0" style="position:absolute;right:6;top:6; z-index:2;">
  </div>
  <div id="c1" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>1</b></div>
  <div id="c2" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>2</b></div>
  <div id="c3" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>3</b></div>
  <div id="c4" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>4</b></div>
  <div id="c5" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>5</b></div>
  <div id="c6" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>6</b></div>
  <div id="c7" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>7</b></div>
  <div id="c8" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>8</b></div>
  <div id="c9" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>9</b></div>
  <div id="c10" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>10</b></div>
  <div id="c11" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>11</b></div>
  <div id="c12" style="position:absolute;left:20;top:-20;
z-index:5;font-size:11px;"><b>12</b></div>
  <div id="ob0" style="position:absolute;left:-20;top:-20;z-index:1"> </div>
  <div id="ob1" style="position:absolute;left:-20;top:-20;z-index:8"> <font size="+3"
color="#0000FF"><b>.</b></font></div>
  <div id="ob2" style="position:absolute;left:-20;top:-20;z-index:8"> <font size="+3"
color="#0000FF"><b>.</b></font></div>
  <div id="ob3" style="position:absolute;left:-20;top:-20;z-index:8"> <font size="+3"
color="#0000FF"><b>.</b></font></div>
  <div id="ob4" style="position:absolute;left:-20;top:-20;z-index:8"> <font size="+3"
color="#0000FF"><b>.</b></font></div>
  <div id="ob5" style="position:absolute;left:-20;top:-20;z-index:8"> <font size="+3"
color="#0000FF"><b>.</b></font></div>
  <div id="ob6" style="position:absolute;left:-20;top:-20;z-index:7"> <font size="+3"
color="#00FFFF"><b>.</b></font></div>
  <div id="ob7" style="position:absolute;left:-20;top:-20;z-index:7"> <font size="+3"
color="#00FFFF"><b>.</b></font></div>
```

```

    <div id="ob8" style="position:absolute;left:-20;top:-20;z-index:7"> <font size="+3"
color="#00FFFF"><b>.</b></font></div>
    <div id="ob9" style="position:absolute;left:-20;top:-20;z-index:7"> <font size="+3"
color="#00FFFF"><b>.</b></font></div>
    <div id="ob10" style="position:absolute;left:-20;top:-20;z-index:6"> <font size="+3"
color="#F30000"><b>.</b></font></div>
    <div id="ob11" style="position:absolute;left:-20;top:-20;z-index:6"> <font size="+3"
color="#F30000"><b>.</b></font></div>
    <div id="ob12" style="position:absolute;left:-20;top:-20;z-index:6"> <font size="+3"
color="#F30000"><b>.</b></font></div>

```

第三步：把<body>中内容改为：

```

<body style="background-color:#ffffff"
onLoad="ob(),setNum(),setInterval('timer()',100);setInterval('runClock()',100)">

```

距离某天时间

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT language=javascript><!--
BirthDay=new Date("january 01,2000");//改成你的计时日期
today=new Date();
timeold=(today.getTime()-BirthDay.getTime());
sectimeold=timeold/1000
secondsold=Math.floor(sectimeold);
msPerDay=24*60*60*1000
e_daysold=timeold/msPerDay
daysold=Math.floor(e_daysold);
e_hrsold=(e_daysold-daysold)*24;
hrsold=Math.floor(e_hrsold);
e_minsold=(e_hrsold-hrsold)*60;
minsold=Math.floor((e_hrsold-hrsold)*60);
seconds=Math.floor((e_minsold-minsold)*60);
//-->
</SCRIPT><SCRIPT language=javascript><!--
document.write("新世纪已经进去了"+daysold+"天"+hrsold+"小时"+minsold+"分"+seconds+"
秒了!");
//-->
</SCRIPT>

```

显示特殊节日脚本

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT language=javascript>

```

```

<!--
calendar = new Date();
day = calendar.getDay();
month = calendar.getMonth();
date = calendar.getDate();
year = calendar.getYear();
if (year < 100) year = 1900 + year;
cent = parseInt(year/100);
g = year % 19;
k = parseInt((cent - 17)/25);
i = (cent - parseInt(cent/4) - parseInt((cent - k)/3) + 19*g + 15) % 30;
i = i - parseInt(i/28)*(1 - parseInt(i/28)*parseInt(29/(i+1))*parseInt((21-g)/11));
j = (year + parseInt(year/4) + i + 2 - cent + parseInt(cent/4)) % 7;
l = i - j;
emonth = 3 + parseInt((l + 40)/44);
edate = 1 + 28 - 31*parseInt((emonth/4));
emonth--;
var dayname = new Array ("星期日", "星期一", "星期二", "星期三", "星期四", "星期五", "星期六");
var monthname =
new Array ("1月", "2月", "3月", "4月", "5月", "6月", "7月", "8月", "9月", "10月", "11月", "12月");
document.write("<font color=FF0000>" + year + "年");
document.write(monthname[month]);
document.write(date + "日");
document.write(dayname[day] + " " + "</font>");

// January(1月份节日, 以下同。)
if ((month == 0) && (date == 1)) document.write("元旦");
if ((month == 0) && (date == 10)) document.write("我的生日");
if ((month == 4) && (date == 1)) document.write("国际劳动节");
if ((month == 4) && (date == 4)) document.write("青年节");
if ((month == 5) && (date == 1)) document.write("国际儿童节");
if ((month == 11) && (date == 25)) document.write("圣诞节");

document.write("<br></font>");

//-->
</SCRIPT>

```

时钟加在背景上

脚本说明：

第一步:把如下代码加入<head>区域中:

```

<script language=JavaScript>
<!--//

```

```

function clockon() {
thistime= new Date()
var hours=thistime.getHours()
var minutes=thistime.getMinutes()
var seconds=thistime.getSeconds()
if (eval(hours) <10) {hours="0"+hours}
if (eval(minutes) < 10) {minutes="0"+minutes}
if (seconds < 10) {seconds="0"+seconds}
thistime = hours+":"+minutes+": "+seconds

if(document.all) {
bgclocknoshade.innerHTML=thistime
bgclockshade.innerHTML=thistime
}

if(document.layers) {
document.bgclockshade.document.write('<div
                                                                    id="bgclockshade"
style="position:absolute;visibility:visible;font-family:Verdana;color:FFAAAAA;font-size:120px;to
op:10px;left:152px">'+thistime+'</div>')
document.bgclocknoshade.document.write('<div
                                                                    id="bgclocknoshade"
style="position:absolute;visibility:visible;font-family:Verdana;color:DDDDDD;font-size:120px;to
p:10px;left:150px">'+thistime+'</div>')
document.close()
}
var timer=setTimeout("clockon()",200)
}

//-->
</script>

```

第二步:把<body>中加入如下代码 :

```

<div
                                                                    id="bgclockshade"
style="position:absolute;visibility:visible;font-family:Arial;color:FF8888;font-size:120px;top:102
px;left:152px"></div>

<div
                                                                    id="bgclocknoshade"
style="position:absolute;visibility:visible;font-family:Arial;color:DDDDDD;font-size:120px;top:1
00px;left:150px"></div>

<div id="mainbody" style="position:absolute; visibility:visible">
</div>

```


第三步：把<body>中内容改为：

```
<body bgcolor="#ffffff" onLoad="clockon()">
```

Fom中的时钟

脚本说明:

第一步：把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!--
```

```
var timerID = null
```

```
var timerRunning = false
```

```
function stopclock(){
```

```
    if(timerRunning)
```

```
        clearTimeout(timerID)
```

```
        timerRunning = false
```

```
}
```

```
function startclock(){
```

```
    stopclock()
```

```
    showtime()
```

```
}
```

```
function showtime(){
```

```
    var now = new Date()
```

```
    var hours = now.getHours()
```

```
    var minutes = now.getMinutes()
```

```
    var seconds = now.getSeconds()
```

```
    var timeValue = "" + ((hours > 12) ? hours - 12 : hours)
```

```
    timeValue += ((minutes < 10) ? ":0" : ":") + minutes
```

```
    timeValue += ((seconds < 10) ? ":0" : ":") + seconds
```

```
    if (hours>=6 && hours<=12)
```

```
        {timeValue += ("上午")}
```

```
    if(hours>12 && hours<=18)
```

```
        {timeValue += ("下午")}
```

```
    if(hours>18 && hours <=24)
```

```
        {timeValue +=("晚上")}
```

```
    if(hours<6)
```

```
        {timeValue += ("深夜")}
```

```
    document.clock.face.value = timeValue
```

```
    timerID = setTimeout("showtime()",1000)
```

```
    timerRunning = true
```

```
}
```

```

//-->
</script>
<form method="POST" name="clock">
    <p>
        <input type="text" name="face" size="11" style="font-size: 9pt">
    </p>
</form>

```

第二步：把<body>区域改为

```
<body bgcolor="#ffffff" onLoad="startclock();">
```

带开关的 Form时钟

脚本说明:

把如下代码加入<body>区域中

```

<script language="JavaScript">
    var enabled=0;
function TOfunc() {
    TO = window.setTimeout( "TOfunc()", 1000
);
    var today = new Date();
    document.clock.disp.value =
today.toLocaleString();
    }
</script>

    <form name="clock">
        <input type="text" name="disp" value="" size=20
onFocus="this.blur()" >
        <br>
        <input type="radio" name="rad" value="off"
onClick="
    if( enabled==1 )
    {
        document.clock.disp.value=";
        clearTimeout( TO );
        enabled = 0;
    }
" checked>
        关<font color="#FFFF99"> </font>
        <input type="radio" name="rad" value="on"
onClick="
    if( enabled == 0 ) {
        var TO = setTimeout( 'TOfunc()', 1000 );

```

```
enabled = 1;    }" >
    开<font color="#FFFF99"> </font>
</form>
```

距离某日时间

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
<!-- // (c) Henryk Gajewski
var urodz= new Date("6/1/2000");
var s="今天离六一儿童节";
var now = new Date();
var ile = urodz.getTime() - now.getTime();
var dni = Math.floor(ile / (1000 * 60 * 60 * 24));
if (dni > 1)
    document.write(""+s+"还有"+dni+"天")
else if (dni == 1)
    document.write("只有 2 天啦！")
else if (dni == 0)
    document.write("只有 1 天啦！")
else
    document.write("好象已经过了哦！");
// -->
</script>
```

记录几天后的日期

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
<!-- Begin
function AddDays(form) {
DaysToAdd=document.form.DaysToAdd.value;

var now=new Date();
var newdate=new Date();
var newtimems=newdate.getTime()+(DaysToAdd*24*60*60*1000);
newdate.setTime(newtimems);
document.form.display.value=newdate.toLocaleString();
}
// End -->
</script>

<form name=form>
    <input type=text name=DaysToAdd size=4 value=10
onFocus="this.select()" onMouseOver="this.focus()">
```

```
        <input type=button value=" 天 后 的 日 期 将 是 .."
onClick="AddDays(this.form)" name="button">
        <input type=text name="display" size=20 value="">
    </form>
```

Form栏特全时钟

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
<!-- Hide
    var timerID = null
    var timerRunning = false
    function MakeArray(size)
    {
    this.length = size;
    for(var i = 1; i <= size; i++)
    {
    this[i] = "";
    }
    return this;
    }
    function stopclock (){
    if(timerRunning)
    clearTimeout(timerID);
    timerRunning = false
    }
    function showtime () {
    var now = new Date();
    var year = now.getYear();
    var month = now.getMonth() + 1;
    var date = now.getDate();
    var hours = now.getHours();
    var minutes = now.getMinutes();
    var seconds = now.getSeconds();
    var day = now.getDay();
    Day = new MakeArray(7);
    Day[0]="星期天";
    Day[1]="星期一";
    Day[2]="星期二";
    Day[3]="星期三";
    Day[4]="星期四";
    Day[5]="星期五";
    Day[6]="星期六";
    var timeValue = "";
```

```

timeValue += year + "年";
timeValue += ((month < 10) ? "0" : "") + month + "月";
timeValue += date + "日 ";
timeValue += (Day[day]) + " ";
timeValue += ((hours <= 12) ? hours : hours - 12);
timeValue += ((minutes < 10) ? ":0" : ":") + minutes;
timeValue += ((seconds < 10) ? ":0" : ":") + seconds;
timeValue += (hours < 12) ? "上午" : "下午";
document.jsfrm.face.value = timeValue;
timerID = setTimeout("showtime()",1000);
timerRunning = true
}
function startclock () {
stopclock();
showtime()
}
//-->

</script>
<form name='jsfrm'>

</form>

```

第二步:把<body>中的内容改为:

```
<body bgcolor="#ffffff" onLoad="startclock()">
```

全球时间表

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!-- Begin
```

```
var timerRunning = false;
```

```
var timezone = "格林尼治标准时间";
```

```
var adjust = 0;
```

```
function timeCheck(tzone, diff) {
```

```
if (timerRunning) {
```

```
clearTimeout(uptatetime);
```

```
timerRunning = false; }
```

```
gmtOffset=eval(diff+adjust);
```

```
timezone = tzone;
```

```
checkDateTime();
```

```
}
```

```

function checkDateTime () {
var today = new Date();
var year = today.getYear() + 00;
var month = today.getMonth()+1;
var date = today.getDate();
var day = today.getDay();
var hour = today.getHours();
var minute = today.getMinutes();
var second = today.getSeconds();

var lastSat = date - (day+1);
while (lastSat < 32) lastSat+=7;
if (lastSat > 31) lastSat+=-7;
var firstSat = date - (day+1);
while (firstSat > 0) firstSat+=-7;
if (firstSat < 1) firstSat+=7;
if (((month == 4) && (date >= firstSat)) || month > 4) &&
(month < 11 || ((month == 10) && day <= lastSat))) adjust += 60;
yourOffset = (new Date()).getTimezoneOffset();
yourOffset = yourOffset + adjust;

var xx = navigator.appName
var xy = navigator.appVersion;
xy = xy.substring(0,1);
if ((xy == 4) && (xx == "Netscape")) yourOffset = yourOffset+adjust;
if (((month == 4) && (date > 20)) || month > 4) && (month < 11 || ((month == 10) &&
day < 30))) adjust -= 60;

ourDifference = eval(gmtOffset - yourOffset);
var half = eval(ourDifference % 60);
ourDifference = Math.round(ourDifference / 60);
hour = eval(hour - ourDifference);
var m = new Array("",
"1","2","3",
"4","5","6",
"7","8","9",
"10","11","12");
var leap = eval(year % 4);

if ((half == -30) || (half == 30)) minute += 30;
if (minute > 59) minute -= 60, hour++;
if (minute < 0) minute += 60, hour--;
if (hour > 23) hour -= 24, date += 1;
if (((month == 4) || (month == 6) ||

```

```

(month == 9) || (month == 11) && (date==31)) date = 1, month ++;
if (((month == 2) && (date > 28)) && (leap != 0)) date = 1, month ++;
if ((month == 2) && (date > 29)) date = 1, month++;
if (hour < 0) hour += 24, date --;
if ((date == 32) && (month == 12)) month = m[1], date = 1, year++;
if (date == 32) date = 1, month++;
if ((date < 1) && (month == 1)) month= m[12], date = 31, year--;
if (date < 1) date = 31, month --;
if (((month == 4) || (month == 6) ||
(month== 9) || (month == 11)) && (date == 31)) date = 30;
if ((month == 2) && (date > 28)) date = 29;
if (((month == 2) && (date > 28)) && (leap != 0)) date=28;
for (i=1; i<13; i++) {
if (month == i) {
month = m[i]; break;
}
}
}

```

```

var dateTime = hour;
dateTime = ((dateTime < 10) ? "0:" : "") + dateTime;
dateTime = " " + dateTime;
dateTime += ((minute < 10) ? ":0" : ":") + minute;
dateTime += ((second < 10) ? ":0" : ":") + second;
dateTime += (hour >= 12) ? "下午, " : "上午, ";
dateTime += year + "年" + month + "月" + date + "日";

```

```

document.clock.zonetime.value = dateTime;
document.clock.zonename.value = timezone;
updatetime=setTimeout("checkDateTime()", 900);
timerRunning = true;
}
// End -->
</script>

```

```

<br>
<form name=clock>
  <input type=text name=zonetime size=28>
  <br>
  <br>
  <b>当前的地区</b><br>
  <input type=text name=zonename size=21>
  <br>
  <br>
  <table border=1 cellpadding=5>
    <tr>

```

```

        <td align=center>
            <input type=button value=" 太 平 洋 "
onClick="timeCheck(this.value, +480)" name="button">
        </td>
        <td align=center>
            <input type=button value="中心" onClick="timeCheck(this.value,
+420)" name="button">
        </td>
        <td align=center>
            <input type=button value="东方" onClick="timeCheck(this.value,
+300)" name="button">
        </td>
    </tr>
    <tr>
        <td align=center>
            <input type=button value=" 夏 威 夷 "
onClick="timeCheck(this.value, +600)" name="button">
        </td>
        <td align=center>
            <input type=button value=" 墨 西 哥 "
onClick="timeCheck(this.value, +360)" name="button">
        </td>
        <td align=center>
            <input type=button value=" 新 德 里 "
onClick="timeCheck(this.value, -330)" name="button">
        </td>
    </tr>
    <tr>
        <td align=center>
            <input type=button value="北京" onClick="timeCheck(this.value,
-420)" name="button">
        </td>
        <td align=center>
            <input type=button value="东京" onClick="timeCheck(this.value,
-540)" name="button">
        </td>
        <td align=center>
            <input type=button value="伦敦" onClick="timeCheck(this.value,
+0)" name="button">
        </td>
    </tr>
</table>
</form>

```


第二步：把<body>区域改为

```
<body bgcolor="#ffffff" OnLoad="timeCheck(timezone, 0)">
```

随时间变化提示

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT language="JavaScript">
<!-------
    var enabled = 0;    today = new Date();
    var day;    var date;
    if(today.getDay()===0)    day = "星期日"
    if(today.getDay()===1)    day = "星期一"
    if(today.getDay()===2)    day = "星期二"
    if(today.getDay()===3)    day = "星期三"
    if(today.getDay()===4)    day = "星期四"
    if(today.getDay()===5)    day = "星期五"
    if(today.getDay()===6)    day = "星期六"
    document.fgColor = " FF0072";
    date1 = "<font size=2 color=red>" + (today.getYear()) + "年" + (today.getMonth() + 1) + "
月" + today.getDate() + "日" + "</font>";
    date2 = "<font size=1 color=red>" + day + "</font>";
    document.write("<center>" + date1.fontSize(3) + date2.fontSize(3) + "</center>");

//---->
</SCRIPT>
<SCRIPT language="JavaScript">

<!--
document.write("<center><font color=#0066ff size=+1> ")
day = new Date()
hr = day.getHours()
if (hr ==1)
document.write("凌晨一点已过，别忘了休息喔！")
if (hr ==2)
document.write("该休息了，身体可是革命的本钱啊！")
if (hr ==3)
document.write("夜深人静，只有你敲击鼠标的声音...")
if (hr ==4)
document.write("四点过了，你明天不上班？？？")
if (hr ==5)
document.write("该去晨运了!!! ")
if (hr ==6)
document.write("你知道吗，此时是国内网络速度最快的时候！")
```

```

if (hr ==7)
document.write("新的一天又开始了，祝你过得快乐！")
if ((hr ==8) || (hr == 9) || (hr ==10))
document.write("上午好！今天你看上去好精神哦！")
if (hr ==11)
document.write("十一点过了，快下班了吧？")
if (hr ==12)
document.write("十二点过了，还不下班？")
if ((hr==13) || (hr==14))
document.write("你不睡午觉？")
if ((hr==15) || (hr==16) || (hr==17))
document.write("下午好！")
if ((hr==18) || (hr==19))
document.write("吃晚饭了吧？")
if ((hr==20) || (hr==21) || (hr==22))
document.write("今晚又在这玩电脑了，没节目？")
if (hr==23)
document.write("真是越玩越精神，不打算睡了？")
if (hr==0)
document.write("凌晨了，还不睡？")
document.write("</font></center>")
//--->

```

</SCRIPT>

特酷的倒影时钟

脚本说明:

第一步:把如下代码加入<head>区域中

```

<head>
<style>
.time { font-size: 12pt; line-height: 14pt; color:red;}
</style>
<SCRIPT language=JavaScript>
<!-- Hiding
var ctimer;

function init(){
if (document.all){
tim2.style.left=tim1.style.posLeft;
tim2.style.top=tim1.style.posTop+tim1.offsetHeight-6;
settimes();
}
}

```

```

function settimes(){
var time= new Date();
hours= time.getHours();
mins= time.getMinutes();
secs= time.getSeconds();
if (hours<10)
hours="0"+hours;
if(mins<10)
mins="0"+mins;
if (secs<10)
secs="0"+secs;
tim1.innerHTML=hours+":"+mins+":"+secs
tim2.innerHTML=hours+":"+mins+":"+secs
ctimer=setTimeout('settimes()',960);
}
// Done hiding -->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<DIV class=time id=tim1
style="HEIGHT: 20px; LEFT: 50px; POSITION: absolute; TOP: 10px; WIDTH: 10px"></DIV>
<DIV class=time id=tim2
style="FILTER: flipv() alpha(opacity=20); FONT-STYLE: italic; POSITION: absolute"></DIV>

```

第三步:把<body>改为

```
<body bgcolor="#ffffff" onload="init()">
```

特酷的日期显示

脚本说明：

把如下代码加入<body>区域中:

```

<script LANGUAGE="JavaScript">
<!-- Begin
Stamp = new Date();
document.write('<font size="2" face="Arial"><B>' + (Stamp.getMonth() + 1)
+ "/" + Stamp.getDate() + "/" + Stamp.getYear() + '</B></font><BR>');
var Hours;
var Mins;
var Time;
Hours = Stamp.getHours();
if (Hours >= 12) {
Time = " P.M.";
}
else {

```

```

Time = " A.M.";
}
if (Hours > 12) {
Hours -= 12;
}
if (Hours == 0) {
Hours = 12;
}
Mins = Stamp.getMinutes();
if (Mins < 10) {
Mins = "0" + Mins;
}
document.write('<font size="2" face="Arial"><B>' + Hours + ":" + Mins + Time + '</B></font>');
// End
// --></script>

```

2000年日历

脚本说明:

第一步：把如下代码加入<body>区域中

```

<script language="javascript">
<!--
// fill the month table with column headings
function day_title(day_name){
    document.write("<TD ALIGN=center WIDTH=35>" + day_name + "</TD>")
}

// fills the month table with numbers

function fill_table(month,month_length)

{

    day=1

    // begin the new month table

    document.write("<TABLE BORDER=3 CELLSPACING=3 CELLPADDING=% 3><TR>")

    document.write("<TD COLSPAN=7 ALIGN=center><B>" + month + "    " + year + "</B><TR>")

    // column headings

    day_title("Mon")

```

```
day_title("Tue")

day_title("Wed")

day_title("Thu")

day_title("Fri")

day_title("Sat")

day_title("Sun")

// pad cells before first day of month

document.write("</TR><TR>")

for (var i=1;i<start_day;i++){

    document.write("<TD>")

}

// fill the first week of days

for (var i=start_day;i<8;i++){

    document.write("<TD ALIGN=center>"+day+"</TD>")

    day++

}

document.write("<TR>")

// fill the remaining weeks

while (day <= month_length) {

    for (var i=1;i<=7 && day<=month_length;i++){

        document.write("<TD ALIGN=center>"+day+"</TD>")
```

```
        day++

    }

    document.write("</TR><TR>")

    // the first day of the next month

    start_day=i

}

document.write("</TR></TABLE><BR>")

}

// end hiding -->

</script>
```

第二步：把如下代码加入<body>区域中
<script language="javascript">

```
// year

year=2000

// first day of the week of the new year

today= new Date("January 1, "+year)

start_day = today.getDay() + 1    // starts with 0

fill_table("January",31)

fill_table("February",28)

fill_table("March",31)

fill_table("April",30)

fill_table("May",31)
```

```
fill_table("June",30)
```

```
fill_table("July",31)
```

```
fill_table("August",31)
```

```
fill_table("September",30)
```

```
fill_table("October",31)
```

```
fill_table("November",30)
```

```
fill_table("December",31)
```

```
</script>
```

时间日期转换

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script Language="JavaScript">
```

```
<!-- Helpers for JSI page...
```

```
// Navigation - Start
```

```
function goback(){
```

```
    alert("Good Bye!");
```

```
    history.go(-1);
```

```
}
```

```
function getname(str) {
```

```
    alert("Hi, "+ str+"!");
```

```
}
```

```
function gettheDate() {
```

```
    stopclock();
```

```
    Todays = new Date();
```

```

TheDate = "" + (Todays.getMonth()+ 1) + " / " + Todays.getDate() + " / " +
Todays.getYear()

document.clock.face.value = TheDate;

}

function showit () {

    var now = new Date();

    var hours = now.getHours();

    var minutes = now.getMinutes();

    var seconds = now.getSeconds();

    stopclock();

    TotalTime = (minutes > GetTotal)? (minutes-GetTotal):TotalTime;

    document.clock.face.value = TotalTime + " in minutes ";

}

// Navigation - Stop

// Netscapes Clock - Start

// this code was taken from Netscapes JavaScript documentation at

// www.netscape.com on Jan.25.96

var timerID = null;

var TotalTime = 0;

var GetTotal = 0;

var timerRunning = false;

```



```
function stopclock (){  
  
    if(timerRunning)  
  
        clearTimeout(timerID);  
  
    timerRunning = false;  
  
}
```

```
function startclock () {  
  
    // Make sure the clock is stopped  
  
    var now = new Date();  
  
    stopclock();  
  
    GetTotal=now.getMinutes();  
  
    gettheDate()  
  
    showtime();  
  
}
```

```
function showtime () {  
  
    var now = new Date();  
  
    var hours = now.getHours();  
  
    var minutes = now.getMinutes();  
  
    var seconds = now.getSeconds()  
  
    var timeValue = "" + ((hours >12) ? hours -12 :hours)  
  
    timeValue += ((minutes < 10) ? ":0" : ":") + minutes  
  
    timeValue += ((seconds < 10) ? ":0" : ":") + seconds
```

```

timeValue += (hours >= 12) ? " P.M." : " A.M."

document.clock.face.value = timeValue;

timerID = setTimeout("showtime()",1000);

timerRunning = true;

}

function showtimer () {

    var now = new Date();

    var hours = now.getHours();

    var minutes = now.getMinutes();

    var seconds = now.getSeconds()

    var timeValue = "" + ((hours >12) ? hours -12 :hours)

    timeValue += ((minutes < 10) ? ":0" : ":") + minutes

    timeValue += ((seconds < 10) ? ":0" : ":") + seconds

    timeValue += (hours >= 12) ? " P.M." : " A.M."

    document.clock.Tspent.value = timeValue;

    timerID = setTimeout("showtime()",1000);

    timerRunning = true;

}

// Netscapes Clock - Stop

// end Helpers -->
</script>

```

第二步:把如下代码加入<body>区域中

```
<form name="clock" onSubmit="0">
    <input type=button value="Time" size=12 onClick="showtime()">
    <input type=button value="Date" size=12 onClick="gettheDate()">
    <input type="text" name="face" size=12 value="" StartTimer()>
</form>
```

第三步:把<body>区中内容改为

```
<body bgcolor="#ffffff" onLoad="startclock()">
```

时间跳动物器

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="JavaScript">
<!-- Hide this script from old browsers --
```

```
function modRange (value, min, max) {

    if (min == max) {

        return (min)

    }

    var low = Math.min (min, max)

    var high = Math.max (min, max)

    var range = high - low + 1

    var valOff = parseInt (value) - low

    var mod = range * Math.floor (valOff / range)

    result = low + valOff - mod

    if (result < low) {

        result += high

    }

}
```

```
    if (result > high) {  
        result = low  
    }  
  
    return (result)  
}  
  
function array () {  
    this[0] = null  
}  
  
function timerAppStart () {  
    this.stop ()  
  
    this.loop ()  
}  
  
function timerAppStop () {  
    clearTimeout (this.timeout)  
  
    this.timeout = null  
}  
  
function timerAppToggle () {  
    if (this.timeout) {  
        this.stop ()  
    } else {  
        this.start ()  
    }  
}
```

```

}

function timerAppLoop () {

    this.update ()

    command = this.name + '.loop()'

    for (var i = 0; i < this.syncCount; i++) {

        if (this.syncName[i] != "") {

            if (--this.syncCountdown[i] <= 0) {

                this.syncCountdown[i] = this.syncInterval[i]

                command += ';' + this.syncName[i] + '.update()'

            }

        }

    }

    this.timeout = setTimeout (command, this.interval)

}

function timerAppSetOutput (output) {

    if (! this.output) {

        this.output = output

    }

}

function timerAppSetInterval (interval) {

    if (interval) {

        var newInterval = parseInt (interval)
    }
}

```

```
    if (newInterval > 0) {

        this.interval = newInterval

    } else {

        alert ('Interval value must be a positive number: ' + interval)

    }

}

}

function timerAppSync (name, interval) {

    if (interval == null) {

        interval = 1

    }

    if (interval <= 0) {

        eval (this.name + '.unsync("'" + name + "'')')

        return

    }

    var newIndex = this.syncCount

    for (var i = 0; i < this.syncCount; i++) {

        if (this.syncName[i] == name) {

            newIndex = i

            break

        }

    }

}
```

```

    if (newIndex == this.syncCount) {

        this.syncCount++

    }

    this.syncInterval[newIndex] = interval

    this.syncCountdown[newIndex] = interval

    this.syncName[newIndex] = name

}

function timerAppUnsync (name) {

    for (var i = 0; i < this.syncCount; i++) {

        if (this.syncName[i] == name) {

            this.syncName[i] = ""

            if (i == (this.syncCount - 1)) {

                this.syncCount--

            }

        }

    }

}

function timerAppSetIncrement (increment) {

    if (increment) {

        var newIncrement = parseInt (increment)

        /*Unix only*   if (! isNaN (newIncrement)) {

            if (newIncrement != 0) {

```

```

        this.increment = newIncrement
    } else {

        alert ('Increment value must be a number: ' + increment)

    }

}

function timerAppSetBounce (bounce) {

    if (bounce) {

        var newBounce = parseInt (bounce)

        /*Unix only*   if (! isNaN (newBounce)) {

            if (newBounce != 0) {

                this.bounce = newBounce

            } else {

                alert ('Bounce value must be a number: ' + bounce)

            }

        }

    }

}

function timerAppSetOffset (offset) {

    if (offset) {

        var newOffset = parseInt (offset)

        if ((newOffset > 0)

            && (newOffset <= this.output.length)) {

```



```

        this.offset = newOffset

    } else {

        warnMessage = 'Value of offset must be a valid index (0 - '
                    + this.output.length + '): ' + offset

        alert (warnMessage)

    }

}

function clock (name, output, interval) {

    // Initialize with default values

    this.name = name           // object name, needed for setTimeout

    this.output = null        // output area

    this.interval = 1000      // milliseconds

    this.timeout = null

    this.syncCount = 0

    this.syncName = new array ()

    this.syncInterval = new array ()

    this.syncCountdown = new array ()

    // Define object methods

    this.update = clockUpdate

    this.start = timerAppStart

    this.stop = timerAppStop

```

```

this.toggle = timerAppToggle

this.loop = timerAppLoop

this.setOutput = timerAppSetOutput

this.setInterval = timerAppSetInterval

this.sync = timerAppSync

this.unsync = timerAppUnsync

// Initialize with specified values

this.setOutput (output)

this.setInterval (interval)

this.start()

}

function clockUpdate () {

    var now = new Date()

    var timeHH = now.getHours();

    var timeMM = now.getMinutes()

    var timeSS = now.getSeconds()

    var msec = now.getTime ()

    var timeSSm = msec - 1000 * Math.floor (msec / 1000)

    timeSSm = '00' + timeSSm

    timeSSm = timeSSm.substring(timeSSm.length-3, timeSSm.length)

    var timeString = ((timeHH < 10) ? '0' : '') + timeHH

                    + ':' + ((timeMM < 10) ? '0' : '') + timeMM

```

```

        + ':' + ((timeSS < 10) ? '0' : '') + timeSS

        + '.' + timeSSm

    if (this.output) {

        this.output.value = timeString

    } else {

        self.status = timeString

    }

}

function buttons (name, output, interval, increment, bounce, offset) {

    // Initialize with default values

    this.name = name

    this.output = null

    this.interval = 1000

    this.increment = 1

    this.bounce = 1

    this.offset = 0

    this.timeout = null

    this.syncCount = 0

    this.syncName = new array ()

    this.syncInterval = new array ()

    this.syncCountdown = new array ()

    // Define object methods

```

```
this.update = buttonsUpdate

this.start = timerAppStart

this.stop = timerAppStop

this.toggle = timerAppToggle

this.loop = timerAppLoop

this.setOutput = timerAppSetOutput

this.setInterval = timerAppSetInterval

this.sync = timerAppSync

this.unsync = timerAppUnsync

this.setIncrement = timerAppSetIncrement

this.setBounce = timerAppSetBounce

this.setOffset = timerAppSetOffset

// Initialize with specified values

this.setOutput (output)

this.setInterval (interval)

this.setIncrement (increment)

this.setBounce (bounce)

this.setOffset (offset)

this.start()

}

function buttonsUpdate () {

    if (this.output) {
```

```

var newOffset = this.offset + this.increment

if ((newOffset < this.output.length)

    && (newOffset >= 0)) {

    this.offset = newOffset

} else {

    this.increment *= this.bounce

    if (this.increment >= 0) {

        this.increment = modRange (this.increment, 0, this.output.length-1)

    } else {

        this.increment = 0 - modRange (Math.abs (this.increment),

                                        0, this.output.length-1)

    }

    this.offset += this.increment

    this.offset = modRange (this.offset, 0, this.output.length-1)

}

this.output[this.offset].checked = true

}

}

// -- End Hiding Here -->
</script>

```

第二步:把如下代码加入<body>区域中
<FORM NAME='clock' ACTION='>

```
<TABLE BORDER=2><TR><TD>
```

```
<FONT SIZE=-2>
```

```
<INPUT TYPE='text' NAME='display' SIZE=8
```

```
onFocus='wClock.toggle()'
```

```
onMouseOver='self.status="Click here to turn on/off clock"; return true'>
```

```
</FONT>
```

```
</TD></TR></TABLE>
```

```
</FORM>
```

```
<FORM NAME='imastudios'>
```

```
<P>
```

```
<INPUT TYPE='radio' NAME='buttons'>
```

Tick

```
<INPUT TYPE='radio' NAME='buttons'>
```

Tock

```
<INPUT TYPE='radio' NAME='buttons'>
```

Tick

```
<INPUT TYPE='radio' NAME='buttons'>
```

Tock

```
<INPUT TYPE='radio' NAME='buttons'>
```

Tick

</FORM>

第三步:把<body>区中内容改为

```
<body bgcolor="#ffffff" onLoad='wClock = new clock ("wClock", document.clock.display);
wButtons = new buttons ("wButtons", document.imastudios.buttons, 500, 1,-1); wButtons.stop();
wClock.sync ("wButtons", 1)'onUnload='wClock.stop(); wButtons.stop()' bgcolor="#FFFFFF">
```

自己创建日历

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!--
```

```
function displayCalendar(init) {

    var i;

    var now = new Date();

        var nowYear = now.getFullYear() - 95;

    var nowMonth = now.getMonth();

    var nowDay    = now.getDate();

    // on open of document

    if (init==1) {

        document.calControl.month.selectedIndex = nowMonth;

        document.calControl.year.selectedIndex = nowYear;

    }

    var month=document.calControl.month.selectedIndex

    var year=document.calControl.year.selectedIndex+1995
```

```
var days=getDaysInMonth(month+1,year);

var firstOfMonth = new Date (year, month, 1);

var startingPos=firstOfMonth.getDay()+7;

days+=startingPos;

// label days of week

i=0;

    document.calButtons.elements[i++].value = " S ";

document.calButtons.elements[i++].value = " M ";

document.calButtons.elements[i++].value = " T ";

document.calButtons.elements[i++].value = " W ";

document.calButtons.elements[i++].value = " T ";

document.calButtons.elements[i++].value = " F ";

document.calButtons.elements[i++].value = " S ";

// blank out non date buttons

for (i=7; i<startingPos; i++)

    document.calButtons.elements[i].value = "   ";
```



```

    for (i=startingPos; i<days; i++)

        document.calButtons.elements[i].value = i-startingPos+1;

// show focus on today if the calendar is the proper month and year
if (month==nowMonth && year==nowYear+1995)

    document.calButtons.elements[nowDay+startingPos-1].focus();

// blank out rest of non date buttons

    for (i=days; i<49; i++)

        document.calButtons.elements[i].value = "    ";
}

function leapYear (Year) {

    if (((Year % 4)==0) && ((Year % 100)!=0) || ((Year % 400)==0))

        return (1);

    else

        return (0);

}

function getDaysInMonth(month,year) {

```

```

var days;

if (month==1 || month==3 || month==5 || month==7 || month==8 ||

    month==10 || month==12)  days=31;

else if (month==4 || month==6 || month==9 || month==11) days=30;

else if (month==2)  {

    if (leapYear (year)==1)  days=29;

    else days=28;

}

return (days);

}

// -->

</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<FORM  NAME="calControl">month  <SELECT  NAME="month"><OPTION>Jan
<OPTION>Feb <OPTION>Mar <OPTION>Apr <OPTION>May <OPTION>Jun <OPTION>Jul
<OPTION>Aug <OPTION>Sep <OPTION>Oct <OPTION>Nov <OPTION>Dec </SELECT>

year  <SELECT  NAME="year"><OPTION>1995  <OPTION>1996  <OPTION>1997
<OPTION>1998  <OPTION>1999  <OPTION>2000  </SELECT><INPUT  TYPE="button"
NAME="button1"  VALUE="Create"

    onClick="displayCalendar(0)"></FORM><FORM  NAME="calButtons"><INPUT
TYPE="button"  NAME="but0"  value="    "><INPUT  TYPE="button"  NAME="but1"
value="    "><INPUT  TYPE="button"  NAME="but2"  value="    "><INPUT
TYPE="button"  NAME="but3"  value="    "><INPUT  TYPE="button"  NAME="but4"
value="    "><INPUT  TYPE="button"  NAME="but5"  value="    "><INPUT
TYPE="button"  NAME="but6"  value="    "></CENTER>

```

<CENTER><INPUT TYPE="button" NAME="but7" value="" "><INPUT TYPE="button" NAME="but8" value="" "><INPUT TYPE="button" NAME="but9" value="" "><INPUT TYPE="button" NAME="but10" value="" "><INPUT TYPE="button" NAME="but11" value="" "><INPUT TYPE="button" NAME="but12" value="" "><INPUT TYPE="button" NAME="but13" value="" "></CENTER>

<CENTER><INPUT TYPE="button" NAME="but14" value="" "><INPUT TYPE="button" NAME="but15" value="" "><INPUT TYPE="button" NAME="but16" value="" "><INPUT TYPE="button" NAME="but17" value="" "><INPUT TYPE="button" NAME="but18" value="" "><INPUT TYPE="button" NAME="but19" value="" "><INPUT TYPE="button" NAME="but20" value="" "></CENTER>

<CENTER><INPUT TYPE="button" NAME="but21" value="" "><INPUT TYPE="button" NAME="but22" value="" "><INPUT TYPE="button" NAME="but23" value="" "><INPUT TYPE="button" NAME="but24" value="" "><INPUT TYPE="button" NAME="but25" value="" "><INPUT TYPE="button" NAME="but26" value="" "><INPUT TYPE="button" NAME="but27" value="" "></CENTER>

<CENTER><INPUT TYPE="button" NAME="but28" value="" "><INPUT TYPE="button" NAME="but29" value="" "><INPUT TYPE="button" NAME="but30" value="" "><INPUT TYPE="button" NAME="but31" value="" "><INPUT TYPE="button" NAME="but32" value="" "><INPUT TYPE="button" NAME="but33" value="" "><INPUT TYPE="button" NAME="but34" value="" "></CENTER>

<CENTER><INPUT TYPE="button" NAME="but35" value="" "><INPUT TYPE="button" NAME="but36" value="" "><INPUT TYPE="button" NAME="but37" value="" "><INPUT TYPE="button" NAME="but38" value="" "><INPUT TYPE="button" NAME="but39" value="" "><INPUT TYPE="button" NAME="but40" value="" "><INPUT TYPE="button" NAME="but41" value="" "></CENTER>

<CENTER><INPUT TYPE="button" NAME="but42" value="" "><INPUT TYPE="button"

```
NAME="but43" value="" "><INPUT TYPE="button" NAME="but44" value="
"><INPUT TYPE="button" NAME="but45" value="" "><INPUT TYPE="button"
NAME="but46" value="" "><INPUT TYPE="button" NAME="but47" value="
"><INPUT TYPE="button" NAME="but48" value="" "></CENTER>
```

```
<CENTER></FORM>
```

第三步:把<body>区中内容改为

```
<body bgcolor="#ffffff" ONLOAD="displayCalendar(1)">
```

生日提醒器

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

```
function birthday(year,month,date,person) {
```

```
    this.year=year
```

```
    this.month=month
```

```
    this.date=date
```

```
    this.person=person
```

```
}
```

```
function birthdaylist() {
```

```
}
```

```

blist=new birthdaylist()

blist[0]= new birthday(84,1,16,"Matthew")

blist[1]= new birthday(53,1,27,"Brenda")

blist[2]= new birthday(82,3,1,"Ray")

blist[3]= new birthday(88,4,27,"Michael")

blist[4]= new birthday(86,9,2,"Andrew")

blist[5]= new birthday(49,11,24,"Raymond")

var now=new Date()

today=new Date(now.getYear(),now.getMonth(),now.getDate()) // today 0:00:00

function daysFromToday(sdate) {

    return Math.round((sdate.getTime()-today.getTime())/(24*60*60*1000))

}

function writeNextBirthday(list) {

    var daysToClosest=888

    var closest

    for (var i in list) {

        thisDate=new Date(today.getYear(),list[i].month,list[i].date)

        if (daysFromToday(thisDate)<0)

            thisDate.setYear(today.getYear()+1)

        if (daysFromToday(thisDate)<daysToClosest) {

```

```

        daysToClosest=daysFromToday(thisDate)

        closest=i

    }

}

if (daysToClosest==0)

    document.write("<B>So      today      "+list[closest].person+"      became
"+(today.getYear()-list[closest].year)+" years old !! Hoorah!</B><P>")

    else if (daysToClosest==1)

        document.write("So      tomorrow      "+list[closest].person+"      will      become
"+(today.getYear()-list[closest].year)+" !<P>")

    else

        document.write("So the next birthday will be "+list[closest].person+"s, in
"+daysToClosest+" days.<P>")

}

// end hiding -->

</SCRIPT>

```

第二步:把如下代码加入<body>区域中
<SCRIPT LANGUAGE="JavaScript">

<!--

```

writeNextBirthday(blist)

```

```
// -->
```

```
</SCRIPT>
```

计算任一天星期几

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="LiveScript">
```

```
<!--
```

```
function mod(x, x_div){
```

```
    for (var i=x; i>=x_div; i -= x_div);
```

```
        return i;
```

```
}
```

```
function checkNum(str, min, max) {
```

```
    if (str == "") {
```

```
        alert("Enter a number in the field, please.");
```

```
        return false;
```

```
    }
```

```
    for (var i = 0; i < str.length; i++) {
```

```
        var ch = str.substring(i, i + 1);
```

```
        if (ch < "0" || ch > "9") {
```

```
            alert("Try a number, please.");
```

```
            return false;
```

```
        }
```

```
    }
```

```

var val = parseInt(str, 10);

if ((val < min) || (val > max)) {

    alert("Try a number from 1 to "+max+".");

    return false;

}

return true;

}

function pushbutton(form){

    //Check for a valid date

    if ((checkNum(form.day.value,1,31)) && (checkNum(form.month.value,1,12)) &&
(checkNum(form.year.value,0,99))){

        var cur_day = parseInt(form.day.value,10);

        var cur_month = parseInt(form.month.value,10);

        var cur_year = parseInt(form.year.value,10);

        //alert(" "+cur_day+" "+cur_month+" "+cur_year);

        //Significant value

        var sig_val;

        if (cur_month == 1)

            sig_val = 0;

        else if (cur_month == 2)

            sig_val = 3;

```



```
else if (cur_month == 3)

    sig_val = 3;

else if (cur_month == 4)

    sig_val = 6;

else if (cur_month == 5)

    sig_val = 1;

else if (cur_month == 6)

    sig_val = 4;

else if (cur_month == 7)

    sig_val = 6;

else if (cur_month == 8)

    sig_val = 2;

else if (cur_month == 9)

    sig_val = 5;

else if (cur_month == 10)

    sig_val = 0;

else if (cur_month == 11)

    sig_val = 3;

else if (cur_month == 12)

    sig_val = 5;

var val1 = mod((cur_year + parseInt(cur_year/4) + cur_day + sig_val),7);
```

```
//Display the correct file

    if (val1 == 0)

        alert("Sunday");

    else if (val1 == 1)

        alert("Monday");

    else if (val1 == 2)

        alert("Tuesday");

    else if (val1 == 3)

        alert("Wednesday");

    else if (val1 == 4)

        alert("Thursday");

    else if (val1 == 5)

        alert("Friday");

    else if (val1 == 6)

        alert("Saturday");

        return true;

    }

else

return false;

}

//-->
</SCRIPT>
<FORM NAME = "What_Day">
```

```
<PRE><B>Day:</B>
```

```
<INPUT TYPE="num" name="day" onChange="if (!checkNum(this.value, 1, 31)){this.focus();this.select();} else {}" size=10 value="">
```

```
<B>Month:</B>
```

```
<INPUT TYPE="num" name="month" onChange="if (!checkNum(this.value, 1, 12)){this.focus();this.select();} else {}" size=10 value="">
```

```
<B>Year:</B>
```

```
<INPUT TYPE="num" name="year" onChange="if (!checkNum(this.value, 0, 99)){this.focus();this.select();} else {}" size=10 value="">
```

```
<INPUT TYPE="button" name="Find_Out" value="OK, I'm ready" onclick="pushbutton(this.form)"></PRE>
```

```
</FORM>
```

离开某一天日期

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

按钮上的时间

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
var timerID = null;
var timerRunning = false;
// Called by both onLoad in BODY tag, and Resume button.
function startclock ()
{
  // Make sure the clock is stopped
  stopclock();
  time();
}
```

```

// Kills clock.
function stopclock ()
{
    if(timerRunning)
        clearTimeout(timerID);
    timerRunning = false;
}
function time ()
{
    var now = new Date();
    var yr = now.getYear();
    var mName = now.getMonth() + 1;
    var dName = now.getDay() + 1;
    var dayNr = ((now.getDate()<10) ? "0" : "")+ now.getDate();
    var ampm = (now.getHours() >= 12) ? " P.M." : " A.M."
    var hours = now.getHours();
        hours = ((hours > 12) ? hours - 12 : hours);
    var minutes = ((now.getMinutes() < 10) ? ":0" : ":") + now.getMinutes();
    var seconds = ((now.getSeconds() < 10) ? ":0" : ":") + now.getSeconds();
    if(dName==1) Day = "Sunday";
    if(dName==2) Day = "Monday";
    if(dName==3) Day = "Tuesday";
    if(dName==4) Day = "Wednesday";
    if(dName==5) Day = "Thursday";
    if(dName==6) Day = "Friday";
    if(dName==7) Day = "Saturday";
    if(mName==1) Month="January";
    if(mName==2) Month="February";
    if(mName==3) Month="March";
    if(mName==4) Month="April";
    if(mName==5) Month="May";
    if(mName==6) Month="June";
    if(mName==7) Month="July";
    if(mName==8) Month="August";
    if(mName==9) Month="September";
    if(mName==10) Month="October";
    if(mName==11) Month="November";
    if(mName==12) Month="December";
    // String to display current date.
    var DayDateTime=(" "
        + Day
        + " "
        + Month
        + " "

```

```

        + dayNr
        + ", "
        + ""
        + yr
        + "      "
        + hours
        + minutes
        + seconds
        + " "
        + ampm
    );

    // Displays Day-Date-Time on the staus bar.
    document.clock.face.value=DayDateTime;
    timerID = setTimeout("time()",1000);
    timerRunning = true;
    }
// Stops clock and clears status bar.
function clearStatus()
    {
    if(timerRunning)
        clearTimeout(timerID);
    timerRunning = false;
    window.status=" ";
    }
// -- End Hiding Here -->
</script>

<form name="clock" onSubmit="0">
<input type=button name="face" size=100 value=" JavaScript!!  ">
</form>

```

第二步:把<body>中的内容改为:

```
<body bgcolor="#ffffff" onLoad="startclock ()">
```

Fom中时间显示

脚本说明:

把如下代码加入<body>区域中

```

<FORM>
<SELECT NAME="dates" SIZE=1>
<SCRIPT LANGUAGE="JavaScript">

```

```
//-----
```

```
// By mattias.sjoberg@swipnet.se 26/7-97
```

```

// The JavaScript Planet
// http://www.geocities.com/SiliconValley/7116
// You're welcome to use/edit this script,
// just keep the comments and drop me a note.
//-----

today = new Date();
thismonth = today.getMonth() + 1;
thisyear = today.getYear();
thisday = today.getDate();

maxdays=31;//default

// months with 30 days
if (thismonth==4 || thismonth==6 || thismonth==9 || thismonth==11)
{
    maxdays=30
}

// february, leap year
if (thismonth==2)
{
    // feb
    if ((thisyear/4)!=parseInt(thisyear/4))
    {
        maxdays=28
    }
    else
    {
        //leap year
        maxdays=29
    }
}

thismonth = "" + thismonth
if (thismonth.length == 1)
{
    thismonth = "0" + thismonth;
}

for (var theday = 0; theday <= maxdays; theday++)
{
    if (theday == 0)
    {

```

```

        document.write ("<OPTION SELECTED> "+ thisday + "-" +
thismonth + "-" + thisyear )
        document.write ("<OPTION> =====")
    }
    else
    {
        var thed = "" + theday
        if (thed.length == 1)
        {
            thed = "0" + thed;
        }
        document.write ("<OPTION> " + thed + "-" + thismonth + "-" +
thisyear)
    }
}
}
</SCRIPT>
</SELECT>
</FORM>

```

检测星期几并导航

脚本说明：

把如下代码加入<body>区域中:

```

<SCRIPT>
<!--

function initArray()
{
    this.length = initArray.arguments.length;
    for (var i = 0; i < this.length; i++)
        this[i+1] = initArray.arguments[i];
}

var DOWArray = new
initArray("Monday","Tuesday","Wednesday","Thursday","Friday","Saturday","Sunday");
var today = new Date();
var day = DOWArray[today.getDay()];
alert("Today is " + day + "! If the file " + day + ".html had existed, you would have been taken
there.")
if (day == "Monday") window.location = "Monday.html"
if (day == "Tuesday") window.location = "Tuesday.html"
if (day == "Wednesday") window.location = "Wednesday.html"
if (day == "Thursday") window.location = "Thursday.html"
if (day == "Friday") window.location = "Friday.html"

```

```
if (day == "Saturday") window.location = "Saturday.html"
if (day == "Sunday") window.location = "Sunday.html"
//-->
</SCRIPT>
```

最近的星期天

脚本说明：

把如下代码加入<body>区域中:

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Begin
function isLeapYear () {
year = new Date().getFullYear();
year += (year < 2000 ? 1900 : 0);
return (year % 4==0 && year % 100!=0 || year % 400==0);
}
function formatDate(date) {
mymonth = date.getMonth()+1;
myweekday = date.getDate();
return (mymonth + "/" + myweekday);
}
function printWeek() {
beginDay = 0; // first day of each week
// 0 = sunday, 1= monday .... 6 = saturday

var dayarray = new Array(31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31);
dayarray[1] = (isLeapYear()) ? 29 : 28;
dayfactor = 86400000; // one day equals 86400000 milliseconds
weekstart = new Date();
weekend = new Date();
while (weekstart.getDay() != beginDay) {
weekstart.setTime(weekstart.getTime() - dayfactor);
}
weekend.setTime(weekend.getTime() + 6*dayfactor);
document.write(" 最近两个星期天为： " + formatDate(weekstart) + " - " +
formatDate(weekend));
}
// End -->
</script>
```

```
<script>
printWeek();
</script>
```


全日制时钟

脚本说明：

第一步:把如下代码加入<body>区域中:

```
<script language="JavaScript">
```

```
function showMilitaryTime()
```

```
{
```

```
    if (document.form.showMilitary[0].checked)
```

```
    {
```

```
        return true;
```

```
    }
```

```
    return false;
```

```
}
```

```
function showTheHours(theHour)
```

```
{
```

```
    if (showMilitaryTime() || (theHour > 0 && theHour < 13))
```

```
    {
```

```
        if (theHour == "0") theHour = 12;
```

```
        return (theHour);
```

```
    }
```

```
    if (theHour == 0)
```

```
    {
```

```
        return (12);
```

```
    }
```

```
    return (theHour-12);
```

```
}
```

```
function showZeroFilled(inValue)
```

```
{
```

```
    if (inValue > 9)
```

```
    {
```

```
        return "" + inValue;
```

```
    }
```

```
    return "0" + inValue;
```

```
}
```

```
function showAmPm()
```

```
{
```

```
    if (showMilitaryTime())
```

```
    {
```

```
        return ("");
```

```
    }
```

```
    if (now.getHours() < 12)
```

```
    {
```

```
        return (" am");
```

```
    }
```

```

        return (" pm");
    }
function showTheTime()
{
    now = new Date
    document.form.showTime.value    =    showTheHours(now.getHours())    +    ":"    +
showZeroFilled(now.getMinutes()) + ":" + showZeroFilled(now.getSeconds()) + showAmPm()
    setTimeout("showTheTime()",1000)
}
</script>
<FORM name=form><INPUT name=showTime size=11>
<P><INPUT CHECKED name=showMilitary type=radio>Military Time<BR><INPUT
name=showMilitary type=radio Unchecked> 12 Hour Time </FORM>

```

第二步:把<body>区域中的内容改为:

```
<body bgcolor="#ffffff" onload=showTheTime()>
```

用图片显示日期

脚本说明 :

把如下代码加入<body>区域中:

```
<SCRIPT LANGUAGE="JavaScript">
```

```

<!-- Begin
theDate= new Date();
months = new Array();
days = new Array();
months[1] ="jan.gif";
months[2] ="feb.gif";
months[3] ="mar.gif";
months[4] ="apr.gif";
months[5] ="may.gif";
months[6] ="jun.gif";
months[7] ="jul.gif";
months[8] ="aug.gif";
months[9] ="sep.gif";
months[10] ="oct.gif";
months[11] ="nov.gif";
months[12] ="dec.gif";
days[1] ="1st.gif";
days[2] ="2nd.gif";

```

```

days[3] ="3rd.gif";
days[4] ="4th.gif";
days[5] ="5th.gif";
days[6] ="6th.gif";
days[7] ="7th.gif";
days[8] ="8th.gif";
days[9] ="9th.gif";
days[10] ="10th.gif";
days[11] ="11th.gif";
days[12] ="12th.gif";
days[13] ="13th.gif";
days[14] ="14th.gif";
days[15] ="15th.gif";
days[16] ="16th.gif";
days[17] ="17th.gif";
days[18] ="18th.gif";
days[19] ="18th.gif";
days[20] ="20th.gif";
days[21] ="21st.gif";
days[22] ="22nd.gif";
days[23] ="23rd.gif";
days[24] ="24th.gif";
days[25] ="25th.gif";
days[26] ="26th.gif";
days[27] ="27th.gif";
days[28] ="28th.gif";
days[29] ="29th.gif";
days[30] ="30th.gif";
days[31] ="31st.gif";
function printDate() {
document.write(''); // month
document.write('<br>');
document.write(''); // day
}
// End -->
</script>
<script>
printDate();
</script>

```

详细计算你的年龄

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT LANGUAGE="JavaScript">
```

```

<!-- Begin
function run() {
with (document.agecalc) {
dd = parseInt(day.selectedIndex) + 1;
mm = parseInt(month.selectedIndex) + 1;
yy = year.value;
if (yy.length != 4 || isNaN(yy)) {
document.agecalc.timealive.value = "Please enter a 4-digit year.";
document.agecalc.year.select();
document.agecalc.year.focus();
return;
    }
}
days = new Date();
gdate = days.getDate();
gmonth = days.getMonth();
gyear = days.getYear();
if (gyear < 2000) gyear += 1900;
age = gyear - yy;
if ((mm == (gmonth + 1)) && (dd <= parseInt(gdate))) {
age = age;
} else {
if (mm <= (gmonth)) {
age = age;
} else {
age = age - 1;
    }
}
if (age == 0)
age = age;
document.agecalc.timealive.value = "You are " + age + " years old . . .\n\n";
if (mm <= (gmonth + 1))
age = age - 1;
if ((mm == (gmonth + 1)) && (dd > parseInt(gdate)))
age = age + 1;
var m;
var n;
if (mm == 12) n = 31 - dd;
if (mm == 11) n = 61 - dd;
if (mm == 10) n = 92 - dd;
if (mm == 9) n = 122 - dd;
if (mm == 8) n = 153 - dd;
if (mm == 7) n = 184 - dd;

```

```

if (mm == 6) n = 214 - dd;
if (mm == 5) n = 245 - dd;
if (mm == 4) n = 275 - dd;
if (mm == 3) n = 306 - dd;
if (mm == 2) { n = 334 - dd; if (leapyear(yy)) n++; }
if (mm == 1) { n = 365 - dd; if (leapyear(yy)) n++; }
if (gmonth == 1) m = 31;
if (gmonth == 2) {
m = 59;
if (leapyear(gyear)) m++;
}
if (gmonth == 3) { m = 90; if (leapyear(gyear)) m++; }
if (gmonth == 4) { m = 120; if (leapyear(gyear)) m++; }
if (gmonth == 5) { m = 151; if (leapyear(gyear)) m++; }
if (gmonth == 6) { m = 181; if (leapyear(gyear)) m++; }
if (gmonth == 7) { m = 212; if (leapyear(gyear)) m++; }
if (gmonth == 8) { m = 243; if (leapyear(gyear)) m++; }
if (gmonth == 9) { m = 273; if (leapyear(gyear)) m++; }
if (gmonth == 10) { m = 304; if (leapyear(gyear)) m++; }
if (gmonth == 11) { m = 334; if (leapyear(gyear)) m++; }
if (gmonth == 12) { m = 365; if (leapyear(gyear)) m++; }
months = age * 12;
months += 12 - parseInt(mm);
months += gmonth;
totdays = (parseInt(age) * 365);
totdays += age / 4;
totdays = parseInt(totdays) + gdate + m + n;
if (gmonth == 1) p = 31 + gdate;
if (gmonth == 2) {
p = 59 + gdate;
if (leapyear(gyear)) m = m+1;
}
if (gmonth == 3) { p = 90 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 4) { p = 120 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 5) { p = 151 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 6) { p = 181 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 7) { p = 212 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 8) { p = 243 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 9) { p = 273 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 10) { p = 304 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 11) { p = 334 + gdate; if (leapyear(gyear)) p++; }
if (gmonth == 12) { p = 365 + gdate; if (leapyear(gyear)) p++; }
weeks = (age * 365) + n + p;
weeks = weeks / 7;

```

```

etcdays = parseFloat(weeks) - parseInt(weeks);
etcdays = Math.round(etcdays * 7);
weeks = parseInt(weeks);
etcdays += parseInt(age / 4);
if (etcdays > 7)
weeks += parseInt(etcdays / 7);
document.agecalc.timealive.value += "    or " + weeks + " Weeks old\n";
document.agecalc.timealive.value += "    or " + months + " Months old\n";
document.agecalc.timealive.value += "    or " + totdays + " days old\n";
var time = new Date();
ghour = time.getHours();
gmin = time.getMinutes();
gsec = time.getSeconds();
hour = ((age * 365) + n + p) * 24;
hour += (parseInt(age / 4) * 24);
document.agecalc.timealive.value += "    or " + hour + " Hours old\n";
var min = (hour * 60) + gmin;
document.agecalc.timealive.value += "    or " + min + " Minutes old\n";
sec = (min * 60) + gsec;
document.agecalc.timealive.value += "    or " + sec + " Seconds old";
mm = mm - 1;
var r;
if (mm == 0) r = 0;
if (mm == 1) r = 31;
if (mm == 2) { r = 59; if (leapyear(gyear)) m++; }
if (mm == 3) { r = 90; if (leapyear(gyear)) r++; }
if (mm == 4) { r = 120; if (leapyear(gyear)) r++; }
if (mm == 5) { r = 151; if (leapyear(gyear)) r++; }
if (mm == 6) { r = 181; if (leapyear(gyear)) r++; }
if (mm == 7) { r = 212; if (leapyear(gyear)) r++; }
if (mm == 8) { r = 243; if (leapyear(gyear)) r++; }
if (mm == 9) { r = 273; if (leapyear(gyear)) r++; }
if (mm == 10) { r = 304; if (leapyear(gyear)) r++; }
if (mm == 11) { r = 334; if (leapyear(gyear)) r++; }
mm = mm + 1;
r = parseInt(r) + parseInt(dd);

if ((mm >= (gmonth + 1)) && (dd > gdate)) {
bday = r - m - gdate;
}
else {
if ((leapyear(gyear)) && ((mm > 2) && (dd < 29))) {
a = 366;
} else {

```

```

a = 365;
}
bday = a + (r - m - gdate);
}
nhour = 24 - parseInt(ghour);
nmin = 60 - parseInt(gmin);
nsec = 60 - parseInt(gsec);
while (bday > 366) bday -= 365;
if (((bday == 366) && (leapyear(gyear)) || ((bday == 365) && (!leapyear(gyear)))) {
document.agecalc.timealive.value += "\n\nAnd, today is your birthday!";
} else {
document.agecalc.timealive.value += "\n\nAnd, your next birthday is in:\n"
+ bday + " days " + nhour + " hrs " + nmin + " mins " + nsec + " secs";
setTimeout("run()", 1000);
}
}
function leapyear(a) {
if (((a%4 == 0) && (a%100 != 0)) || (a%400 == 0))
return true;
else
return false;
}
// End -->
</script>

```

```

<form name=agecalc>
<table>
<tr><td align=center>
Birthday: <select name=month size=1>
<option>January
<option>February
<option>March
<option>April
<option>May
<option>June
<option>July
<option>August
<option>September
<option>October
<option>November
<option>December
</select>

<select name=day size=1>

```

```
<option>1
<option>2
<option>3
<option>4
<option>5
<option>6
<option>7
<option>8
<option>9
<option>10
<option>11
<option>12
<option>13
<option>14
<option>15
<option>16
<option>17
<option>18
<option>19
<option>20
<option>21
<option>22
<option>23
<option>24
<option>25
<option>26
<option>27
<option>28
<option>29
<option>30
<option>31
</select>
<input type=text name=year size=4 maxlength=4>
<br>
<input type=button name=start value="Calculate" onclick="run();"><br>
<br>
<textarea rows=12 cols=35 name=timealive></textarea>
</td></tr>
</table>
</form>
```

时间按钮提醒

脚本说明：

把如下代码加入<body>区域中：


```
<script LANGUAGE="JavaScript">
<!-- Begin
day = new Date();
miVisit = day.getTime();
function clock() {
today = new Date();
hrNow = today.getHours();
mnNow = today.getMinutes();
scNow = today.getSeconds();
miNow = today.getTime();
if (hrNow == 0) {
hour = 12;
ap = "A";
} else if(hrNow <= 11) {
ap = "A";
hour = hrNow;
} else if(hrNow == 12) {
ap = "P";
hour = 12;
} else if (hrNow >= 13) {
hour = (hrNow - 12);
ap = "P";
}
if (hrNow >= 13) {
hour = hrNow - 12;
}
if (mnNow <= 9) {
min = "0" + mnNow;
}
else (min = mnNow)
if (scNow <= 9) {
secs = "0" + scNow;
} else {
secs = scNow;
}
time = hour + ":" + min + ":" + secs + ap;
document.form.button.value = time;
setTimeout('clock()', 1000);
}
function timeInfo() {
milliSince = miNow;
milliNow = miNow - miVisit;
secsVisit = Math.round(milliNow / 1000);
minsVisit = (milliNow / 1000) / 60;
```

```

alert("给你提个醒： "
+ "你已经在本页面上停留了大约" + minsVisit + "分或"
+ secsVisit + "秒");
}
document.write("<left><form name=\"form\">"
+ "<input type=button value=\"Click for info!\">"
+ " name=button onClick=\"timeInfo()\"></form></left>");
onError = null;
clock();
// End -->
</script>

```

计算出生时间

脚本说明：

第一步:把如下代码加入<body>区域中:

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var mm = prompt('What month were you born in?','1-12');
var bday = prompt('What day were you born on?','1-31');
var byear = prompt('What year were you born in?','1975');
var year = new Date();
var year2 = year.getYear();
var year3 = (year < 2000) ? year2 + 1900 : year2;
thedata = new Date();
mm2 = thedate.getMonth() + 1;
dd2 = thedate.getDate();
yy2 = thedate.getYear();
if (yy2 < 100) yy2 += 1900
yourage = yy2 - byear;
if (mm2 < mm) yourage--;
if ((mm2 == mm) && (dd2 < bday)) yourage--;
TMonth = new Array(
'January','February','March',
'April','May','June','July',
'August','September','October',
'November','December'
);
CurMonth = mm - 1;
bmonth = TMonth[CurMonth];
var age2 = yourage + 1;
var timerID;
var timerRunning = false;
var today = new Date();
var startday = new Date();

```

```

var enday = new Date();
var secPerDay = 0;
var minPerDay = 0;
var hourPerDay = 0;
var secsLeft = 0;
var secsRound = 0;
var secsRemain = 0;
var minLeft = 0;
var minRound = 0;
var minRemain = 0;
var timeRemain = 0;
function stopclock() {
if(timerRunning)
clearTimeout(timerID);
timerRunning = false;
}
function startclock() {
stopclock();
showtime();
showtime1();
}
function showtime() {
today = new Date();
enday = new Date(""+bmonth+", "+bday+" "+year3+" 00:00");
enday.setYear(""+year3+ "");
secsPerDay = 1000 ;
minPerDay = 60 * 1000 ;
hoursPerDay = 60 * 60 * 1000;
PerDay = 24 * 60 * 60 * 1000;
secsLeft = (enday.getTime() - today.getTime()) / minPerDay;
secsRound = Math.round(secsLeft);
secsRemain = secsLeft - secsRound;
secsRemain = (secsRemain < 0) ? secsRemain = 60 - ((secsRound - secsLeft) * 60) : secsRemain
= (secsLeft - secsRound) * 60;
secsRemain = Math.round(secsRemain);
minLeft = ((enday.getTime() - today.getTime()) / hoursPerDay);
minRound = Math.round(minLeft);
minRemain = minLeft - minRound;
minRemain = (minRemain < 0) ? minRemain = 60 - ((minRound - minLeft) * 60) : minRemain
= ((minLeft - minRound) * 60);
minRemain = Math.round(minRemain - 0.495);
hoursLeft = ((enday.getTime() - today.getTime()) / PerDay);
hoursRound = Math.round(hoursLeft);
hoursRemain = hoursLeft - hoursRound;

```

```

hoursRemain = (hoursRemain < 0) ? hoursRemain = 24 - ((hoursRound - hoursLeft) * 24) :
hoursRemain = ((hoursLeft - hoursRound) * 24);
hoursRemain = Math.round(hoursRemain - 0.5);
daysLeft = ((enday.getTime() - today.getTime()) / PerDay);
daysLeft = (daysLeft - 0.5);
daysRound = Math.round(daysLeft);
daysRemain = daysRound;
if (daysRemain == 1) day_rem = " day, "
else day_rem = " days, "
if (hoursRemain == 1) hour_rem = " hour, "
else hour_rem = " hours, "
if (minRemain == 1) min_rem = " minute, "
else min_rem = " minutes, "
if (secsRemain == 1) sec_rem = " second"
else sec_rem = " seconds"
timeRemain = daysRemain + day_rem + hoursRemain + hour_rem + minRemain + min_rem +
secsRemain + sec_rem;
document.down.face.value = timeRemain;
timerID = setTimeout("showtime()",1000);
timerRunning = true;
if (daysRemain < 0) year3 = year3 + 1
}
function showtime1() {
startday = new Date(""+bmonth+" "+bday+", "+byear+" 00:00 EDT");
startday.setYear(""+byear+"");
today = new Date();
secsPerDay = 1000 ;
minPerDay = 60 * 1000 ;
hoursPerDay = 60 * 60 * 1000;
PerDay = 24 * 60 * 60 * 1000;
secsLeft = (today.getTime() - startday.getTime()) / minPerDay;
secsRound = Math.round(secsLeft);
secsRemain = secsLeft - secsRound;
secsRemain = (secsRemain < 0) ? secsRemain = 60 - ((secsRound - secsLeft) * 60) : secsRemain
= (secsLeft - secsRound) * 60;
secsRemain = Math.round(secsRemain);
minLeft = ((today.getTime() - startday.getTime()) / hoursPerDay);
minRound = Math.round(minLeft);
minRemain = minLeft - minRound;
minRemain = (minRemain < 0) ? minRemain = 60 - ((minRound - minLeft) * 60) : minRemain =
((minLeft - minRound) * 60);
minRemain = Math.round(minRemain - 0.495);
hoursLeft = ((today.getTime() - startday.getTime()) / PerDay);
hoursRound = Math.round(hoursLeft);

```

```

hoursRemain = hoursLeft - hoursRound;
hoursRemain = (hoursRemain < 0) ? hoursRemain = 24 - ((hoursRound - hoursLeft) * 24) :
hoursRemain = ((hoursLeft - hoursRound) * 24);
hoursRemain = Math.round(hoursRemain - 0.5);
daysLeft = ((today.getTime() - startday.getTime()) / PerDay);
daysLeft = (daysLeft - 0.5);
daysRound = Math.round(daysLeft);
daysRemain = daysRound;
if (daysRemain == 1) day_rem = " day, "
else day_rem = " days, "
if (hoursRemain == 1) hour_rem = " hour, "
else hour_rem = " hours, "
if (minRemain == 1) min_rem = " minute, "
else min_rem = " minutes, "
if (secsRemain == 1) sec_rem = " second"
else sec_rem = " seconds"
timeRemain = daysRemain + day_rem + hoursRemain + hour_rem + minRemain + min_rem +
secsRemain + sec_rem;
document.up.face.value = timeRemain;
timerID = setTimeout("showtime1()",1000);
timerRunning = true;
}
// End -->
</script>
<form name="down" onSubmit="0">
<script Language="JavaScript">
document.write("<b> 你 出 生 于 "+bmonth+ " "+bday+", " "+byear+".
("+mm+ "/" +bday+ "/" +byear+)"</b>");
document.write("<br><br>你已经 "+yourage+ " 了,离你生日还有.");
</script>
<br>
<input type="text" name="face" size="47" value="A browser supporting JavaScript 1.1+ is
needed.">
</form>
<p>
<br>
<form name="up" onSubmit="1">
你已经生活了...<br>
<input type="text" name="face" size="47" value="A browser supporting JavaScript 1.1+ is
needed.">
</form>

```

第二步:把<body>区域中的内容改为:

```
<body bgcolor="#ffffff" OnLoad="startclock()">
```

页面完成时间

脚本说明 :

把如下代码加入<body>区域中:

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function HowLongSince(startmonth, startdate, startyear) {
sdate=startdate;
smmonth=startmonth-1;
syear=startyear;
var DaysInMonth = new Array(31,28,31,30,31,30,31,31,30,31,30,31);
today = new Date()
var thisyear = today.getFullYear();
var thismonth = today.getMonth();
var thisdate = today.getDate();
mstart = new Date(syear,(smmonth==12?1:smmonth+1),1);
days1 = (mstart - new Date(syear,smmonth,sdate))/(24*60*60*1000)-1;
mend = new Date(thisyear,thismonth,1);
days2 = (new Date(thisyear,thismonth,thisdate) - mend)/(24*60*60*1000)+1;
dayst = days1 + days2;
if (dayst >= DaysInMonth[smmonth]) {
AddOneMonth = 1;
dayst -= DaysInMonth[smmonth];
}
else AddOneMonth = 0;
ydiff1 = thisyear-mstart.getFullYear();
mdiff1 = thismonth-mstart.getMonth()+AddOneMonth;
if (mdiff1 >11) { mdiff1=0; ydiff1++; }
if (mdiff1 < 0) { mdiff1 = mdiff1 + 12; ydiff1--; }
temp = (ydiff1==0?"":(ydiff1==1?ydiff1+" year and ":ydiff1 + " years, "));
temp += (mdiff1==0?"0 months, and ":(mdiff1==1?mdiff1+" month, and ":mdiff1+" months, and
"));
temp += (dayst==0?"no days":(dayst==1 ? " 1 day." : dayst + " days" ));
return temp;
}
// End -->
</script>
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
document.write("本页面已经制作完成:");
document.write("<font color=red>");
document.write(HowLongSince(06,15,99));
```

```
// this is the date your site was created.  day,month,year
document.write("</font>了");
// End -->
</script>
```

页面导航类

显示站点信息的导航

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language=javascript>
<!--
function linkDisplay(selection){
if(selection=="1"){document.form.info.value="凡是主页制作需要的图片资料,这里都有。";document.form.go.value="time1.htm";}
else if(selection=="2"){document.form.info.value="流行软件和注册机码下载,软件分类齐全!";document.form.go.value="time2.htm";}//链接自己可以加入,说明也可以更改!
else if(selection=="3"){document.form.info.value="主页制作密技奉献,正在学习和制作主页的朋友在这里一定能发现有用的资料。";document.form.go.value="3.htm";}
else if(selection=="4"){document.form.info.value="大量的中外影视明星美女的剧照和写真,詹姆斯邦德,施瓦辛格,第五元素,哈里森福特,周润发,泰坦尼克,蝙蝠侠,变脸及 X-档案等剧照。苏慧伦,王菲,酒井法子,朱茵等美女桌布!";document.form.go.value="4.htm";}
else if(selection=="5"){document.form.info.value="几千个注册机码等着你呢!而且在不断地添加新的东西";document.form.go.value="5.htm";}
else if(selection=="6"){document.form.info.value="MIDI 音乐屋当然是最首欢迎的 MIDI 乐曲下载天地了,中外流行曲,美国乡谣,影视主题曲...";document.form.go.value="6.htm";}}function moreInfo(){
var page=document.form.go.value;window.location=page;}

//-->

</SCRIPT>
```

第二步:把如下代码加入区域中

```
<form name=form> <input type=hidden name=go value=><table border=0 width=300> <tr> <td align=center width=111><a href=javascript:linkDisplay(1);>网页图片库</a><br> </td> <td align=center width=123><a href=javascript:linkDisplay(2);>软件下载仓库</a><br> </td> <td align=center width=160><a href=javascript:linkDisplay(3);>主页制作密技</a><br> </td> </tr> <tr> <td align=center width=111><a href=javascript:linkDisplay(4);>美女明星写真<br></a></td> <td align=center width=123><a href=javascript:linkDisplay(5);>注册机码集中营</a><br> </td> <td align=center width=160><a href=javascript:linkDisplay(6);>MIDI 音乐屋
```

```
</a><br> </td> </tr> <tr> <td colspan=3 align=center width=402><div align=center><p><textarea name=info rows=5 cols=34 wrap=virtual>点击连接看个仔细</textarea><br> <input type=button name=button value=去看看 onClick=moreInfo()> </td></tr> </table></form>
```

任意位置显示导航信息

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT language=javascript><!--  
document.onclick = popUp
```

```
function popUp() {  
newX = window.event.x + document.body.scrollLeft  
newY = window.event.y + document.body.scrollTop  
menu = document.all.itemopen  
if ( menu.style.display == "" ){  
    menu.style.display = "none" }  
else {  
    menu.style.display = "" }  
  
    menu.style.pixelLeft = newX - 50  
    menu.style.pixelTop = newY - 50  
}  
/-->
```

```
</SCRIPT>
```

```
<!-- Start of Popup Menu -->
```

```
<table id="itemopen" class="box" style='display:none'>  
<tr><td><a href='index.htm' class="cc" >弹出菜单</a></td></tr>  
<tr><td><a href='time1.htm' class="cc" >本站首页</a></td></tr>  
<tr><td><a href='time2.htm' class="cc">My 求职信</a></td></tr>  
<tr><td><a href='time3.htm' class="cc" >网上赚钱</a></td></tr>  
<tr><td><a href='ye1.htm' class="cc" >免费资源</a></td></tr>  
<tr><td><a href='ye2.htm' class="cc" >更多连接</a></td></tr>  
<tr><td><a href='ye3.htm' class="cc" >更多连接</a></td></tr>  
<tr><td><a href='zh1.htm' class="cc" >更多连接</a></td></tr>  
</table>
```

```
<!-- End of Popup Menu -->
```


动态导航脚本

脚本说明:

把如下代码加入<body>区域中

```
<script language=javascript>
```

```
<!--
```

```
var index = 9
```

```
link = new Array(8);
```

```
text = new Array(8);
```

```
link[0] ='time1.htm'
```

```
link[1] ='time2.htm'
```

```
link[2] ='time3.htm'
```

```
link[3] ='time1.htm'
```

```
link[4] ='time2.htm'
```

```
link[5] ='time3.htm'
```

```
link[6] ='time1.htm'
```

```
link[7] ='time2.htm'
```

```
link[8] ='time3.htm'
```

```
text[0] ='说明一'
```

```
text[1] ='说明一'
```

```
text[2] ='说明一'
```

```
text[3] ='说明一'
```

```
text[4] ='说明一'
```

```
text[5] ='说明一'
```

```
text[6] ='说明一'
```

```
text[7] ='说明一'
```

```
text[8] ='说明一'
```

```
document.write ("<marquee scrollamount='1' scrolldelay='100' direction= 'up' width='150'  
height='150'>");
```

```
for (i=0;i<index;i++){
```

```
document.write ("&nbsp;<img src='arrow.gif' width='12' height='12'><a href="+link[i]+"  
target='_blank'>");
```

```
document.write (text[i] + "</A><br>");
```

```
}
```

```
document.write ("</marquee>")
```

```
// -->
```

```
</script>
```

下拉式导航菜单

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style>
<!--
#iewrap{
position:relative;
height:30px
}

#iewrap2{
position:absolute
}

#dropmenu03{
filter:revealTrans(Duration=1.5,Transition=12)
visibility:hide
}
-->
</style>
```

第二步:把如下代码加入<body>区域中

```
<ilayer id="dropmenu01" height=35px>
<layer id="dropmenu02" visibility=show>
<span id="iewrap">
<span id="iewrap2" onClick="dropit2();event.cancelBubble=true;return false">
<font face="宋体"><a href="default.htm">点这里看本站栏目</a></font>
</span>
</span>
</layer>
</ilayer>
```

```
<SCRIPT language=javascript><!--
var enableeffect=true
```

//将如下数组修改成你自己的。

```
var selection=new Array()
selection[0]='<font face="宋体"><a href="time1.htm">本站首页</a></font><br>'
selection[1]='<font face="宋体"><a href="time2.htm">My 求职信</a></font><br>'
selection[2]='<font face="宋体"><a href="time3.htm">网上赚钱</a></font><br>'
selection[3]='<font face="宋体"><a href="ye1.htm">免费资源</a></font><br>'
selection[4]='<font face="宋体"><a href="ye2.htm">免费资源</a></font><br>'
selection[5]='<font face="宋体"><a href="ye3.htm">免费资源</a></font><br>'
```

```
selection[6]='<font face="宋体"><a href="ye4.htm">免费资源</a></font><br>'
selection[7]='<font face="宋体"><a href="zh5.htm">免费资源</a></font>'
```

```
if (document.layers)
document.dropmenu01.document.dropmenu02.visibility='show'
```

```
function dropit2(){
if (document.all){
dropmenu03.style.left=document.body.scrollLeft+event.clientX-event.offsetX
dropmenu03.style.top=document.body.scrollTop+event.clientY-event.offsetY+18
if (dropmenu03.style.visibility=="hidden"){
if (enableeffect)
dropmenu03.filters.revealTrans.apply()
dropmenu03.style.visibility="visible"
if (enableeffect)
dropmenu03.filters.revealTrans.play()
}
else{
hidemenu()
}
}
}
```

```
function dropit(e){
if (document.dropmenu03.visibility=="hide")
document.dropmenu03.visibility="show"
else
document.dropmenu03.visibility="hide"
document.dropmenu03.left=e.pageX-e.layerX
document.dropmenu03.top=e.pageY-e.layerY+19
return false
}
```

```
function hidemenu(){
if (enableeffect)
dropmenu03.filters.revealTrans.stop()
dropmenu03.style.visibility="hidden"
}
```

```
function hidemenu2(){
document.dropmenu03.visibility="hide"
}
```

```
if (document.layers){
```

```
document.dropmenu01.document.dropmenu02.captureEvents(Event.CLICK)
document.dropmenu01.document.dropmenu02.onclick=dropit
}
else if (document.all)
document.body.onclick=hidemenu
```

```
//-->
```

```
</SCRIPT>
<!-- 你可以改变菜单出现的绝对位置和外观风格-->
<div id="dropmenu03"
style="position:absolute;left:10;top:0;layer-background-color:seashell;background-color:seashell;
width:100;visibility:hidden;border:1px solid black;padding:0px">
<script language="JavaScript1.2">
if (document.all)
dropmenu03.style.padding='6px'
for (i=0;i<selection.length;i++)
document.write(selection[i])
</script>
</div>
```

```
<script language="JavaScript1.2">
if (document.layers){
document.dropmenu03.captureEvents(Event.CLICK)
document.dropmenu03.onclick=hidemenu2
}
</script>
```

静止导航脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language=javascript><!--
function setVariables() {
if (navigator.appName == "Netscape") {
v=".top=";
dS="document.";
sD="";
y="window.pageYOffset";
}
else {
v=".pixelTop=";
dS="";
```

```

sD=".style";
y="document.body.scrollTop";
}
}
function checkLocation() {
object="object1";
yy=eval(y);
eval(dS+object+sD+v+yy);
setTimeout("checkLocation()",10);
}

//-->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```
<div id="object1" style="position:absolute; visibility:show; left:0px; top:0px; z-index:2">
```

```

<table width=128 border=0 cellspacing=20 cellpadding=0>
<tr>
<td height="97">
<a href="dao1.htm"></a><br>
<a href="dao2.htm"></a><br>
<a href="dao3.htm"></a>
</td>
</tr>
</table>
</div>

```

第三步:把<body>区域改为

```
<body bgcolor="#ffffff" OnLoad="setVariables();checkLocation()">
```

静止图片脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT LANGUAGE="JavaScript">
function setVariables() {
imgwidth=235;
imgheight=19;
if (navigator.appName == "Netscape") {
horz=".left";
vert=".top";
docStyle="document.";

```

```

styleDoc="";
innerW="window.innerWidth";
innerH="window.innerHeight";
offsetX="window.pageXOffset";
offsetY="window.pageYOffset";
}
else {
horz=".pixelLeft";
vert=".pixelTop";
docStyle="";
styleDoc=".style";
innerW="document.body.clientWidth";
innerH="document.body.clientHeight";
offsetX="document.body.scrollLeft";
offsetY="document.body.scrollTop";
}
}
function checkLocation() {
objectXY="branding";
var availableX=eval(innerW);
var availableY=eval(innerH);
var currentX=eval(offsetX);
var currentY=eval(offsetY);
x=availableX-(imgwidth+30)+currentX;
y=availableY-(imgheight+20)+currentY;
evalMove();
setTimeout("checkLocation()",10);
}
function evalMove() {
eval(docStyle + objectXY + styleDoc + horz + "=" + x);
eval(docStyle + objectXY + styleDoc + vert + "=" + y);
}
}
</script>

```

第二步:把如下代码加入<body>区域中

```

<div id="branding" style="position:absolute; visibility:show; left:235px; top:50px; z-index:2">
<table width=10 bgcolor=#ffffff><td>
<a href="http://javacool.yeah.net" onmouseover="window.status='超级 JAVA 酷';return true"
onmouseout="window.status="";return true"><center></center></a></font></td>
</table>
</div>

```

第三步:把<body>区域改为

```
<body bgcolor="#ffffff" onload="setVariables(); checkLocation();">
```

文本静止不动

脚本说明:

把如下代码加入<body>区域中

```
<div id="KBStatic" style="position:absolute; left:3px; top:0px; width:553px; height:70px; z-index:25">
```

```
    <font size="5" color="#CC3366"><a href=lu.htm>欢迎来到 Javascript  
世界</a></font></div>
```

```
    <script language=JavaScript>  
function KB_keepItInIE(theName,theWantTop,theWantLeft) {  
theRealTop=parseInt(document.body.scrollTop)  
theTrueTop=theWantTop+theRealTop  
document.all[theName].style.top=theTrueTop  
theRealLeft=parseInt(document.body.scrollLeft)  
theTrueLeft=theWantLeft+theRealLeft  
document.all[theName].style.left=theTrueLeft  
}  
function KB_keepItInNN(theName,theWantX,theWantY) {  
theRealLay=document.layers[theName]  
theBadX=self.pageYOffset  
theBadY=self.pageXOffset  
theRealX=theBadX+theWantX  
theRealY=theBadY+theWantY  
theRealLay.moveTo(theRealY,theRealX)  
}  
IE4=(document.all)?1:0  
NN4=(document.layers)?1:0  
if (IE4)  
setInterval('KB_keepItInIE("KBStatic",0,0)',1)  
if (NN4)  
setInterval('KB_keepItInNN("KBStatic",0,0)',1)  
</script>
```

信息框显示链接

脚本说明:

第一步:把如下代码加入<head>区域中(你可以对链接及说明作相应修改)

```
<SCRIPT Language="JavaScript">
```

```
<!-- Hide from JavaImpaired Browsers
```

```
function MakeArray(n) {  
this.length = n;  
for (var i = 1; i <= n; i++) {
```

```

this[i] = 0 }
return this
}
var ToolTips = new MakeArray(1);
ToolTips[0] = 1;
ToolTips[1] = "聊天室";
ToolTips[2] = "搜索引擎";
ToolTips[3] = "把鼠标放到链接上看看信息框的信息。";
function writeTip(imgIndex ){
document.hform.tips.value=(ToolTips[imgIndex]);} //--></Script>

```

第二步:把如下代码加入<body>区域中

```

<FORM NAME='hform'><INPUT TYPE="text" NAME="tips" SIZE="70" value="把鼠标放到
链接上看看信息框的信息。 "></FORM><CENTER><A HREF="chat.htm"
onMouseOver="writeTip(1);return true" onMouseOut="writeTip(3)">聊天室 </A> | <A
HREF="chsearch.htm" onMouseOver="writeTip(2);return true" onMouseOut="writeTip(3)">搜
索引擎</A></CENTER>

```

友情链接导航框

脚本说明:

把如下代码加入<body>区域中(你可以对链接及说明作相应修改)

```

<script language="JavaScript"><!-- Hide function surfTo(form) { var
myindex=form.dest.selectedIndex
location=form.dest.options[myindex].value;}!--></SCRIPT><FORM NAME="myform">
<SELECT NAME="dest" SIZE=4> <OPTION SELECTED VALUE="">选项<OPTION
VALUE="search.htm"> 搜索引擎 <OPTION VALUE="chat.htm"> 聊天
</SELECT><INPUT TYPE="BUTTON" VALUE="GO NOW!"
onClick="surfTo(this.form)"></FORM>

```

目录式导航菜单

脚本说明:

第一步:把如下代码加入<head>区域中

```

<SCRIPT language=javascript><!--
function out()
{
if(window.event.toElement.id!="menu" && window.event.toElement.id!="link")
menu.style.visibility="hidden";
}
//-->

function out1()
{

```



```

if(window.event.toElement.id!="menu1"                                &&
window.event.toElement.id!="link")
    menu1.style.visibility="hidden";
}
//-->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<div                                                    id="back"
onmouseout="out()"style="position:absolute;top:180;left:310;width:160;height:40;z-index:1;visib
ility:visible;">
<span id="menubar"  onmouseover="menu.style.visibility='visible'">
<font  color=red size=2>菜单</span>
<div                border=1                            id="menu"
style="position:absolute;top:15;left:0;width:50;height:10;z-index:2;visibility:hidden;">
<a id="link" href="rjxz.htm">软件下载</a>
<a id="link" href="yxxz.htm">游戏下载</a>
<a id="link" href="hjsj.htm">黄金书籍</a>
<a id="link" href="mntk.htm">美女图库</a>
<a id="link" href="mp3.htm">MP3 金曲</a>
<a id="link" href="flash.htm">FLASH</a>
</div>
</div>
<div                                                    id="back"
onmouseout="out1()"style="position:absolute;top:180;left:370;width:160;height:40;z-index:3;visi
bility:visible;">
<span id="menubar"  onmouseover="menu1.style.visibility='visible'">
<font  color=red size=2>菜单</span>
<div                border=1                            id="menu1"
style="position:absolute;top:15;left:0;width:50;height:10;z-index:4;visibility:hidden;">
<a id="link" href="rjxz.htm">软件下载</a>
<a id="link" href="yxxz.htm">游戏下载</a>
<a id="link" href="hjsj.htm">黄金书籍</a>
<a id="link" href="mntk.htm">美女图库</a>
<a id="link" href="mp3.htm">MP3 金曲</a>
<a id="link" href="flash.htm">FLASH</a>
</div>
</div>

```

重要信息说明脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="javascript">
```

//显示的信息，可以使用 HTML 语法，注意引号用法，单套双。

```
var message='<b><font size=5 face=arial color=red><a href="http://vs_server.hrw.cn/bbs" target="_blank">请点击进入本站 BBS</a></font></b>'
```

```
//背景色
```

```
var backgroundcolor="#eeffee"
```

```
//0 代表信息永远显示，1 代表信息只显示一段时间，2 为随机显示模式；
```

```
var displaymode=1
```

```
//如果显示模式为在指定时间内显示，输入时间段(1000 为 1 秒)；
```

```
var displayduration=30000
```

```
//1 代表闪烁，0 代表不闪烁；
```

```
var flashmode=1
```

```
//如果设置了闪烁，输入闪烁的颜色；
```

```
var flashtocolor="lightgreen"
```

```
////下面不必修改////
```

```
function regenerate(){  
window.location.reload()  
}
```

```
var which=0
```

```
function regenerate2(){  
if (document.layers)  
setTimeout("window.onresize=regenerate",400)  
}
```

```
function display2(){  
if (document.layers){  
if (topmsg.visibility=="show")  
topmsg.visibility="hide"  
else  
topmsg.visibility="show"  
}  
else if (document.all){  
if (topmsg.style.visibility=="visible")  
topmsg.style.visibility="hidden"  
else  
topmsg.style.visibility="visible"
```

```
setTimeout("display2()",Math.round(Math.random()*10000)+10000)
}
}
```

```
function flash(){
if (which==0){
if (document.layers)
topmsg.bgColor=flashtocolor
else
topmsg.style.backgroundColor=flashtocolor
which=1
}
else{
if (document.layers)
topmsg.bgColor=backgroundcolor
else
topmsg.style.backgroundColor=backgroundcolor
which=0
}
}
```

```
if (document.all){
document.write('<span id="topmsg"
style="position:absolute;visibility:hidden">'+message+'</span>')
}
```

```
function logoit(){
document.all.topmsg.style.left=document.body.scrollLeft+document.body.clientWidth/2-document
t.all.topmsg.offsetWidth/2
document.all.topmsg.style.top=document.body.scrollTop+document.body.clientHeight-document.
all.topmsg.offsetHeight-4
}
```

```
function logoit2(){
topmsg.left=pageXOffset+window.innerWidth/2-topmsg.document.width/2
topmsg.top=pageYOffset+window.innerHeight-topmsg.document.height-5
setTimeout("logoit2()",90)
}
```

```
function setmessage(){
document.all.topmsg.style.left=document.body.scrollLeft+document.body.clientWidth/2-documen
```

```

t.all.topmsg.offsetWidth/2
document.all.topmsg.style.top=document.body.scrollTop+document.body.clientHeight-document.
all.topmsg.offsetHeight-4
document.all.topmsg.style.backgroundColor=backgroundcolor
document.all.topmsg.style.visibility="visible"
if (displaymode==1)
setTimeout("topmsg.style.visibility='hidden'",displayduration)
else if (displaymode==2)
display2()
if (flashmode==1)
setInterval("flash()",1000)
window.onscroll=logoit
window.onresize=new Function("window.location.reload()")
}

```

```

function setmessage2(){
topmsg=new Layer(window.innerWidth)
topmsg.bgColor=backgroundcolor
regenerate2()
topmsg.document.write(message)
topmsg.document.close()
logoit2()
topmsg.visibility="show"
if (displaymode==1)
setTimeout("topmsg.visibility='hide'",displayduration)
else if (displaymode==2)
display2()
if (flashmode==1)
setInterval("flash()",1000)
}

```

```

if (document.layers)
window.onload=setmessage2
else if (document.all)
window.onload=setmessage
</script>

```

滚动链接导航

脚本说明:

把如下代码加入<body>区域中

```
<script>

var scrollerwidth=115

var scrollerheight=131

var scrollerbgcolor='#FFFFFF'

//3000 milliseconds=9 seconds

var pausebetweenimages=4000

var slideimages=new Array()

slideimages[0]='<a href="http://www.yahoo.com.cn" target="_blank">中文雅虎</a><br><br><a href="http://www.263.net" target="_blank"> 首 都 在 线 </a><br><br><a href="http://fsnet.yes8.com/" target="_blank"> 网 络 特 区 </a><br><br><a href="http://go.163.com/~xiaofengyun/" target="_blank">风 云 居</a>'

slideimages[1]='<a href="" target="_blank">你的链接</a><br><br><a href="" target="_blank">你的链接 </a><br><br><a href="" target="_blank"> 你的链接 </a><br><br><a href="" target="_blank">你的链接</a>'

slideimages[2]='<a href="http://www.yahoo.com.cn" target="_blank">中文雅虎</a><br><br><a href="http://www.263.net" target="_blank"> 首 都 在 线 </a><br><br><a href="http://fsnet.yes8.com/" target="_blank"> 网 络 特 区 </a><br><br><a href="" target="_blank">你的链接</a>'

slideimages[3]='<a href="" target="_blank">你的链接</a><br><br><a href="" target="_blank">你的链接 </a><br><br><a href="" target="_blank"> 你的链接 </a><br><br><a href="" target="_blank">你的链接</a>'

if (slideimages.length>1)

i=2

else
```

```
i=0
```

```
function move1(whichlayer){
```

```
  tlayer=eval(whichlayer)
```

```
  if (tlayer.top>0&&tlayer.top<=4){
```

```
    tlayer.top=0
```

```
    setTimeout("move1(tlayer)",pausebetweenimages)
```

```
    setTimeout("move2(document.main.document.second)",pausebetweenimages)
```

```
  return
```

```
  }
```

```
  if (tlayer.top>=tlayer.document.height*-1){
```

```
    tlayer.top-=4
```

```
    setTimeout("move1(tlayer)",100)
```

```
  }
```

```
  else{
```

```
    tlayer.top=scrollerheight
```

```
    tlayer.document.write(slideimages[i])
```

```
    tlayer.document.close()
```

```
    if (i==slideimages.length-1)
```

```
      i=0
```

```
    else
```

```
      i++
```

```
}
```

```
}
```

```
function move2(whichlayer){
```

```
  tlayer2=eval(whichlayer)
```

```
  if (tlayer2.top>0&&tlayer2.top<=4){
```

```
    tlayer2.top=0
```

```
    setTimeout("move2(tlayer2)",pausebetweenimages)
```

```
    setTimeout("move1(document.main.document.first)",pausebetweenimages)
```

```
    return
```

```
  }
```

```
  if (tlayer2.top>=tlayer2.document.height*-1){
```

```
    tlayer2.top-=4
```

```
    setTimeout("move2(tlayer2)",100)
```

```
  }
```

```
  else{
```

```
    tlayer2.top=scrollerheight
```

```
    tlayer2.document.write(slideimages[i])
```

```
    tlayer2.document.close()
```

```
    if (i==slideimages.length-1)
```

```
      i=0
```

```
    else
```

```
i++
```

```
}
```

```
}
```

```
function move3(whichdiv){
```

```
tdiv=eval(whichdiv)
```

```
if (tdiv.style.pixelTop>0&&tdiv.style.pixelTop<=4){
```

```
tdiv.style.pixelTop=0
```

```
setTimeout("move3(tdiv)",pausebetweenimages)
```

```
setTimeout("move4(second2)",pausebetweenimages)
```

```
return
```

```
}
```

```
if (tdiv.style.pixelTop>=tdiv.offsetHeight*-1){
```

```
tdiv.style.pixelTop-=4
```

```
setTimeout("move3(tdiv)",100)
```

```
}
```

```
else{
```

```
tdiv.style.pixelTop=scrollerheight
```

```
tdiv.innerHTML=slideimages[i]
```

```
if (i==slideimages.length-1)
```

```
i=0
```

```
else
```



```
i++
```

```
}
```

```
}
```

```
function move4(whichdiv){
```

```
tdiv2=eval(whichdiv)
```

```
if (tdiv2.style.pixelTop>0&&tdiv2.style.pixelTop<=4){
```

```
tdiv2.style.pixelTop=0
```

```
setTimeout("move4(tdiv2)",pausebetweenimages)
```

```
setTimeout("move3(first2)",pausebetweenimages)
```

```
return
```

```
}
```

```
if (tdiv2.style.pixelTop>=tdiv2.offsetHeight*-1){
```

```
tdiv2.style.pixelTop-=4
```

```
setTimeout("move4(second2)",100)
```

```
}
```

```
else{
```

```
tdiv2.style.pixelTop=scrollerheight
```

```
tdiv2.innerHTML=slideimages[i]
```

```
if (i==slideimages.length-1)
```

```
i=0
```

```
else
```

```
i++
```

```
}
```

```
}
```

```
function startscroll(){
```

```
if (document.all){
```

```
move3(first2)
```

```
second2.style.top=scrollerheight
```

```
}
```

```
else if (document.layers){
```

```
move1(document.main.document.first)
```

```
document.main.document.second.top=scrollerheight+5
```

```
document.main.document.second.visibility='show'
```

```
}
```

```
}
```

```
window.onload=startscroll
```

```
if (document.layers)
```

```
document.write(slideimages[0])
```

```
if (document.layers)
```

```

document.write(slideimages[1])

if (document.layers)

document.write(slideimages[0])

if (document.all){

document.writeln('<span                                id="main2"
style="position:relative;width:'+scrollerwidth+';height:'+scrollerheight+';overflow:hidden;background-color:'+scrollerbgcolor+'">')

document.writeln('<div
style="position:absolute;width:'+scrollerwidth+';height:'+scrollerheight+';clip:rect(0
'+scrollerwidth+' '+scrollerheight+' 0);left:0;top:0">')

document.writeln('<div                                id="first2"
style="position:absolute;width:'+scrollerwidth+';left:0;top:1;">')

document.write(slideimages[0])

document.writeln('</div>')

document.writeln('<div                                id="second2"
style="position:absolute;width:'+scrollerwidth+';left:0;top:0">')

document.write(slideimages[1])

document.writeln('</div>')

document.writeln('</div>')

document.writeln('</span>')

}

</script>

```

图片代替按钮脚本

脚本说明:

把如下代码加入<body>区域中

```
<script language=JavaScript>
<!-- Hide the script from old browsers --
function surfto(form) {
    var myindex=document.myform.dest.selectedIndex
    location=document.myform.dest.options[myindex].value;
}
//-->
</script>

<form name="myform">
    <select name="dest" size=1>
        <option selected>选项</option>
        <option value="http://www.163.net">163 电子邮箱</option>
        <option value="http://www.263.net">263 电子邮箱</option>
    </select>
    <a href="javascript: surfto()" onMouseOver="self.status='';return true"
onMouseOut="self.status='';return true"></a>
</form>
```

打开窗口等待

脚本说明:

把如下代码加入<body>区域中

```
<script language="javascript">
function opencolortext(){
window.open('http://www.990.net','colortext')
}
setTimeout("opencolortext()",3000)
</script>
```

正在下载文件，请耐心等待.....

静态导航菜单

脚本说明:

把如下代码加入<body>区域中

```
<BODY bgcolor="#ffffff" OnLoad="setVariables();checkLocation()">

<script language="JavaScript">

function setVariables() {
if (navigator.appName == "Netscape") {
v=".top=";
dS="document.";
sD="";
```

```

y="window.pageYOffset";
}
else {
v=".pixelTop=";
dS="";
sD=".style";
y="document.body.scrollTop";
}
}
function checkLocation() {
object="object1";
yy=eval(y);
eval(dS+object+sD+v+yy);
setTimeout("checkLocation()",10);
}
</script>
<div id="object1" style="position:absolute; visibility:show; left:0px; top:0px; z-index:5">


|                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |  |                                                                                                                                                                                                                                                                                                                      |  |                                                                                                                                                                |  |  |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| <tr> <td &gt;&lt;a="" &gt;yahoo&lt;="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://www.yahoo.com" td&gt;="" tr=""> <tr> <td &gt;&lt;a="" &gt;any="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://www.anysite.com" site&lt;="" td&gt;="" tr=""> <tr> <td &gt;&lt;a="" &gt;final="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://java2000.126.com" java2000&lt;="" td&gt;="" tr="">  </td></tr></td></tr></td></tr> |  | <tr> <td &gt;&lt;a="" &gt;any="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://www.anysite.com" site&lt;="" td&gt;="" tr=""> <tr> <td &gt;&lt;a="" &gt;final="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://java2000.126.com" java2000&lt;="" td&gt;="" tr="">  </td></tr></td></tr> |  | <tr> <td &gt;&lt;a="" &gt;final="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://java2000.126.com" java2000&lt;="" td&gt;="" tr="">  </td></tr> |  |  |  |
| <tr> <td &gt;&lt;a="" &gt;any="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://www.anysite.com" site&lt;="" td&gt;="" tr=""> <tr> <td &gt;&lt;a="" &gt;final="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://java2000.126.com" java2000&lt;="" td&gt;="" tr="">  </td></tr></td></tr>                                                                                                                                               |  | <tr> <td &gt;&lt;a="" &gt;final="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://java2000.126.com" java2000&lt;="" td&gt;="" tr="">  </td></tr>                                                                                                                                                       |  |                                                                                                                                                                |  |  |  |
| <tr> <td &gt;&lt;a="" &gt;final="" <="" a&gt;&lt;="" bgcolor="#EAEAEA" colspan="2" href="http://java2000.126.com" java2000&lt;="" td&gt;="" tr="">  </td></tr>                                                                                                                                                                                                                                                                                                     |  |                                                                                                                                                                                                                                                                                                                      |  |                                                                                                                                                                |  |  |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |  |                                                                                                                                                                                                                                                                                                                      |  |                                                                                                                                                                |  |  |  |


```

层叠式导航菜单

脚本说明:

第一步：把如下代码加入<body>区域中

```
<script language="JavaScript1.2">
```

```

//菜单 1 的内容
var menu1=new Array()
menu1[0]='<a href=http://www.163.net>网易</a><br>'
menu1[1]='<a href=http://www.sina.com.cn>新浪网</a><br>'
menu1[2]='<a href=http://www.cctv.com>中央电视台</a><br>'
//菜单 2 的内容
var menu2=new Array()
menu2[0]='<a href=http://vs_server.njvat.net/bbs>本站论坛</a><br>'
menu2[1]='<a href=http://vs_server.hrw.cn/aspchitchat>本站聊天室</a><br>'
menu2[2]='<a href=mailto:webmaster@hrw.cn>来信联络</a><br>'
</script>

```

```

<style>
<!--
.iewrap1 {
position:relative;
height:30px;
; font-family: "宋体"; font-size: 9pt}
.iewrap2{
position:absolute;
; font-family: "宋体"; font-size: 9pt}
#dropmenu0, #dropmenu1 {
visibility:hide;
z-index:100;
}
#dropmenu0 { font-family: "宋体" ; font-size: 9pt}#dropmenu1 { font-family: "宋体" ; font-size:
9pt}-->
</style>

```

第二步：把<body>区域改为

```

<script language="JavaScript1.2">
//以下不要改
var zindex=100
function dropit2(whichone){
if (window.themenu&&themenu.id!=whichone.id)
themenu.style.visibility="hidden"
themenu=whichone
if (document.all){
themenu.style.left=document.body.scrollLeft+event.clientX-event.offsetX
themenu.style.top=document.body.scrollTop+event.clientY-event.offsetY+18
if (themenu.style.visibility=="hidden"){
themenu.style.visibility="visible"
themenu.style.zIndex=zindex++

```

```
}
else{
hidemenu()
}
}
}
```

```
function dropit(e,whichone){
if (window.themenu&&themenu.id!=eval(whichone).id)
themenu.visibility="hide"
themenu=eval(whichone)
if (themenu.visibility=="hide")
themenu.visibility="show"
else
themenu.visibility="hide"
themenu.zIndex++
themenu.left=e.pageX-e.layerX
themenu.top=e.pageY-e.layerY+19
return false
}
```

```
function hidemenu(whichone){
if (window.themenu)
themenu.style.visibility="hidden"
}
```

```
function hidemenu2(){
themenu.visibility="hide"
}
```

```
if (document.all)
document.body.onclick=hidemenu
```

```
//以上不要改
</script>
```

```
<!-------菜单 1 开始----->
```

```
<ilayer height=35px>
<layer visibility=show>
<span class=iewrap1>
<span class=iewrap2 onClick="dropit2(dropmenu0);event.cancelBubble=true;return false"><font
face= 宋 体 ><a href="default.htm" onClick="if(document.layers) return dropit(event,
'document.dropmenu0')">站点列表</a></font>
```

```
</span>
</span>
</layer>
</ilayer><br>
<!-----菜单 1 结束----->

<!-----菜单 2 开始----->

<ilayer height=35px>
<layer visibility=show>
<span class=iewrap1>
<span class=iewrap2 onClick="dropit2(dropmenu1);event.cancelBubble=true;return false"><font
face= 宋 体 ><a href="default.htm" onClick="if(document.layers) return dropit(event,
'document.dropmenu1')">联络方式</a></font>
</span>
</span>
</layer>
</ilayer><br>
<!-----菜单 2 结束----->
```

```
<div id=dropmenu0
style="position:absolute;left:0;top:0;layer-background-color:#CDECF5;background-color:#CDEC
F5;width:80;visibility:hidden;border:1px solid black;padding:0px">
<script language="JavaScript1.2">
if (document.all)
dropmenu0.style.padding="4px"
for (i=0;i<menu1.length;i++)
document.write(menu1[i])
</script>
</div>
<script language="JavaScript1.2">
if (document.layers){
document.dropmenu0.captureEvents(Event.CLICK)
document.dropmenu0.onclick=hidemenu2
}
</script>
```

```
<div id=dropmenu1
style="position:absolute;left:0;top:0;layer-background-color:#CDECF5;background-color:#CDEC
F5;width:80;visibility:hidden;border:1px solid black;padding:0px">
<script language="JavaScript1.2">
if (document.all)
dropmenu1.style.padding="4px"
for (i=0;i<menu2.length;i++)
```



```
document.write(menu2[i])
</script>
</div>
<script language="JavaScript1.2">
if (document.layers){
document.dropmenu1.captureEvents(Event.CLICK)
document.dropmenu1.onclick=hidemenu2
}
</script>
```

隐现导航脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style>
```

```
<!--
```

```
#tickertape{
position:relative;
```

```
layer-background-color:black;
width:400;
height:12;
; font-family: "宋体"; font-size: 9pt}
```

```
#subtickertape{
background-color:black;
position:absolute;
border: 1px solid black;
width:400;
height:12;
; font-family: "宋体"; font-size: 9pt
}
```

```
.subtickertapefont{
font:bold 9pt "宋体";
text-decoration:none;
color:white;
}
```

```
.subtickertapefont a{
color:white;
text-decoration:none;
; font-family: "宋体"; font-size: 9pt}
```

```
-->
</style>
```

第二步:把如下代码加入<body>区域中

```
<div id="tickertape">
<div id="subtickertape" class="subtickertapefont">初始化...</div>
</div>
<script language="JavaScript1.2">
```

```
//默认速度 4.5 秒，自己修改速度快慢。
```

```
var speed=4500
```

```
var news=new Array()
```

```
news[0]="<a href='index1.htm'>连接 1</a>"
```

```
news[1]="<a href='index2.htm'>连接 2</a>"
```

```
news[2]="<a href='index3.htm'>连接 3</a>"
```

```
news[3]="<a href='index4.htm'>连接 4</a>"
```

```
news[4]="<a href='index5.htm'>连接 5</a>"
```

```
news[5]="<a href='index6.htm'>连接 6</a>"
```

```
news[6]="<a href='index7.htm'>连接 7</a>"
```

```
//显示的信息内容可以任意按照格式添加。
```

```
i=0
```

```
if (document.all)
```

```
tickerobject=document.all.subtickertape.style
```

```
else
```

```
tickerobject=document.tickertape.document
```

```
function regenerate(){
```

```
window.location.reload()
```

```
}
```

```
function regenerate2(){
```

```
if (document.layers)
```

```
setTimeout("window.onresize=regenerate",450)
```

```
}
```

```
function update(){
```

```
  BgFade(0xff,0xff,0xff, 0x00,0x00,0x00,10);
```

```
if (document.layers){
```

```
  document.tickertape.document.subtickertape.document.write('<span  
  class="subtickertapefont">'+news[i]+'</span>')
```

```
  document.tickertape.document.subtickertape.document.close()
```

```
}
```

```

else
document.all.subtickertape.innerHTML=news[i]

if (i<news.length-1)
i++
else
i=0
setTimeout("update()",speed)
}

function BgFade(red1, grn1, blu1, red2,
grn2, blu2, steps) {
sred = red1; sgrn = grn1; sblu = blu1;
ered = red2; egrn = grn2; eblu = blu2;
inc = steps;
step = 0;
RunFader();
}
function RunFader() {
var epct = step/inc;
var spct = 1 - epct;
if (document.layers)
tickerobject.bgColor =
Math.floor(sred * spct + ered *
epct)*256*256 +
Math.floor(sgrn * spct + egrn * epct)*256 +
Math.floor(sblu * spct + eblu * epct);
else
tickerobject.backgroundColor=
Math.floor(sred * spct + ered *
epct)*256*256 +
Math.floor(sgrn * spct + egrn * epct)*256 +
Math.floor(sblu * spct + eblu * epct);
if ( step < inc ) {
setTimeout('RunFader()',50);
}
step++;
}

</script>

```

第三步:把<body>区域改为

```
<body bgcolor="#ffffff" onload="if (document.all||document.layers) {regenerate2();update()}">
```

页面内部导航

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT="javascript">
```

```
<form>
```

```
<p><input TYPE="button" VALUE="去代码处" onClick="parent.location='#code'"> </p>
```

```
</form>
```

```
</SCRIPT>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
```

```
<br>
<br>
<a name="code">ddsag</a>
```

图片代替按钮脚本

脚本说明:

把如下代码加入<body>区域中

```
<script language=JavaScript>
<!-- Hide the script from old browsers --
function surfto(form) {
    var myindex=document.myform.dest.selectedIndex
    location=document.myform.dest.options[myindex].value;
}
//-->
</script>

<form name="myform">
    <select name="dest" size=1>
        <option selected>选项</option>
        <option value="http://www.163.net">163 电子邮局</option>
        <option value="http://www.263.net">263 电子邮局</option>
    </select>
    <a href="javascript: surfto()" onMouseOver="self.status='';return true"
onMouseOut="self.status='';return true"></a>
</form>
```

打开窗口等待

脚本说明:

把如下代码加入<body>区域中

```
<script language="javascript">
function opencolortext(){
window.open('http://www.990.net','colortext')
}
setTimeout("opencolortext()",3000)
</script>
```

正在下载文件，请耐心等待.....

滚动的超级链接

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--  
  
var a,b,go,word;  
  
function greenlight(word){  
  
    a="怀柔网";  
  
    word.style.color="red";  
  
    linkSwitch();  
  
}  
  
function linkSwitch(){  
  
    clearTimeout(go);  
  
    b=a;  
  
    a=a.substring(1,100)+a.charAt(0);  
  
    esh.innerText=a;  
  
    go=setTimeout("linkSwitch()",100);  
  
}  
  
function stp(word){  
  
    clearTimeout(go);  
  
    esh.innerText="怀柔网";  
  
    word.style.color="blue";  
  
}  
  
//-->  
  
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<A HREF="http://netgo.silversand.net" onmouseover="greenlight(this);  
onmouseout="stp(this)"><span id="esh"> 网页之作站点</span></A>
```

先后点击链接

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="JavaScript">  
var num = 2;  
var mypage = 'http://www.hrw.cn/javascript.zip';  
var pissoff = ' 请先点击上方链接 ';  
allow = Array();  
allow[num] = 2;  
function gotoit(link){  
    if (link != num){  
        allow[link] = 2;  
    } else {  
        for (i=1;i<=num;i++){  
            if (allow[i] != 2){  
                i = num + 1;  
                lemmeIn = 0;  
            } else {  
                lemmeIn = 1;  
            }  
        }  
        if (lemmeIn == 1){  
            window.location = mypage;  
        } else {  
            alert(pissoff);  
        }  
    }  
}  
//--->  
</script>
```

第二步:把如下代码加入<body>区域中

```
<a href="Upper1/default.htm" onClick="gotoit(1)" target="_blank"><u>先帮忙点击这里</u></a><BR>
```

```
<a href="javascript:gotoit(num)"><u>下载本站所有页面</u></a>
```

按钮选择导航

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!--HIDE
function changeIt(newLoc) {
    document.links[0].href=newLoc
}
//STOP HIDING-->
</SCRIPT>
<A HREF="Upper1/default.htm">
<h4>去看看</h4></A>
<FORM>
<INPUT TYPE="radio" NAME="choices" onClick=
    "changeIt('http://www.cctv.com')">
    中央电视台<br>
<INPUT TYPE="radio" NAME="choices" onClick=
    "changeIt('http://www.sarft.gov.cn')">
    广电总局<br>
<INPUT TYPE="radio" NAME="choices" onClick=
    "changeIt('http://www.qdcatv.com.cn')">
    青岛有线台<br>
```

不停变化的导航

脚本说明:

第一步:把如下代码加入<head>区域中(你可以对链接及说明作相应修改)

```
<SCRIPT LANGUAGE="JavaScript">
<!-- begin
// please help yourself to this code.
var startTime =null;
var timerID =null;
var initial =new Date();
var pos =0;
var menuItem =null;

function initArray() {
    this.length = initArray.arguments.length
    for (var i = 0; i < this.length; i++) {
        this[i+1] = initArray.arguments[i]
    }
}
```



```
}
```

```
function parsemenuItem(data,num) {  
  for(var i=0;i<data.length;i++) {  
    if(data.substring(i,i+1)=="|") break;  
  }  
  if (num==0) return(data.substring(0,i));  
  else return(data.substring(i+1,data.length));  
}
```

```
function startTimer() {  
  initial = new Date();  
  startTime=initial.getTime();  
  stopTimer();  
  menuItem = new initArray("Netscape|http://www.netscape.com",  
    "Microsoft|http://www.microsoft.com",  
    "IBM|http://www.ibm.com",  
    "Yahoo|http://www.yahoo.com",  
    "Excite|http://www.excite.com",  
    "Hotbot|http://www.hotbot.com",  
    "GrapeJam|http://www.grapejam.com",  
    "Email|mailto:rzeitel@mars.superlink.net"  
  );  
  showTimer();  
}
```

```
function stopTimer() {  
  timerID=null;  
  menuItem=null;  
  //clearTimeout(timerID);  
}
```

```
function showTimer() {  
  pos= (pos == menuItem.length) ? 1 : pos + 1;  
  document.forms[0].elements[0].value=parsemenuItem(menuItem[pos],0);  
  
  timerID=window.setTimeout('showTimer()',4000);  
}
```

```
function goToUrl() {  
  //parent.welcome.location=parsemenuItem(menuItem[pos],1);  
  this.location=parsemenuItem(menuItem[pos],1);  
  return (false);  
}
```

```
// end -->
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<FORM>
<INPUT TYPE="button" VALUE=" WHERE TO? " NAME="goTo"
      onClick="window.goToUrl()">
</FORM>
```

第三步:把<body>中的内容改为 :

```
<body bgcolor="#ffffff" onLoad="window.startTimer()">
```

随机的导航

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
p = new Array(14);
t = new Array(14);

p[0] = 'http://www.geocities.com/SunsetStrip/5928'
p[1] = 'http://www.geocities.com/Area51/Vault/1261/'
p[2] = 'http://idola.net.id'
p[3] = 'http://members.aol.com/BobYang/index.html'
p[4] = 'http://www.geocities.com/Hollywood/hills/6760'
p[5] = 'http://www.geocities.com/TimesSquare/3278/'
p[6] = 'http://slugfest.kaizen.net/'
p[7] = 'http://www.chorizon.com/'
p[8] = 'http://www.geocities.com/SouthBeach/2584/'
p[9] = 'http://www.en.com/users/battags/'
p[10] = 'http://hudson.idt.net/~lechat19'
p[11] = 'http://www.radiks.net/dgrundjr/'
p[12] = 'http://desktoppublishing.com/'
p[13] = 'http://www.quadzilla.com/'
p[14] = 'http://www.azstarnet.com/~garycr'

t[0] = "The Alien's Lair"
t[1] = "Alien's wacky world"
t[2] = 'Arch'
t[3] = 'Bob Senan Bob Senan Bob Senan Bob'
t[4] = 'Braveheart: The Legend Remains...'
t[5] = 'Caos Games'
t[6] = 'Celebrity Slugfest'
```

```
t[7] = 'Changing Horizons'  
t[8] = "Coop's Place"  
t[9] = "CYBERDEMON'S WEBPAGE"  
t[10] = 'The Cyberspaceship'  
t[11] = "Dave's Ultimate Hangout"  
t[12] = 'desktopPublishing.com'  
t[13] = "D.J. Quad's Ultimate HTML Site"  
t[14] = 'The Electric Lighthouse'
```

```
index = Math.floor(Math.random() * p.length);document.write("<H4>");  
document.write("<DL>\n");  
document.write("这次的链接地址为:");  
document.write("<BR><UL>");  
document.write("<A HREF="+p[index]+">"+p[index]+"</A>");  
document.write("</UL><P>");  
document.write("这个站点的名称是:");  
document.write("<BR><UL><FONT COLOR=RED>");  
document.write(t[index]);  
document.write("</DL>\n");  
document.write("</h4>");</SCRIPT></FONT>  
</UL></UI>
```

链接窗口说明

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

```
function PopIt(label, msg, URLE){
```

```
    // Set up Page Colors & Table
```

```
    var DQUOTE = "\""
```

```
    var s1 = "<TITLE>" + label + "</TITLE>" +
```

```
    "<BODY BGCOLOR='ffffff'><TABLE BORDER=0><TR>" +
```

```

"<TD WIDTH=90% HEIGHT=90 VALIGN=TOP ALIGN=LEFT>"+

"<FONT SIZE=4>"

var s2 = "<FONT COLOR='FF0000'><B>"+label+"</B></FONT><P>"

var s3 = "</TD><TD WIDTH=10%> </TD></TR><TR><TD> </TD>"+

"<TD VALIGN=TOP ALIGN=RIGHT>"+

"<FORM><INPUT TYPE='BUTTON' VALUE='Close'" +

"onClick='self.close()'" +

"<INPUT TYPE='BUTTON' VALUE='Jump to!'"+

"onClick='window.open("+DQUOTE+URLE+DQUOTE+")'" +

"</FORM></TD></TR></TABLE></BODY>"

popup = window.open("", "popDialog", "height=200,width=300,scrollbars=no")

popup.document.write(s1+s2+msg+s3)

popup.document.close()

}

// -->

</SCRIPT>

<A HREF="JavaScript:PopIt('链接一','网易!', 'http://www.163.com')">网易</A>

<BR>

<A HREF="JavaScript:PopIt('链接二','怀柔网', 'http://www.hrw.cn')">怀柔网</A>

<BR>

```

```
<A HREF="JavaScript:PopIt('链接三','中央电视台!','http://www.cctv.com')">中央电视台</A>
```

```
<BR>
```

```
<A HREF="JavaScript:PopIt('链接四','新浪!','http://www.sina.com.cn')">新浪</A>
```

打开链接显示信息

脚本说明：

把如下代码加入<body>区域中：

```
<script language=JavaScript>

function jdk1x() {
    var num1 = document.x.jdk.value;
    if(num1 == 'three') {
        document.x.jdk.value = document.x.jdk.value
    }
    else {
        document.x.jdk.value = "可别急着走呀!"
    }
}

location="Upper1/default.htm"
}
</script>

<form name=x>
<input type=button value="怀柔网" onClick="jdk1x()"><br>
<input type=text name=jdk width="300" onChange="document.x.jdk.value="; return
true">
</form>
```

又一动态导航脚本

脚本说明：

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">

function makeArray(q){
for(i=1 ; i < q ; i++){this[i]=0}}
w=1;
howmanysites=4; // How many sites are listed below?

Sites = new makeArray(howmanysites);
```

```
Sites[1] = "http://www.js-planet.com~JavaScript Planet|Hundreds of JavaScripts!";
Sites[2] = "http://www.js-planet.com/dhtml~dHTML Scripts|Free dHTML Scripts!";
Sites[3] = "http://www.altavista.com~Altavista|The best search engine";
Sites[4] = "http://www.dynamicdrive.com~Dynamic Drive|More dHTML Scripts";
```

```
function showSites() {
if (w > howmanysites) { w=1; };
var string=Sites[w] + "";
var split1=string.indexOf("~");
var split2=string.indexOf("|");
var url=string.substring(0,split1);
var name=string.substring(split1 + 1,split2);
var word=string.substring(split2 + 1,string.length);
document.form.url.value=url;
document.form.name.value=name;
document.form.word.value=word;
w+=1;
window.setTimeout('showSites()',3000);
```

// You can change the speed! 3000 = 3 sec delay. 5000 = 5 sec delay, etc.

```
}
function visitSite() {
window.location=document.form.url.value;
}
</SCRIPT>
<form name=form>
<table><tr><td align=center>
<input type=button name=name value="Visit" onClick="visitSite()" size=25>
<input type=hidden name=url value="">
<input type=text name=word value="" size=40>
</td></tr></table>
</form>
</center>

<script>
showSites();
</script>
```

Form框中导航

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
//by Leif King e-mail:leif.d.king@vanderbilt.edu
//Feel free to use this or modify it Please leave this comment.
```

```
function makeArray(q){
for(i=1 ; i < q ; i++){this[i]=0}}
w=1;
howmanysites=4; // How many sites are listed below?
```

```
Sites = new makeArray(howmanysites);
```

```
Sites[1] = "http://www.js-planet.com|Great scripts!";
//put yoursites then | and what you want the box to show here's where I got the orig.
Sites[2] = "http://www.geocities.com|Free webspace!";
Sites[3] = "http://www.yahoo.com|Great Search Engine!";
```

```
function showSites() {
if (w > howmanysites) { w=1; };
var string=Sites[w] + "";
var split=string.indexOf("|");
var url=string.substring(0,split);
var word=string.substring(split + 1,string.length);
document.form.url.value=url;
document.form.word.value=word;
w+=1;
window.setTimeout('showSites()',5000);
```

```
}
function visitSite() {
window.location=document.form.url.value;
}
</SCRIPT>
<center>
<form name=form>
<table><tr><td align=center>
<input type=hidden name=url value="">
<input type=text name=word value="" onFocus="visitSite()" size=40>
</td></tr></table>
</form>
</center>

<script>
showSites();
</script>
```

屏幕翻滚导航

脚本说明:

第一步:把如下代码加入<head>区域中
<SCRIPT>

```
var i=0
```

```
var i_cell=0
```

```
i_bg=0
```

```
var linklist
```

```
var bg = new Array('AACC00','77AA00', '557700', '335500', '003300', '000000', '#335500',  
'557700', '77AA00', 'AACC00', 'CCFF00')
```

```
function initObjects() {
```

```
if (document.all) {
```

```
linklist = document.all.linkliste.style
```

```
linklist.visibility='VISIBLE'
```

```
linklist.posTop = i
```

```
linklist.posLeft = 3
```

```
scrollIE()
```

```
}
```

```
if (document.layers) {
```

```
linklist = document.linkliste
```

```
linklist.visibility='VISIBLE'
```

```
linklist.top = i
```

```
linklist.left = 3
```

```
scrollNN()
```



```
}
```

```
}
```

```
function scrollINN() {
```

```
if (i_cell < 100) {
```

```
    i_cell++
```

```
    linklist.top = i--
```

```
    var timer = setTimeout('scrollINN()',20)
```

```
}
```

```
else {
```

```
    clearTimeout('timer')
```

```
    changebgNN()
```

```
}
```

```
}
```

```
function scrollIIE() {
```

```
if (i_cell < 100) {
```

```
    i_cell++
```

```
    linklist.posTop = i--
```

```
    var timer = setTimeout('scrollIIE()',20)
```

```
}
```

```
else {
```

```
    clearTimeout('timer')
```

```
    document.bgColor='CCFF00'
```

```
changebgIE()

}

}

function changebgNN() {

if (i_bg <= bg.length) {

document.bgColor=bg[i_bg]

i_bg++

var bgagain = setTimeout('changebgNN()',20)

}

else {

clearTimeout('bgagain')

document.bgColor='CCFF00'

i_bg=0

makepauseNN()

}

}

function changebgIE() {

if (i_bg <= bg.length) {

document.bgColor=bg[i_bg]

i_bg++

var bgagain = setTimeout('changebgIE()',50)

}
```

```
else {

clearTimeout('bgagain')

i_bg=0

makepauseIE()

}

}

function makepauseNN() {

if (i < (-1*1700)) {

i=0

}

i_cell=0

var scrollagain = setTimeout('scrollNN()',3000)

}

function makepauseIE() {

if (i < (-1*1700)) {

i=0

}

i_cell=0

var scrollagain = setTimeout('scrollIE()',3000)

}

</SCRIPT>

<STYLE>.alldiv {
```

```

        POSITION: absolute; VISIBILITY: hidden
    }
</STYLE>

```

第二步:把如下代码加入<body>区域中

```

<DIV class=alldiv id=linkliste>
<CENTER>
<TABLE border=0 cellPadding=0 cellSpacing=0 width=156>
  <TBODY>
    <TR>
      <TD height=100></TD></TR>
    <TR vAlign=top>
      <TD align=left height=100><FONT size=1><A
        href="http://www.netby.net/Nord/Rosinstraede/Rosenlund/"
        target=_blank><FONT size=1><B>DHTML and javascript, games and
        gimics</B></FONT></A><BR>A collection of a few of my own javascripted
        games and gimics and some links to other sites. Some remarkable scripts.
        <BR>Rating: <FONT color=#ff0000>**</FONT><FONT
        color=#999999>***</FONT><BR><BR></FONT></TD></TR>
    <TR vAlign=top>
      <TD align=left height=100><FONT size=1><A
        href="http://skandal.homepage.com/" target=_blank><FONT
        size=1><B>Skandal's Digital art and graffiti
        (DHTML)</B></FONT></A><BR>site with lots of images made with adobe
        photoshop. Slow loading. Nice effects.<BR>Rating: <FONT
        color=#ff0000>**</FONT><FONT
color=#999999>***</FONT><BR><BR></FONT></TD></TR>
    <TR vAlign=top>
      <TD align=left height=100><FONT size=1><A
        href="http://www2.mozcom.com/~halos/" target=_blank><FONT
        size=1><B>Emmanuel Halos Web Studio</B></FONT></A><BR>First-rate
        JavaScripts from the Philippines. You will be enthusiastic about the
        elegance and power of the samples.<BR>Rating: <FONT
        color=#ff0000>*****</FONT><FONT
color=#999999></FONT><BR><BR></FONT></TD></TR>
    <TR vAlign=top>
      <TD align=left height=100><FONT size=1><A
        href="http://www.geocities.com/~lef" target=_blank><FONT size=1><B>Scripts
        by Lfteris Haritou</B></FONT></A><BR>Lfteris Haritou is a very creative
        JavaScript writer. Why? Check it out! A perfect starting point for
        beginners. <BR>Rating: <FONT color=#ff0000>*****</FONT><FONT
        color=#999999>*</FONT><BR><BR></FONT></TD></TR>
  <TR vAlign=top>

```

```

<TD align=left height=100><FONT size=1><A
  href="http://home.thezone.net/~rbennett/utility/javahead.htm"
  target=_blank><FONT size=1><B>Racoon's JavaScript
  Site</B></FONT></A><BR>Feel the spirit and the humour of a great
  script-programmer. Lots of inspiration.<BR>Rating: <FONT
  color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A
    href="http://goepfert.hypermart.net/" target=_blank><FONT size=1><B>Free
    WebResources</B></FONT></A><BR>Contains all kinds of free resources for
    webmasters: JavaScript, HTML, DHTML, CGI, Java, Graphics. Useful site
    checkers.<BR>Rating: <FONT color=#ff0000>***</FONT><FONT
    color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A href="http://igor.net/"
    target=_blank><FONT size=1><B>Igor net</B></FONT></A><BR>No doubt IGOR is
    one of the great javascript-masters of the universe. His games are superb.
    High-End-Scripting at it's best.<BR>Rating: <FONT
    color=#ff0000>*****</FONT><FONT
color=#999999></FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A
    href="http://www.alienalchemy.com/" target=_blank><FONT size=1><B>Alien
    Alchemy</B></FONT></A><BR>12 free cut &pastejavascripts made by
    designers who know that form follows function.<BR>Rating: <FONT
    color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A
    href="http://home.netvigator.com/~mkpunnl" target=_blank><FONT
    size=1><B>Leo Pun's homepage</B></FONT></A><BR>Open your eyes and you will
    find quite a few precious javacripts.<BR>Rating: <FONT
    color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A
    href="http://www.geocities.com/SiliconValley/Way/1265/"
    target=_blank><FONT size=1><B>Surfin' the web with Willem
    Jonkman</B></FONT></A><BR>Great samples of javascript, HTML, sounds, fonts
    mixed with lots of fun.<BR>Rating: <FONT color=#ff0000>***</FONT><FONT
    color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A

```

```

href="http://www.geocities.com/SiliconValley/Lakes/8620"
target=_blank<FONT size=1><B>Virtual_Max's</B></FONT></A><BR>One of the
most popular sites at GeoCities: applets, scripts, crazy stuff. As funny
as a web bazar can be.<BR>Rating: <FONT color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
<TD align=left height=100><FONT size=1><A href="http://www.reallybig.com/"
target=_blank<FONT size=1><B>Reallybig.com</B></FONT></A><BR>United
Power
of Web Builders! More than 3000 resources for web builders including free
clipart, CGI, counters, fonts, html, java, animation, backgrounds and much
more.<BR>Rating: <FONT color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
<TD align=left height=100><FONT size=1><A
href="http://stars.bilkent.edu.tr/Authoring/DHTML/Resources.html"
target=_blank<FONT size=1><B>Dynamic HTML Tools and
Resources</B></FONT></A><BR>The web developer's virtual library: DHTML,
CSS, JavaScript, CGI, Perl, Graphics<BR>Rating: <FONT
color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
<TD align=left height=100><FONT size=1><A
href="http://www.javascripts.com/" target=_blank<FONT
size=1><B>Javascripts.com</B></FONT></A><BR>More than 2000 scripts. Each
script has been written or uploaded by a member of this site. Many have
been written by JavaScript professionals.<BR>Rating: <FONT
color=#ff0000>****</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
<TD align=left height=100><FONT size=1><A
href="http://www.coolfreebies.com/" target=_blank<FONT size=1><B>Cool
free stuff</B></FONT></A><BR>Screensavers, various freebies, free
software, free sound tools, free graphics, free midis, free image viewers,
free prizes, chat freebies, FTP freebies, free fun stuff, free webmasters
tools, free graphics.<BR>Rating: <FONT color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>
<TR vAlign=top>
<TD align=left height=100><FONT size=1><A
href="http://javascript.internet.com/" target=_blank<FONT size=1><B>The
JavaScript Source</B></FONT></A><BR>Collection of hundreds of free
JavaScripts that are available to you for use on your web page<BR>Rating:
<FONT color=#ff0000>****</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR>

```

```

<TR vAlign=top>
  <TD align=left height=100><FONT size=1><A
    href="http://www.dynamicdrive.com/" target=_blank><FONT size=1><B>Free,
    original DHTML-scripts</B></FONT></A><BR>A premier place on the net to
    obtain free, original DHTML scripts and components to enhance your web
    site!<BR>Rating: <FONT color=#ff0000>***</FONT><FONT
color=#999999>*</FONT><BR><BR></FONT></TD></TR></TBODY></TABLE></CENTE
R></DIV>

```

第三步:把<body>区域改为

```
<body bgcolor="#ffffff" onload=initObjects(>
```

带说明的导航

脚本说明：

把如下代码加入<body>区域中:

```
<script language="JavaScript">
```

```
<!--
```

```

function go_to_station(){
  if (document.stationform.stationselect.options[0].selected){
    window.location.href = "http://www.abctelevision.com";}
  else if (document.stationform.stationselect.options[1].selected)
  { window.location.href = "http://www.cbs.com";}
  else if (document.stationform.stationselect.options[2].selected)
  { window.location.href = "http://www.nbc.com";}
  else if (document.stationform.stationselect.options[3].selected)
  { window.location.href = "http://www.foxnetwork.com";}
  else if (document.stationform.stationselect.options[4].selected)
  { window.location.href =
"http://www.filmzone.com/SpaceGhost/cartoonnet.html";}
  else if (document.stationform.stationselect.options[5].selected)
  { window.location.href = "http://www.discovery.com";}
  else if (document.stationform.stationselect.options[6].selected)
  { window.location.href = "http://www.cs.brandeis.com";}
  else if (document.stationform.stationselect.options[7].selected)
  { window.location.href = "http://www.qvc.com";}
  else if (document.stationform.stationselect.options[8].selected)
  { window.location.href = "http://www.historychannel.com";}
  else if (document.stationform.stationselect.options[9].selected)
  { window.location.href = "http://www.mtv.com";}
  else if (document.stationform.stationselect.options[10].selected)
  { window.location.href = "http://www.cnn.com";}
}

```

```

else if (document.stationform.stationsselect.options[11].selected)
{
    window.location.href = "http://www.aetv.com";}
else if (document.stationform.stationsselect.options[12].selected)
{
    window.location.href = "http://www.amctv.com";}
else if (document.stationform.stationsselect.options[13].selected)
{
    window.location.href = "http://www.bravotv.com";}
else if (document.stationform.stationsselect.options[14].selected)
{
    window.location.href = "http://www.c-span.org";}
else if (document.stationform.stationsselect.options[15].selected)
{
    window.location.href = "http://www.comcentral.com";}
else if (document.stationform.stationsselect.options[16].selected)
{
    window.location.href = "http://espnnet.sportszone.com";}
else if (document.stationform.stationsselect.options[17].selected)
{
    window.location.href = "http://www.fxnetworks.com";}
else if (document.stationform.stationsselect.options[18].selected)
{
    window.location.href = "http://www.hbohomevideo.com";}
else if (document.stationform.stationsselect.options[19].selected)
{
    window.location.href = "http://www.scifi.com";}
else if (document.stationform.stationsselect.options[20].selected)
{
    window.location.href = "http://showtimeonline.com";}
else if (document.stationform.stationsselect.options[21].selected)
{
    window.location.href = "http://vh1.com";}
else if (document.stationform.stationsselect.options[22].selected)
{
    window.location.href = "http://www.weather.com";}
else if (document.stationform.stationsselect.options[23].selected)
{
    window.location.href = "http://www.disneychannel.com";}

return true;
}

```

```

function textValue(){
    var stationInteger, stationString
    stationInteger=document.stationform.stationsselect.selectedIndex
    stationString=document.stationform.stationsselect.options[stationInteger].text
    document.stationform.stationtext.value = "Go to " + stationString + "!" }

```

```
//-->
```

```

</script>
<form name="stationform">
<select name="stationsselect" onChange="textValue()" multiple size="5">
<option>ABC
<option>CBS
<option>NBC

```



```

<option>Fox
<option>Cartoon Network
<option>Discovery Channel
<option>Warner Brothers Network
<option>QVC
<option>History Channel
<option>MTV
<option>CNN
<option>A&E
<option>American Movie Classics(AMC)
<option>Bravo
<option>C-SPAN
<option>Comedy Central
<option>ESPN
<option>FX
<option>HBO
<option>Sci-Fi Channel
<option>Showtime
<option>VH-1
<option>Weather Channel
<option>Disney Channel
</select>

<br><p>
<input type="button" name="stationbutton" value="Go!" onClick="go_to_station()">
<p>
<input type="text" name="stationtext" value="" size="35" maxlength="35">
<p>
</form>

```

任意多友情链接

脚本说明：

把如下代码加入<body>区域中：

```

<script language="JavaScript">
<!--
function go_to_station(){
    if (document.stationform.stationselect.options[0].selected){
        window.location.href = "http://java2000.126.com";}
        else if (document.stationform.stationselect.options[1].selected)
    {    window.location.href = "http://zjjg.yeah.net/";}
    else if (document.stationform.stationselect.options[2].selected)
    {    window.location.href = "http://mcg.yeah.net/";}
    else if (document.stationform.stationselect.options[3].selected)

```

```

    { window.location.href = "http://tonyest.yeah.net/";}
else if (document.stationform.stationselect.options[4].selected)
    { window.location.href = "http://cp33.yeah.net/";}
        else if (document.stationform.stationselect.options[5].selected)
    { window.location.href = "http://ftp.maoming.gd.cn/e/yanghai";}
        else if (document.stationform.stationselect.options[6].selected)
    { window.location.href = "http://jgq.yeah.net/";}
        else if (document.stationform.stationselect.options[7].selected)
    { window.location.href = "http://nns.yeah.net/";}
        return true;
    }
}
//This is were you load the Discription and the Author
function textValue(){
    if (document.stationform.stationselect.options[0].selected){
        document.stationform.disc.value = "Java 脚本下载资源站"
        document.stationform.author.value = "【最酷的 Java 脚本资源站】";}
        else if (document.stationform.stationselect.options[1].selected)
    { document.stationform.disc.value = "军事动态新闻及 MUD"
        document.stationform.author.value = "【军事与泥巴】";}
else if (document.stationform.stationselect.options[2].selected)
    { document.stationform.disc.value = "培训教学"
        document.stationform.author.value = "【微软认证专家园地】";}
else if (document.stationform.stationselect.options[3].selected)
    { document.stationform.disc.value = "电脑网络"
        document.stationform.author.value = "【梧桐世界】";}
else if (document.stationform.stationselect.options[4].selected)
    { document.stationform.disc.value = "图形图象制作"
        document.stationform.author.value = "【菜盆的'无中生有'】";}
        else if (document.stationform.stationselect.options[5].selected)
    { document.stationform.disc.value = "美术吉它"
        document.stationform.author.value = "【杨海“倾心小筑”】";}
else if (document.stationform.stationselect.options[6].selected)
    { document.stationform.disc.value = "电脑网络"
        document.stationform.author.value = "【江光强主页】";}
        else if (document.stationform.stationselect.options[7].selected)
    { document.stationform.disc.value = "游戏,编程"
        document.stationform.author.value = "【未名创作室】";}
    return true;
}
}
//-->
</script>
<div align="center"><font color="#ffffff" size="5">

```

```
<p align="center">不错的友情连接脚本</font> </p>
</div>
```

```
<form name="stationform">
  <table>
<TBODY>
  <tr>
    <td><select class="yk9" multiple name="stationselect" onchange="textValue()" size="8">
      <option>Java2000</option>
      <option>军事与泥巴</option>
      <option>微软认证专家园地</option>
      <option>梧桐世界</option>
      <option>菜盆的"无中生有"</option>
      <option>杨海 " 倾心小筑 " </option>
      <option>江光强主页</option>
      <option>未名创作室</option>
    </select> </td>
    <td>站点名称<br>
      <textarea class="yk9" cols="40" name="author" rows="1"></textarea> <br>
      站点主题<br>
      <textarea class="yk9" cols="40" name="disc" rows="3" wrap="physical"></textarea>
    </td>
  </tr>
</TBODY>
</table>
<input class="yk9" name="stationbutton" onclick="go_to_station()"
  type="button" value="参观参观">
</form>
```

链接自动说明脚本

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var description = new Array();
description[0] = "<font color=blue>国内最大的综合性站点，内容丰富，国内第一.</font>";
description[1] = "<font color=red>国内最大的<b>新闻</b>站点，新闻更新非常快</font>";
description[2] = "<font color=green><i>国内最大的搜索引擎站点，人气非常旺.</i></font>";
// End -->
</script>
<table border="0">
<tr>
<td valign=top width="50">
<a onMouseOver="Words.innerHTML = description[0];" href="http://www.163.com">网易</a>
```

```

<br><a onMouseOver="Words.innerHTML = description[1];" href="http://www.sina.com.cn">新
浪</a>
<br><a onMouseOver="Words.innerHTML = description[2];" href="http://www.sohu.com">搜狐
</a>
</td>
<td width="600">
<!-- Cell with the descriptions -->
<a id="Words">把鼠标放在文字链接上，就会出现相应的说明信息.</a>
</td>
</tr>
</table>

```

时钟显示在任意指定位置

脚本说明：

第一步:把如下代码加入<body>区域中:

```

<span id=liveclock style=position:absolute;left:250px;top:122px;; width: 109px; height: 15px>
</span>    ( 这里可以调整时钟的方位。调用脚本时去掉括号中内容 )
<SCRIPT language=javascript>
<!--

```

```

function show5(){if(!document.layers&&!document.all)
return
var Digital=new Date()
var hours=Digital.getHours()
var minutes=Digital.getMinutes()
var seconds=Digital.getSeconds()
var dn="AM"
if(hours>12){dn="PM"
hours=hours-12
}if(hours==0)
hours=12
if(minutes<=9)
minutes="0"+minutes
if(seconds<=9)
seconds="0"+seconds
//change font size here to your desire
myclock="<font          size='5'          face='Arial!'><b><font          size='1'>Current
Time:</font></br>"+hours+"."+minutes+"."
+seconds+" "+dn+"</b></font>"
if(document.layers){document.layers.liveclock.document.write(myclock)
document.layers.liveclock.document.close()
}else if(document.all)
liveclock.innerHTML=myclock
setTimeout("show5()",1000)

```

```
}  
//>  
</SCRIPT>
```

第二步:把<body>中的内容改为

```
<body bgcolor="#ffffff" ONLOAD=show5()>
```

链接处出现图标

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">  
<!-- Begin  
function imgover(imgname){  
imgname.src = "arrow.gif"  
}  
function imgout(imgname){  
imgname.src = "blank.gif"  
}  
// End -->  
</SCRIPT>  
  
<table border=0>  
<tr><td>  
<img name="pic1" SRC="blank.gif" width=10 height=10 border=0>  
<A          HREF="http://altavista.digital.com"          onMouseOver="imgover(pic1)"  
onMouseOut="imgout(pic1)">Altavista</A>  
<br>  
<img name="pic2" SRC="blank.gif" width=10 height=10 border=0>  
<A          HREF="http://www.excite.com"          onMouseOver="imgover(pic2)"  
onMouseOut="imgout(pic2)">Excite</A>  
<br>  
<img name="pic3" SRC="blank.gif" width=10 height=10 border=0>  
<A          HREF="http://www.hotbot.com"          onMouseOver="imgover(pic3)"  
onMouseOut="imgout(pic3)">Hotbot</A>  
<br>  
<img name="pic4" SRC="blank.gif" width=10 height=10 border=0>  
<A          HREF="http://www.infoseek.com"          onMouseOver="imgover(pic4)"  
onMouseOut="imgout(pic4)">Infoseek</A>  
<br>  
<img name="pic5" SRC="blank.gif" width=10 height=10 border=0>  
<A          HREF="http://www.lycos.com"          onMouseOver="imgover(pic5)"  
onMouseOut="imgout(pic5)">Lycos</A>  
<br>
```

```

<img name="pic6" SRC="blank.gif" width=10 height=10 border=0>
<A          HREF="http://www.magellan.com"          onMouseOver="imgover(pic6)"
onMouseOut="imgout(pic6)">Magellan</A>
<br>
<img name="pic7" SRC="blank.gif" width=10 height=10 border=0>
<A          HREF="http://www.webcrawler.com"        onMouseOver="imgover(pic7)"
onMouseOut="imgout(pic7)">Webcrawler</A>
<br>
<img name="pic8" SRC="blank.gif" width=10 height=10 border=0>
<A          HREF="http://www.yahoo.com"            onMouseOver="imgover(pic8)"
onMouseOut="imgout(pic8)">Yahoo!</A>
</td></tr></table>

```

导航菜单选择

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
site = "http://javacool.3322.net/time"; // Do not include the final "/"
function combineMenus(frm, menu1, menu2) {
with (frm) {
str = menu1.options[menu1.selectedIndex].value;
str += menu2.options[menu2.selectedIndex].value;
url = site + "/" + str + ".htm";
window.location.href = url;
}
}
// End -->
</script>
<form name=menufrm>
<select name=menu1>
<option value="">时间类</option>
<option value="time">time</option>
</select>
<select name=menu2>
<option value="">哪个</option>
<option value="1">1</option>
<option value="2">2</option>
<option value="3">3</option>
</select>
<input type=button value="Select" onClick="combineMenus(this.form, this.form.menu1,
this.form.menu2)">
</form>

```

按钮特效类

跑马灯式样的站点栏目指南

脚本说明:

把如下代码加入<body>区域中(你可以对链接及说明作相应修改)

```
<div id="tooltip2" style="position:absolute;visibility:hidden;clip:rect(0 150 50 0);width:150px;background-color:seashell">
<layer name="nstip" width=1000px bgColor="seashell"></layer>
</div>
<SCRIPT language="JavaScript">
<!--
if (!document.layers&&!document.all)
event="test"
function showtip2(current,e,text){

if (document.all&&document.readyState=="complete"){
document.all.tooltip2.innerHTML='<marquee style="border:1px solid black">'+text+'</marquee>'
document.all.tooltip2.style.pixelLeft=event.clientX+document.body.scrollLeft+10
document.all.tooltip2.style.pixelTop=event.clientY+document.body.scrollTop+10
document.all.tooltip2.style.visibility="visible"
}

else if (document.layers){
document.tooltip2.document.nstip.document.write('<b>'+text+'</b>')
document.tooltip2.document.nstip.document.close()
document.tooltip2.document.nstip.left=0
currentscroll=setInterval("scrolltip()",100)
document.tooltip2.left=e.pageX+10
document.tooltip2.top=e.pageY+10
document.tooltip2.visibility="show"
}
}
function hidetip2(){
if (document.all)
document.all.tooltip2.style.visibility="hidden"
else if (document.layers){
clearInterval(currentscroll)
document.tooltip2.visibility="hidden"
}
}
}
```

```

function scrolltip(){
if (document.tooltip2.document.nstip.left>=document.tooltip2.document.nstip.document.width)
document.tooltip2.document.nstip.left-=5
else
document.tooltip2.document.nstip.left=150
}
//-->

</SCRIPT>
<table border="0">
<tr>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b>
<a href="ye0.htm" onMouseOver="showtip2(this,event,' 字符从天而降 !)'
onMouseOut="hidetip2()">新的链接</a></b></font></td>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b><a href="ye1.htm"
onMouseOver="showtip2(this,event,'状态栏跑马灯 1!)" onMouseOut="hidetip2()">新的链接
</a></b></font></td>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b><a href="ye2.htm"
onMouseOver="showtip2(this,event,'状态栏跑马灯 2!)" onMouseOut="hidetip2()">新的链接
</a>
</b></font></td>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b><a href="ye3.htm"
onMouseOver="showtip2(this,event,'页面自动滚屏效果!)" onMouseOut="hidetip2()">新的链接
</a>
</b></font></td>
</tr>
<tr>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b><a href="ye1.htm"
onMouseOver="showtip2(this,event,'隐藏显示字符脚本!)" onMouseOut="hidetip2()">新的链接
</a></b></font></td>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b><a href="ye2.htm"
onMouseOver="showtip2(this,event,'滚动显示的 LOGO!)" onMouseOut="hidetip2()">新的链接
</a></b></font></td>
<td><font face="Arial, Helvetica, sans-serif" size="3"><b><a href="ye3.htm"
onMouseOver="showtip2(this,event,'鼠标跟踪器!)" onMouseOut="hidetip2()">新的链接
</a></b></font></td>
<td></td>
</tr>
</table>

```

窗口打开关闭脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
<!--
function openclk() {
another=open('time1.htm','NewWindow');
}
function closeclk() {
another.close();
}
//-->
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<FORM>
<INPUT TYPE="BUTTON" NAME="open" value="打开一个窗口" onClick="openclk()">
<BR>
<INPUT TYPE="BUTTON" NAME="close" value="关闭这个窗口" onClick="closeclk()">
</FORM>
```

连接说明浮动条脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
<!--
bname=navigator.appName;
bversion=parseInt(navigator.appVersion)
if (bname=="Netscape")
brows=true
else
brows=false
var x=0;
var link=new Array();

function dspl(msg,bgcolor,dtop,dleft){
this.msg=msg;
this.bgcolor=bgcolor;
this.dtop=dtop;
this.dleft=dleft;
}
-->
```

link[0]=new dspl(' [本站宗旨]
为制作交互的动态页面提供全面的分类齐全的 JS 脚本资源和主页制作技巧。','bisque',150,430)

link[1]=new dspl(' [本站论坛]
讨论一些我们共同关心的问题,主页制作,JS 脚本的应用技巧等。','bisque',175,430)

link[2]=new dspl(' [本站栏目]
分类齐全的 JS 脚本资源,JavaApplet 小程序,精彩动画欣赏,各种实用资源及邮件列表(JS 脚本先睹为快)等。','bisque',200,430)

link[3]=new dspl(' [关于本站]
创建于 99 年 8 月 25 日,Webmaster:天涯网人','bisque',235,430)

// Do not edit anything else in the script !!!!

```
function don(x){
if ((bname=="Netscape" && bversion>=4) || (bname=="Microsoft Internet Explorer" &&
bversion>=4)){
if (brows){
with(link[x]){
document.layers['linkex'].bgColor=bgcolor;
document.layers['linkex'].document.writeln(msg);
document.layers['linkex'].document.close();
document.layers['linkex'].top=dtop;
document.layers['linkex'].left=dleft;
}
document.layers['linkex'].visibility="show";
}
else{
with(link[x]){
linkex.innerHTML=msg;
linkex.style.top=dtop;
linkex.style.left=dleft;
linkex.style.background=bgcolor;
}
linkex.style.visibility="visible";
}
}
}
```

```
function doff(){
if ((bname=="Netscape" && bversion>=4) || (bname=="Microsoft Internet Explorer" &&
bversion>=4)){
if (brows)
document.layers['linkex'].visibility="hide";
else
linkex.style.visibility="hidden";
}
}
```

```
}
```

```
//-->
```

```
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<Div id="linkex" style="position: absolute; visibility: hidden; width=80%">
</Div>
<Layer name="linkex" visibility="hide" width=80%>
</Layer>
<p align="center">
<a href="time1" onmouseover="don(0)" onmouseout="doff()" target="_blank"> [ 本站宗旨 ]
</a><BR>
  <BR>
  <a href="time2" onmouseover="don(1)" onmouseout="doff()" target="_blank"> [ 本站论坛 ]
</a><BR>
  <br>
  <a href="time3" onmouseover="don(2)" onmouseout="doff()" target="_blank"> [ 本站栏目 ]
</a><BR>
  <BR>
  <a href="time4" onmouseover="don(3)" onmouseout="doff()" target="_blank"> [ 关于本站 ]
</a>
</p>
```

链接处变换色彩

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function initArray() {
for (var i = 0; i < initArray.arguments.length; i++) {
this[i] = initArray.arguments[i];
}
this.length = initArray.arguments.length;
}
var colors = new initArray(
"red",
"blue",
"green",
"purple",
"black",
```

```

"tan",
"yellow",
"lime",
"coral",
"palegreen",
"silver",
"gold",
"red");
delay = .5; // seconds
link = 0;
vlink = 0;
function linkDance() {
link = (link+1)%colors.length;
vlink = (vlink+1)%colors.length;
document.linkColor = colors[link];
document.vlinkColor = colors[vlink];
setTimeout("linkDance()",delay*1000);
}
linkDance();
// End -->
</script>

```

那么链接处就会出现彩色字体

注意：不能在<style>中定义好链接颜色

变换链接色和底色

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```

<!-- Begin
function doColor(item, color, bg) {
item.style.color = color; // changes text color
item.style.backgroundColor = bg; // changes background
}

function undoColor(item) {
item.style.color = "#000000"; // sets color back to black
item.style.backgroundColor = ""; // sets background to default
}
// End -->
</script>
</HEAD>

```

第二步:在<body>区中加入如下代码

```
<a name="link1" href="http://www.internet.com" onmouseover="doColor(link1, 'yellow','black');" onmouseout="undoColor(link1);">internet.com</a>
<p>
<a name="link2" href="http://www.javascriptsource.com" onmouseover="doColor(link2, 'blue','red');" onmouseout="undoColor(link2);">javascriptsource.com</a>
```

按顺序点击链接

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
<!--
function MM_showHideLayers() { //v2.0
  var i, visStr, args, theObj;
  args = MM_showHideLayers.arguments;
  for (i=0; i<(args.length-2); i+=3) { //with arg triples (objNS,objIE,visStr)
    visStr = args[i+2];
    if (navigator.appName == 'Netscape' && document.layers != null) {
      theObj = eval(args[i]);
      if (theObj) theObj.visibility = visStr;
    } else if (document.all != null) { //IE
      if (visStr == 'show') visStr = 'visible'; //convert vals
      if (visStr == 'hide') visStr = 'hidden';
      theObj = eval(args[i+1]);
      if (theObj) theObj.style.visibility = visStr;
    }
  }
}

function MM_preloadImages() { //v2.0
  if (document.images) {
    var imgFiles = MM_preloadImages.arguments;
    if (document.preloadArray==null) document.preloadArray = new Array();
    var i = document.preloadArray.length;
    with (document) for (var j=0; j<imgFiles.length; j++) if (imgFiles[j].charAt(0)!="#{"){
      preloadArray[i] = new Image;
      preloadArray[i++].src = imgFiles[j];
    }
  }
}
//-->

</SCRIPT>
```

第二步:在<body>区中加入如下代码

```
<div id="Layer1" style="position:absolute; left:240px; top:175px; width:306px; height:63px;
```

```

z-index:1; visibility: hidden"><a href="javascript.zip"><font color=green size="5" face="隶书">
下载所有 Javascript 特效!</font></a></font></div>
<div id="Layer2" style="position:absolute; left:280px; top:237px; width:147px; height:82px;
z-index:2; visibility: visible">
  <p align="center"><a href="Upper1/default.htm" target="_blank">
    <img SRC="tb3.jpg" border="0"
onMouseDown="MM_showHideLayers('document.layers[\Layer1\'],'document.all[\Layer1\'],'sh
ow')"></a></font><br>
  </p>
</div>

```

第三步:把<body>区中内容改为:

```
<body bgcolor="#ffffff" onLoad="MM_preloadImages()">
```

查看源代码按钮

脚本说明:

把如下代码加入<body>区域中

```
<input type="BUTTON" value="查看源代码" onClick= 'window.location = "view-source:" +
window.location.href' name="BUTTON">
```

前进后退按钮

脚本说明:

把如下代码加入<body>区域中

```
<script language="VBScript">
```

```
<!--
```

```
Sub GoForward()
```

```
  form1.btn2.value="正在前进"
```

```
  history.go(1)
```

```
end sub
```

```
Sub GoBack()
```

```
  form1.btn1.value="正在后退"
```

```
  history.go(-1)
```

```
end sub
```

```
-->
```

```
</script>
```

```

      <form name=form1>
        <input type="button" name="btn1" value="<< 后退 "
onClick="GoBack">
        <input type="button" name="btn2" value="前进 >>"
onClick="GoForward">
      </form>

```

按钮定制打开窗口

脚本说明:

把如下代码加入<body>区域中

```
<input type="button" value=" 怀柔网 " onClick="window.open('Upper1/default.htm', 'Sample', 'toolbar=no,location=no,directories=no,status=no,menubar=no,scrollbars=no,resizable=yes,copyhistory=yes,width=490,height=320,left=0,top=0')" name="Input">
```

按钮打开全屏窗口

脚本说明:

把如下代码加入<body>区域中

```
<script>
<!--
function winopen(){
var targeturl="http://www.hrw.cn"
newwin=window.open("", "", "scrollbars")
if (document.all){
newwin.moveTo(0,0)
newwin.resizeTo(screen.width,screen.height)
}
newwin.location=targeturl
}
//-->
</script>
<input type="button" onClick="winopen()" value="怀柔网" name="button">
```

自由打开各种窗口

脚本说明:

把如下代码加入<body>区域中

```
<script language="JAVASCRIPT">
<!-- hide

function customize(form) {
    var address = document.form1.url.value;
    var op_tool  = (document.form1.tool.checked == true) ? 1 : 0;
    var op_loc_box  = (document.form1.loc_box.checked == true) ? 1 : 0;
    var op_dir  = (document.form1.dir.checked == true) ? 1 : 0;
    var op_stat  = (document.form1.stat.checked == true) ? 1 : 0;
    var op_menu  = (document.form1.menu.checked == true) ? 1 : 0;
    var op_scroll  = (document.form1.scroll.checked == true) ? 1 : 0;
    var op_resize  = (document.form1.resize.checked == true) ? 1 : 0;
    var op_wid  = document.form1.wid.value;
    var op_heigh  = document.form1.heigh.value;
    var option = "toolbar=" + op_tool + ",location=" +
```

```

op_loc_box +                ",directories="
+ op_dir +                    ",status="      + op_stat
+                            ",menubar="    + op_menu +                ",scrollbars="

+ op_scroll +                ",resizeable=" + op_resize
+                            ",width="
+ op_wid +                    ",height="    + op_heigh;
var win3 = window.open("", "what_I_want", option);
var win4 = window.open(address, "what_I_want");
}
function clear(form){
    document.form1.wid.value="";
    document.form1.heigh.value="";
}
// done hiding -->
</script>

```

```

<form name="form1" action="javascript:" method="POST">
    <div align="left">
        <table width="100%" border="0" cellspacing="0" cellpadding="0">
            <tr align="center">
                <td colspan="4" height="35"> URL :
                <input type="text" size="40" name="url" value="http://">
            </td>
            </tr>
            <tr align="center">
                <td width="25%" height="25">
                    <input
type="checkbox" name="tool" value="ON">
                    : 快捷键 </td>
                <td width="25%" height="25">
                    <input type="checkbox" name="loc_box" value="ON">
                    : 地址栏 </td>
                <td width="25%" height="25">
                    <input
type="checkbox" name="dir" value="ON">
                    : 链接 </td>
                <td width="25%" height="25">
                    <input type="checkbox" name="stat" value="ON">
                    : 状态栏 </td>
            </tr>
            <tr align="center">
                <td width="25%" height="25">
                    <input

```



```

type="checkbox" name="resize" value="ON">
    : 调大小 </td>
<td width="25%" height="25">
    <input type="checkbox" name="scroll" value="ON">
    : 滚动条</td>
<td width="25%" height="25">
    <input
type="checkbox" name="menu" value="ON">
    : 菜单 </td>
<td width="25%" height="25"> </td>
</tr>
<tr align="center">
<td colspan="2" height="35">
    <input type="text" name="wid"
size="14">
    : 宽</td>
<td colspan="2" height="25">
    <input type="text" name="heigh" size="14">
    : 高</td>
</tr>
<tr align="center">
<td colspan="4" height="25">
    <input
type="button" size="10" value="确认" onClick="customize(this.form)" name="button">
    <input type="reset"
size="10" value="重填" onClick="clear(this.form)" name="reset">
</td>
</tr>
</table>
</div>
</form>

```

按钮回到默认首页

脚本说明:

把如下代码加入<body>区域中

```

<script>
<!--//
function gohome(){
if (document.layers)
window.home()
else if (document.all)
window.location="about:home"
else
alert("You need NS 4+ or IE 4+ to go back home!")

```

```
}
//-->
</script>
<form>
<input type="button" onClick="gohome()" value="Take Me Home!">
</form>
```

各种用途的按钮

脚本说明：

把如下代码加入<body>区域中：

```
<form>
  <p>
    <input type="button" value=" 返回 " onClick="history.go(-1)" name="button"
class="pt9">
    <input TYPE="button" NAME="view" VALUE=" 查看本例的源码 "
OnClick="window.location='view-source:'+window.location.href" class="pt9">
  </p>
</form>
```

```
<form>
  <p><input TYPE="button" VALUE="返回上一步" ONCLICK="history.back(-1)"></p>
</form>
```

```
<form>
  <p><input TYPE="button" VALUE="刷新按钮一" ONCLICK="ReloadButton()"></p>
</form>
```

```
<script language="JavaScript"><!--
function ReloadButton(){location.href="allbutton.htm";}
// --></script>
```

```
<form>
  <p><input TYPE="button" VALUE="刷新按钮二" onClick="history.go(0)"> </p>
</form>
```

```
<form>
  <p><input TYPE="button" VALUE="回首页按钮" ONCLICK="HomeButton()"></p>
</form>
```

```
<script language="JavaScript"><!--
function HomeButton(){location.href="http://nettrain.126.com";}
// --></script>
```

```
<form>
  <p><input TYPE="button" VALUE="弹出警告框" ONCLICK="AlertButton()"></p>
</form>
<script language="JavaScript"><!--
function AlertButton(){window.alert("要多多光临呀！");}
// --></script>
```

```
<form>
  <p><input TYPE="button" VALUE="状态栏信息" ONCLICK="StatusButton()"></p>
</form>
<script language="JavaScript"><!--
function StatusButton(){window.status="要多多光临呀！";}
// --></script>
```

```
<form>
  <p><input TYPE="button" VALUE="背景色变换" onClick="BgButton()"></p>
</form>
<script>function BgButton(){
if (document.bgColor=='#00ffff')
  {document.bgColor='#ffffff';}
else{document.bgColor='#00ffff';}
}
</script>
```

```
<form>
  <p><input TYPE="button" VALUE="打开新窗口" ONCLICK="NewWindow()"></p>
</form>
<script language="JavaScript"><!--
function
NewWindow(){window.open("../navigation/maillist.htm","", "height=240,width=340,status=no,loc
ation=no,toolbar=no,directories=no,menubar=no");}
// --></script>
```

频道方式打开窗口

脚本说明：

把如下代码加入<body>区域中：

```
<script>
<!--
function channel(){
window.open("an12.htm","", "channelmode,scrollbars")
}
```

```
//-->
</script>

<p>
<form>
<input type="button" onClick="channel()" value="打开窗口" name="button">
</form>
```

按钮特殊效果

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style type="text/css">
<!--
.over {color:yellow; background: navy}
.down {color:yellow; background: navy; font-style: italic}
-->
</style>
```

第二步:在<body>区中加入如下代码

```
<input
type="Button"
onMouseOver="this.className='over';"
onMouseOut="this.className=";"
onMouseDown="this.className='down';"
onMouseUp="this.className='over';"
value="按钮也疯狂"
onClick="this.value='我真的好喜欢你！'" name="Button">
```

浏览器全屏显示

脚本说明:

把如下代码加入<body>区域中

```
<form>
<div align="center">
<input type="BUTTON" name="FullScreen" value=" 全 屏 显 示 "
onClick="window.open(document.location, 'big', 'fullscreen=yes')">
</div>
</form>
```

跳出说明窗口

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="Javascript">
```



```

}

// This is a bit hard to edit if you don't do javascript.
// Here you can edit the HTML of the profile window
// Keep in mind you'll get errors if you use " without a slash (\")
function makePUP(num){
    makePupWin();
    PUP.document.write("<HTML>\n<HEAD>\n<TITLE>Profile for: " + peepName[num] +
"</TITLE>");
    PUP.document.write("\n<HEAD>\n<BODY BGCOLOR=\"" + pageAtr[0] + "\" TEXT=\"" +
pageAtr[1] + "\">");
    PUP.document.write("\n<CENTER>\n<TABLE        WIDTH=\"250\"        BORDER=\"1\"
HEIGHT=\"100\">\n<TR>\n<TD>Name</TD><TD><CENTER>" + peepName[num] +
"</CENTER></TD>");
    PUP.document.write("\n<TR>\n<TR>\n<TD>Title:</TD><TD><CENTER>" + peepPos[num]
+ "</CENTER></TD>");
    PUP.document.write("\n<TR>\n<TR>\n<TD>Quote:</TD><TD><CENTER>" + peepAd[num]
+ "</CENTER></TD>");
    PUP.document.write("\n<TR>\n</TABLE>\n<FORM>\n<INPUT        TYPE=\"button\"
VALUE=\"Close Profile\" onClick=\"self.close();\">\n</FORM>\n</BODY>\n</HTML>");
    PUP.status=(peepName[num] + "'s Pop Up Profile");
    PUP.document.close();
}
</SCRIPT>
<CENTER>
<FORM>
<INPUT TYPE="button" VALUE="Jason's profile" onClick="makePUP(1)"><P>
<INPUT TYPE="button" VALUE="John's profile" onClick="makePUP(2)"><P>
<INPUT TYPE="button" VALUE="Joe's profile" onClick="makePUP(3)"><P>
<INPUT TYPE="button" VALUE="Ryan's profile" onClick="makePUP(4)"><P>
<INPUT TYPE="button" VALUE="Jessica's profile" onClick="makePUP(5)"><P>
<INPUT TYPE="button" VALUE="Mrs. Jacobson's profile" onClick="makePUP(6)"><P>
</FORM>
</CENTER>

```

关不掉的跳出框

脚本说明：

把如下代码加入<body>区域中：

```
<input type=button value=hmm onClick="var e=1;while(1==1){alert('你是关不掉我的!!!!')}">
```

循环的警告框

脚本说明：

把如下代码加入<body>区域中：

```
<script>
```

```

<!-- Script by Juan Valdez
function hate()
{
alert('  from ');
alert('  what');
alert('  you');
alert('  can');
alert('  see');
alert('  this');
alert('  is');
alert(' annoying');
return hate()
}
//-- done -->
</script>
<a href="javascript:hate()" onmouseover="window.status='按了可就关不掉了!';return true">
<b>最好别按</b></a>

```

检测页面来源

脚本说明：

把如下代码加入<body>区域中:

```

<SCRIPT>
<!--
function check(){ //remove this line to use the script for real
var from = document.referrer
var here = "http://www.hrw.cn/javascript/an22.htm" //Change this to your site
alert("From:"+from);//remove this line to use the script for real
alert("Here:"+here);//remove this line to use the script for real
if (from.substring(0,here.length) != here) history.back()
else document.location.replace('http://www.hrw.cn/javascript/an22.htm'); //Page to go to if OK
} //remove this line to use the script for real
//-->
</SCRIPT>
<FORM>
<INPUT TYPE=button VALUE="Check" onClick="check()">
</FORM>

```

屏幕抖动脚本

脚本说明：

把如下代码加入<body>区域中:

```

<script language="JavaScript">
<!--
function surfto(form) {
var myindex=form.select1.selectedIndex

```

```

        if (form.select1.options[myindex].value != null) {
            parent.main.location.href=form.select1.options[myindex].value;
        }
    }
// -->
</script>
<script language="JavaScript1.2">
<!--
function shake(n) {
if (window.top.moveBy) {
for (i = 10; i > 0; i--) {
for (j = n; j > 0; j--) {
window.top.moveBy(0,i);
window.top.moveBy(i,0);
window.top.moveBy(0,-i);
window.top.moveBy(-i,0);
        }
    }
}
alert(" 没吓坏吧!!! ");
}
// End -->
</script>
<script
language="JavaScript">
<!--
function moyamoya(htmlfile) {
    parent.main.location.href=htmlfile;
}
// -->
</script>

<form>
    <div align="center"><center><p><input onclick="shake(2)" type="button"
    value="地震拉 !!! "> </p>
    </center></div>
</form>

```

页面被冻结

脚本说明:

把如下代码加入<body>区域中

```

<script>
function freeze(){

```



```

alert ('对不起，你死机了，哈哈!!!');while(true){ window.history.back(-1)}
</script>
<FORM>
<INPUT TYPE="BUTTON" VALUE="Freeze" onClick="freeze()">
</FORM>

```

代码生成类

动态按钮代码生成器

脚本说明：

第一步:把如下代码加入<head>区域中:

```

<SCRIPT LANGUAGE="JavaScript">
<!--
var a = 21
function create() {

    this.line = "

}

function skrivut(formet) {
bild1 = formet.bilden.value;
bild2 = formet.bildtva.value;
kall1 = formet.srcen.value;
kall2 = formet.srctva.value;
bildnamn = formet.bildnmn.value;
widd = formet.widden.value;
hojd = formet.hojden.value;

line = new Array()
for(var i=1; i<=a; i++) { line[i] = new create() }
line[1] = '<html><head><title>Code Window</title></head><body bgcolor="#FFFFFF">'
line[2] = '&lt;HTML&gt;&lt;HEAD&gt;<br>&lt;TITLE&gt;Title of your page&lt;/title&gt;<P>'
line[3] = '                                =                                &lt;SCRIPT
LANGUAGE=&quot;JavaScript&quot;&gt;&lt;BR>&lt;!--&lt;BR>/**luxiaoqing
http://www.hrw.cn/javascript/dai1.htm**/&lt;BR>Browser                                =
false ;&lt;BR>if(navigator.appName.indexOf("Netscape") != -1)&lt;BR>'
line[5] = '    {    if(    (navigator.appVersion.indexOf("3.")    !=    -1)    ||
(navigator.appVersion.indexOf("4.") != -1) )&lt;BR>'
line[6] = ' Browser = true}&lt;BR>'
line[7]='if(navigator.appVersion.indexOf("MSIE")                                !=                                -1)
{ if( navigator.appVersion.indexOf("4.") != -1)&lt;BR>'
line[8]='Browser=true}&lt;BR>'
line[9]='if ( Browser == true) {&lt;BR>'

```

```

line[10] = bild1+'= new Image();<BR>'
line[11] = bild1+'.src = '"+kall1+"'<BR>'
line[12] = bild2+'= new Image();<BR>'
line[13] = bild2+'.src = '"+kall2+"'<BR><P>'
line[14] = 'function byt(place, imgName) {<BR>'
line[15] = 'if (Browser == true) {<BR>'
line[16] = 'document[place].src =eval(imgName + ".src");<BR>'
line[17] = '}'<BR>'
line[18] = '//-&gt;<BR>'
line[19] = '&lt;/SCRIPT&gt;<P>&lt;/HEAD&gt;<br>&lt;/BODY&gt;<P>Here comes the
link:<BR>'
line[20] = '&lt;A HREF=".html"
onMouseOver="byt(&#039;'+bildnamn+'&#039;,&#039;'+bild2+'&#039;)"
onMouseOut="byt(&#039;'+bildnamn+'&#039;,&#039;'+bild1+'&#039;)"&gt;'
line[21] = '&lt;IMG SRC="'+kall1+'" NAME="'+bildnamn+'" HEIGHT="'+hojd+'
WIDTH="'+widd+' BORDER="0"&gt;&lt;/A&gt;'
line[22] = '<P>&lt;/BODY&gt;&lt;/HTML&gt;<P><FORM><INPUT TYPE="button" VALUE="
关闭" OnClick="self.close()"></FORM></BODY></HTML>'
nyaWin =
window.open(", 'utskrift', 'toolbar=0,location=0,directories=0,status=1,menubar=1,scrollbars=1,resi
zable=0,copyhistory=0,width=600,height=400')
nytt ()
}
g = 0
function nytt() {
g++
nyaWin.document.writeln(line[g]);
if (g < (a+1)) nytt()
nyaWin.document.close()
g = 0
}

Browser = false ;
if(navigator.appName.indexOf("Netscape") != -1)
{ if( (navigator.appVersion.indexOf("3.") != -1) ||
(navigator.appVersion.indexOf("4.") != -1) )
{ Browser = true;
fredrik= new Image();
fredrik.src = "knapp1.gif";
sover = new Image();
sover.src = "knapp2.gif";
} }

function byt(place, imgName) {

```

```

if (Browser == true) {
document[place].src =eval(imgName + ".src");
} }
//-->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中:

```

<form>
  图片 1 的名字 :
  <INPUT TYPE="text" NAME="bilden" class="pt9" value="mouseoutpic">
  <BR>
  图片 1 的路径 :
  <INPUT TYPE="text" NAME="srcen" class="pt9" value="images/pic1.gif">
  <BR>
  图片 1 的宽度 :
  <INPUT TYPE="text" NAME="widden" class="pt9" value="100">
  <BR>
  图片 1 的高度 :
  <INPUT TYPE="text" NAME="hojden" class="pt9" value="50">
  <P> 图片 2 的名字 :
    <INPUT TYPE="text" NAME="bildtva" class="pt9" value="mouseoverpic">
    <BR>
    图片 2 的路径 :
    <INPUT TYPE="text" NAME="srctva" class="pt9" value="images/pic2.gif">
    <BR>
    操作的名字 :
    <INPUT TYPE="text" NAME="bildnmn" class="pt9" value="first_pic">
    <BR>
    <INPUT TYPE="BUTTON" VALUE="生成代码" OnClick="skrivut(this.form)"
class="pt9">

```

```
</FORM>
```

```
<P>
```

<P>说明: 图片 1==》 mouse out 时的图片, 正常显示时。 图片 2==》 mouse over 时的图片。
图片的名字和操作的名字可以随便取。有所区别即可。

<P>2 个图片的尺寸必须一致才可以。

浏览器检测生成器

脚本说明:

第一步:把如下代码加入<head>区域中:

```

<script language="javascript">
<!--
function createcodes(entry)
{

```

```

line="<script>version=parseInt(navigator.appVersion);          browser='OTHER';          if
(navigator.appName=='Netscape'){browser='NS'+version;}  if (navigator.appName=='Microsoft
Internet Explorer'){browser='MSIE'+version;}  if (navigator.appVersion.indexOf('MSIE 3')>0)
{browser='MSIE3'}";
with (document.detectform)
{
  if      (MSIE3.value!="")          {line=line+"if      (browser=='MSIE3')
{window.location=""+MSIE3.value+""}";}
  if      (MSIE4.value!="")          {line=line+"if      (browser=='MSIE4')
{window.location=""+MSIE4.value+""}";}
  if      (MSIE5.value!="")          {line=line+"if      (browser=='MSIE5')
{window.location=""+MSIE5.value+""}";}
  if (NS3.value!="") {line=line+"if (browser=='NS3') {window.location=""+NS3.value+""}";}
  if (NS4.value!="") {line=line+"if (browser=='NS4') {window.location=""+NS4.value+""}";}
  if (NS5.value!="") {line=line+"if (browser=='NS5') {window.location=""+NS5.value+""}";}
  if      (OTHER.value!="")          {line=line+"if      (browser=='OTHER')
{window.location=""+OTHER.value+""}";}
}
line=line+"</script>"

entry.code.value=line;
}
//-->
</script>

```

第二步:把如下代码加入<body>区域中:

```

<TABLE width="100%" border="0" cellspacing="0" cellpadding="0" align="CENTER"
valign="TOP">
  <tr>
    <td colspan=3 bgcolor="#6C6C6C"></td>
  </tr>
  <tr>
    <td height="3"></td>
    <TABLE align="CENTER">
      <tr>
        <td>
          <form name="detectform">
            <table align="center">
              <tr>
                <td></td>
                <td>
                  <div align="center">
                    <center>

```

```

<table border="1" width="100%">
  <tr>
    <td bgcolor="#CCCCDD" colspan="2" width="100%">
      <p>请输入各项连接
    </td>
  </tr>
  <tr align="center">
    <td bgcolor="#FFFFFF" colspan=2 align=left> </td>
  </tr>
  <tr align="center">
    <td bgcolor="#EEEEFF" colspan="">BROWSER</td>
    <td bgcolor="#EEEEFF" colspan="">PAGE-URL</td>
  </tr>
  <tr align="center">
    <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2"> MSIE
      3 </font></td>
    <td bgcolor="#E4E4E4" colspan="">
      <input type="text" name="MSIE3" size="25"
value="http://www.yahoo.com">
    </td>
  </tr>
  <tr align="center">
    <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2"> MSIE
      4 </font></td>
    <td bgcolor="#E4E4E4" colspan="">
      <input type="text" name="MSIE4" size="25"
value="http://www.yahoo.com">
    </td>
  </tr>
  <tr align="center">
    <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2"> MSIE
      5 </font></td>
    <td bgcolor="#E4E4E4" colspan="">
      <input type="text" name="MSIE5" size="25"
value="http://www.yahoo.com">
    </td>
  </tr>
  <tr align="center">
    <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2">NETSCAPE
      3</font></td>

```

```

        <td bgcolor="#E4E4E4" colspan="">
            <input type="text" name="NS3" size="25"
value="http://www.yahoo.com">
        </td>
    </tr>
    <tr align="center">
        <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2">NETSCAPE
            4</font></td>
        <td bgcolor="#E4E4E4" colspan="">
            <input type="text" name="NS4" size="25"
value="http://www.yahoo.com">
        </td>
    </tr>
    <tr align="center">
        <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2">NETSCAPE
            5</font></td>
        <td bgcolor="#E4E4E4" colspan="">
            <input type="text" name="NS5" size="25"
value="http://www.yahoo.com">
        </td>
    </tr>
    <tr align="center">
        <td bgcolor="#E4E4E4" colspan=""><font color="#000000"
size="2">OTHER
            BROWSERS</font></td>
        <td bgcolor="#E4E4E4" colspan="">
            <input type="text" name="OTHER" size="25"
value="http://www.yahoo.com">
        </td>
    </tr>
    <tr align="center">
        <td colspan="2" bgcolor="#C0C0C0" align="left">
            <input
type="button" value="代码生成" name="B1" onClick="createcodes(this.form)"
class="pt9">
            <br>
            <input type="reset" value="清除重选" name="B2"
class="pt9">
        </td>
    </tr>
</table>

```

```

        </center>
    </div>
</td>
<td></td>
</tr>
</table>

<table align="center">
<tr>
<td>
<table border="1" align="center">
<tr>
<td bgcolor="#CCCCDD" colspan="2">
<p>生成的代码如下 :
</td>
</tr>

<tr>
<tr>
<td bgcolor="#EEEEFF">
<div align="center">
<center>
<p>拷贝如下代码</p>
</center>
</div>
</td>
</tr>
<tr>
<td bgcolor="#EEEEEE">
<div align="center">
<center>
<p>
<textarea name="code" cols="45" rows="20"
wrap="PHYSICAL" class="pt9">选择上面的项目生成代码

```

BrowserCheck脚本

脚本说明：

把如下代码加入<body>区域中：

```
<script>
```

```

function go(){
document.forms[1].scriptfield.value="<script>\n//BrowserCheck 浏览器检测脚本生成器
\n//luxiaoqing http://www.hrw.cn/javascript/dai3.htm\n"
document.forms[1].scriptfield.value=document.forms[1].scriptfield.value+"if

```

```
("+document.forms[0].version.value+"<=parseFloat(navigator.appVersion)){ if
(navigator.appName.indexOf(""+document.forms[0].browser.options[document.forms[0].browser.s
electedIndex].value+"")!=-1){ if (4<=parseFloat(navigator.appVersion)){ if
("+document.forms[0].width.value+"<=screen.width){ if
("+document.forms[0].height.value+"<=screen.height){ if
("+document.forms[0].depth.value+"<=screen.colorDepth){ } else{error()} } else{error()} } else{erro
r()} } } else{error()} } else{error()} "
if (document.forms[0].em.options[document.forms[0].em.selectedIndex].value=="popup"){
// document.forms[1].scriptfield.value=document.forms[1].scriptfield.value+'window.alert(" 本站
推 荐 使 用
'+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+" 版 本
"+document.forms[0].version.value+' 以 上 。 最 佳 分 辨 率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
'+document.forms[0].depth.value+' 位 色 。 您 现 在 使 用 "+navigator.appName+"
"+navigator.appVersion+",您的显示器属性和颜色数无法检测。")}'
document.forms[1].scriptfield.value=document.forms[1].scriptfield.value+'function
error(){if(parseFloat(navigator.appVersion)<4.00){ window.alert(" 本 站 推 荐 使 用
'+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+"
"+document.forms[0].version.value+' 以 上 。 最 佳 分 辨 率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
pix.'+document.forms[0].depth.value+' 位 色 。 您 现 在 使 用 "+navigator.appName+"
"+navigator.appVersion+",您的显示器属性和颜色数无法检测。")}else{ window.alert("本站推荐
使用 '+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+"
"+document.forms[0].version.value+' 以 上 。 最 佳 分 辨 率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
'+document.forms[0].depth.value+' 位 色 。 您 现 在 使 用 "+navigator.appName+"
"+navigator.appVersion+", 分 辨 率 "+screen.width+"x"+screen.height+"
"+screen.colorDepth+" 位色"))}\n</sc+'ript>'}
else{
// document.forms[1].scriptfield.value=document.forms[1].scriptfield.value+'document.write(" 本
站 推 荐 使 用
'+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+"
"+document.forms[0].version.value+' 以 上 。 最 佳 分 辨 率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
pix.'+document.forms[0].depth.value+' 位 色 。 您 现 在 使 用 "+navigator.appName+"
"+navigator.appVersion+",您的显示器属性和颜色数无法检测。")}else{error()}'
// document.forms[1].scriptfield.value=document.forms[1].scriptfield.value+'function
error(){ document.write(" 本 站 推 荐 使 用
'+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+"
"+document.forms[0].version.value+' 以 上 。 最 佳 分 辨 率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
'+document.forms[0].depth.value+' 位 色 。 您 现 在 使 用 "+navigator.appName+"
"+navigator.appVersion+", 分 辨 率 "+screen.width+"x"+screen.height+"
"+screen.colorDepth+" 位色"))}\n</sc+'ript>'}
```



```

document.forms[1].scriptfield.value=document.forms[1].scriptfield.value+function
error(){if(parseFloat(navigator.appVersion)<4.00){document.write(" 本站推荐使用
'+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+'
"+document.forms[0].version.value+' 以上。最佳分辨率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
'+document.forms[0].depth.value+' 位色。您现在使用 "+navigator.appName+"
"+navigator.appVersion+",您的显示器属性和颜色数无法检测。")}else{document.write("本站推
荐使用 '+document.forms[0].browser.options[document.forms[0].browser.selectedIndex].value+"
"+document.forms[0].version.value+' or higher, 分辨率
'+document.forms[0].width.value+'x'+document.forms[0].height.value+'
'+document.forms[0].depth.value+' 位色。您现在使用 "+navigator.appName+"
"+navigator.appVersion+", 分辨率 "+screen.width+"x"+screen.height+" and
"+screen.colorDepth+" 位色"))}\n</sc'+ript>'}

```

```

}

```

```

//)}

```

```

</script>

```

```

<table border="0" width="100"

```

```

bgcolor="#9BADB8">

```

```

<tr>

```

```

<td

```

```

style="border-left: 5px groove; border-right: 5 groove; border-top:

```

```

5 groove; border-bottom: 5 groove"

```

```

align="center" height="646">

```

```

<form method="POST">

```

```

<table border="0" width="443">

```

```

<tr>

```

```

<td width="123" align="right"><font color="#000000"

```

```

face="Arial"><strong><br>

```

```

Browser</strong></font></td>

```

```

<td width="310" align="left" valign="bottom"><font color="#000000"

```

```

face="Arial"><br>

```

```

<select name="browser" size="1" style="font-family: MS Sans

```

```

Serif, Arial">

```

```

<option value="Microsoft Internet Explorer" selected>Microsoft
Internet Explorer</option>

```

```

<option value="Netscape">Netscape Navigator</option>

```

```

</select>

```

```

</font></td>

```

```

</tr>

```

```

<tr>

```

```

<td width="123" align="right"><font color="#000000"

```

```

face="Arial"><strong>Browser version</strong></font></td>

```

```

<td width="310" align="left"><font face="Arial">

```

```

<input

```

```

type="text" name="version" size="5"
value="4.0">
    </font></td>
</tr>
<tr>
    <td width="123" align="right"><font color="#000000"
face="Arial"><strong>Screen width</strong></font></td>
    <td width="310" align="left"><font color="#000000"
face="Arial">
        <input type="text"
name="width" size="5" value="800">
        pixels</font></td>
</tr>
<tr>
    <td width="123" align="right"><font color="#000000"
face="Arial"><strong>Screen height</strong></font></td>
    <td width="310" align="left"><font color="#000000"
face="Arial">
        <input type="text"
name="height" size="5" value="600">
        pixels</font></td>
</tr>
<tr>
    <td width="123" align="right" valign="top"><font
color="#000000" face="Arial"><strong>Screen depth</strong></font></td>
    <td width="310" align="left"><font color="#000000"
face="Arial">
        <input type="text"
name="depth" size="5" value="32">
        bit <br>
        <small><small>(32 bit colors 32 bit, for 16 bit colors 16
        bit, for 256 colors 8 bit and for 16 colors 4
        bit)</small></small></font></td>
</tr>
<tr>
    <td width="123" align="right"><font color="#000000"
face="Arial">代码生成方式</font></td>
    <td width="310" align="left"> <font color="#000000" face="Arial">
        <select name="em" size="1" class="pt9">
            <option value="popup">Alert pop-up message</option>
            <option value="doc">Display error line in document</option>
        </select>
        </font></td>
</tr>

```

```

        <tr>
            <td width="123" align="right"><font face="Arial"></font></td>
            <td width="310" align="left"><font color="#000000"
face="Arial">
                <input type="button"
value="生成代码" name="make"
onClick="go()" class="pt9">
                </font></td>
        </tr>
    </table>
</form>
<form method="POST">
    <table border="0" width="431">
        <tr valign="top">
            <td width="425" height="363"> 将如下代码加入 HTML 的<HEAD> 区 :
                <div
align="center">
                    <center>
                        <p><font
color="#000000">
                            <input type="button" value="选择代码"
name="selectbutton"
onClick="document.forms[1].scriptfield.focus();document.forms[1].scriptfield
.select()" class="pt9">
                                <br>
                                <textarea rows="15" name="scriptfield" cols="60"
class="pt9" wrap="VIRTUAL">

```

颜色代码生成器

脚本说明：

第一步:把如下代码加入<head>区域中:

```

<script language=JavaScript1.2>
<!--
var bName=navigator.appName;
var bVer=parseInt(navigator.appVersion);
var NS4=(bName=="Netscape" && bVer >= 4);
var IE4=(bName=="Microsoft Internet Explorer" && bVer >= 4);
var fstr_r;
var fstr_g;
var fstr_b;
var sItem="S";

```

```

function display(id, str){

```

```

if(NS4 || IE4){
  if(NS4){
    with (document[id].document){
      open(); write(str); close();
    }
  }else document.all[id].innerHTML=str;
}else{
  document.fsampl2.startcolor.value=document.GradForm.start.value;
  document.fsampl2.endcolor.value=document.GradForm.end.value;
}
}

```

```

function makeArray(){
  for(i = 0; i<makeArray.arguments.length; i++)
    this[i] = makeArray.arguments[i];
}

```

```

var convert = new
makeArray('0','1','2','3','4','5','6','7','8','9','A','B','C','D','E','F','G','H','I','J','K','L','M','N','O','P','Q','R','S','T','U','V','W','X','Y','Z');

```

```

function returnBase(number,base) {
  eval("var output=parseInt(number)");
  if(isNum(number,base)){
    if(number < base) output = convert[output];
    else{
      var MSD = " + Math.floor(number / base);
      var LSD = number - MSD*base;
      if(MSD > base) output = returnBase(MSD,base) + convert[LSD];
      else output = convert[MSD] + convert[LSD];
    }
  }else{
    output=0;
  }
  return output;
}

```

```

function isNum(no, base){
  var cmp="0123456789";
  var chkStr=no;
  var chkChar;
  var rc=true;
  var nLen;

```

```

if(base == 16){
    cmp+="ABCDEFabcdef";
}else if(base == 10){
    eval("chkStr="+parseInt(chkStr));
}
nLen=chkStr.length;

for(var i=0; i<nLen; i++){
    chkChar=chkStr.substring(i,i+1)
    if(i==0 && chkChar == "#" && base == 16){
    }else if(cmp.indexOf(chkChar)<0){
        rc=false;
    }
    if(rc == false) i=nLen;
}
return rc;
}

function chkNum(obj,base){
    var form=document.GradientForm;
    var rc=true;

    if(base==10){
        eval("rc=form."+obj+".value <= 255");
    }

    if(rc){
        eval("rc=isNum(form."+obj+".value,"+base+"");
        if(!rc){
            alert("输入的数值不正确！");
            eval("form."+obj+".focus()");
        }
    }else{
        alert("输入的数值大于 255！");
        eval("form."+obj+".focus()");
    }
    return rc;
}

function twobyte(no){
    var str=no;

    if(isNum(no,16)){
        str="0"+str;
    }
}

```

```

        str=str.substring((str.length-3)+1);
    }else{
        str="00";
    }
    return str;
}

function CstrLen(cStr){
    var sLen=cStr.length;
    var j=0;
    for(var i=0;i<sLen;i++){
        str=cStr.charAt(i);
        if(NS4 && str.charCodeAt(0)<1){
            i++;
        }
        j++;
    }
    return j;
}

function GradientText(form, color1, color2, color3, gStr, gType){
    var redStep, greenStep, BlueStep;
    var str_r, str_g, str_b, str;

    var gStep=CstrLen(gStr);

    var b1 = color1 % 0x100; if(isNaN(b1)) b1=0;
    var g1 = parseInt(color1 / 0x100) % 0x100; if(isNaN(g1)) g1=0;
    var r1 = parseInt(color1 / 0x10000) % 0x100; if(isNaN(r1)) r1=0;

    var b2 = color2 % 0x100; if(isNaN(b2)) b2=0;
    var g2 = parseInt(color2 / 0x100) % 0x100; if(isNaN(g2)) g2=0;
    var r2 = parseInt(color2 / 0x10000) % 0x100; if(isNaN(r2)) r2=0;

    var cStepAdd = parseInt(256 / gStep);

    if(g1 > g2){
        greenStep = 0;
    }else if(g2 > g1){
        greenStep = 1;
    }else{
        greenStep = 2;
    }
}

```

```

if(r1 > r2){
    redStep = 0;
}else if(r2 > r1){
    redStep = 1;
}else{
    redStep = 2;
}

if(b1 > b2){
    BlueStep = 0;
}else if(b2 > b1){
    BlueStep = 1;
}else{
    BlueStep = 2;
}

var GradStr="";
if(gType == 'S'){
    GradStr+="




```

```

        g1 = g1 + cStepAdd;
        if(g1 > g2) g1 = g2;
    }else if(greenStep==0){
        g1 = g1 - cStepAdd;
        if(g1 < g2) g1 = g2;
    }

    if(BlueStep==1){
        b1 = b1 + cStepAdd;
        if(b1 > b2) b1 = b2;
    }else if(BlueStep==0){
        b1 = b1 - cStepAdd;
        if(b1 < b2) b1 = b2;
    }
}

if(gType == 'S'){
    GradStr+='<br>&nbsp;</TD></TR></TABLE>';
}

return GradStr;
}

function GenTag(form){
    var ss,ee,bb;

    if(!isNum(form.start.value,16)){
        alert("请检查起始颜色数值");
    }else if(!isNum(form.end.value,16)){
        alert("请检查结束颜色数值");
    }else if(!isNum(form.bg.value,16)){
        alert("请检查背景颜色数值");
    }else{
        eval("ss=0x"+form.start.value.substring(1)+");");
        eval("ee=0x"+form.end.value.substring(1)+");");
        eval("bb=form.bg.value");
        form.code.value=GradientText(form,ss,ee,bb,form.showstr.value,"C");
    }
}

function newRGB(type, field2){
    var form=document.GradForm;
    var chkOK=true;
    var vNo;

```



```

if(field2==""){
  if(sItem=="S"){
    chkOK=chkNum('start',16);
  }else if(sItem=="E"){
    chkOK=chkNum('end',16);
  }else if(sItem=="B"){
    chkOK=chkNum('bg',16);
  }
}

if(chkOK){
  if(type==0){
    if(field2 != "") eval("chkOK=isNum(form.rgb_"+field2+".value,10)");
    if(chkOK){
      if(field2 != "") eval("chkOK=chkNum('rgb_"+field2+"',10)");
      if(chkOK){
        fstr_r=twobyte(returnBase(form.rgb_r.value,16));
        fstr_g=twobyte(returnBase(form.rgb_g.value,16));
        fstr_b=twobyte(returnBase(form.rgb_b.value,16));
        if(sItem=="S"){
          form.start.value="#" + fstr_r + fstr_g + fstr_b;
        }else if(sItem=="E"){
          form.end.value="#" + fstr_r + fstr_g + fstr_b;
        }else if(sItem=="B"){
          form.bg.value="#" + fstr_r + fstr_g + fstr_b;
        }
      }
    }else{
      alert("输入的颜色数值不正确。");
      eval("form.rgb_"+field2+".focus()");
    }
  }else{
    if(sItem=="S"){
      fstr_r=form.start.value.substring(1,3);
      fstr_g=form.start.value.substring(3,5);
      fstr_b=form.start.value.substring(5,7);
    }else if(sItem=="E"){
      fstr_r=form.end.value.substring(1,3);
      fstr_g=form.end.value.substring(3,5);
      fstr_b=form.end.value.substring(5,7);
    }else if(sItem=="B"){
      fstr_r=form.bg.value.substring(1,3);
      fstr_g=form.bg.value.substring(3,5);
    }
  }
}

```

```

        fstr_b=form.bg.value.substring(5,7);
    }
    form.rgb_r.value=parseInt(fstr_r,16);
    form.rgb_g.value=parseInt(fstr_g,16);
    form.rgb_b.value=parseInt(fstr_b,16);
}
if(chkOK) AddText();
}
}

```

```

function AddText(){
    var form=document.GradForm;
    var ss,ee,bb;

    eval("ss=0x"+form.start.value.substring(1)+"");
    eval("ee=0x"+form.end.value.substring(1)+"");
    eval("bb=form.bg.value");

    str=GradientText(form,ss,ee,bb,form.showstr.value,"S");
    display("fsample", str);
}

```

```

function setRGB(id,no){
    var form=document.GradForm;
    var nid="rgb_"+id;

    if(id){
        var tmp=eval("parseInt(form."+nid+".value)+parseInt("+no+"")");
        if(tmp<0) tmp=255;
        else if(tmp>255) tmp=0;

        eval("form."+nid+".value="+tmp);
    }
}

```

```

fstr_r=twobyte(returnBase(form.rgb_r.value,16));
fstr_g=twobyte(returnBase(form.rgb_g.value,16));
fstr_b=twobyte(returnBase(form.rgb_b.value,16));

```

```

if(sItem=="S"){
    form.start.value="#" + fstr_r + fstr_g + fstr_b;
} else if(sItem=="E"){
    form.end.value="#" + fstr_r + fstr_g + fstr_b;
} else if(sItem=="B"){
    form.bg.value="#" + fstr_r + fstr_g + fstr_b;
}

```

```

    }

    AddText();
}

function SetColor(clr){
    if(sItem=="S"){
        document.GradForm.start.value="#" +clr;
    }else if(sItem=="E"){
        document.GradForm.end.value="#" +clr;
    }else if(sItem=="B"){
        document.GradForm.bg.value="#" +clr;
    }

    ResetValue();
    AddText();
}

function set(swch){
    if(swch == 1) sItem="S";
    else if (swch == 2) sItem="E";
    else if (swch == 0) sItem="B";
    ResetValue();
}

function ResetValue(){
    var form=document.GradForm;
    var str_r, str_g, str_b;

    if(sItem=="S"){
        str_r=form.start.value.substring(1,3);
        str_g=form.start.value.substring(3,5);
        str_b=form.start.value.substring(5,7);
    }else if(sItem=="E"){
        str_r=form.end.value.substring(1,3);
        str_g=form.end.value.substring(3,5);
        str_b=form.end.value.substring(5,7);
    }else if(sItem=="B"){
        str_r=form.bg.value.substring(1,3);
        str_g=form.bg.value.substring(3,5);
        str_b=form.bg.value.substring(5,7);
    }
    form.rgb_r.value=parseInt(str_r,16);
    form.rgb_g.value=parseInt(str_g,16);
}

```

```

    form.rgb_b.value=parseInt(str_b,16);
}

function nomsg(){
    self.status="";
}

function myReset(){
    AddText();
}

//-->
</script>

```

第二步:把如下代码加入<body>区域中:

```

<form name=GradForm>
<table border=1><tr><td>
    <INPUT type=radio name=setitem value="bg" onClick="set(0)">背景色 <input type=text
name="bg" size=6 value="#FFFFFF" onChange="newRGB(1,)">
    <INPUT type=radio name=setitem value="start" onClick="set(1)" checked>起始色 <input
type=text name="start" size=6 value="#FF0000" onChange="newRGB(1,)">
    <INPUT type=radio name=setitem value="end" onClick="set(2)">结束色 <input type=text
name="end" size=6 value="#0000FF" onChange="newRGB(1,)">
</td></tr>

<tr><td>
<font color="#FF0000"> 红 </font> <input type="Button" value="+"
onClick="setRGB('r',1)"><INPUT type=text name=rgb_r size=3 value=0
onChange="newRGB(0,'r')"><input type="Button" value="-" onClick="setRGB('r',-1)">
    <font color="#009900"> 绿 </font> <input type="Button" value="+"
onClick="setRGB('g',1)"><INPUT type=text name=rgb_g size=3 value=0
onChange="newRGB(0,'g')"><input type="Button" value="-" onClick="setRGB('g',-1)">
    <font color="#0000FF"> 蓝 </font> <input type="Button" value="+"
onClick="setRGB('b',1)"><INPUT type=text name=rgb_b size=3 value=255
onChange="newRGB(0,'b')"><input type="Button" value="-" onClick="setRGB('b',-1)">

</td></tr>

<tr><td>
<TABLE BORDER=1 CELLSPACING=-1 CELLPADDING=1>
<TR>

```



```

onMouseOver="nomsg();return true"> </a></TD>
</TR>
</TABLE>
</td></tr>

<tr><td>
显示文字 : <input type=text name="showstr" value="怀柔网" onChange="AddText()">
</td></tr>

<tr><td>
<input type=hidden name="tempVal" value="">
代码如下 : <br>
<TEXTAREA wrap=soft name=code COLS=62 ROWS=6"></TEXTAREA>
</td></tr><tr><td>
<INPUT TYPE="button" VALUE="生成代码" onClick='GenTag(this.form)'\>
<INPUT TYPE="button" VALUE="预览效果" onClick='AddText()'\>
<INPUT TYPE="reset" VALUE="全部清除">
</td></tr></table>
</form>
</CENTER>
<SPAN ID="fsample" STYLE="position: absolute;left:280;top:460; color: black; font-weight:
normal; font-size: 9pt">
<form name="fsample2">
起始颜色<input type=text name="startcolor" size=8 onfocus="this.blur()"\>
结束颜色<input type=text name="endcolor" size=8 onfocus="this.blur()"\>
</form>
</SPAN>

<SCRIPT LANGUAGE="JavaScript">
<!--
onload = myReset;
//-->
</SCRIPT>

```

分割 Frame的代码

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT language="Javascript">
```

```

var top="<HTML>" + "\r" + "<TITLE>My Frame Page</TITLE>" + "\r" + "<HEAD></HEAD>"
var nf="<noframes>" + "\r" + "You need a frames capable browser to view this page." +
"\r" + "</noframes>" + "\r" + "</HTML>"
var f="</frameset>"
var bc="bordercolor=blue>"

```

```
var MW="marginwidth=0"
var MH="marginheight=0"
```

```
function framesa() {
document.Framer.Fillit.value=top
+ "\r" + "<frameset cols=50%,* "
+ " " + bc + "\r" + "<frame src=1.htm" + " " + "name=One"
+ "\r" + "scrolling=auto" + " " + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + "<frame src=2.htm" + " " + "name=Two"
+ "\r" + "scrolling=auto" + " " + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + f
+ "\r" + nf
}
```

```
function framesb() {
document.Framer.Fillit.value=top
+ "\r" + "<frameset rows=50%,* "
+ " " + bc + "\r" + "<frame src=1.htm" + " " + "name=One"
+ "\r" + "scrolling=auto" + " " + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + "<frame src=2.htm" + " " + "name=Two"
+ "\r" + "scrolling=auto" + " " + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + f
+ "\r" + nf
}
```

```
function framemixa() {
document.Framer.Fillit.value=top
+ "\r" + "<frameset cols=30%,* " + bc + " " + "noresize=yes>"
+ "\r" + "<frame src=1.htm" + " " + "name=One" + " " + "scrolling=yes"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + "<frameset rows=50%,*>"
+ "\r" + "<frame src=2.htm" + " " + "name=Two" + " " + MW
+ "\r" + MH + " " + "scrolling=yes>"
+ "\r" + "<frame src=3.htm" + " " + "name=Three" + " " + "scrolling=no"
+ "\r" + MW + " " + MH + " " + "noresize=no>"
+ "\r" + f
+ "\r" + f
+ "\r" + nf
}
```

```
function frames3v(){
document.Framer.Fillit.value=top
+ "\r" + "<frameset cols=33%,33%,*" + " " + bc
+ "\r" + "<frame src=1.htm name=One" + " " + "scrolling=auto"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + "<frame src=2.htm" + " " + "name=Two" + " " + "scrolling=auto"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
}
```



```

+ "\r" + "<frame src=3.htm" + " " + "name=Three" + " " +
"scrolling=auto"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + f
+ "\r" + nf
}
function frames3h(){
document.Framer.Fillit.value=top
+ "\r" + "<frameset rows=33%,33%,*" + " " + bc
+ "\r" + "<frame src=1.htm name=One" + " " + "scrolling=auto"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + "<frame src=2.htm" + " " + "name=Two" + " " + "scrolling=auto"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + "<frame src=3.htm" + " " + "name=Three" + " " +
"scrolling=auto"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + f
+ "\r" + nf
}
function framemixb() {
document.Framer.Fillit.value=top
+ "\r" + "<frameset cols=30%,* " + bc + " " + "noresize=yes>"
+ "\r" + "<frameset rows=50%,*>" + "\r" + " <frame src=1.htm" + " " +
"name=One"
+ " " + "scrolling=no" + " " + MW + "\r" + MH + " " + "noresize=yes>"
+ "\r" + "<frame src=2.htm" + " " + "name=Two" + " " + MW
+ "\r" + MH + " " + "scrolling=yes>"
+ "\r" + f
+ "\r" + "<frameset rows=50%,*>" + "\r" + "<frame src=3.htm" + " " +
"name=Three"
+ "\r" + "scrolling=no" + " " + MW + " " + MH + " " + "noresize=no>"
+ "\r" + "<frame src=4.htm" + " " + "name=Four" + " " + "scrolling=yes"
+ "\r" + MW + " " + MH + " " + "noresize=yes>"
+ "\r" + f
+ "\r" + f
+ "\r" + nf
}
function Copy(){
if (document.Framer.Fillit.value=="") {
alert ("The top box is empty. Please enter a script by clicking one of the frames buttons.")
}
else {
document.Framer.Pastetext.value=document.Framer.Fillit.value
}
}

```

```

}
function view(){
if (document.Framer.Pastebox.value=="") {
alert ("The paste box is empty. Please enter a script by clicking the Copy/Edit button.")
return false;
}
else {
alert('If you like the results, remember to paste it to a text editor!')
boat = open ("", "DisplayWindow")
see = parent.document.Framer.Pastebox.value
boat.document.write (see)
return true;
}
}
function Instruct(){

help =
open("", "helpWindow", "resizable=yes,location=no,toolbar=no,directories=no,status=no,scrollbars
=yes,menubar=no,width=500,height=250")
help.document.write("<TITLE>Frame Builder Help</TITLE>")
help.document.write("<P><Center><B><FONT
                                SIZE=+0><FONT
COLOR='black'>Instructions</FONT></FONT></B></Center></P>")
help.document.write("<P>1. Load a frame script into the top box by clicking one of the 6 pre built
frame scripts buttons.")
help.document.write("<P>2. Copy the script to the bottom box using the <B>Copy/Edit</B>
button. Edit the script from the bottom box. If a mistake is made, a fresh copy will allways be
available in the top box to compare or to reload.</P>")
help.document.write("<P><B>Editing:</B></P>")
help.document.write("<LI>Make sure to change the frame src=???.htm to YOUR pages and
rename name=?? to suit.</LI>")
help.document.write("<LI>Change the width or height of the frames by changing frameset
Cols/Rows=?%.</LI>")
help.document.write("<LI>Deleting noresize=yes allows movable frames.</LI>")
help.document.write("<LI>Deleting bordercolor defaults to the Netscape grey bars.</LI>")
help.document.write("<LI>Changing bordercolor to border=no hides the bars.</LI>")
help.document.write("<LI>Changing scrolling=??? to auto or yes allows PAGE scrolling.</LI>")
help.document.write("<P>3. When satisfied with your changes in the bottom box, hit
<b>View</b> to see the frames in a new window.</P>")
help.document.write("<P>4. Hit your browser's close option to return to the work window.</P>")
help.document.write("<P>5. When happy with how the frames look and operate, paste the script
to a text editor. <B>Save it as an .htm file.</B></P>")
help.document.write("<P><CENTER><FORM><INPUT
                                TYPE='button'
                                VALUE='OK'
onClick='window.close()'></CENTER></FORM></P>")
help.document.bgColor=('deepskyblue')

```

```

help.document.close()
}
</SCRIPT>
<DT><FORM Name="Framer"></DT>
<TABLE BORDER=1 >
<TR>
<TD>
<DT><INPUT Type=button Value="2 Vertical" onClick="framesa()"></DT>
<DT><INPUT Type=button Value="3 Vertical" onClick="frames3v()"></DT>
<DT><INPUT Type=button Value="2 Horizontal" onClick="framesb()"></DT>
<DT><INPUT Type=button Value="3 Horizontal" onClick="frames3h()"></DT>
<DT><INPUT Type=button Value="3 Mixed" onClick="framemixa()"></DT>
<DT><INPUT Type=button Value="4 Mixed" onClick="framemixb()"></DT>
</TD>
<TD VALIGN=TOP>
<DT><TEXTAREA Name=Fillit COLS="56" ROWS="6"></TEXTAREA></DT>
<CENTER><DT><INPUT
Type=button Value="Instructions"
onClick="Instruct()"></DT></CENTER>
</TD>
</TR>
<TR>
<TD>
<DT><INPUT Type=button Value="Copy/Edit" onClick="Copy()"></DT>
<DT><INPUT Type=button Value="Start Over" onClick="alert('Misfire? No problem, a new copy
will be pasted to the bottom box. Good Luck!');Copy()"></DT>
<DT><INPUT Type=button Value="Clear All" onClick="reset()"></DT>
</TD>
<TD VALIGN=TOP>
<DT><TEXTAREA Name="Pastebox" COLS="56" ROWS="6"></TEXTAREA></DT>
<CENTER><DT><INPUT Type=button Value=" View It! "
onClick="view()"></DT></CENTER>
</TD>
</TR>
</TABLE>
</FORM><P>
</FONT></CENTER>

```

主页制作器

脚本说明：

把如下代码加入区域中：

```
<FORM METHOD="Post" ACTION="">
```

```
<script language = "JavaScript">
```

```
<!--hide this script from old browsers
```

```
document.write('<B>Prompt mode is now working.</B><BR>')
```

```
document.write('<PRE><B>Help status: </B>')
```

```
helpon = false // ...true or false
```

```
document.write('<input type="radio" name="radiohelp" value="true" onClick = " helpon = true"> ON ')
```

```
document.write('<input type="radio" name="radiohelp" value="false" checked onClick = " helpon = false"> OFF <BR>')
```

```
document.write('<B>HTML mode: </B>')
```

```
modeindex = 0 // ...0=simple, 1=sample, 2=prompt
```

```
document.write('<input type="radio" name="radiomode" value="Copyright 1996 Ray Daly"
checked onClick = " modeindex = 0 "> Simple ')
```

```
document.write('<input type="radio" name="radiomode" value="Copyright 1996 Ray Daly"
onClick = " modeindex = 1"> Sample ')
```

```
document.write('<input type="radio" name="radiomode" value="Copyright 1996 Ray Daly"
onClick = " modeindex = 2"> Prompt <BR></PRE>')
```

```
document.write('<TABLE CELLSPACING="0" BORDER="0">')
```

```
document.write('<TR><TH><input type="button" value=" Start "
onClick="HjButton(this.form,jStart)">')
```

```
document.write('<input type="button" value=" End " onClick="HjButton(this.form,jEnd)">')
```

```
document.write('</TH><TH><input type="button" value=" 页 面 显 示 "
onClick="preview(this.form)">')
```

```
document.write('</TH><TH><input type="button" value="保存" onClick="Save(this.form)">')
```

```
document.write('</TH><TH><input type="button" value="关于" onClick="About(this.form)">')
```

```
document.write('</TH></TR><TR><TH><input type="button" value=" B "'  
onClick="HjButton(this.form,jBold)">')
```

```
document.write('<input type="button" value=" I "' onClick="HjButton(this.form,jItalics)">')
```

```
document.write('<input type="button" value=" PRE "' onClick="HjButton(this.form,jPre)"> ')
```

```
document.write('</TH><TH><input type="button" value=" H1 "'  
onClick="HjButton(this.form,jH1)">')
```

```
document.write('<input type="button" value=" H2 "' onClick="HjButton(this.form,jH2)">')
```

```
document.write('<input type="button" value=" H3 "' onClick="HjButton(this.form,jH3)"> ')
```

```
document.write('</TH><TH><input type="button" value=" OL "'
onClick="HjButton(this.form,jOL)">')
```

```
document.write('<input type="button" value=" UL " onClick="HjButton(this.form,jUL)">')
```

```
document.write('<input type="button" value=" LI " onClick="HjButton(this.form,jLI)"> ')
```

```
document.write('</TH><TH><input type="button" value=" DL "'
onClick="HjButton(this.form,jDL)">')
```

```
document.write('<input type="button" value=" DT " onClick="HjButton(this.form,jDT)">')
```

```
document.write('<input type="button" value=" DD " onClick="HjButton(this.form,jDD)"><BR>')
```

```
document.write('</TH></TR><TR><TH><input type="button" value=" P "'
onClick="HjButton(this.form,jPara)">')
```

```
document.write('<input type="button" value=" BR " onClick="HjButton(this.form,jBreak)">')
```

```
document.write('<input type="button" value=" HR " onClick="HjButton(this.form,jRule)">  ')
```

```
document.write('</TH><TH><input type="button" value=" Anchor "
onClick="HjButton(this.form,jAnchor)">  ')
```

```
document.write('</TH><TH><input type="button" value=" L"
onClick="HjButton(this.form,jImageL)">')
```

```
document.write('<input type="button" value=" Image " onClick="HjButton(this.form,jImage)">')
```

```
document.write('<input type="button" value="R" onClick="HjButton(this.form,jImageR)">  ')
```

```
document.write('</TH><TH><input type="button" value=" Center "
onClick="HjButton(this.form,jCenter)">  ')
```

```
document.write('</TH></TR></TABLE>')
```



```
function HjReset (form) { // ...required because RESET does not reset values,  
just GUI
```

```
    helpon = false
```

```
    modeindex = 0
```

```
    form.TEXT.value = ""
```

```
}
```

```
function HTMLtag (buttonname, insertmode, inserttext, tagstart, tagmiddle, tagend, sampletext,  
sampletext2, helptext) {
```

```
    // ...this fuction defines the object HTMLtag
```

```
    this.buttonname = buttonname
```

```
    this.insertmode = insertmode
```

```
// ...1=none 2=standard input 3=lists (UL and OL) 4=DL list 5=anchor
```

```
this.inserttext = inserttext // ...prompt when asking for insert text
```

```
this.tagstart = tagstart
```

```
this.tagmiddle = tagmiddle
```

```
this.tagend = tagend
```

```
this.sampletext = sampletext // ...sample text placed between tags in TextArea
```

```
this.sampletext2= sampletext2
```

```
this.helpertext = helpertext
```

```
}
```

```
jStart = new HTMLtag ( "Start", "2", "Enter the document TITLE", "  
<HTML><HEAD><TITLE>", "", "</TITLE></HEAD><BODY>",
```

"Title of the document (eg. HTMLjive Page)", "",

"Tags for start of document and the TITLE go here. Use the END button when your document is complete.")

```
jEnd = new HTMLtag ( "End", "1", "", " </BODY></HTML>", "", "",
```

"" ,

"This puts in the closing tags when your document is complete.")

```
jBold = new HTMLtag ( "B", "2", "Enter the text to be BOLD", " <B>", "", "</B>",
```

"This will be bold", "",

"The text placed between the and the will be BOLD")

```
jItalics = new HTMLtag ( "I", "2", "Enter the text to be ITALICIZED", " <I>", "", "</I>",
```

"This will be in italics", "",

"The text placed between the <I> and the </I> will be ITALICIZED")

```
jPre = new HTMLtag ( "PRE", "2", "Enter the text to be PREformatted", " <PRE>", "", "</PRE>",
```

"This will be PREformatted", "" ,

"The text placed between the <PRE> and the </PRE> will be PREformatted")

```
jPara = new HTMLtag ( "P", "2", "Enter the text for a PARAGRAPH", " <P>", "", "</P>",
```

"Start of a PARAGRAPH that continues until the start of next PARAGRAPH.", "" ,

"The text placed after the <P> will be a separate PARAGRAPH until the next <P>")

```
jBreak = new HTMLtag ( "BR", "1", "", " <BR>", "", "",
```

"" , "" ,

"This tag forces a line break, start of the next line.")

```
jRule = new HTMLtag ( "HR", "1", "", " <HR>", "", "",
```

"" , "" ,

"This tag puts a (horizontal rule) line on the page.")

```
jH1 = new HTMLtag ( "H1", "2", "Enter the text for the HEADLINE", " <H1>", "", "</H1>",
```

"This will be a top level HEADLINE", "" ,

"The text placed between the <H1> and the </H1> will be the HEADLINE.")

```
jH2 = new HTMLtag ( "H2", "2", "Enter the text for the HEADLINE", " <H2>", "", "</H2>",
```

"This will be a next to top level HEADLINE", "" ,

"The text placed between the <H2> and the </H2> will be the HEADLINE.")

```
jH3 = new HTMLtag ( "H3", "2", "Enter the text for the HEADLINE", " <H3>", "", "</H3>",
```

"This will be a third from top level HEADLINE", "" ,

"The text placed between the <H3> and the </H3> will be the HEADLINE.")

```
jCenter = new HTMLtag ( "Center", "2", "Enter the text to be CENTERED", " <CENTER>", "",
"</CENTER>",
```

```
"This will be a CENTERED", "" ,
```

```
"The text placed between the <CENTER> and the </CENTER> will be the
CENTERED." )
```

```
jOL = new HTMLtag ( "OL", "3", "Enter FIRST item for (Numbered) ORDERED LIST", "
<OL><LI> ", "</LI><LI> ", "</LI></OL>",
```

```
"This is one item in the numbered list", "Next item in the numbered list" ,
```

```
"Create an ORDERED LIST by placing multiple items between <LI> and </LI>" )
```

```
jOL.inserttext2 = "Enter NEXT item for ORDERED LIST"
```

```
jUL = new HTMLtag ( "UL", "3", "Enter FIRST item for (Plain) UNORDERED LIST", "
<UL><LI> ", "</LI><LI> ", "</LI></UL>",
```

```
"This is one item in the plain list", "Next item in the plain list" ,
```

"Create an ORDERED LIST by placing multiple items between and ")

jUL.inserttext2 = "Enter NEXT item for UNORDERED LIST"

jLI = new HTMLtag ("LI", "2", "Enter the text for an item in a LIST", " ", "", "",

"This is an item in a LIST", "" ,

"The text placed between the <L1> and the </L1> will one item in a LIST. Requires
OL or UL.")

jDL = new HTMLtag ("UL", "4", "Enter item for DEFINITION LIST", " <DL><DT>", "</DT>
<DD>", " </DD></DL>",

"Item to be defined", "Definition of the item" ,

"DEFINITION LISTS have two elements: item and definition. Enter the item.")

jDL.inserttext2 = "Enter the definition "

```
jDL.tagmiddle2='</DD> <DT>'
```

```
jDT = new HTMLtag ( "DT", "2", "Enter item for a DEFINITION LIST", " <DT>", "", "</DT>",
```

```
"This is item for a DEFINITION LIST", "" ,
```

```
"The text placed between the <DT> and the </DT> will one item in a LIST. Requires  
DL." )
```

```
jDD = new HTMLtag ( "DD", "2", "Enter definition for a DEFINITION LIST", " <DD>", "",  
"</DD>",
```

```
"This is definition in a DEFINITION LIST", "" ,
```

```
"The text placed between the <DD> and the </DD> will one item in a LIST. Requires  
DL." )
```

```
jImageL = new HTMLtag ("Image", 2, "Enter the URL (e.g., sample.gif)", ' <IMG SRC="' , "" , ""  
ALIGN=LEFT>',
```

```
"URL to graphic (e.g. sample.gif)" , "" ,
```


"Enter the URL for the graphic (e.g., sample.gif) for LEFT alignment")

```
jImage = new HTMLtag ("Image", 2, "Enter the URL (e.g., sample.gif)", ' <IMG SRC="' , "" , "'>',
```

"URL to graphic (e.g. sample.gif)" , "" ,

"Enter the URL for the graphic (e.g., sample.gif)")

```
jImageR = new HTMLtag ("Image", 2, "Enter the URL (e.g., sample.gif)", ' <IMG SRC="' , "" , "'  
ALIGN=RIGHT>',
```

"URL to graphic (e.g. sample.gif)" , "" ,

"Enter the URL for the graphic (e.g., sample.gif) for RIGHT alignment")

```
jAnchor = new HTMLtag ("Anchor", 5, "Enter the URL (e.g., http://www.yahoo.com)", ' <A  
HREF="' , "">', '</A>',
```

"http://www.yahoo.com", "Yahoo (description here)",

"Enter the URL (e.g., http://www.yahoo.com/index.html) followed by the description.")

```
jAnchor.inserttext2 = "Enter description (e.g., Yahoo)"
```

```
function About (form) {
```

```
    alert('怀柔网 panda http://www.hrw.cn')
```

```
}
```

```
function Save (form) {
```

```
    alert('No SAVE function is available. You must "cut & paste" your document into  
another application.')
```

```
}
```

```
function HjButton (form,selection) { // ...all HTML button call this routine
```

```
    if (helpon) {
```

```
        if (confirm(selection.helptext)){
```

```
            addHTML (form,selection)
```

```
        }  
  
    }else{  
  
        addHTML (form,selection)  
  
    }  
  
}
```

```
function addHTML (form,selection) {  
  
    // ...add text to value of TextArea  
  
    cancel = false  
  
    addText=selection.tagstart  
  
    if (modeindex==2) {        // ...insert mode
```

```
if (selection.insertmode != 1 ) {      // ...if none, skip it all
```

```
    addText += addHTMLinsert (selection, addText, form)
```

```
    if (addText == selection.tagstart) {
```

```
        cancel = true
```

```
    }
```

```
    }
```

```
    }
```

```
if (modeindex==1) {      // ...sample mode
```

```
    addText = addText + selection.sampletext + selection.tagmiddle +  
selection.sampletext2
```

```
    }
```

```
if (modeindex==0) { // ...simple mode

    addText += selection.tagmiddle

}

addText += selection.tagend

if (cancel == false) { // ...put text into TextArea unless canceled

    form.TEXT.value += addText

}

}
```

```
function addHTMLinsert (selection, addText, form) {
```

```
    // ...insert mode
```

```
// ...addText ahead as .tagstart, cancel=false

// ...insertmodes 1=none, 2=insert, 3=lists (UL and OL), 4=DL list, 5=anchor

if (selection.insertmode ==2) {           // ...simple insert (eg.<B>...</B>)

    i = ""

    i = prompt (selection.inserttext, "")

    if ((i != null) && (i != "")) {           // ...if input add

        addText = i

    }else{

        addText = ""

    }

}
```

```
if (selection.insertmode == 3) {           // ...UL and OL lists

    addText = ""

    i = ""

    i = prompt (selection.inserttext, "")

    if ((i != null) && (i != "")) {

        addText = i

        while ((i != null) && (i != "")) {           // ...get next until null

            i=prompt (selection.inserttext2, "")

            if ((i != null) && (i != "")) {

                addText=addText + selection.tagmiddle + i

            }

        }

    }

}
```

```
        }

    }

}

if (selection.insertmode == 4) { // ...DL list

    i= "dummy"

    j = i

    addText = ""

    count = 0

    while ((i != null) && (i != "") && (j != null) && (j != "")) { // ...get next
until null

        ++count

        i = ""
```



```
i = prompt (selection.inserttext, "")

// ... used for debugging form.TEXT.value += "-->" + i + "<--"

if ((i != null) && (i != "")) {

    j = ""

    j=prompt (selection.inserttext2, "")

    if ((j != null) && (j != "")) {

        if (count > 1){

            addText += selection.tagmiddle2

        }

        addText=addText +i + selection.tagmiddle + j

    }

}
```

```
        }  
  
    }  
  
}  
  
if (selection.insertmode == 5) {           // ...Anchor  
  
    addText = ""  
  
    i = ""  
  
    i = prompt (selection.inserttext, "")  
  
    // ... used for debugging form.TEXT.value += "-->" + i + "<--"  
  
    if ((i != null) && (i != "")) {  
  
        j = ""  
  
        j=prompt (selection.inserttext2, "")
```

```
        if ((j != null) && (j != "")) {

            addText=i + selection.tagmiddle + j

        }

    }

}

return addText

}

function preview(form) {

    msg=open("", "DisplayWindow", "toolbar=no,directories=no,menubar=yes");

    msg.document.write(form.TEXT.value);

}
```

```
<!-- done hiding from old browsers -->
```

```
</script>
```

```
<b>HTMLjive Document:</b><br>
```

```
<TEXTAREA NAME="TEXT" ROWS="16" COLS="75" WRAP="VIRTUAL"></TEXTAREA>
```

```
<INPUT TYPE="reset" VALUE= "Erase and Restart Document" onClick="HjReset(this.form)">
```

```
</FORM>
```

综合类

加密源代码脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language=javascript>
```

```
<!--
```

```
var Words;
```

```
function SetWords(word)
```

```
{
```

```
    Words = escape(word.value);
```

```
}
```

```

function SetNewWords(form)
{
    var NewWords;
    NewWords = Words
    form.NewWords.value = NewWords;
}

//-->
</SCRIPT>

```

第二步:把如下代码加入<body>区域中

```

<FORM METHOD="POST">
    <div align="center">
        <div align="center">
            <font color="#0066FF">加密页面源代码脚本</font></div>
            <p>将你的页面源代码粘贴在下面的框内,要包括所有的标签例如 html , head, body 等。
        </p>
        </div>
        <P align="center">
            <TEXTAREA NAME="Word" VALUE="" ROWS=7 COLS=50
ONCHANGE="SetWords(this)">
        </TEXTAREA>

        <P align="center">
            <INPUT TYPE=BUTTON ONCLICK="SetNewWords(this.form)"
VALUE="开始转换">

        <P align="center">
            <TEXTAREA NAME="NewWords" VALUE="" ROWS=7 COLS=50>
        </TEXTAREA>

```

</FORM><p align="center"> 以上是转换好的代码,将他们加入如下脚本的引号""区内,就是加密后的 HTML 了!

```

<p>
<font face="Arial, Helvetica, sans-serif"><b><HTML><br>
    <HEAD><br>
    <SCRIPT LANGUAGE="Javascript"><br>
    <!--<br>
    var Words =<font color=red>" " </font>//put your cripto code there<br>
    function SetNewWords()<br>
    {<br>
    var NewWords;<br>

```

```

NewWords = unescape(Words);<br>
document.write(NewWords);<br>
} <br>
SetNewWords();<br>
// --><br>
</SCRIPT><br>
</HEAD><br>
<BODY><br>
</BODY><br>
</HTML></b></font>

```

访问时间限制脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```

<SCRIPT language="JavaScript">
<!--
var limit="0:59"
if (document.images){
var parselimit=limit.split(":")
parselimit=parselimit[0]*60+parselimit[1]*1
}
function begintimer(){
if (!document.images)
return
if (parselimit==1)
//下面是限制时间到了后去的连接页面,自己修改。
window.location="zh1.htm"
else{
parselimit-=1
curmin=Math.floor(parselimit/60)
cursec=parselimit
if (curmin!=0)
curtime="你只有"+curmin+"分"+cursec+"秒的时间保存此页。"
else
curtime="你只有"+cursec+"秒的时间访问此页。"
setTimeout("begintimer()",1000)
//下一句告诉访问者剩余的时间,在文本框中显示,不想要去掉即可。
document.lefttime.left.value=curtime
//下一句告诉访问者剩余的时间,在状态栏中显示。
window.status=curtime
}
}
//-->
</SCRIPT>

```

第二步:把<body>区域改为

```
<body bgcolor="#ffffff" onload="begintimer()">
```

给页面加一个 '热键' 脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
<!--
var hotkey=97
var destination="zh1.htm"
if (document.layers)
document.captureEvents(Event.KEYPRESS)
function backhome(e){
if (document.layers){
if (e.which==hotkey)
window.location=destination
}
else if (document.all){
if (event.keyCode==hotkey)
window.location=destination
}
}
document.onkeypress=backhome
//-->

</SCRIPT>
```

第二步:把<body>区域改为

```
<body bgcolor="#ffffff" onload="begintimer()">
```

浏览器毁灭者 - 请小心使用

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="JavaScript">

<!--hide--

function pop(){
```

```
    for(i=1;i<=3;i++){
```

```
window.open('icq.htm','width=400,height=460','status=off','location=off','toolbar=off','scrollbars=off')}]}
```

```
//--->  
</script>
```

第二步:把如下代码加入<body>区域中

```
<form name="form">  
  <p>  
    <input type="button" value="测试:一点击就打开 3 个 60*60 的小窗口" onClick="pop()" name="button" class="unnamed1">  
  </p>  
</form>
```

文本中首字母全改为大写

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">  
<!-- Begin  
function changeCase(frmObj) {  
var index;  
var tmpStr;  
var tmpChar;  
var preString;  
var postString;  
var strLen;  
tmpStr = frmObj.value.toLowerCase();  
strLen = tmpStr.length;  
if (strLen > 0) {  
for (index = 0; index < strLen; index++) {  
if (index == 0) {  
tmpChar = tmpStr.substring(0,1).toUpperCase();  
postString = tmpStr.substring(1,strLen);  
tmpStr = tmpChar + postString;  
}  
else {  
tmpChar = tmpStr.substring(index, index+1);  
if (tmpChar == " " && index < (strLen-1)) {  
tmpChar = tmpStr.substring(index+1, index+2).toUpperCase();  
preString = tmpStr.substring(0, index+1);  
postString = tmpStr.substring(index+2,strLen);
```



```

tmpStr = preString + tmpChar + postString;
    }
    }
}
frmObj.value = tmpStr;
}
// End -->
</script>

```

第二步:把如下代码加入<body>区域中

```

<form name=form>
<input type=text name=box value="type in here!">
<input type=button value="Convert" onClick="javascript:changeCase(this.form.box)">
</form>

```

查看某网址的源代码

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT>
function add()
{
var ress=document.forms[0].luxiaoqing.value
window.location="view-source:"+ress;
}
</SCRIPT>

```

输入要查看源代码的 URL 地址:

```

<FORM><input type="text" name="luxiaoqing" size=40 value="http://"></FORM>
<FORM><br>
<INPUT type="button" value="查看源代码" onClick=add()>
</FORM>

```

综合的搜索引擎

脚本说明:

把如下代码加入<body>区域中

```

<form Name="InputForm">
<div align="center"><center><p><script language="JavaScript">
var FirstForm;
function StartSearch()
{
document.forms[FirstForm+document.InputForm.SearchSelect.
selectedIndex].elements[0].value=document.InputForm.SearchWords.value;

```

```

document.forms[FirstForm+document.InputForm.SearchSelect.
selectedIndex].submit();
}
</script><span style="font-size: 9pt">查找内容:</span><input name="SearchWords" type="text"
size="21" style=" margin-left: 1px"><br>
<span style="font-size: 9pt"> 搜索引擎 :</span><select Name="SearchSelect" size="1"
style="background-color: rgb(0,0,0); color: rgb(255,255,0)">
<option selected>Yahoo </option>
<option>InfoSeek </option>
<option>altavista</option>
<option value="Magellan">Magellan</option>
<option value="Point ">Point </option>
<option value="中文 YAHOO">中文 YAHOO</option>
<option value="全球 FTP 资源搜索系统">全球 FTP 资源搜索系统</option>
<option value="全球游戏资源搜索系统">全球游戏资源搜索系统</option>
<option>Yeah 中文搜索</option>
<option>Cseek 中文搜索</option>
<option value="台湾绿世界中文搜索">台湾绿世界中文搜索</option>
<option value="台湾番薯藤">台湾番薯藤</option>
<option value="东方网景">东方网景</option>
</select><br>
<input type="button" value=" 开始查找 " onClick="StartSearch()"> <script
language="JavaScript">
FirstForm=document.forms.length
</script></p>
</center></div>
</form>
<form action="http://search.yahoo.com/bin/search" method="get">
<input type="hidden" name="p" value>
</form>
<form METHOD="GET" ACTION="http://www3.infoseek.com/Titles">
<input type="hidden" name="qt" value><input type="hidden" name="col" value="WW"><input
type="hidden" name="sv" value="IS"><input type="hidden" name="lk"
value="noframes"><input type="hidden" name="nh" value="10">
</form>
<form action="http://www.altavista.digital.com/cgi-bin/query?pg=q&what=web&q=">
<input type="hidden" name="q" value>
</form>
<form action="http://www.mckinley.com/searcher.cgi?query=">
<input type="hidden" name="query" value>
</form>
<form action="http://point.lycos.com/cgi-bin/pursuit?query=">
<input type="hidden" name="query" value>
</form>

```

```
<form action="http://search.chinese.yahoo.com/search/gb" method="get">
<input type="hidden" name="p" value>
</form>
<form action="http://ftpsearch.unit.no/ftpsearch">
<input type="hidden" name="query" value>
</form>
<form action="http://www.gamesdomain.com/cgi-bin/wwwwais">
<input type="hidden" name="keywords" value>
</form>
<form action="http://www.yeah.net/cgi-bin/search/search.cgi">
<input type="hidden" name="key" value>
</form>
<form action="http://www.cseek.com/homepage/cgi/srchengine.cgi">
<input type="hidden" name="searchkey" value>
</form>
<form action="http://greenworld.com.tw/explorer/search.pl?Keywords=">
<input type="hidden" name="Keywords" value>
</form>
<form action="http://search.yam.org.tw/b5/search/">
<input type="hidden" name="k" value>
</form>
<form action="http://www.orinet.cn.net/cgi-bin/yang/addlinks/searchlink.pl">
<input type="hidden" name="keywords" value>
</form>
```

搜索引擎登记

<center>

脚本说明:

```
<form name="choose" Action="javascript:Simpleall(document.choose) //">
  <table border="0" cellSpacing="2" cellpadding="2" align="center">
    <tr>
      <td>站点名称</td>
      <td><input maxLength="35" name="title" size="31"></td>
    </tr>
    <tr>
      <td>站点 URL</td>
      <td><input maxLength="58" name="http" size="31" value="http://"></td>
    </tr>
    <tr>
      <td>简要描述</td>
      <td><textarea cols="30" name="comm" rows="4" wrap="virtual"></textarea></td>
    </tr>
    <tr>
      <td>关键词</td>
```

```

        <td><input maxLength="58" name="keyw" size="31"></td>
</tr>
<tr>
    <td>用户名</td>
    <td><input maxLength="20" name="name" size="31"></td>
</tr>
<tr>
    <td>E-mail</td>
    <td><input maxLength="58" name="email" size="31"></td>
</tr>
<tr>
    <td bgcolor="#FFFFFF">密码</td>
    <td bgcolor="#FFFFFF"><input maxLength="10" name="passwd" type="password" value
size="31"></td>
</tr>
<tr>
    <td colspan="2" bgcolor="#FFFFFF"><input checked name="modify" type="radio"
value="no">
        新站加注 <input name="modify" type="radio" value="yes"> 修改已加注信息</td>
</tr>
<tr>
    <td colspan="2" bgcolor="#FFFFFF"><hr size="1">
</td>
</tr>
<tr>
    <td colspan="2" bgcolor="#FFFFFF"><table border="0">
        <tr valign="top" bgColor="#8edaad">
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.yahoo.com/info/suggest/">Yahoo</a> </td>
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.mckinley.com/magellan/Info/addsite.html">Magellan</a> </td>
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.linkmonster.com/contest.html">Linkmonst</a> </td>
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.aol.com/netfind/info/addurl.html">AOL find</a> </td>
        </tr>
        <tr bgColor="#8edaad">
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.newhoo.com/add.html">Newhoo</a> </td>
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.scrubtheweb.com/addurl.html">Scrubthe</a> </td>
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.whatsnew.com/whatsnew/submit">Whatsnew</a> </td>
            <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a

```

```
href="http://rex.skyline.net/add/">Rexsky</a> </td>
</tr>
<tr bgColor="#cdc191">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.profind.com/">Profind</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.altavista.digital.com/av/content/addurl.htm">Alta Vista</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.nlsearch.com/docs/register.htm">Nlsearch</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.lycos.com/addasite.html">Lycos</a> </td>
</tr>
<tr bgColor="#cdc191">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.excite.com/Info/add_url.html">Excite</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.hotbot.com/addurl.html">Hotbot</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://index.opentext.com/main/submitURL.html">Opentext</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.linkstar.com/linkstar/bin/doform?form=ecard">Linkstar</a> </td>
</tr>
<tr bgColor="#cdc191">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.surfgoopher.com/addurl.htm">Surfgoopher</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.northernlight.com/docs/register.htm">Northernl</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.webcrawler.com/Help/GetListed/AddURLS.html">Webcrawler</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://guide-p.infoseek.com/AddUrl?pg=DCaddurl.html">InfoSeek</a> </td>
</tr>
<tr bgColor="#cdc191">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.stpt.com/general/submit.html">STPT</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.searchking.com/add_url.htm">SearchKing</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.jayde.com/cgi-bin/addurl.cgi">Jayde</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://in-142.infospace.com/_1_7815569__info/submit.htm">Infospace</a>
</td>
</tr>
```

```
<tr bgColor="#8edaad">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.infohiway.com/isn/addurl.shtml">Infohiway</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.cozycabin.com/add.htm">Cozycabin</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.dewa.com/submit/sub-universal.shtml">Dewa</a></td>
</td><input name="check" type="checkbox" value="ON"><a
  href="http://www.web-search.com/faq.html">Websearch</a> </td>
</tr>
</table>
</td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
  href="http://www.web-search.com/faq.html">Websearch</a> </td>
</tr>
<tr bgColor="#8edaad">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.fathead.net/search/addsite.html">Fathead</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.yehaa.com/addurl.shtml">Yehaa</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.whatuseek.com/addurl.htm">Whatuseek</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.findlink.com/searchit/s-addurl.cgi">Findlink</a> </td>
</tr>
<tr bgColor="#8edaad">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://personalweb.net/search/add.html">Personalweb</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.iexplorer.com/submiturl.asp">Iexplorer</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.psychcrawler.com/plweb/pcsubmit.html">Psychcrawler</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.411locate.com/join.htm">411locate</a> </td>
</tr>
<tr bgColor="#8edaad">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.looksmart.com/r?notnew">Looksmart</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://www.mcp.com/directories/yppsubmit.html">Yellowpage</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://astalavista.box.sk/add.html">Astalavista</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
    href="http://addsite.euroseek.net/page.cfm?page=start&ifl=uk">Euroseek</a> </td>
```

```
</tr>
<tr bgColor="#8edaad">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://galaxy.einet.net/cgi-bin/annotate">Galaxy</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.lexiconn.com/dir/addurl.cgi">Lexiconn</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://homepages.whowhere.com/bin/showpage.pl?add">Whowhere</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"> <a
href="http://www.register-it.com/scripts_clean/states/router.cgi?banner=metacrawler&istate=start
&pflg=1&status=+++New+User+++">MetaCrawler</a></td>
</tr>
<tr bgColor="#8edaad">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://cmtgroup.com/links/addurl.html">cMT</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.powercrawler.com/add.htm">PowerCrawler</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://home.snap.com/directory/submiturl/0,158,home-3,00.html">Snap</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.nerdworld.com/cgi-bin/nwadd.cgi">Nerdworld</a> </td>
</tr>
<tr bgColor="#cdc191">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://gbchinese.yahoo.com/docs/info/suggest.html">GB Yahoo</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.whatsite.com/main/add_url.htm">Whatsite</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://pccms.pku.edu.cn:8000/addurl.htm">天网</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.goyoyo.com.cn/bj/serv/urlgb.htm">Goyoyo_GB</a> </td>
</tr>
<tr bgColor="#cdc191">
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://cgi.chinabyte.com/cgi-bin/webdriver?MIval=searchjoin">Chinabyte</a>
</td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.c3s.org.sg:80/template/urladd.BackCSite.html">华页指南</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.searchchina.com/cgi-bin/chsearch?page=form">中文查寻</a> </td>
  <td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.cnnic.net.cn:802/cregister.html">若比邻</a> </td>
</tr>
<tr bgColor="#bcbcbc">
```

```

<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.beijixing.com.cn/register.htm">北极星</a> </td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://newtoo.manifest.com/submit.html">Newtoo</a> </td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://matilda.aaa.com.au/dir2/add.shtml">AAA</a> </td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.yeah.net/addurl.html">网易</a> </td>
</tr>
<tr bgcolor="#bcbcbc">
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.chinaok.com/add_db.htm">华好网景</a></td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.search.com.cn/addurl/url.htm">网现引擎</a> </td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.richsurf.com/richsurf/url_add.htm">四通</a> </td>
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.chinavista.com/hyper-c/chadd.html">中国指南</a> </td>
</tr>
<tr bgcolor="#bcbcbc">
<td bgcolor="#FFFFFF"><input name="check" type="checkbox" value="ON"><a
href="http://www.sohoo.com.cn/cgi-bin/sohoo/regform.pl">搜狐</a> </td>
</tr>
</table>
<table align="center">
<tr>
<td width="422" height="32" bgcolor="#FFFFFF">
<div align="center"><center><p><input
name="send" type="submit" value=" 递 交 " class="buttonface"> </div></td>
</tr>
</table>
</form>

```

下载记时器脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language="JavaScript">
```

```
<!--
```

```

function MakeArray(n) {
this.length = n;
for (var i = 1; i <= n; i++) {
this[i] = 0 }
return this
}

```



```

speedVar = new MakeArray(11);
speedVar[1] = "1.1719"
speedVar[2] = "1.7578"
speedVar[3] = "3.5156"
speedVar[4] = "4.1016"
speedVar[5] = "6.8359"
speedVar[6] = "7.8125"
speedVar[7] = "16.6250"
speedVar[8] = "187.9883"
speedVar[9] = "1220.7031"
speedVar[10] = "3295.8984"
speedVar[11] = "5493.1641"
speedVar[12] = "18920.8984"
function compute(form, mult){
for (i=1; i < 13; i++){
if (form.size.value==null||form.size.value.length==0){
form.size.value=0;}
if (form[i+"hour"].value==null||form[i+"hour"].value.length==0){
form[i+"hour"].value=0;}
if (form[i+"minute"].value==null||form[i+"minute"].value.length==0){
form[i+"minute"].value=0;}
if (form[i+"second"].value==null||form[i+"second"].value.length==0){
form[i+"second"].value=0;}
if (mult != 0 && form.size.value != 0){
with (Math){
var speed = speedVar[i];
var TotalTime = ((form.size.value*mult)/speed);
var TotalHours = floor((TotalTime/3600));
var TotalHoursMod = (TotalTime%3600);
var TotalMin = floor(TotalHoursMod/60);
var TotalMinMod = (TotalHoursMod%60);
var TotalSec = floor(TotalMinMod);
form[i+"hour"].value=TotalHours;
form[i+"minute"].value=TotalMin;
form[i+"second"].value=TotalSec;
}
}
}
return;
}
//-->

```

</SCRIPT>

第二步:把如下代码加入<body>区域中

```
<form METHOD="POST" name="s">

  <input type="hidden" name="8hour" value>
  <input type="hidden" name="8minute" value>
  <input type="hidden" name="8second" value>
  <input type="hidden" name="9hour" value>
  <input type="hidden" name="9minute" value>
  <input type="hidden" name="9second" value>
  <input type="hidden" name="10hour" value>
  <input type="hidden" name="10minute" value>
  <input type="hidden" name="10second" value>
  <input type="hidden" name="11hour" value>
  <input type="hidden" name="11minute" value>
  <input type="hidden" name="11second" value>
  <input type="hidden" name="12hour" value>
  <input type="hidden" name="12minute" value>
  <input type="hidden" name="12second" value>
  <div align="center"><center>
    <table BORDER="4">
      <tr>
        <td>文件大小
        <input TYPE="TEXT" NAME="size" SIZE="10">
          <input TYPE="BUTTON"
            OnClick="compute(this.form, 1)" VALUE="KB">
          <input TYPE="BUTTON"
            OnClick="compute(this.form, 1024)" VALUE="MB">
        </td>
        <script language="JavaScript">
<!--
document.s.size.focus();

// -->
</script>
          <td colspan="3">
            <div align="center">
              <center>
                需要下载时间(理想值)
              </center>
            </div>
          </td>
        </tr>
      </table>
    </div>
  </center>
</div>
```

```
<tr align="center">
  <td>调制解调器速率...</td>
  <td>小时</td>
  <td>分钟</td>
  <td>秒</td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFFFFF">9.6 Kb</td>
  <td>
    <input TYPE="TEXT" NAME="1hour" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="1minute" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="1second" SIZE="6">
  </td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFFFFF">14.4 Kb</td>
  <td>
    <input TYPE="TEXT" NAME="2hour" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="2minute" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="2second" SIZE="6">
  </td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFFFFF">28.8 Kb</td>
  <td>
    <input TYPE="TEXT" NAME="3hour" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="3minute" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="3second" SIZE="6">
  </td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFffff">33.6K</td>
```

```
<td>
  <input type="TEXT" name="4hour" size="6">
</td>
<td>
  <input type="TEXT" name="4minute" size="6">
</td>
<td>
  <input type="TEXT" name="4second" size="6">
</td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFCCCC">56 Kb</td>
  <td>
    <input TYPE="TEXT" NAME="5hour" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="5minute" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="5second" SIZE="6">
  </td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFFFFF">ISDN (64 Kb)</td>
  <td>
    <input TYPE="TEXT" NAME="6hour" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="6minute" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="6second" SIZE="6">
  </td>
</tr>
<tr align="center">
  <td BGCOLOR="#FFFFFF">ISDN (128 Kb)</td>
  <td>
    <input TYPE="TEXT" NAME="7hour" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="7minute" SIZE="6">
  </td>
  <td>
    <input TYPE="TEXT" NAME="7second" SIZE="6">
  </td>
```

```
</td>
</tr>
</table>
</center></div>
</form>
```

随机播放背景音乐

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT language="JavaScript">
<!--
var sound1="song1.mid"
var sound2="song2.mid"
var sound3="song3.mid"
var sound4="song4.mid"
var sound5="song5.mid"
var sound6="song6.mid"
var sound7="song7.mid"
var sound8="song8.mid"
var sound9="song9.mid"
var sound10="song10.mid"
var x=Math.round(Math.random()*9)
if (x==0) x=sound1
else if (x==1) x=sound2
else if (x==2) x=sound3
else if (x==3) x=sound4
else if (x==4) x=sound5
else if (x==5) x=sound6
else if (x==6) x=sound7
else if (x==7) x=sound8
else if (x==8) x=sound9
else x=sound10
if (navigator.appName=="Microsoft Internet Explorer")
document.write('<bgsound src='+x+'.mid' loop="infinite">')
else
document.write('<embed src='+x+'.mid' hidden="true" border="0" width="20" height="20"
autostart="true" loop="true">')

//-->

</SCRIPT>
```

随日期播放音乐

脚本说明:

把如下代码加入<head>区域中

```
<table border=5 bordercolor=blue borderlight=green>
<tr><td align=center><font size=5 color=red face="Arial, Helvetica, sans-serif"><strong>跟据日期能听到不同的音乐 !</strong></font></td></tr><tr><td align=center><SCRIPT language="JavaScript">
<!--
page=new Date();
if (page.getDate() == 1)
document.write("<bgsound src=song1.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 2)
document.write("<bgsound src=song2.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 3)
document.write("<bgsound src=song3.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 4)
document.write("<bgsound src=song4.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 5)
document.write("<bgsound src=song5.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 6)
document.write("<bgsound src=song6.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 7)
document.write("<bgsound src=song7.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 8)
document.write("<bgsound src=song8.mid width=145 height=30 autostart=true loop=-1 volume=50>");

if (page.getDate() == 9)
document.write("<bgsound src=song9.mid width=145 height=30 autostart=true loop=-1 volume=50>");
```

```
volume=50>");
```

```
if (page.getDate() == 10)
```

```
document.write("<bgsound src=song10.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 11)
```

```
document.write("<bgsound src=song1.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 12)
```

```
document.write("<bgsound src=song2.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 13)
```

```
document.write("<bgsound src=song3.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 14)
```

```
document.write("<bgsound src=song4.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 15)
```

```
document.write("<bgsound src=song5.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 16)
```

```
document.write("<bgsound src=song6.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 17)
```

```
document.write("<bgsound src=song7.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 18)
```

```
document.write("<bgsound src=song8.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 19)
```

```
document.write("<bgsound src=song9.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 20)
```

```
document.write("<bgsound src=song10.mid width=145 height=30 autostart=true loop=-1
```

```
volume=50>");
```

```
if (page.getDate() == 21)
```

```
document.write("<bgsound src=song1.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 22)
```

```
document.write("<bgsound src=song2.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 23)
```

```
document.write("<bgsound src=song3.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 24)
```

```
document.write("<bgsound src=song4.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 25)
```

```
document.write("<bgsound src=song5.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 26)
```

```
document.write("<bgsound src=song6.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 27)
```

```
document.write("<bgsound src=song7.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 28)
```

```
document.write("<bgsound src=song8.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 29)
```

```
document.write("<bgsound src=song9.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 30)
```

```
document.write("<bgsound src=song10.mid width=145 height=30 autostart=true loop=-1  
volume=50>");
```

```
if (page.getDate() == 31)
```

```
document.write("<bgsound src=song1.mid width=145 height=30 autostart=true loop=-1
```



```

volume=50>");
page=new Date();
var months = new Array(13);
months[1] = "1 月";
months[2] = "2 月";
months[3] = "3 月";
months[4] = "4 月";
months[5] = "5 月";
months[6] = "6 月";
months[7] = "7 月";
months[8] = "8 月";
months[9] = "9 月";
months[10] = "10 月";
months[11] = "11 月";
months[12] = "12 月";

var dateObj = new Date()
var lmonth = months[dateObj.getMonth() + 1]
var date = dateObj.getDate()

document.write("<br>" + "今天是:" + lmonth + date + "日" + "播放 007 主题曲")

<!-->

</SCRIPT></td></tr>
</table>

```

E-mail 表单递交

脚本说明:

把如下代码加入<body>区域中

```

<script language="JavaScript">
<!--
function validate_form() {
    validity = true;
    if (!check_empty(document.form.NAME.value))
        { validity = false; alert('对不起!请你填入你的姓名。'); }
    if (!check_email(document.form.EMAIL.value))
        { validity = false; alert('对不起!请重新正确填入 Email 地址。'); }
    if (!check_empty(document.form.DESCRPTION.value))
        { validity = false; alert('对不起!请你在"简要描述"留言填入留言。'); }
    if (validity)
        alert ("                谢谢你的来信。")
}

```

```

+ "                你所填的信息将以 Email 形式发送给我 ,
"
+ "                假如你认为本站内容不错的话 , 请将本
"
+ "                介绍给你的朋友 , 希望大家经常光顾本站。");
return validity;
}

function check_empty(text) {
return (text.length > 0);
}

function check_email(address) {
if ((address == "")
|| (address.indexOf('@') == -1)
|| (address.indexOf('.') == -1))
return false;
return true;
}

// -->
</script>
<form name="form" method="post" action="mailto:xiaoqinglu@263.net?SUBJECT=网友的留言
"
enctype="text/plain" onSubmit="return validate_form()">





```

```
<td>
  <div align="center"><br>
    <input type="submit" name="submit" value="发送">
    <input type="reset" value="清除" name="reset">
  </div>
</td>
</tr>
</table>
</form>
```

JavaScript 容错脚本

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Hide
```

```
function killErrors() {
return true;
}
```

```
window.onerror = killErrors;
```

```
// -->
```

```
</SCRIPT>
```

计算器 (一)

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!-- Hide the script from old browsers --
```

```
function compute(obj)
  {obj.expr.value = eval(obj.expr.value)}
var one = '1'
var two = '2'
var three = '3'
var four = '4'
var five = '5'
var six = '6'
var seven = '7'
var eight = '8'
var nine = '9'
var zero = '0'
var plus = '+'
var minus = '-'
```

```

var multiply = '*'
var divide = '/'
var decimal = '.'
function enter(obj, string)
    {obj.expr.value += string}
function clear(obj)
    {obj.expr.value = ""}
// --End Hiding Here -->
</script>
<form name="calc">
<table border=1>
<td colspan=4><input type="text" name="expr" size=30 action="compute(this.form)"> <tr>
<td><input type="button" value=" 7 " onClick="enter(this.form, seven)">
<td><input type="button" value=" 8 " onClick="enter(this.form, eight)">
<td><input type="button" value=" 9 " onClick="enter(this.form, nine)">
<td><input type="button" value=" / " onClick="enter(this.form, divide)">
<tr><td><input type="button" value=" 4 " onClick="enter(this.form, four)">
<td><input type="button" value=" 5 " onClick="enter(this.form, five)">
<td><input type="button" value=" 6 " onClick="enter(this.form, six)">
<td><input type="button" value=" * " onClick="enter(this.form, multiply)">
<tr><td><input type="button" value=" 1 " onClick="enter(this.form, one)">
<td><input type="button" value=" 2 " onClick="enter(this.form, two)">
<td><input type="button" value=" 3 " onClick="enter(this.form, three)">
<td><input type="button" value=" - " onClick="enter(this.form, minus)">
<tr><td colspan=2><input type="button" value=" 0 " onClick="enter(this.form,
zero)">
<td><input type="button" value=" . " onClick="enter(this.form, decimal)">
<td><input type="button" value=" + " onClick="enter(this.form, plus)">
<tr><td colspan=2><input type="button" value=" = " onClick="compute(this.form)">
<td colspan=2><input type="button" value="AC" size= 3 onClick="clear(this.form)"> </table>
</form>

```

计算器 (二)

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!--
```

```

function equal() {
    a = document.form1.aa.value;
    b = document.form1.ab.value;
    c = a-b;
    document.form1.total1.value = c

```

```

    }
function equa2() {
    a = document.form1.ba.value;
    b = document.form1.bb.value;
    c = (a*1)+(b*1);
    document.form1.total2.value = c
}
function equa3() {
    a = document.form1.ca.value;
    b = document.form1.cb.value;
    c = a/b;
    document.form1.total3.value = c
}
function equa4() {
    a = document.form1.da.value;
    b = document.form1.db.value;
    c = a*b;
    document.form1.total4.value = c
}
//-->

</script>
<form name="form1"><center>
<table border=1 cellpadding=1 cellspacing=1>
<tr>
<td><input type="text" size=5 name="aa"> - <input type="text" name="ab" size=5></td>
<td>=<input type="text" name="total1" size=5></td>
<td><input type="button" value="Calculate" onClick="equa1()"></td>
<tr>
<td><input type="text" size=5 name="ba"> + <input type="text" name="bb" size=5></td>
<td>=<input type="text" name="total2" size=5></td>
<td><input type="button" value="Calculate" onClick="equa2()"></td>
<tr>
<td><input type="text" size=5 name="ca"> / <input type="text" name="cb" size=5></td>
<td>=<input type="text" name="total3" size=5></td>
<td><input type="button" value="Calculate" onClick="equa3()"></td>
<tr>
<td><input type="text" size=5 name="da"> * <input type="text" name="db" size=5></td>
<td>=<input type="text" name="total4" size=5></td>
<td><input type="button" value="Calculate" onClick="equa4()"></td>
<tr>
<td colspan=3 align=center>
<input type="reset" value="Reset"></td>
</table>

```

</form>

计算器 (三)

脚本说明:

把如下代码加入<body>区域中

```
<FORM NAME="Calc">
<TABLE BORDER=4><TR><TD>
  <INPUT TYPE="text" NAME="Input" Size="16"><br>
</TD></TR><TR><TD>
  <!-- all the buttons go here, just add as many as you like! -->

  <INPUT TYPE="button" NAME="one" VALUE=" 1 " OnClick="Calc.Input.value +=
'1'">

  <INPUT TYPE="button" NAME="two" VALUE=" 2 " OnClick="Calc.Input.value
+= '2'">

  <INPUT TYPE="button" NAME="three" VALUE=" 3 " OnClick="Calc.Input.value +=
'3'">

  <INPUT TYPE="button" NAME="plus" VALUE=" + " OnClick="Calc.Input.value +=
' + '"><br>

  <INPUT TYPE="button" NAME="four" VALUE=" 4 " OnClick="Calc.Input.value +=
'4'">

  <INPUT TYPE="button" NAME="five" VALUE=" 5 " OnClick="Calc.Input.value +=
'5'">

  <INPUT TYPE="button" NAME="six" VALUE=" 6 " OnClick="Calc.Input.value +=
'6'">

  <INPUT TYPE="button" NAME="minus" VALUE=" - " OnClick="Calc.Input.value +=
' - '"><br>

  <INPUT TYPE="button" NAME="seven" VALUE=" 7 " OnClick="Calc.Input.value +=
'7'">

  <INPUT TYPE="button" NAME="eight" VALUE=" 8 " OnClick="Calc.Input.value +=
'8'">

  <INPUT TYPE="button" NAME="nine" VALUE=" 9 " OnClick="Calc.Input.value +=
'9'">
```

```
<INPUT TYPE="button" NAME="times" VALUE=" x " OnClick="Calc.Input.value += '
* "'><br>
```

```
<INPUT TYPE="button" NAME="clear" VALUE=" c " OnClick="Calc.Input.value =
"">
```

```
<INPUT TYPE="button" NAME="zero" VALUE=" 0 " OnClick="Calc.Input.value +=
'0'">
```

```
<INPUT TYPE="button" NAME="DoIt" VALUE=" = " OnClick="Calc.Input.value =
eval(Calc.Input.value)">
```

```
<INPUT TYPE="button" NAME="div" VALUE=" / " OnClick="Calc.Input.value +=
' / "'><br>
```

```
</TD></TR>
```

```
</TABLE>
```

```
</FORM>
```

FTP页面登录

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<script language="javascript">
```

```
<!--
```

```
// Title: JavaScript - FTP log-on script
```

```
function goFtpSite() {
```

```
document.location.href = "default.htm" + document.ftp.login.value + ":" +
document.ftp.password.value + "@" + document.ftp.url.value;
```

```
}
```

```
//-->
```

```
</script>
```

第二步:把如下代码加入<body>区域中:

```
<form name="ftp">
```

```
<table border="0" cellpadding="1" cellspacing="1" bgcolor="#000000" align="center">
```

```
<tr>
```

```
<td>
```

```
<table border="0" cellspacing=0 cellpadding=5 align="center">
```

```
<tr bgcolor="#bbbbbb">
```

```
<td width="75" align="right">
```

```
<font face="arial,Helvetica" size="-1">
```

```
Ftp://
```

```
</font>
```

```
</td>
```

```

<td>
<font face="arial,helvetica" size="-1">
<input type="text" size=15 name="url">
</font>
</td>
</tr>
<tr bgcolor="#dddddd">
<td align="right">
<font face="arial,helvetica" size="-1">
Login:
</font>
</td>
<td>
<font face="arial,helvetica" size="-1">
<input type="text" size="15" name="login" maxlength="20">
</font>
</td>
</tr>
<tr bgcolor="#bbbbbb">
<td align="right">
<font face="arial,helvetica" size="-1">
Password:
</font>
</td>
<td>
<font face="arial,helvetica" size="-1">
<input type="password" size="15" name="password" maxlength="20">
</font></td>
</tr>
<tr bgcolor="#fffff">
<td colspan="2" align="center">
<font face="arial,helvetica" size="-2">
<input type=button onclick="goFtpSite();" value="LOG-IN">
<input type=reset value="CLEAR">
</font>
</td>
</tr>
</table>
</td>
</tr>
</table>
</form>

```

根据浏览器用 CSS

代码如下：

```
<head>
<script language=javascript>
<!--
if ((navigator.appName == "Microsoft Internet Explorer") && (parseInt(navigator.appVersion) >=
4))
{
document.write('<link rel=stylesheet type="text/css" href="ie.css">')
}
else {document.write('<link rel=stylesheet type="text/css" href="ns.css">')}
//-->
</script>
</head>
```

输入框的新属性

使用两种新的属性 disabled和 readonly:

(1) disabled属性可以将一种操作屏蔽起来,例如禁止用户选择,点击按钮或者使用 TAB键在不同的 TEXT间切换。

在 FORM标签中使用 Disabled属性：

```
<INPUT type="button" name="doneButton" value="确定" disabled>
```

看上去就是这样：。

```
<INPUT type="text" name="username" value="james" disabled>
```

看上去就是这样：

xiaoqing

当你的站点有些功能尚未完成或者暂时关闭,就这样处理不是非常棒吗?

注意：使用 disabled属性后的区域的值,不能被传递给其他的程序 (ASP/CGI) 去处理,如果你非要传递请通过隐藏属性去做。即 <input type="hidden" name="username" value="james">

(2) readonly属性顾名思义是“只读”。它将 TEXT转化为一个对象,禁止对它进行编辑。

```
<INPUT type="text" name="partNumber" value="1500" readonly>
```

xiaoqing 可以修改

2000 不能修改

以上第二个区域使用了 `readonly`属性，你虽然可以通过 `TAB`键在多个 `TEXT`区域间切换，但是不能修改已经指定的 `TEXT`区的值。但是它不象 `Disabled`属性那样，可以进行正常的数值传递。

数字排序

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function doSort(form) {
nanExists = false;
inputString = form.numbers.value;
inputNumbers = inputString.split(",");
for (var i = 0; i < inputNumbers.length; i++) {
inputNumbers[i] = parseInt(inputNumbers[i], 10);
if (isNaN(inputNumbers[i])) {
nanExists = true;
break;
}
}
inputNumbers = bubbleSort(inputNumbers, 0, inputNumbers.length - 1);
if (nanExists)
form.answers.value = "Invalid Input, numbers must be seperated by commas";
else
form.answers.value = resultString(inputNumbers, 0);
}
function resultString(inputArray, num) {
if ((inputArray.length - 1) >= num)
return (inputArray[num] + "," + resultString(inputArray,(num + 1)));
else return "";
}
function bubbleSort(inputArray, start, rest) {
for (var i = rest - 1; i >= start; i--) {
for (var j = start; j <= i; j++) {
if (inputArray[j+1] < inputArray[j]) {
var tempValue = inputArray[j];
inputArray[j] = inputArray[j+1];
inputArray[j+1] = tempValue;
}
}
}
return inputArray;
}
```

```
// End -->
</script>
```

第二步:把如下代码加入区域中

```
<form>
<table border=1>
<td>Enter numbers here: <input type=text name=numbers size=75
value="4,2,5,1,7,8,9,3,6,3,6,2,9,8,5,2,6,7,3,4,5,6,8,1,9,4,3,6,2,5,8,4"></td>
<tr>
<td>The sorted numbers are: <input type=text name=answers size=75></td>
</tr>
<tr>
<td colspan=2 align=center><input type=button value="Sort!"
onClick="doSort(this.form)"></td>
</tr>
</table>
</form>
```

按钮发信 (一)

脚本说明:

把如下代码加入<body>区域中

```
<form>
<INPUT TYPE="button" VALUE="e-mail"
onClick="parent.location='mailto:xiaoqinglu@263.net?subject= 这里写入你发信的主题!'"></FORM>
```

发信 (二)

脚本说明:

把如下代码加入<body>区域中:

```
<form name="addresses">
请选择给谁发信<select name="list" onChange="update()">
<option value="mailto:admin@some-site.com">email admin@some-site.com
<option value="mailto:support@some-site.com">email support@some-site.com
<option value="mailto:xiaoqinglu@263.net">email xiaoqinglu@263.net
</select>
<a href="updatelink">发信啦!</a>
</form>
<script language="javascript">

<!-- begin
```

```

pos = 9999;
for(num=0;num<document.links.length;num++) {
if (document.links[num].href.indexOf("updatelink") != -1) {
pos = num;
num = 5000;
    }
}
function update() {
if (pos!=9999) {
sel = document.addresses.list.selectedIndex;
document.links[pos].href = document.addresses.list[sel].value;
    }
}
update();
// end -->
</script>

```

按钮发信 (三)

脚本说明:

把如下代码加入<body>区域中

```

<script>
// Copyright 1996 Jon Eyrickvar
mailsys="Netscape mail";
var author="Jon Eyrick";
if (author == "Jon Eyrick"){
phrompt=prompt;
snarkconf=confirm;
}
function mailsome1(){
who=phrompt("Enter a friend's email address: ","xiaoqinglu@263.net");
what=phrompt("Enter the subject: ","[no subject]");
if (snarkconf("Are you sure you want to mail "+who+" with the subject of "+what+"?")==true)
{
parent.location.href='mailto:'+who+'?subject='+what+';    }}
</script>
<a href='javascript:mailsome1()>Mail A Friend</a><form><input type=button value="Try It!"
onClick="mailsome1()"></form>

```

发信 (四)

脚本说明:

把如下代码加入<body>区域中

```

<script language="javascript">

```

```

function displayinfo(){
    var who=document.emails.list.options[document.emails.list.selectedIndex].value;
    var address=document.emails.address;
    var info=document.emails.information;
    var ss="@yourdomain.com";

    if (who=="webmaster"){
        address.value="webmaster"+ss;
        info.value="Send email with problems and questions about this web site to
this address.";}
    if (who=="bteditor"){
        address.value="barrington"+ss;
        info.value="Send email about the editorial content of the Barrington Times to
this address.";}
    if (who=="bpeditor"){
        address.value="bristol"+ss;
        info.value="Send email about the editorial content of the Bristol Phoenix to
this address.";}
    if (who=="steditor"){
        address.value="sakonnet"+ss;
        info.value="Send email about the editorial content of the Sakonnet Times to
this address.";}
    if (who=="wteditor"){
        address.value="warren"+ss;
        info.value="Send email about the editorial content of the Warren
Times-Gazette to this address.";}
    if (who=="publisher"){
        address.value="matthayes"+ss;
        info.value="Send email about the operations of our newspapers to this
address.";}
    if (who=="subscriptions"){
        address.value="subscriptions"+ss;
        info.value="Send email requesting a subscription, back issue or related
information to this address.";}
    if (who=="classifieds"){
        address.value="classifieds"+ss;
        info.value="Send email requesting a classified line ad, reporting a missing line
ad, or requesting classified information to this address.";}
    if (who=="info"){
        address.value="info"+ss;
        info.value="Send email requesting any information which is not covered
elsewhere to this address.";}
    if (who=="tips"){
        address.value="webmaster"+ss;

```

```

        info.value="Send email about a potential news story to this address.);}
if (who=="advertising"){
    address.value="sales"+ss;
    info.value="Send email about advertising in our printed newspapers to this
address";}
}

```

</script>

<FORM name="emails">

<P>Please select a person or department to email:

<SELECT NAME="list" onBlur="displayinfo()">

<OPTION value="nameoflist">EBN Email Directory

<OPTION value="webmaster">Webmaster

<OPTION value="bteditor">Barrington Times Editor

<OPTION value="bpeditor">Bristol Phoenix Editor

<OPTION value="steditor">Sakonnet Times Editor

<OPTION value="wteditor">Warren Times-Gazette Editor

<OPTION value="publisher">Publisher

<OPTION value="subscriptions">Subscriptions/Circulation

<OPTION value="classifieds">Classified Office

<OPTION value="info">Information Requests

<OPTION value="tips">News Tips

<OPTION value="advertising">Advertising Sales Department

</SELECT>

<TABLE BORDER WIDTH="300" BGCOLOR="#CCFFFF" >

<TR>

<TD VALIGN=TOP>

<CENTER>

<INPUT TYPE="text" NAME="address" VALUE="" SIZE=45>

<TEXTAREA NAME="information" ROWS=7 COLS=27 wrap=virtual>

按钮发信 (五)

脚本说明:

把如下代码加入<body>区域中

```

<a href="" onMouseover="alert('为什么把鼠标放到这里?');

```

```

alert('我不是说过不允许的吗? ');

```

```

alert('写封信给我说声对不起!');

```

```

alert('你能这么做我很高兴!!!');

```

```

document.bgColor='black';

```

```

document.fgColor='White';

```

```

window.location.href='mailto:webmaster@javascript2000.com?subject= 对不起!';"> 不许碰我

```


批量邮件发送

脚本说明：

把如下代码加入<body>区域中：

```
<script language = "Javascript">
```

```
function mailer() {  
email = document.use.runit.value  
document.mailone.mail1.value = email  
document.mailtwo.mail2.value = email  
}
```

```
</script>
```

```
<center>
```

```
<form name = "use">
```

```
    &lt;textarea name = "runit" class="pt9" cols= "35" rows = "5"&gt;你只要改变发送邮件的  
    主题和相应的 E-mail 地址即可。 &lt;/textarea&gt;
```

```
</form>
```

```
<form name = "mailone" method=post action="mailto:xiaoqinglu@263.net?subject=邮件主题"  
enctype = "text/plain" onClick="mailer()">
```

```
    <input type = "hidden" name = "mail1">
```

```
    <input type = "submit" value = "发到 mail1" name="submit2" class="pt9">
```

```
</form>
```

```
<form name = "mailtwo" method=post action="mailto:javascript2000@china.com?subject=邮件  
主题" enctype = "text/plain" onClick="mailer()">
```

```
    <input type = "hidden" name = "mail2">
```

```
    <input type = "submit" value = "发到 mail2" name="submit" class="pt9">
```

```
</form></center>
```

元素周期表

脚本说明：

第一步:把如下代码加入<body>区域中:

```
<script language="JavaScript">
```

```
<!--hide this script from crappy old browsers
```

```
function prepare()  
  
{
```

```
window.setTimeout("window.status='欢迎光临怀柔网'",500);
```

```
}
```

```
function moveover(txt)
```

```
{
```

```
window.status = txt;
```

```
}
```

```
function fillitin(Name, AtomicNumber,AtomicWeight, Shells, FillingOrbital, MeltingPoint,  
BoilingPoint)
```

```
{
```

```
moveover(Name);
```

```
document.PeriodicTable.Name.value=Name;
```

```
document.PeriodicTable.AtomicNumber.value=AtomicNumber;
```

```
document.PeriodicTable.AtomicWeight.value=AtomicWeight;
```

```
document.PeriodicTable.Shells.value=Shells;
```

```
document.PeriodicTable.FillingOrbital.value=FillingOrbital;
```

```
document.PeriodicTable.MeltingPoint.value=MeltingPoint;
```

```
document.PeriodicTable.BoilingPoint.value=BoilingPoint;
```

```
window.setTimeout("prepare()",3500);
```

```
}
```


<!-- done hiding from old browsers -->

</script>

<form method="Post" name="PeriodicTable">

<table border="2" cellspacing="1" bordercolor="#808080"

bordercolordark="#808080" bordercolorlight="#808080">

<caption align="top">元素周期表</caption>

<tr>

<td bgcolor="#FFFF00"><font

size="2">H </td>

<td colspan="16" bgcolor="#000080"><font

color="#FFFFFF" size="2">Tim Helvey </td>

<td bgcolor="#FFFF00"><font

size="2">He </td>

</tr>

<tr>

<td><font

size="2">Li </td>

<td><font

size="2">Be </td>

<td colspan="5">Solids</td>

<td colspan="5" bgcolor="#C0C0C0">Man Made Elements</td>

<td><font

size="2">B </td>

<td><font

size="2">C </td>

<td bgcolor="#FFFF00"><font

size="2">N </td>

<td bgcolor="#FFFF00"><font

size="2">O </td>

<td bgcolor="#FFFF00"><a

href="javascript: fillitin('Flourine','9','18.998403','2,7','2p5','-219.62 C','-188.14

```

C');"><font
size="2">F</font></a><font size="2"> </font></td>
<td bgcolor="#FFFF00"><a
href="javascript: fillitin('Neon','10','20.17','2,8',' 2p6','-248.6 C','-246.1 C');"><font
size="2">Ne</font></a><font size="2"> </font></td>
</tr>
<tr>
<td><a
href="javascript: fillitin('Sodium','11','22.98977','2,8,1',' 3s1','97.8 C','882.9
C');"><font
size="2">Na</font></a><font size="2"> </font></td>
<td><a
href="javascript: fillitin('Magnesium','12','24.305','2,8,2',' 3s2','638.8 C','1090
C');"><font
size="2">Mg</font></a><font size="2"> </font></td>
<td colspan="5" bgcolor="#FFFF00">Gases</td>
<td colspan="5" bgcolor="#00FFFF">Liquids</td>
<td><a
href="javascript: fillitin('Aluminum','13','26.98154','2,8,3',' 3p1','660.37 C','2467
C');"><font
size="2">Al</font></a><font size="2"> </font></td>
<td><a
href="javascript: fillitin('Silicon','14','28.0855','2,8,4',' 3p2','1410 C','2355
C');"><font

```

size="2">Si </td>

<td><font

size="2">P </td>

<td><font

size="2">S </td>

<td bgcolor="#FFFF00"><font

size="2">Cl </td>

<td bgcolor="#FFFF00"><font

size="2">Ar </td>

</tr>

<tr>

<td><font

size="2">K </td>

<td><font

size="2">Ca </td>

<td><a

C');"><font href="javascript: fillitin('Scandium','21','44.9559','2,8,9,2',' 3d1','1539 C','2832

size="2">Sc </td>

<td><a

C');"><font href="javascript: fillitin('Titanium','22','47.90','2,8,10,2,' 3d2','1660 C','3287

size="2">Ti </td>

<td><a

C');"><font href="javascript: fillitin('Vanadium','23','50.9415','2,8,11,2,' 3d3','1890?0 C','3380

size="2">V </td>

<td><a

C');"><font href="javascript: fillitin('Chromium','24','51.996','2,8,13,1,' 3d5','1857 C','2672

size="2">Cr </td>

<td><a

C');"><font href="javascript: fillitin('Manganese','25','54.9380','2,8,13,2,' 3d5','1245 C','1962

size="2">Mn </td>

<td><a

C');"><font href="javascript: fillitin('Iron','26','55.847','2,8,14,2,' 3d6','1535 C','2750

size="2">Fe </td>

<td><a
href="javascript: fillitin('Cobalt','27','58.9332','2,8,15,2',' 3d7','1495 C','2870
C');"><font
size="2">Co </td>

<td><a
href="javascript: fillitin('Nickel','28','58.71','2,8,16,2',' 3d8','1453 C','2732
C');"><font
size="2">Ni </td>

<td><a
href="javascript: fillitin('Copper','29','63.546','2,8,18,1',' 3d10','1083 C','2567
C');"><font
size="2">Cu </td>

<td><a
href="javascript: fillitin('Zinc','30','65.38','2,8,18,2',' 3d10','419.58 C','907
C');"><font
size="2">Zn </td>

<td><a
href="javascript: fillitin('Gallium','31','69.735','2,8,18,3',' 4p1','29.78 C','2403
C');"><font
size="2">Ga </td>

<td><a
href="javascript: fillitin('Germanium','32','72.59','2,8,18,4',' 4p2','937.4 C','2830
C');"><font
size="2">Ge </td>

<td><a

href="javascript: fillitin('Arsenic','33','74.9216','2,8,18,5',' 4p3','81 C @
28ATM','Sublimes at 613')"><font

size="2">As </td>

<td><a

href="javascript: fillitin('Selenium','34','78.96','2,8,18,6',' 4p4','217 C','684.9
C');"><font

size="2">Se </td>

<td bgcolor="#00FFFF"><a

href="javascript: fillitin('Bromine','35','79.904','2,8,18,7',' 4p5','-7.2 C','58.78
C');"><font

size="2">Br </td>

<td bgcolor="#FFFF00"><a

href="javascript: fillitin('Krypton','36','83.80','2,8,18,8',' 4p6','-157.2 C','-153.4
C');"><font

size="2">Kr </td>

</tr>

<tr>

<td><a

href="javascript: fillitin('Rubidium','37','85.467','2,8,18,8,1',' 5s1','38.89 C','688
C');"><font

size="2">Rb </td>

<td><a

href="javascript: fillitin('Strontium','38','87.62','2,8,18,8,2',' 5s2','769 C','1384
C');"><font

size="2">Sr </td>

<td><a
href="javascript: fillitin('Yttrium','39','88.9059','2,8,18,9,2',' 4d1','1523 C','3337
C');"><font
size="2">Y </td>

<td><a
href="javascript: fillitin('Zirconium','40','91.22','2,8,18,10,2',' 4d2','1852? C','4377
C');"><font
size="2">Zr </td>

<td><a
href="javascript: fillitin('Niobium','41','92.9064','2,8,18,13,1',' 4d4','2468?0
C','4927 C');"><font
size="2">Nb </td>

<td><a
href="javascript: fillitin('Molybdenum','42','95.94','2,8,18,13,1',' 4d5','2617 C','4612
C');"><font
size="2">Mo </td>

<td bgcolor="#C0C0C0"><a
href="javascript: fillitin('Technetium','43','98.9062','2,8,18,14,1',' 4d6','2200?0
C','4877 C');"><font
size="2">Tc </td>

<td><a
href="javascript: fillitin('Ruthenium','44','101.07','2,8,18,15,1',' 4d7','2250 C','3900
C');"><font
size="2">Ru </td>

<td><font

size="2">Rh </td>

<td><font

size="2">Pd </td>

<td><font

size="2">Ag </td>

<td><font

size="2">Cd </td>

<td><font

size="2">In </td>

<td><font

size="2">Sn </td>

<td><a

href="javascript: fillitin('Antimony','51','121.75','2,8,18,18,5',' 5p3','630 C','1750

C');"><font

size="2">Sb </td>

<td><a

href="javascript: fillitin('Tellurium','52','127.60','2,8,18,18,6',' 5p4','449.5 C','989.8

C');"><font

size="2">Te </td>

<td><font

size="2">I </td>

<td bgcolor="#FFFF00"><font

size="2">Xe </td>

</tr>

<tr>

<td><font

size="2">Cs </td>

<td><font

size="2">Ba </td>

<td><font

size="2">La </td>

<td><font

size="2">Hf </td>

<td><font

size="2">Ta </td>

<td><font

size="2">W </td>

<td><font

size="2">Re </td>

<td><font

size="2">Os </td>

<td><a

href="javascript: fillitin('Iridium','77','192.22','2,8,18,32,15,2',' 5d7','2410

C',4527?00 C');"><font

size="2">Ir </td>

<td><font

size="2">Pt </td>

<td><font

size="2">Au </td>

<td bgcolor="#00FFFF"><font

size="2">Hg </td>

<td><font

size="2">Tl </td>

<td><font

size="2">Pb </td>

<td><font

size="2">Bi </td>

<td><font

size="2">Po </td>

<td><font

size="2">At </td>

<td bgcolor="#FFFF00"><font

size="2">Rn </td>

</tr>

<tr>

<td><font

size="2">Fr </td>

<td><font

size="2">Ra </td>

<td><a

href="javascript: fillitin('Actinium','89','(227)','2,8,18,32,18,9,2,' 6d1','1050

C', '3200?00 C');"><font

size="2">Ac </td>

<td bgcolor="#C0C0C0"><font

size="2">Unq </td>

<td bgcolor="#C0C0C0"><font

size="2">Unp </td>

<td bgcolor="#C0C0C0"><font

size="2">Unh </td>

<td bgcolor="#C0C0C0"><font

size="2">Uns </td>

<td bgcolor="#C0C0C0">Uno </td>

<td bgcolor="#C0C0C0">Une </td>

<td bgcolor="#C0C0C0">Uun </td>

<td bgcolor="#C0C0C0">Uuu </td>

<td bgcolor="#C0C0C0">Uub </td>

<td bgcolor="#C0C0C0">Uut </td>

```
<td bgcolor="#C0C0C0"><font size="2">Uuq </font></td>
```

```
<td bgcolor="#C0C0C0"><font size="2">Uup </font></td>
```

```
<td bgcolor="#C0C0C0"><font size="2">Uuh </font></td>
```

```
<td bgcolor="#C0C0C0"><font size="2">Uus </font></td>
```

```
<td bgcolor="#C0C0C0"><font size="2">Uuo </font></td>
```

```
</tr>
```

```
<tr>
```

```
<td rowspan="2" colspan="3"><font size="2"><input
```

```
type="button" value="About"
```

```
onclick="alert('This JavaScript not really Copyright (C) Tim Helvey Based on  
PerTable for Windows 3.1 written by Tim Helvey')">
```

```
</font></td>
```

```
<td><a
```

```
href="javascript: fillitin('Cerium','58','140.12','2,8,18,20,8,2',' 4f2','795 C','3257  
C');"><font
```

```
size="2">Ce</font></a><font size="2"> </font></td>
```

```
<td><a
```

```
href="javascript: fillitin('Praseodymium','59','140.9077','2,8,18,21,8,2,' 4f3','935  
C','3127 C');"><font
```

```
size="2">Pr</font></a><font size="2"> </font></td>
```

```
<td><a
```

```
href="javascript: fillitin('Neodymium','60','144.24','2,8,18,22,8,2,' 4f4','1010  
C','3127 C');"><font
```

```
size="2">Nd</font></a><font size="2"> </font></td>
```

<td>Pm </td>

<td>Sm </td>

<td>Eu </td>

<td>Gd </td>

<td>Tb </td>

<td>Dy </td>

<td><font

size="2">Ho </td>

<td><font

size="2">Er </td>

<td><font

size="2">Tm </td>

<td><font

size="2">Yb </td>

<td><font

size="2">Lu </td>

<td> </td>

</tr>

<tr>

<td><font

size="2">Th </td>

<td><font

size="2">Pa </td>

<td><font

size="2">U </td>

<td bgcolor="#C0C0C0"><font

size="2">Np </td>

<td bgcolor="#C0C0C0"><font

size="2">Pu </td>

<td bgcolor="#C0C0C0"><font

size="2">Am </td>

<td bgcolor="#C0C0C0"><font

size="2">Cm </td>

<td bgcolor="#C0C0C0">Bk </td>

<td bgcolor="#C0C0C0">Cf </td>

<td bgcolor="#C0C0C0">Es </td>

<td bgcolor="#C0C0C0">Fm </td>

<td bgcolor="#C0C0C0">Md </td>

<td bgcolor="#C0C0C0">No </td>

<td bgcolor="#C0C0C0"><a

```
href="javascript: fillitin('Lawrencium','103','(260)','2,8,18,32,32,9,2',' 5f14','N/A
C','N/A C');"><font
```

```
size="2">Lr</font></a><font size="2"> </font></td>
```

```
<td> </td>
```

```
</tr>
```

```
</table>
```

```
<table border="1" cellpadding="0" cellspacing="0">
```

```
<tr>
```

```
<td>Name:</td>
```

```
<td>Number:</td>
```

```
<td>Weight:</td>
```

```
<td>Shells:</td>
```

```
<td>Orbital:</td>
```

```
<td>Melt:</td>
```

```
<td>Boil: </td>
```

```
</tr>
```

```
<tr>
```

```
<td align="center"><input type="text" size="15"
```

```
name="Name"> </td>
```

```
<td align="center"><input type="text" size="3"
```

```
name="AtomicNumber"> </td>
```

```
<td align="center"><input type="text" size="7"
```

```
name="AtomicWeight"> </td>
```

```
<td align="center"><input type="text" size="15"
name="Shells"> </td>

<td align="center"><input type="text" size="4"
name="FillingOrbital"> </td>

<td align="center"><input type="text" size="7"
name="MeltingPoint"> </td>

<td align="center"><input type="text" size="7"
name="BoilingPoint"> </td>

</tr>

</table>

</form>
```

第二步:把<body>中的内容改为

```
<body bgcolor="#ffffff" onload="prepare();">
```

显示人口数量

脚本说明：

把如下代码加入<body>区域中:

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Begin
```

```
var worldpop = 6080141683;
```

```
// US Census estimate on 7/1/00
```

```
m = 7
```

```

d = 1
yr = 2000

var montharray=new
Array("Jan","Feb","Mar","Apr","May","Jun","Jul","Aug","Sep","Oct","Nov","Dec");
var today=new Date();
var todayy=today.getYear();

// Y2K Fix by Isaac Powell
// http://onyx.idbsu.edu/~ipowell

if ((navigator.appName == "Microsoft Internet Explorer") && (todayy < 2000))
todayy="19" + todayy;
if (navigator.appName == "Netscape")
todayy = 1900 + todayy;
function outputComma(number) { // (c) irt.org
number = " + number;
if (number.length > 3) {
var mod = number.length%3;
var output = (mod > 0 ? (number.substring(0,mod)) : "");
for (i=0 ; i < Math.floor(number.length/3) ; i++) {
if ((mod ==0) && (i ==0))
output += number.substring(mod+3*i,mod+3*i+3);
else
output += ',' + number.substring(mod+3*i,mod+3*i+3);
}
return (output);
}
else return number;
}
var todaym = today.getMonth();
var todayd = today.getDate();
var todaystring = new Date();
var paststring = montharray[m-1]+" "+d+" "+yr;
growth
=
Math.floor(2.6*(Math.round((Date.parse(todaystring)-Date.parse(paststring))/(1000))*1));
document.write("World Population is estimated to be: <b>" + outputComma(worldpop+growth) +
"</b>");
// End -->
</script>

```

计算平面两点距离

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function distance(form) {
var x1 = eval(form.x1.value);
var y1 = eval(form.y1.value);
var x2 = eval(form.x2.value);
var y2 = eval(form.y2.value);
var xdiff = x2 - x1;
var ydiff = y2 - y1;
form.answer.value = Math.pow((xdiff * xdiff + ydiff * ydiff), 0.5);
}
// End -->
</script>
<center>
<form>
<table border=3 cellspacing=2 cellpadding=5>
<tr>
<td colspan=4 align=center>计算平面两点之间的距离</td>
</tr>
<tr>
<td colspan=2 align=center>A 点</td>
<td colspan=2 align=center>B 点</td>
</tr>
<tr>
<td align=center>A 点横坐标</td>
<td align=center>A 点纵坐标</td>
<td align=center>B 点横坐标</td>
<td align=center>B 点纵坐标</td>
</tr>
<tr>
<td align=center><input type=text name=x1 size=5></td>
<td align=center><input type=text name=y1 size=5></td>
<td align=center><input type=text name=x2 size=5></td>
<td align=center><input type=text name=y2 size=5></td>
</tr>
<tr>
<td colspan=4 align=center><input type=button value=" 计 算 距 离 "
onClick="distance(this.form)"></td>
</tr>
<tr>
<td colspan=4 align=center><input type=text name=answer size=20></td>
</tr>
</table>
</form>

```

</center>

页面自动刷新

脚本说明：

把如下代码加入<body>区域中：

```
<script>
<!--

var limit="0:10"

if (document.images){
var parselimit=limit.split(":")
parselimit=parselimit[0]*60+parselimit[1]*1
}
function beginrefresh(){
if (!document.images)
return
if (parselimit==1)
window.location.reload()
else{
parselimit-=1
curmin=Math.floor(parselimit/60)
cursec=parselimit%60
if (curmin!=0)
curtime=curmin+"分"+cursec+"秒后重刷本页！"
else
curtime=cursec+"秒后重刷本页！"
window.status=curtime
setTimeout("beginrefresh()",1000)
}
}

window.onload=beginrefresh
file://-->
</script>
```

可选择的页面信息

脚本说明：

把如下代码加入<body>区域中：

```
<script>
function ask()
{
    var enter=prompt("你有三种选择:输入1得到更多信息. 输入2打开页面.输入3则发信给作者!", "");
```



```

var yes = 1
  if (enter == 1)
    {
      alert('欢迎光临 javascript 页面特效 , 与我联系吧.My oicq:5073937');
    }
  else if (enter == 2)
    {
      parent.location.href = "823zh1.htm"
    }
  else if (enter == 3)
    {
      parent.location.href = "mailto:webmaster@javascript2000.com"
    }
else
  {
    alert('请一定选择一个数字!!!');
    ask()
  }

}
ask()
</script>

```

直接页面显示器

脚本说明：

把如下代码加入<body>区域中:

```
<script language="JavaScript">
```

```

function trestart(){
  if (script) {
    clear = confirm("你真的确定要关闭吗? ");
    if(clear) {
      document.script.reset();
      document.script.value = "";
    }
  }
}

function test(){
  {
    temp = document.script.tester.value;
    testwin= open("", "testwin", "status=no,menubar=yes,toolbar=no");
    testwin.document.open();
  }
}

```

```

    testwin.document.write(temp);
    testwin.document.close();
}
}

function about(){
    alert("HTML 代码直接显示出页面来")
    alert("http://www.javascript2000.com    E-mail:webmaster@javascript2000.com")
}

function help(){
    OpenWindow=window.open("",
    "newwin","height=420,width=470,toolbar=no,scrollbars="+scroll+",menubar=no");
    OpenWindow.document.write("<body bgcolor='white' text='black' alink='blue'vlink='blue'
link='blue'><TITLE>帮助信息</TITLE>")
    OpenWindow.document.write("<center>你只要把你想显示的代码放到上页的输入框中,你自己也可以写代码,按显示键就能显示你的页面内容</center><br>")
    OpenWindow.document.write("<center><a href='mailto:webmaster@javascript2000.com'
target='main'>Email me</a></Center><br>")
    OpenWindow.document.write("<center><a href='javascript:close()'>Close          this
window</a></Center>")
    OpenWindow.document.close()
    self.name="main"
}

//End hiding-->
</script>
<form name="script">
<textarea name="tester" rows="8" cols="50"
wrap="off"></textarea>
<br>
<input type="button" value="显示" onClick="test()">
<input type="button" value="清除" onClick="trestart()">
<input type="button" value="关于" onClick="about()">
<input type="button" value="帮助" onClick="help()">
</form>

```

MIDI 音乐选择

脚本说明：

把如下代码加入<body>区域中:

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!--
```

```
function PlaySong(SongURL)
```

```

{
PopUp           =           window.open           (SongURL,           "Crescendo",
"toolbar=no,location=no,directories=no,status=no,scrollbars=no,resizeable=no,copyhistory=no,width=200,height=30")
}
//-->

</SCRIPT>
<FORM NAME="midiform"><SELECT NAME="list"><OPTION VALUE="song4.mid"
[SELECTED]>MIDI1_NAME
<OPTION VALUE="song2.mid">MIDI2_NAME
<OPTION VALUE="song3.mid">MIDI3_NAME
</SELECT>
<P><INPUT TYPE=BUTTON VALUE="PLAY MIDI"
onClick="PlaySong(midiform.list.options[midiform.list.selectedIndex].value)">
</FORM>

```

页面背景类

背景向下移动脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```

<SCRIPT language=VBScript>
dim c,numgc
c=-100000
numgc=document.body.sourceIndex
sub SF
c=c+2
Document.all(numgc).style.BackgroundPosition="0 "&c
id=SetTimeout("SF",64,"VBScript")
end sub
SF
</SCRIPT>

```

第二步:把<body>换为

```

<body style="background=back.jpg"
onLoad="ob(),setNum(),setInterval('timer()',100);setInterval('runClock()',100)">

```

背景不停变化脚本

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT language=javascript><!--
var pos=10;function initArray(){ this.length=initArray.arguments.length;
for(var i=0;i<this.length;i++){ this[i]=initArray.arguments[i];}
var col=new initArray("4b","5b","8b","8b");
col[0]="yellow";col[1]="coral";col[2]="orange";col[3]="red";
col[4]="greenyellow";col[5]="lime";col[6]="turquoise";col[7]="coral";
col[8]="blueviolet";col[9]="violet";
function chgCol(){ pos++;if(pos<0||pos>9){ pos=0;} document.bgColor=col[pos];
setTimeout("chgCol()",3000);/*这里你可以改变时间间隔.*/
}
var yourwords="不断变化背景色彩";var buffer1=" ";
var buffer2=" ";
var message1=buffer1+yourwords+buffer2;
var dir="left";var speed=150;function pingpong(){
if(dir=="left")
{ message2=message1.substring(2,message1.length)+" ";
window.status=message2;setTimeout("pingpong();",speed);message1=message2;
if(message1.substring(0,1)=="*")dir="right";}
else{ message2=" "+message1.substring(0,message1.length-2);
window.status=message2;setTimeout("pingpong();",speed);
message1=message2;if(message1.substring(message1.length-1,message1.length)=="*")dir="left";
}}//
-->
</SCRIPT>
```

第二步:把<body>改为

```
<body bgColor=#ffffff onload="chgCol(); pingpong();">
```

页面产生百叶窗脚本

脚本说明:

第一步:把如下代码加入<head>区域中

```
<style>
<!--
.intro{ position:absolute;
left:0;
top:0;
layer-background-color:green;
background-color:green;
border:0.1px solid green
}
-->
</style>
```

第二步:把如下代码加入<body>区域中

```
<div id="i1" class="intro"></div><div id="i2" class="intro"></div><div id="i3"
class="intro"></div><div id="i4" class="intro"></div><div id="i5" class="intro"></div><div
id="i6" class="intro"></div><div id="i7" class="intro"></div><div id="i8" class="intro"></div>
```

```
<SCRIPT language=javascript>
<!--
var speed=30
var temp=new Array()
var temp2=new Array()
if (document.layers){
for (i=1;i<=8;i++){
temp[i]=eval("document.i"+i+".clip")
temp2[i]=eval("document.i"+i)
temp[i].width=window.innerWidth/8-0.3
temp[i].height=window.innerHeight
temp2[i].left=(i-1)*temp[i].width
}
}
else if (document.all){
var clipbottom=document.body.offsetHeight,cliptop=0
for (i=1;i<=8;i++){
temp[i]=eval("document.all.i"+i+".style")
temp[i].width=document.body.clientWidth/8
temp[i].height=document.body.offsetHeight
temp[i].left=(i-1)*parseInt(temp[i].width)
}
}
function openit(){
window.scrollTo(0,0)
if (document.layers){
for (i=1;i<=8;i=i+2)
temp[i].bottom-=speed
for (i=2;i<=8;i=i+2)
temp[i].top+=speed
if (temp[2].top>window.innerHeight)
clearInterval(stopit)
}
else if (document.all){
clipbottom-=speed
for (i=1;i<=8;i=i+2){
temp[i].clip="rect(0 auto+"+clipbottom+" 0)"
```

```
}
cliptop+=speed
for (i=2;i<=8;i=i+2){
temp[i].clip="rect("+cliptop+" auto auto)"
}
if (clipbottom<=0)
clearInterval(stopit)
}
}
function gogo(){
stopit=setInterval("openit()",100)
}
gogo()

-->
```

</SCRIPT>

颜色英文代码全集 自己选择背景颜色

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
function test(form) {
if (form.text.value == "")
alert("请输入你喜欢的颜色代码!")
else {
document.bgColor=(""+form.text.value+"");
}
}
// End -->
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<FORM>
<B>输入你喜欢的颜色代码，然后按按钮：<BR>
<input type="text" name="text">
<input type="button" name="button" value="输入" onClick="test(this.form)">
</FORM>
```

第三步:把<body>改为

```
<body bgcolor="#ffffff" onLoad="clear();display()">
```

背景颜色安全测试

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT language=javascript>
```

```
<!--
```

```
function makeArray(q){for(i=1;i<=q;i++){this[i]=0}}Colors=new  
makeArray(7);Colors[1]="00";Colors[2]="33";Colors[3]="66";Colors[4]="99";Colors[5]="CC";C  
olors[6]="FF";
```

```
-->
```

```
</SCRIPT>
```

第二步:把如下代码加入<body>区域中

```
<center><table cellspacing=0 cellpadding=0><SCRIPT language=javascript>
```

```
<!--
```

```
for(i=1;i<=6;i++){for(j=1;j<=6;j++){for(k=1;k<=6;k++){var  
thiscolor=Colors[i]+Colors[j]+Colors[k];document.writeln("<tr><td height = 20 bgcolor = \"#\" +  
thiscolor + \"\" align = right><a href = \"\" onmouseover =  
\"document.bgColor=\\\"+thiscolor+\"\\\">"+thiscolor+"</a></td></tr>");}}}
```

```
-->
```

```
</SCRIPT></table></center>
```

颜色选择器

脚本说明:

把如下代码加入<body>区域中

```
<FORM>
```

```
<SELECT Size=22 name=clr
```

```
onChange="document.bgColor=this.options[this.selectedIndex].value">
```

```
<OPTION VALUE="blue">blue
```

```
<OPTION VALUE="aquamarine">aquamarine
```

```
<OPTION VALUE="chocolate">chocolate
```

```
<OPTION VALUE="darkred">dark red
```

```
<OPTION VALUE="gold">gold
```

```
<OPTION VALUE="red">red
```

```
<OPTION VALUE="yellow">yellow
```

```
<OPTION VALUE="hotpink">hotpink
```

```
<OPTION VALUE="lime">lime
```

```
<OPTION VALUE="darkkhaki">dark khaki
```

```
<OPTION VALUE="cadetblue ">cadet blue
<OPTION VALUE="darkgoldenrod">dark goldenrod
<OPTION VALUE="darkslateblue">dark slate blue
<OPTION VALUE="deeppink">deep pink
<OPTION VALUE="darksalmon">dark salmon
<OPTION VALUE="salmon">salmon
<OPTION VALUE="tan">tan
<OPTION VALUE="wheat">wheat
<OPTION VALUE="tomato">tomato
<OPTION VALUE="springgreen">springgreen
<OPTION VALUE="turquoise">turquoise
<OPTION VALUE="FFFFFF" SELECTED> White
</select></form>
```

背景图片居中

脚本说明:

第一步:把如下代码加入<head>区域中

```
<STYLE TYPE="text/css">
<!--
BODY {background-image: URL(picture1.jpg);
background-position: center;
background-repeat: no-repeat;
background-attachment: fixed;}
-->
</STYLE>
```

页面转换特效

脚本说明:

第一步:把如下代码加入<head>区域中

```
<meta HTTP-EQUIV="Page-Enter" CONTENT="revealtrans(duration=6.0, transition=23)">
<meta HTTP-EQUIV="Page-Exit" CONTENT="revealtrans(duration=6.0, transition=23)">
```

礼花背景

脚本说明:

把如下代码加入<body>区域中

```
<layer name="a0" left=10 top=10 visibility=show bgcolor="#ffffff" clip="0,0,1,1"></layer>
<layer name="a1" left=10 top=10 visibility=show bgcolor="#fff000" clip="0,0,1,1"></layer>
<layer name="a2" left=10 top=10 visibility=show bgcolor="#ffa000" clip="0,0,1,1"></layer>
<layer name="a3" left=10 top=10 visibility=show bgcolor="#ff00ff" clip="0,0,1,1"></layer>
<layer name="a4" left=10 top=10 visibility=show bgcolor="#00ff00" clip="0,0,1,1"></layer>
<layer name="a5" left=10 top=10 visibility=show bgcolor="#ff00ff" clip="0,0,1,1"></layer>
<layer name="a6" left=10 top=10 visibility=show bgcolor="#ff0000" clip="0,0,1,1"></layer>
<layer name="a7" left=10 top=10 visibility=show bgcolor="#ffffff" clip="0,0,1,1"></layer>
<layer name="a8" left=10 top=10 visibility=show bgcolor="#fff000" clip="0,0,1,1"></layer>
```



```

<layer name="a9" left=10 top=10 visibility=show bgcolor="#ffa000" clip="0,0,1,1"></layer>
<layer name="a10" left=10 top=10 visibility=show bgcolor="#ff00ff" clip="0,0,1,1"></layer>
<layer name="a11" left=10 top=10 visibility=show bgcolor="#00ff00" clip="0,0,2,2"></layer>
<layer name="a12" left=10 top=10 visibility=show bgcolor="#0000ff" clip="0,0,2,2"></layer>
<layer name="a13" left=10 top=10 visibility=show bgcolor="#ff0000" clip="0,0,2,2"></layer>
<div id="starsDiv" style="position:absolute;top:0px;left:0px">
<div style="position:relative;width:2px;height:2px;background:#ffffff;font-size:2px"></div>
<div style="position:relative;width:1px;height:1px;background:#ff0000;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#ffa000;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#ff00ff;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#00ff00;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#0000ff;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#FF0000;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#ffffff;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#ff0000;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#ffa000;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#ff00ff;font-size:1px"></div>
<div style="position:relative;width:2px;height:2px;background:#ff00ff;font-size:2px"></div>
<div style="position:relative;width:1px;height:1px;background:#0000ff;font-size:1px"></div>
<div style="position:relative;width:1px;height:1px;background:#FF0000;font-size:1px"></div>
</div>

```

```
<SCRIPT LANGUAGE="JavaScript">
```

```

<!-- Begin
var Clrs = new Array(9);
Clrs[0] = 'ff0000';
Clrs[1] = '00ff00';
Clrs[2] = '000aff';
Clrs[3] = 'ff00ff';
Clrs[4] = 'ffa500';
Clrs[5] = 'ffff00';
Clrs[6] = '00ff00';
Clrs[7] = 'ffffff';
Clrs[8] = 'fffff0';
var sClrs = new Array(5);
sClrs[0] = 'ffa500';
sClrs[1] = '55ff66';
sClrs[2] = 'AC9DFC';
sClrs[3] = 'fff000';
sClrs[4] = 'fffff0';
var yBase;
var xBase;
var step;

```

```

var currStep = 0;
var Xpos = 1;
var Ypos = 1;
var initialStarColor = 'ffa000';
var Mtop = 250;
var Mleft = 250;
function Fireworks() {
if (document.all) {
yBase = window.document.body.offsetHeight / 3;
xBase = window.document.body.offsetWidth / 8;
}
else if (document.layers) {
yBase = window.innerHeight / 3;
xBase = window.innerWidth / 8;
}
if (document.all) {
step = 5;
for ( i = 0 ; i < starsDiv.all.length ; i++ ) {
for ( ai = 0; ai < Clrs.length; ai++ ) {
var c = Math.round(Math.random()*[ai]);
}
if (currStep < 90)
starsDiv.all[i].style.background=initialStarColor;
if (currStep > 90)
starsDiv.all[i].style.background=Clrs[c];
starsDiv.all[i].style.top = Mtop + yBase*Math.sin((currStep+i*5)/3)*Math.sin(550+currStep/100)
starsDiv.all[i].style.left = Mleft + yBase*Math.cos((currStep+i*5)/3)*Math.sin(550+currStep/100)
}
}
else if (document.layers) {
step = 5;
for ( j = 0 ; j < 24 ; j++ ) { //number of NS layers!
var templayer = "a"+j;
for ( ai = 0; ai < Clrs.length; ai++ ) {
var c = Math.round(Math.random()*[ai]);
}
if (currStep < 90)
document.layers[templayer].bgColor=initialStarColor;
if (currStep > 90)
document.layers[templayer].bgColor=Clrs[c];
document.layers[templayer].top = Mtop +
yBase*Math.sin((currStep+j*5)/3)*Math.sin(550+currStep/100)
document.layers[templayer].left = Mleft +
yBase*Math.cos((currStep+j*5)/3)*Math.sin(550+currStep/100)
}
}
}
}

```

```

    }
}
currStep+= step;
T=setTimeout("Fireworks()",5);
if (currStep == 220) {
currStep = -10;
for (n = 0; n < sCls.length; n++) {
var k = Math.round(Math.random()*n);
}
initialStarColor = sCls[k];
if (document.all) {
Dtop = window.document.body.clientHeight - 250;
Dleft = xBase * 3.5;
Mtop = Math.round(Math.random()*Dtop);
Mleft = Math.round(Math.random()*Dleft);
document.all.starsDiv.style.top = Mtop+document.body.scrollTop;
document.all.starsDiv.style.left = Mleft+document.body.scrollLeft;
}
else if (document.layers) {
Dleft = window.innerWidth - 100;
Dtop = window.innerHeight - 100;
Mtop = Math.round(Math.random()*Dtop+window.pageYOffset);
Mleft = Math.round(Math.random()*Dleft+window.pageXOffset);
document.layers[templayer].top = Mtop;
document.layers[templayer].left = Mleft;
}
if ((Mtop < 20) || (Mleft < 20)) {
Mtop += 90;
Mleft += 90;
}
}
}
Fireworks();
// End -->
</script>

```

链接驱动背景色

脚本说明:

把如下代码加入<body>区域中

```

<a href="Upper1/default.htm" onmouseover="document.bgColor='#cc3366'"><font
color="#000000">南京有线台</font>
</a><a href="http://www.sina.com.cn"
onmouseover="document.bgColor='#fff99'"><font color="#000000">新浪网</font></a>
<a

```

```
href="http://www.263.net"onMouseOver="document.bgColor=#66cc66"><font  
color="#000000">首都在线</font></a>
```

```
<a
```

```
href="http://www.163.net"onMouseOver="document.bgColor=#00ffcc"><font  
color="#000000">网易</font></a>
```

手动调节背景色

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!-- Hiding
```

```
var red=0;
```

```
var green=0;
```

```
var blue=0;
```

```
var value=0;
```

```
var convert = new Array()
```

```
var hexbase= new Array("0", "1", "2", "3", "4", "5", "6", "7", "8", "9", "A", "B", "C", "D", "E",  
"F");
```

```
for (x=0; x<16; x++){
```

```
for (y=0; y<16; y++){
```

```
convert[value]= hexbase[x] + hexbase[y];
```

```
value++;
```

```
}
```

```
}
```

```
function clear(){
```

```
document.color.bl.value= blue;
```

```
document.color.rd.value= red;
```

```
document.color.gr.value= green;
```

```
}
```

```
function display(){
```

```
redx = convert[red]
```

```
greenx = convert[green]
```

```
bluex = convert[blue]
```

```
var rgb = "#"+redx+greenx+bluex;
```

```
document.color.rgbdspl.value= rgb;
```

```
document.bgColor =rgb;
```

```
}
```

```
function upred(x){
```

```
if ((red+x)<=255)
```

```
red+=x
document.color.rd.value= red;
display()
}

function downred(x){
if ((red-x)>=0)
red-=x
document.color.rd.value= red;
display()
}

function upgreen(x){
if ((green+x)<=255)
green+=x
document.color.gr.value= green;
display()
}

function downgreen(x){
if ((green-x)>=0)
green-=x
document.color.gr.value= green;
display()
}

function upblue(x){
if ((blue+x)<=255)
blue+=x
document.color.bl.value= blue;
display()
}

function downblue(x){
if ((blue-x)>=0)
blue-=x
document.color.bl.value= blue;
display()
}

// done hiding -->
</script>
<form name="color">
<table>
```

```

<tr align="Center">
  <td>
    <input name="red" type="button" value=" +50 "
onClick="upred(50)">
  </td>
  <td>
    <input name="red2" type="button" value=" + 10 "
onClick="upred(10)">
  </td>
  <td>
    <input name="red2" type="button" value=" + 1"
onClick="upred(1)">
  </td>
  <td width="50"><font color="#FF0000" size=+3><b><font
color="#FA0000">±</font></b></font></td>
  <td>
    <input name="red-" type="button" value=" - 1"
onClick="downred(1)">
  </td>
  <td>
    <input name="red-" type="button" value=" - 10 "
onClick="downred(10)">
  </td>
  <td>
    <input name="red-" type="button" value=" -50 "
onClick="downred(50)">
  </td>
  <td>
    <input type="text" name="rd" size=3>
  </td>
</tr>
<tr align="Center">
  <td>
    <input name="green" type="button" value=" +50 "
onClick="upgreen(50)">
  </td>
  <td>
    <input name="green" type="button" value=" + 10 "
onClick="upgreen(10)">
  </td>
  <td>
    <input name="green" type="button" value=" + 1"
onClick="upgreen(1)">
  </td>

```

```

        <td width="50"><font color="#00FF00" size="+3"><b><font
color="#00FA00">绿</font></b></font></td>
        <td>
            <input name="green-" type="button" value=" - 1"
onClick="downgreen(1)">
        </td>
        <td>
            <input name="green-" type="button" value=" - 10 "
onClick="downgreen(10)">
        </td>
        <td>
            <input name="green-" type="button" value=" -50 "
onClick="downgreen(50)">
        </td>
        <td>
            <input type="text" name="gr" size=3>
        </td>
    </tr>
    <tr align="Center">
        <td>
            <input name="blue" type="button" value=" +50 "
onClick="upblue(50)">
        </td>
        <td>
            <input name="blue" type="button" value=" + 10 "
onClick="upblue(10)">
        </td>
        <td>
            <input name="blue" type="button" value=" + 1"
onClick="upblue(1)">
        </td>
        <td width="50"><font color="#0000FF" size="+3"><b><font
color="#0000FA">蓝</font></b></font></td>
        <td>
            <input name="blue-" type="button" value=" - 1"
onClick="downblue(1)">
        </td>
        <td>
            <input name="blue-" type="button" value=" - 10 "
onClick="downblue(10)">
        </td>
        <td>
            <input name="blue-" type="button" value=" -50 "
onClick="downblue(50)">

```

```

        </td>
        <td>
            <input type="text" name="b1" size=3>
        </td>
    </tr>
    <tr align="Center">
        <td> </td>
        <td> </td>
        <td> </td>
        <td width="50">
            <input type="text" name="rgbdsp1" size=7>
        </td>
        <td> </td>
        <td> </td>
        <td> </td>
        <td> </td>
    </tr>
</table>
</form>

```

鼠标使链接变色

脚本说明:

把如下代码加入<body>区域中

```
<script language="javascript">
```

```
<!--
```

```
function bgcolor(form){
```

```
    temp = ""
```

```
    for (var i = 0; i < 16; i++) {
```

```
        temp = form.color[i].value
```

```
        if (form.color[i].checked){ document.bgColor = temp }
```

```
    }
```

```
}
```



```
function randombackground(){

    document.bgColor = getColor()

}

function getColor(){

    currentdate = new Date()

    backgroundcolor = currentdate.getSeconds()

    if (backgroundcolor > 44)

        backgroundcolor = backgroundcolor - 45

    else if (backgroundcolor > 29)

        backgroundcolor = backgroundcolor - 30

    else if (backgroundcolor > 15)

        backgroundcolor = backgroundcolor - 16

    if (backgroundcolor == 0 )

        return "olive";

    else if (backgroundcolor == 1 )

        return "teal";

    else if (backgroundcolor == 2 )

        return "red";

    else if (backgroundcolor == 3 )

        return "blue";

    else if (backgroundcolor == 4 )

        return "maroon";
```

```
else if (backgroundcolor == 5 )
```

```
    return "navy";
```

```
else if (backgroundcolor == 6 )
```

```
    return "lime";
```

```
else if (backgroundcolor == 7 )
```

```
    return "fuschia";
```

```
else if (backgroundcolor == 8 )
```

```
    return "green";
```

```
else if (backgroundcolor == 9 )
```

```
    return "purple";
```

```
else if (backgroundcolor == 10 )
```

```
    return "gray";
```

```
else if (backgroundcolor == 11 )
```

```
    return "yellow";
```

```
else if (backgroundcolor == 12 )
```

```
    return "aqua";
```

```
else if (backgroundcolor == 13 )
```

```
    return "black";
```

```
else if (backgroundcolor == 14 )
```

```
    return "white";
```

```
else if (backgroundcolor == 15 )
```

```
    return "silver";
```

```
}
```

```
// -->
```

```
</script>
```

```
<a href=Upper1/default.htm onMouseOver=randombackground()>怀柔网</a>
```

跟随鼠标旋转背景

脚本说明:

把如下代码加入<body>区域中

```
<LAYER NAME="a0" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#ffffff"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a1" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#fff000"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a2" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#ffa000"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a3" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#ff00ff"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a4" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#00ff00"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a5" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#FF00FF"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a6" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#FF0000"
CLIP="0,0,1,1"></LAYER>
<LAYER NAME="a7" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#ffffff"
CLIP="0,0,2,2"></LAYER>
<LAYER NAME="a8" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#fff000"
CLIP="0,0,2,2"></LAYER>
<LAYER NAME="a9" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#ffa000"
CLIP="0,0,2,2"></LAYER>
<LAYER NAME="a10" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#ff00ff"
CLIP="0,0,2,2"></LAYER>
<LAYER NAME="a11" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#00ff00"
CLIP="0,0,2,2"></LAYER>
<LAYER NAME="a12" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#0000ff"
CLIP="0,0,2,2"></LAYER>
<LAYER NAME="a13" LEFT=10 TOP=10 VISIBILITY=SHOW BGCOLOR="#FF0000"
CLIP="0,0,3,3"></LAYER>
<div id="starsDiv" style="position:absolute;top:0px;left:0px">
<div
style="position:relative;width:1px;height:1px;background:#ffffff;font-size:1px;visibility:visible">
</div>
```

```
<div
style="position:relative;width:1px;height:1px;background:#fff000;font-size:1px;visibility:visible"
></div>
<div
style="position:relative;width:1px;height:1px;background:#ffa000;font-size:1px;visibility:visible"
></div>
<div
style="position:relative;width:1px;height:1px;background:#ff00ff;font-size:1px;visibility:visible"
></div>
<div
style="position:relative;width:1px;height:1px;background:#00ff00;font-size:1px;visibility:visible"
></div>
<div
style="position:relative;width:1px;height:1px;background:#0000ff;font-size:1px;visibility:visible"
></div>
<div
style="position:relative;width:1px;height:1px;background:#FF0000;font-size:1px;visibility:visible"
"></div>
<div
style="position:relative;width:2px;height:2px;background:#ffffff;font-size:2px;visibility:visible">
</div>
<div
style="position:relative;width:2px;height:2px;background:#fff000;font-size:2px;visibility:visible"
></div>
<div
style="position:relative;width:2px;height:2px;background:#ffa000;font-size:2px;visibility:visible"
></div>
<div
style="position:relative;width:2px;height:2px;background:#ff00ff;font-size:2px;visibility:visible"
></div>
<div
style="position:relative;width:2px;height:2px;background:#00ff00;font-size:2px;visibility:visible"
></div>
<div
style="position:relative;width:2px;height:2px;background:#0000ff;font-size:2px;visibility:visible"
></div>
<div
style="position:relative;width:3px;height:3px;background:#FF0000;font-size:3px;visibility:visible"
"></div>
</div>
<SCRIPT LANGUAGE="JavaScript">
<!-- Original: Kurt Grigg (kurt.grigg@virgin.net) -->
<!-- Web Site: http://freespace.virgin.net/kurt.grigg -->
```

<!-- This script and many more are available free online at -->
<!-- The JavaScript Source!! <http://javascript.internet.com> -->

```
<!-- Begin
var Clrs = new Array(6);
Clrs[0] = 'ff0000';
Clrs[1] = '00ff00';
Clrs[2] = '000aff';
Clrs[3] = 'ff00ff';
Clrs[4] = 'fff000';
Clrs[5] = 'fffff0';
var yBase = 200;
var xBase = 200;
var step;
var currStep = 0;
var Xpos = 1;
var Ypos = 1;
var Xs = 200;
var Ys = 400;
if (document.layers) {
window.captureEvents(Event.MOUSEMOVE);
}
if (document.all) {
function MoveHandler() {
Xpos = document.body.scrollLeft+event.x;
Ypos = document.body.scrollTop+event.y;
}
document.onmousemove = MoveHandler;
}
else if (document.layers) {
function xMoveHandler(evt) {
Xpos = evt.pageX;
Ypos = evt.pageY;
}
window.onMouseMove = xMoveHandler;
}
function Comet() {
if (document.all) {
yBase = window.document.body.offsetHeight / 4;
xBase = window.document.body.offsetWidth / 4;
}
else if (document.layers) {
yBase = window.innerHeight / 4;
xBase = window.innerWidth / 4;
```

```

}
if (document.all) {
for ( i = 0 ; i < starsDiv.all.length ; i++ ) {
step = 3;
starsDiv.all[i].style.top      =      Ypos      +      yBase*Math.cos((currStep      +
i*4)/12)*Math.cos(0.7+currStep/200);
starsDiv.all[i].style.left     =      Xpos      +      xBase*Math.sin((currStep      +
i*3)/10)*Math.sin(8.2+currStep/400);
for ( ai = 0; ai < Clrs.length; ai++ ) {
var c=Math.round(Math.random()*[ai]);
}
starsDiv.all[i].style.background = Clrs[c];
}
}
else if (document.layers) {
for ( j = 0 ; j < 14 ; j++ ) { //number of NS layers!
step = 6;
var templayer = "a"+j;
document.layers[templayer].top      =      Ypos      +      yBase*Math.cos((currStep      +
j*4)/12)*Math.cos(0.7+currStep/200);
document.layers[templayer].left     =      Xpos      +      xBase*Math.sin((currStep      +
j*3)/10)*Math.sin(8.2+currStep/400);
for ( aj=0; aj < Clrs.length; aj++ )
{
var c=Math.round(Math.random()*[aj]);
}
document.layers[templayer].bgColor = Clrs[c];
}
}
currStep += step;
setTimeout("Comet()", 5);
}
Comet();
// End -->
</script>

```

背景调色板

脚本说明:

把如下代码加入<body>区域中

```

<script language="JavaScript">
<!--

```

// Copyright (c) 1996-1997 Tomer Shiran. All rights reserved.

// Permission given to use the script provided that this notice remains as is.

```
// Additional scripts can be found at http://www.geocities.com/~yehuda/
```

```
// create 6-element array  
var hex = new Array(6)
```

```
// assign non-dithered descriptors
```

```
hex[0] = "FF"
```

```
hex[1] = "CC"
```

```
hex[2] = "99"
```

```
hex[3] = "66"
```

```
hex[4] = "33"
```

```
hex[5] = "00"
```

```
// accept triplet string and display as background color
```

```
function display(triplet) {
```

```
    // set color as background color
```

```
    document.backgroundColor = '#' + triplet
```

```
    // display the color hexadecimal triplet
```

```
    alert('现在的背景色是 #' + triplet)
```

```
}
```

```
// draw a single table cell based on all descriptors
```

```
function drawCell(red, green, blue) {
```

```
    // open cell with specified hexadecimal triplet background color
```

```
    document.write('<TD BGCOLOR="#" + red + green + blue + ">')
```

```
    // open a hypertext link with javascript: scheme to call display function
```

```
    document.write('<A HREF="javascript:display(\'" + (red + green + blue) + "\")">')
```

```
    // print transparent image (use any height and width)
```

```
    document.write('<IMG SRC="place.gif" BORDER=0 HEIGHT=12 WIDTH=12>')
```

```
    // close link tag
```

```
    document.write('</A>')
```

```
    // close table cell
```

```
    document.write('</TD>')
```

```
}
```

```
// draw table row based on red and blue descriptors
```

```
function drawRow(red, blue) {
```

```
    // open table row
```

```
    document.write('<TR>')
```

```

// loop through all non-dithered color descriptors as green hex
for (var i = 0; i < 6; ++i) {
    drawCell(red, hex[i], blue)
}

// close current table row
document.write('</TR>')
}

// draw table for one of six color cube panels
function drawTable(blue) {
    // open table (one of six cube panels)
    document.write('<TABLE CELLPADDING=0 CELLSPACING=0 BORDER=0>')

    // loop through all non-dithered color descriptors as red hex
    for (var i = 0; i < 6; ++i) {
        drawRow(hex[i], blue)
    }

    // close current table
    document.write('</TABLE>')
}

// draw all cube panels inside table cells
function drawCube() {
    // open table
    document.write('<TABLE CELLPADDING=5 CELLSPACING=0 BORDER=1><TR>')

    // loop through all non-dithered color descriptors as blue hex
    for (var i = 0; i < 6; ++i) {
        // open table cell with white background color
        document.write('<TD BGCOLOR="#FFFFFF">')

        // call function to create cube panel with hex[i] blue hex
        drawTable(hex[i])

        // close current table cell
        document.write('</TD>')
    }

    // close table row and table
    document.write('</TR></TABLE>')
}

```



```
// call function to begin execution
drawCube()
```

```
// -->
</script>
```

RGB颜色转换

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Original: John Downey (Genaztek@aol.com) -->
```

```
<!-- This script and many more are available free online at -->
```

```
<!-- The JavaScript Source!! http://javascript.internet.com -->
```

```
<!-- Begin
```

```
function showRGB(f) {
```

```
red = f.red.value;
```

```
green = f.green.value;
```

```
blue = f.blue.value;
```

```
var hexarray= new Array(256);
```

```
hexarray[0]="00"; hexarray[1]="01"; hexarray[2]="02";
```

```
hexarray[3]="03"; hexarray[4]="04"; hexarray[5]="05";
```

```
hexarray[6]="06"; hexarray[7]="07"; hexarray[8]="08";
```

```
hexarray[9]="09"; hexarray[10]="0A"; hexarray[11]="0B";
```

hexarray[12]="0C"; hexarray[13]="0D"; hexarray[14]="0E";
hexarray[15]="0F"; hexarray[16]="10"; hexarray[17]="11";
hexarray[18]="12"; hexarray[19]="13"; hexarray[20]="14";
hexarray[21]="15"; hexarray[22]="16"; hexarray[23]="17";
hexarray[24]="18"; hexarray[25]="19"; hexarray[26]="1A";
hexarray[27]="1B"; hexarray[28]="1C"; hexarray[29]="1D";
hexarray[30]="1E"; hexarray[31]="1F"; hexarray[32]="20";
hexarray[33]="21"; hexarray[34]="22"; hexarray[35]="23";
hexarray[36]="24"; hexarray[37]="25"; hexarray[38]="26";
hexarray[39]="27"; hexarray[40]="28"; hexarray[41]="29";
hexarray[42]="2A"; hexarray[43]="2B"; hexarray[44]="2C";
hexarray[45]="2D"; hexarray[46]="2E"; hexarray[47]="2F";
hexarray[48]="30"; hexarray[49]="31"; hexarray[50]="32";
hexarray[51]="33"; hexarray[52]="34"; hexarray[53]="35";
hexarray[54]="36"; hexarray[55]="37"; hexarray[56]="38";
hexarray[57]="39"; hexarray[58]="3A"; hexarray[59]="3B";
hexarray[60]="3C"; hexarray[61]="3D"; hexarray[62]="3E";
hexarray[63]="3F"; hexarray[64]="40"; hexarray[65]="41";
hexarray[66]="42"; hexarray[67]="43"; hexarray[68]="44";
hexarray[69]="45"; hexarray[70]="46"; hexarray[71]="47";
hexarray[72]="48"; hexarray[73]="49"; hexarray[74]="4A";
hexarray[75]="4B"; hexarray[76]="4C"; hexarray[77]="4D";

hexarray[78]="4E"; hexarray[79]="4F"; hexarray[80]="50";
hexarray[81]="51"; hexarray[82]="52"; hexarray[83]="53";
hexarray[84]="54"; hexarray[85]="55"; hexarray[86]="56";
hexarray[87]="57"; hexarray[88]="58"; hexarray[89]="59";
hexarray[90]="5A"; hexarray[91]="5B"; hexarray[92]="5C";
hexarray[93]="5D"; hexarray[94]="5E"; hexarray[95]="6F";
hexarray[96]="60"; hexarray[97]="61"; hexarray[98]="62";
hexarray[99]="63"; hexarray[100]="64"; hexarray[101]="65";
hexarray[102]="66"; hexarray[103]="67"; hexarray[104]="68";
hexarray[105]="69"; hexarray[106]="6A"; hexarray[107]="6B";
hexarray[108]="6C"; hexarray[109]="6D"; hexarray[110]="6E";
hexarray[111]="6F"; hexarray[112]="70"; hexarray[113]="71";
hexarray[114]="72"; hexarray[115]="73"; hexarray[116]="74";
hexarray[117]="75"; hexarray[118]="76"; hexarray[119]="77";
hexarray[120]="78"; hexarray[121]="79"; hexarray[122]="7A";
hexarray[123]="7B"; hexarray[124]="7C"; hexarray[125]="7D";
hexarray[126]="7E"; hexarray[127]="7F"; hexarray[128]="80";
hexarray[129]="81"; hexarray[130]="82"; hexarray[131]="83";
hexarray[132]="84"; hexarray[133]="85"; hexarray[134]="86";
hexarray[135]="87"; hexarray[136]="88"; hexarray[137]="89";
hexarray[138]="8A"; hexarray[139]="8B"; hexarray[140]="8C";
hexarray[141]="8D"; hexarray[142]="8E"; hexarray[143]="8F";

```
hexarray[144]="90"; hexarray[145]="91"; hexarray[146]="92";
```

```
hexarray[147]="93"; hexarray[148]="94"; hex -->-->
```

按钮驱动背景

脚本说明:

第一步:把如下代码加入<head>区域中

```
<script language="Javascript">
```

```
<!--
```

```
function bgcolor(form){
```

```
    temp = ""
```

```
    for (var i = 0; i < 16; i++) {
```

```
        temp = form.color[i].value
```

```
        if (form.color[i].checked){ document.bgColor = temp }
```

```
    }
```

```
    }
```

```
function randombackground(){
```

```
    document.bgColor = getColor()
```

```
    }
```

```
function getColor(){
```

```
    currentdate = new Date()
```

```
    backgroundcolor = currentdate.getSeconds()
```

```
    if (backgroundcolor > 44)
```

```
        backgroundcolor = backgroundcolor - 45
```

```
    else if (backgroundcolor > 29)
```

```
        backgroundcolor = backgroundcolor - 30
```

```
    else if (backgroundcolor > 15)
```

```
        backgroundcolor = backgroundcolor - 16
```

```
    if (backgroundcolor == 0 )
```

```
        return "olive";
```

```
    else if (backgroundcolor == 1 )
```

```
        return "teal";
```

```
    else if (backgroundcolor == 2 )
```

```
        return "red";
```

```
    else if (backgroundcolor == 3 )
```

```
        return "blue";
```

```
    else if (backgroundcolor == 4 )
```

```
        return "maroon";
```

```
else if (backgroundcolor == 5 )
    return "navy";
else if (backgroundcolor == 6 )
    return "lime";
else if (backgroundcolor == 7 )
    return "fuschia";
else if (backgroundcolor == 8 )
    return "green";
else if (backgroundcolor == 9 )
    return "purple";
else if (backgroundcolor == 10 )
    return "gray";
else if (backgroundcolor == 11 )
    return "yellow";
else if (backgroundcolor == 12 )
    return "aqua";
else if (backgroundcolor == 13 )
    return "black";
else if (backgroundcolor == 14 )
    return "white";
else if (backgroundcolor == 15 )
    return "silver";
}
```

```
// -->
</script>
```

第二步:把如下代码加入<body>区域中

```
<FORM>
<input type="button" value="Random" onClick="randombackground()">
</form>
```

颜色选择器

脚本说明:

把如下代码加入<body>区域中

```
<form>
<input type="button" Value="Click for Red" onClick="document.bgColor='red'">
<input type="button" Value="Click for Orange" onClick="document.bgColor='orange'">
<input type="button" Value="Click for Yellow" onClick="document.bgColor='yellow'">
<input type="button" Value="Click for Green" onClick="document.bgColor='green'">
<input type="button" Value="Click for Blue" onClick="document.bgColor='blue'">
<input type="button" Value="Click for Purple" onClick="document.bgColor='purple'">
</form>
```

精彩的变色文字

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
/* This script was made by Erik. You can contact him me worfy@geocities.com or at my homepage www.geocities.com/Area51/Corridor/4090. I know that it doesn't look pretty in the source code, but that couldn't be helped. Feel free to modify this script in any way but please give me credit. This is my first real script.
```

```
BTW for you yankees, I spell colour with the U because I'm Canadain.*/
```

```
hexa = new MakeArray(16)
hexa[10] = "A"
hexa[11] = "B"
hexa[12] = "C"
hexa[13] = "D"
hexa[14] = "E"
hexa[15] = "F"
```

```
function MakeArray(n)
{
this.length = n
for (var i = 0; i <= n; i++)
this[i] = i
return this
}
```

```
function colours(text){

var posa = 0
var posb = 1
while (posa <= text.length){
var r = Math.floor(Math.random() * 15)
var rr= Math.floor(Math.random() * 15)
var g = Math.floor(Math.random() * 15)
var gg = Math.floor(Math.random() * 15)
var b = Math.floor(Math.random() * 15)
var bb = Math.floor(Math.random() * 15)
if (text.substring(posa,posb) == "<"){
var posaa = 0
posaa = posa
```

```

while (text.substring(posaa,posb) != ">"){
posaa++
posb++
}
document.write(text.substring(posa, posb))
posa = posb
posb = posa + 1
}
document.write("<font color=#"+hexa[r]+hexa[rr]+hexa[g]+hexa[gg]+hexa[b]+hexa[bb]+">")
document.write(text.substring(posa, posb)+"</font>")
posaa++
posb++
}
}

```

</script>

```
<script language = "javascript">
```

```

text = "This JavaScript shows every other letter of text as a different, random colour."
text += "You can also use any <blink> <font size=9> HTML </font> </blink> codes that you
want"
text += " As long as you don't use quotation marks and the commands have a space between
them."
text += " You can use any background colour or picture that you want, but black or white is
sugeste"
text += "d <b> <u>HAVE FUN!!! </u> </b>"

```

```
colours(text)
```

</script>

radio颜色选择器

脚本说明:

把如下代码加入<body>区域中

```

<FORM METHOD="POST" NAME="bgcolor">
<font color="silver">click here</font><input type="radio" name="bgcolor"
ONCLICK="document.bgColor='silver'"><BR>
<font color="lightslategray">click here</font><input type="radio" name="bgcolor"
ONCLICK="document.bgColor='lightslategray'"><BR>
<font color="azure">click here</font><input type="radio" name="bgcolor"
ONCLICK="document.bgColor='azure'"><BR>
<font color="lightgreen">click here</font><input type="radio" name="bgcolor"
ONCLICK="document.bgColor='lightgreen'"><BR>

```

```
<font color="lightblue">click here</font><input type="radio" name="bgcolor"
ONCLICK="document.bgColor='lightblue'"><BR>
<font color="white">click here</font><input type="radio" name="bgcolor"
ONCLICK="document.bgColor='white'"><BR>
</form>
```

闪烁的霓虹灯

脚本说明：

第一步:把如下代码加入<body>区域中:

```
<SCRIPT LANGUAGE="JavaScript">

<!--

// create row of radio buttons
lay(20)

// set index of lamp to start animation
var current = 0

// set speed (pause in milliseconds between each movement)
var speed = 1000

function lay(num) {
    // assign "greater than" character to variable
    var gt = unescape("%3e")

    // open form
    document.write("<FORM NAME='animation'" + gt)

    // use loop to lay radio buttons down (all buttons in same group)
    for (var i = 0; i < num; ++i) {
        document.write("<INPUT TYPE='radio' NAME='lamps'" + gt)
    }

    // close form
    document.write("</FORM" + gt)
}

function animate() {
    // click next radio button
    document.animation.lamps[current].click()

    // if radio button is the last one reset variable to 0 (otherwise increment)
```



```

        current = (current == document.animation.lamps.length - 1) ? 0 : ++current

        // recursive call after speed milliseconds
        timerID = setTimeout("animate()", speed)
    }

    // -->

</SCRIPT>

```

第二步:把<body>中的内容改为

```
<body bgcolor="#ffffff" onLoad="animate()">
```

星星从背景中飞出

脚本说明：

第一步:把如下代码加入<head>区域中:

```

<style type="text/css">
.star {
position:absolute;
layer-background-color:white;
visibility:visible;
top:-50px;
width:50px;
height:50px;
font-size:1px;
background-color:white;
}
</style>
<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
var starnum = 175; // Number of stars
var isNS = (document.layers);
var _all = (isNS)? " : 'all.';
var _style = (isNS) ? " : '.style';
var xoffset, yoffset, w_x, w_y, tmpx, tmpy, scr1x, scrly;
function getstartpos(obj) {
obj.deltay = Math.floor(Math.random() * 12);
obj.deltax = Math.floor(Math.random() * 12);
obj.xdir = (Math.floor(Math.random() * 2) == 1) ? '+' : '-';
obj.ydir = (Math.floor(Math.random() * 2) == 1) ? '+' : '-';

```

```

obj.counter = 1;
if (isNS) {
obj.clip.width = 1;
obj.clip.height = 1;
obj.moveTo(xoffset+pageXOffset, yoffset+pageYOffset);
} else {
obj.width = 1;
obj.height = 1;
obj.pixelTop = yoffset+document.body.scrollTop;
obj.pixelLeft = xoffset+document.body.scrollLeft;
}
}
function movestar(starN) {
tmpx = starN.deltax*starN.counter+starN.counter;
tmpy = starN.deltay*starN.counter+starN.counter;
if (isNS) {
starN.clip.width = starN.counter / 3;
starN.clip.height = starN.counter / 3;
scrLx = pageXOffset;
scrLy = pageYOffset;
if ((starN.left+tmpx >= w_x+scrLx) || (starN.top+tmpy >= w_y+scrLy) || (starN.left-tmpx <= scrLx)
|| (starN.top-tmpy <= scrLy)) {
getstartpos(starN);
} else {
eval('starN.moveBy('+starN.xdir+tmpx+', '+starN.ydir+tmpy+')');
}
} else {
starN.width = starN.counter/3;
starN.height = starN.counter/3;
scrLx = document.body.scrollLeft;
scrLy = document.body.scrollTop;
if ((starN.pixelLeft+tmpx >= w_x+scrLx)||starN.pixelTop+tmpy >= w_y+scrLy) ||
(starN.pixelLeft-tmpx <= scrLx)||starN.pixelTop-tmpy <= scrLy) {
getstartpos(starN);
} else {
eval('starN.pixelTop'+starN.ydir+'=tmpy');
eval('starN.pixelLeft'+starN.xdir+'=tmpx');
}
}
starN.counter++;
}
function animate() {
for(i=1; i <= starnum; i++) {
movestar(eval('star'+i));
}
}

```

```

}
setTimeout('animate()', 100);
}
function findwindowparams() {
w_x = (isNS) ? window.innerWidth : document.body.clientWidth;
w_y = (isNS) ? window.innerHeight : document.body.clientHeight;
xoffset = w_x / 2;
yoffset = w_y / 2;
for (i = 1; i <= starnum; i++) {
getstartpos(eval('star'+i));
}
}
function resizeNS() {
setTimeout('document.location.reload()', 400);
}
(isNS) ? window.onresize = resizeNS : window.onresize = findwindowparams;
window.onload = new Function("findwindowparams(); animate();");
// End -->
</script>

```

第二步:把<body>中加入如下代码 :

```

<SCRIPT LANGUAGE="JavaScript">
<!-- Begin
for (i = 1; i <= starnum; i++) {
document.writeln('<div id="star'+i+'" class="star"></div>');
eval('var star'+i+'=document.'+_all+'star'+i+_style);
}
// End -->
</script>

```

背景向下移动 (二)

脚本说明 :

把如下代码加入<body>区域中:

```

<script language="JavaScript">
<!-- Begin
var backgroundOffset = 0;
var bgObject = eval('document.body');
function scrollBG(maxSize) {
backgroundOffset = backgroundOffset + 1;
if (backgroundOffset > maxSize) backgroundOffset = 0;
bgObject.style.backgroundColor = "0 " + backgroundOffset;
}

```

```
var ScrollTimer = window.setInterval("scrollBG(307)", 64);
// End -->
</script>
```

动态选择背景色

脚本说明：

把如下代码加入区域中：

```
<script language="JavaScript">
function color(frm, clr, val)
{
    v = eval("0x" + frm[clr].value) + val;
    if (v < 0 || v > 255) v -= val;
    v = v.toString(16).toUpperCase();
    while (v.length < 2) v = "0" + v;
    frm[clr].value = v; nc = "";
    for(i = 1; i < 8; i += 3) nc += frm.elements[i].value;
    document.bgColor = nc;
}

function setval(item)
{
    v = prompt("New value for " + item.name + " (00 - FF)", item.value);
    if (v)
    {
        v = eval("0x" + v);
        if ((v & 255) == v)
        {
            item.value=v.toString(16).toUpperCase();
            while (item.value.length < 2) item.value = "0" + item.value;
            color(document.f, item.name, 0);
        }
    }
}
</script>
<table border=1>
    <tr>
        <td colspan=3 align=center bgcolor="#ff0000">RED</td>
        <td colspan=3 align=center bgcolor="#00ff00">GREEN</td>
        <td colspan=3 align=center bgcolor="#000ff">BLUE</td>
    </tr>
    <tr>
        <td><input type=button name=rm value="<" onclick = "color(this.form, 'Red' ,
-1);"></td>
        <td><input type=button name=Red value="33" onclick = "setval(this);"></td>
```

```

1);"></td>
        <td><input type=button name=gm value="<" onclick = "color(this.form, 'Green',
-1);"></td>
        <td><input type=button name=Green value="66" onclick = "setval(this);"></td>
        <td><input type=button name=gp value=">" onclick = "color(this.form, 'Green',
1);"></td>
        <td><input type=button name=bm value="<" onclick = "color(this.form, 'Blue',
-1);"></td>
        <td><input type=button name=Blue value="99" onclick = "setval(this);"></td>
        <td><input type=button name=bp value=">" onclick = "color(this.form, 'Blue',
1);"></td>
    </tr>
</table>

```

下雨

脚本说明:

把如下代码加入<body>区域中

```

<script language="JavaScript">
<!--
var no = 50;
var speed = 1;
var ns4up = (document.layers) ? 1 : 0;
var ie4up = (document.all) ? 1 : 0;
var s, x, y, sn, cs;
var a, r, cx, cy;
var i, doc_width = 800, doc_height = 600;
if (ns4up) {
doc_width = self.innerWidth;
doc_height = self.innerHeight;
}
else
if (ie4up) {
doc_width = document.body.clientWidth;
doc_height = document.body.clientHeight;
}
x = new Array();
y = new Array();
r = new Array();
cx = new Array();
cy = new Array();
s = 8;
for (i = 0; i < no; ++ i) {
initRain();

```

```

if (ns4up) {
if (i == 0) {
document.write("<layer name=\"dot"+ i +"\" left=\"1\" ");
document.write("top=\"1\" visibility=\"show\"><font color=\"red\">");
document.write("</font></layer>");
}
else {
document.write("<layer name=\"dot"+ i +"\" left=\"1\" ");
document.write("top=\"1\" visibility=\"show\"><font color=\"red\">");
document.write("</font></layer>");
}
}
else
if (ie4up) {
if (i == 0) {
document.write("<div id=\"dot"+ i +"\" style=\"POSITION: ");
document.write("absolute; Z-INDEX: "+ i +"; VISIBILITY: ");
document.write("visible; TOP: 15px; LEFT: 15px;\"><font color=\"red\">");
document.write("</font></div>");
}
else {
document.write("<div id=\"dot"+ i +"\" style=\"POSITION: ");
document.write("absolute; Z-INDEX: "+ i +"; VISIBILITY: ");
document.write("visible; TOP: 15px; LEFT: 15px;\"><font color=\"red\">");
document.write("</font></div>");
}
}
}
function initRain() {
a = 6;
r[i] = 1;
sn = Math.sin(a);
cs = Math.cos(a);
cx[i] = Math.random() * doc_width + 1;
cy[i] = Math.random() * doc_height + 1;
x[i] = r[i] * sn + cx[i];
y[i] = cy[i];
}
function makeRain() {
r[i] = 1;
cx[i] = Math.random() * doc_width + 1;
cy[i] = 1;
x[i] = r[i] * sn + cx[i];
y[i] = r[i] * cs + cy[i];
}

```

```

}
function updateRain() {
r[i] += s;
x[i] = r[i] * sn + cx[i];
y[i] = r[i] * cs + cy[i];
}
function raindropNS() {
for (i = 0; i < no; ++ i) {
updateRain();
if ((x[i] <= 1) || (x[i] >= (doc_width - 20)) || (y[i] >= (doc_height - 20))) {
makeRain();
doc_width = self.innerWidth;
doc_height = self.innerHeight;
}
document.layers["dot"+i].top = y[i];
document.layers["dot"+i].left = x[i];
}
setTimeout("raindropNS()", speed);
}
function raindropIE() {
for (i = 0; i < no; ++ i) {
updateRain();
if ((x[i] <= 1) || (x[i] >= (doc_width - 20)) || (y[i] >= (doc_height - 20))) {
makeRain();
doc_width = document.body.clientWidth;
doc_height = document.body.clientHeight;
}
document.all["dot"+i].style.pixelTop = y[i];
document.all["dot"+i].style.pixelLeft = x[i];
}
setTimeout("raindropIE()", speed);
}
if (ns4up) {
raindropNS();
}
else
if (ie4up) {
raindropIE();
}

-->
</script>

```

按钮驱动背景变化

脚本说明：

把如下代码加入<body>区域中：

```
<script language="JavaScript">
var COLOR = 999999
var woot = 0
function stoploop()
{
    document.bgColor = '#336699';
    clearTimeout(loopID);
}
function loopBackground()
{
    if (COLOR > 0)
    {
        document.bgColor = '#' + COLOR
        COLOR -= 111111
        loopID = setTimeout("loopBackground()",1)
    }
    else
    {
        document.bgColor = '#336699'
        woot += 10
        COLOR = 999999
        COLOR -= woot
        loopID = setTimeout("loopBackground()",1)
    }
}
</script>
<input type="button" value="Start bgColor WARP" onClick="loopBackground()"><br>
<input type="button" value=" Stop bgColor WARP" onClick="stoploop()">
```

按钮使背景闪烁

脚本说明：

把如下代码加入<body>区域中：

```
<script language="JavaScript">
function blinkit()
{
    intrvl=0;
    for(nTimes=0;nTimes<3;nTimes++)
    {
        intrvl += 200;
        setTimeout("document.bgColor='#0000FF';",intrvl);
        intrvl += 200;
        setTimeout("document.bgColor='#336699';",intrvl);
    }
}
```



```
    }  
  }  
</script>  
  <input type="button" value="Blink" onClick="blinkit()">
```

背景随机显示

脚本说明：

把如下代码加入<head>区域中:

```
<SCRIPT language=javascript>  
<!--  
bg = new Array(2); //设定图片数量，如果图片数为 3，这个参数就设为 2，依次类推  
bg[0] = 'bag.gif' //显示的图片路径，可用 http://  
bg[1] = 'yellow.gif'  
bg[2] = 'xinxin.gif'  
index = Math.floor(Math.random() * bg.length);  
document.write("<BODY BACKGROUND="+bg[index]+">");  
  
//-->
```

```
</SCRIPT>
```

背景快速闪烁

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">  
  
<!-- Hide from old browsers  
var Color= new Array(9);  
Color[1] = "ff";  
Color[2] = "ee";  
Color[3] = "dd";  
Color[4] = "cc";  
Color[5] = "bb";  
Color[6] = "aa";  
Color[7] = "99";  
Color[8] = "88";  
Color[9] = "77";  
Color[10] = "66";  
Color[11] = "55";  
Color[12] = "44";  
Color[13] = "33";  
Color[14] = "22";  
Color[15] = "11";
```

```

Color[16] = "00";
/* Do not display text on a fading background. Instead, let it
fade in and out once or twice, then load a new page.          */
function fadeIn(when) {
if (when >= 1) {
document.bgColor="#" + Color[when] + "0000";
when -= 1;
setTimeout("fadeIn("+when+")", 15);
} else {
setTimeout('fadeOut(1)', 15);
}
}
function fadeOut(when) {
if (when <=16) {
document.bgColor="#" + Color[when] + "0000";
when += 1;
setTimeout("fadeOut("+when+")", 15)
} else {
setTimeout("fadeIn(16)", 15);
// window.location.href="http://www.netscape.com/";
}
}
// Unhide -->
</SCRIPT>

```

第二步:把<body>中的内容改为:

```
<body bgcolor="#ffffff" onLoad="fadeIn(16)">
```

自己选择背景图片

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```

<!-- Begin
if (navigator.appName == "Microsoft Internet Explorer") {
image_directory = "default.htm";
clear = new Image(); clear.src = image_directory + "clear.jpg";
pic1 = new Image(); pic1.src = image_directory + "chameleon.jpg";
pic2 = new Image(); pic2.src = image_directory + "gecko.jpg";
pic3 = new Image(); pic3.src = image_directory + "lizard.jpg";
pic4 = new Image(); pic4.src = image_directory + "toad.jpg";
}

```

```

function imagechange(imgName) {
if (navigator.appName == "Microsoft Internet Explorer") {
document.body.background = eval(imgName + ".src");
    }
}
// End -->
</script>
<a href="default.htm" onmouseover="imagechange('pic1');"
onmouseout="imagechange('clear');"></a>
<a href="default.htm" onmouseover="imagechange('pic2');"
onmouseout="imagechange('clear');"></a>
<a href="default.htm" onmouseover="imagechange('pic3');"
onmouseout="imagechange('clear');"></a>
<a href="default.htm" onmouseover="imagechange('pic4');"
onmouseout="imagechange('clear');"></a>

```

文本特效类

随机信息显示

脚本说明:

把如下代码加入<body>区域中

```

<script language="JavaScript">
<!-- Hide
var a = Math.random() + ""
var rand1 = a.charAt(5)
quotes = new Array
quotes[1] = '文本信息一'
quotes[2] = '文本信息二'
quotes[3] = '文本信息三'
quotes[4] = '文本信息四'
quotes[5] = '文本信息五'
quotes[6] = '文本信息六'
quotes[7] = '文本信息七'
quotes[8] = '文本信息八'
quotes[9] = '文本信息九'
quotes[0] = '文本信息十'
var quote = quotes[rand1]
//-->
</script>
<script language="JavaScript">
<!-- Hide
document.write( quote )
// -->

```

```
</script>
```

随机文本链接

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
<!--Hide from non JavaScript browsers
an = 3
var ran = Math.random();
var talet = Math.round(ran * (an-1))+1;
function create() {
    this.src = "

}

b = new Array()
for(var i=1; i<=an; i++) { b[i] = new create() }

b[1].src    = "<a href='Upper1/default.htm'>"
b[2].src    = "<a href='http://www.263.net'>"
b[3].src    = "<a href='http://www.163.com'>"
var vis = "";
vis += b[talet].src;
//-->
</script>

<script language="JavaScript">
<!--
document.write(vis+"随机文本链接+"</a>");
//-->
</script>
```

所有链接不停变色

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">

<!-- Begin

function initArray() {

for (var i = 0; i < initArray.arguments.length; i++) {
```

```
this[i] = initArray.arguments[i];

}

this.length = initArray.arguments.length;

}

var colors = new initArray(

"red",

"blue",

"green",

"purple",

"black",

"tan",

"red");

delay = .5; // seconds

link = 0;

vlink = 0;

function linkDance() {

link = (link+1)%colors.length;

vlink = (vlink+1)%colors.length;

document.linkColor = colors[link];

document.vlinkColor = colors[vlink];

setTimeout("linkDance()",delay*1000);

}
```

```
linkDance();
```

```
// End -->
```

```
</script>
```

```
<br>
```

```
<a href="http://www.263.net">首都在线</a> <a href="Upper1/default.htm">怀柔网</a>
```

```
<a href="http://www.163.net">163 电 子 邮 局 </a> <a href="http://www.sina.com.cn">新浪网</a>
```

鼠标经过文字变色

脚本说明:

把如下代码加入<body>区域中

```
<p onMouseMove="hello()">鼠标经过时就会变色的文本</p>
```

```
<script language="VBScript">
```

```
sub hello
```

```
document.fgColor=int(256*256*256*rnd)
```

```
end sub
```

```
</script>
```

随日期变换文本

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!-- Hide
```

```
var now = new Date();
```

```
var month = now.getMonth() + 1;
```

```
var date = now.getDate();
```

```
var year = now.getYear();
```

```
msgs = new Array
```

```
msgs[1] = "每月 1 号的信息"
```

```
msgs[2] = "每月 2 号的信息"
```

```
msgs[3] = "每月 3 号的信息"
```

```
msgs[4] = "每月 4 号的信息"
```

```
msgs[5] = "每月 5 号的信息"
```

```
msgs[6] = "每月 6 号的信息"
```

```
msgs[7] = "每月 7 号的信息"  
msgs[8] = "每月 8 号的信息"  
msgs[9] = "每月 9 号的信息"  
msgs[10] = "每月 10 号的信息"  
msgs[11] = "每月 11 号的信息"  
msgs[12] = "每月 12 号的信息"  
msgs[13] = "每月 13 号的信息"  
msgs[14] = "每月 14 号的信息"  
msgs[15] = "每月 15 号的信息"  
msgs[16] = "每月 16 号的信息"  
msgs[17] = "每月 17 号的信息"  
msgs[18] = "每月 18 号的信息"  
msgs[19] = "每月 19 号的信息"  
msgs[20] = "每月 20 号的信息"  
msgs[21] = "每月 21 号的信息"  
msgs[22] = "每月 22 号的信息"  
msgs[23] = "每月 23 号的信息"  
msgs[24] = "每月 24 号的信息"  
msgs[25] = "每月 25 号的信息"  
msgs[26] = "每月 26 号的信息"  
msgs[27] = "每月 27 号的信息"  
msgs[28] = "每月 28 号的信息"  
msgs[29] = "每月 29 号的信息"  
msgs[30] = "每月 30 号的信息"  
msgs[31] = "每月 31 号的信息"  
var msg = msgs[date]
```

```
//-->
```

```
</script>
```

```
<script>
```

```
<!--
```

```
document.write(msg);
```

```
//-->
```

```
</script>
```

文字颜色渐变脚本

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!-- Hide
```

```
function MakeArray(n){
```

```
    this.length=n;
```

```
    for(var i=1; i<=n; i++) this[i]=i-1;
```

```
    return this
```

```
}
```

```
hex=new MakeArray(16);
```

```
hex[11]="A"; hex[12]="B"; hex[13]="C"; hex[14]="D"; hex[15]="E"; hex[16]="F";
```



```
function ToHex(x){  
  
    var high=x/16;  
  
    var s=high+"";  
  
    s=s.substring(0,2);  
  
    high=parseInt(s,10);  
  
    var left=hex[high+1];  
  
    var low=x-high*16;  
  
    s=low+"";  
  
    s=s.substring(0,2);  
  
    low=parseInt(s,10);  
  
    var right=hex[low+1];
```

```
var string=left+""+right;

return string;

}

function rainbow(text){

text=text.substring(3,text.length-4);

color_d1=255;

mul=color_d1/text.length;

for(i=0;i < text.length;i++){

color_d1=255*Math.sin(i/(text.length/3)); "255*Math.sin(i/(text.length/3))"

color_h1=ToHex(color_d1);
```

```
color_d2=mul*i;
```

```
color_h2=ToHex(color_d2);
```

```
document.write("<FONT  
COLOR='#FF"+color_h1+color_h2+"'>"+text.substring(i,i+1)+'</FONT>');
```

```
}
```

```
}
```

```
// -->
```

```
</script>
```

```
<SCRIPT>
```

```
<!--
```

```
{rainbow("--> YOUR MESSAGE GOES HERE. THE LONG THE BETTER!<!--");}
```

```
//-->
```

```
</SCRIPT>
```

文本自动输出

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- Original: Tarjei Davidsen (the@rescueteam.com) -->
```

```
<!-- This script and many more are available free online at -->
```

```
<!-- The JavaScript Source!! http://javascript.internet.com -->
```

```
<!-- Begin
```

```
var max=0;
```

```
function textlist() {
```

```
max=textlist.arguments.length;
```

```
for (i=0; i<max; i++)
```

```
this[i]=textlist.arguments[i];
```

```
}
```

```
tl = new textlist(
```

```
" 随着 INTERNET 时代的逐步到来,人们对网络的认识与感知越来越深刻",
```

```
"上网主要是进行 web 页面浏览,所以 web 页面的精彩程度对一个网站的生",
```

```
"人通过制作个人主页展示自己的才华,而且,由于出现了多种制作网页的软件",
```

```
"但是,光用软件就成制作出你想要的各种页面效果吗?答案肯定是否定的但是,光用软件  
就成制作出你想要的各种页面效果吗?答案肯定是否定的",
```

```
"JavaScript 是 Netscape(网景)公司首先推出的一种针对 WEB 页面的解释型语"
```

```
);
```

```
var x = 0; pos = 0;
```

```
var l = tl[0].length;
```

```
function textticker() {
```

```
document.tickform.tickfield.value = tl[x].substring(0, pos) + "_";
```

```
if(pos++ == l) {
```

```
pos = 0;
```

```
setTimeout("textticker()", 2000);
```

```
if(++x == max) x = 0;
```

```
l = tl[x].length;
```

```
} else
```

```
setTimeout("textticker()", 50);
```

```
}  
// End -->  
</script>  
</HEAD>
```

第二步:把如下代码加入<body>区域中

```
<form name=tickform>  
<textarea name=tickfield rows=3 cols=38 style="background-color: rgb(0,0,0); color:  
rgb(255,255,255); cursor: default; font-family: Arial; font-size: 12px" wrap=virtual>The news will  
appear here when the page has finished loading.</textarea>  
</form>
```

第三步:把<body>改为

```
<body bgcolor="#ffffff" OnLoad="textticker()">
```

文字特效

脚本说明:

把如下代码加入<body>区域中

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: red; position: relative; filter:  
blur(add=1, direction=45, strength=3)">Welcome You</div>
```

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: red; position: relative; filter:  
glow(color=ffff00, strength=5)"> Welcome You</div>
```

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: red; position: relative; filter:  
dropshadow(color=000000, offx=3, offy=3, positive=1)"> Welcome You</div>
```

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: yellow; position: relative; filter:  
invert"> Welcome You</div>
```

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: red; position: relative; filter:  
xray"> Welcome You</div>
```

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: red; position: relative; filter:  
fliph">Welcome You</div>
```

```
<div style="width: 350; font-size:15pt; font-family: Arial ; color: red; position: relative; filter: flipv"> Welcome You</div>
```

文字不停变色

脚本说明：

把如下代码加入<body>区域中:

```
<SCRIPT language=JavaScript1.2>
<!-- Begin
function initArray() {
this.length = initArray.arguments.length;
for (var i = 0; i < this.length; i++) {
this[i] = initArray.arguments[i];
}
}
var ctext = "你好!欢迎您的光临,留下你宝贵意见!!!";
var speed = 2000;
var x = 0;
var color = new initArray(
"#ffff00",
"#ff0000",
"#ff00ff",
"#0000ff",
"#ffffff",
"#000000",
"#00ff00",
"#00ffff",
"#ff0ff0"
);
if(navigator.appName == "Netscape") {
document.write('<layer id="c"><center>'+ctext+'</center></layer><br>');
}
if (navigator.appVersion.indexOf("MSIE") != -1){
document.write('<div id="c"><center><b>'+ctext+'</b></center></div>');
}
function chcolor(){
if(navigator.appName == "Netscape") {
document.c.document.write('<center><font color="'+color[x]');
document.c.document.write('>'+ctext+'</font></center>');
document.c.document.close();
}
else if (navigator.appVersion.indexOf("MSIE") != -1){
document.all.c.style.color = color[x];
}
}
```

```
(x < color.length-1) ? x++ : x = 0;
}
setInterval("chcolor()",1000);
// End -->
</SCRIPT>
```

字符连续消隐

脚本说明：

第一步:把如下代码加入<head>区域中:

```
<SCRIPT>
```

```
messages = new Array()
messages[0] = "你好,最近忙吗?"
messages[1] = "欢迎你的到来"
messages[2] = "请多呆一会"
messages[3] = "你一定会有所收获的"
messages[4] = "Netscape Navigator 不太支持这个"
```

```
mescolor = new Array()
mescolor[0] = "000000"
mescolor[1] = "FF0000"
mescolor[2] = "008800"
mescolor[3] = "0000FF"
mescolor[4] = "888800"
```

```
messize = new Array()
messize[0] = "30pt"
messize[1] = "40pt"
messize[2] = "50pt"
messize[3] = "30pt"
messize[4] = "20pt"
```

```
var i_messages = 0
var timer
```

```
function dotransition() {
  if (document.all) {
    content.filters[0].apply()
    content.innerHTML = "
```

```

    }
    else {
        i_messages++
    }
}

if (document.layers) {
    document.content.document.write("<span
style='color:"+mescolor[i_messages]+">"+messages[i_messages]+"</span>")
    if (i_messages >= messages.length-1) {
        i_messages = 0
    }
    else {
        i_messages++
    }
}
timer = setTimeout("dotransition()",5000)
}

</SCRIPT>

```

第二步:把<body>中加入如下代码 :

```

<DIV id=content
style="FILTER: revealTrans(Transition=12, Duration=2); HEIGHT: 200px; LEFT: 93px;
POSITION: absolute; TEXT-ALIGN: center; TOP: 21px; WIDTH: 559px"></DIV>

```

第三步 : 把<body>中内容改为 :

```

<body bgcolor="#ffffff" onLoad="show3()">

```

公告栏

脚本说明:

第一步 : 把如下代码加入<head>区域中

```

<script language="JavaScript">
<!-- Activate Cloaking Device

```

```

var i = 0;
// used to cycle thru messages
var TextNumber = -1;
// array of messages
var TextInput = new Object();
// used to load manipulate message

```



```

var HelpText="";
// used to load message
var Text = "";
// length of timeout (smaller is faster)
var Speed=50;
// used to display message number
var message=0;
// used to position text in ver 2.0
var addPadding="\r\n";

// Each element of TextInput represents a single message.
TextInput[0] = "今天注意了有新的任务布置";
TextInput[1] = "欢迎你的光临！本站为你提供大量 javascript 下载";
TextInput[2] = "重点介绍 Javascript";
TextInput[3] = "与制作网页特效密切相关的技术";
TextInput[4] = "本站同时有影音空间等栏目";
TextInput[5] = "还有新闻及健康方面的资料";
TextInput[6] = "还有宽带网方面的大量技术文章";
TextInput[7] = "本站网址：http://www.hrw.cn";

TotalTextInput = 7; // (0, 1, 2, 3, 4, 5, 6, 7)

// Positioning and speed vary between versions.
var Version = navigator.appVersion;
if (Version.substring(0, 1)==3)
{
Speed=200;
addPadding="";
}

for (var addPause = 0; addPause <= TotalTextInput; addPause++)
{TextInput[addPause]=addPadding+TextInput[addPause];}
var TimerId
var TimerSet=false;

// Called by >>> button (display next message) .
function nextMessage()
{
if (!TimerSet)
{
TimerSet=true;
clearTimeout (TimerId);
if (TextNumber>=TotalTextInput)
{

```

```

alert("This is the end of the list!");
TimerSet=false;
}
else
{
TextNumber+=1;
message=TextNumber+1;
document.forms[0].elements[2].value= message;
Text = TextInput[TextNumber];
HelpText = Text;
}
teletype();
}
}

// Gets and displays character from rollMessage() .
// Variable Speed controls length of timeout and thus the speed of typing.
function teletype()
{
if (TimerSet)
{
Text=rollMessage();
TimerId = setTimeout("teletype()", Speed);
document.forms[0].elements[0].value=Text;
}
}

// Pulls one character at a time from string and returns (as Text) to function teletype() for
displaying.
function rollMessage ()
{
i++;
var CheckSpace = HelpText.substring(i-1, i);
CheckSpace = "" + CheckSpace;
if (CheckSpace == " ")
{i++;}
if (i >= HelpText.length+1)
{
TimerSet=false;
Text = HelpText.substring(0, i);
i=0;
return (Text);
}
Text = HelpText.substring(0, i);

```

```

return (Text);
}
// Initially called by onLoad in BODY tag to load title.
function initTeleType()
{
Text="\r\n Manual Tele-Type Display";
document.forms[0].elements[0].value=Text;
}
// Called by <<< button (get previous message).
function lastMessage()
{
if (!TimerSet && TextNumber!=-1)
{
TimerSet=true;
clearTimeout (TimerId);
if (TextNumber<=0)
{
alert("This is the beginning of the list!");
TimerSet=false;
}
else
{
TextNumber-=1;
message=TextNumber+1;
document.forms[0].elements[2].value= message;
Text = TextInput[TextNumber];
HelpText = Text;
}
teletype();
}
}
}

// Deactivate Cloaking --></script>

```

第二步：在<body>区域中加入如下代码：

```

<form>
<table CELLSPACING="0" CELLPADDING="0" WIDTH="17%">
<tr>
<td width="100%" colspan="3" valign="top"><div align="center"><p><textarea
NAME="teletype" ROWS="3" COLS="28" wrap="yes"></textarea> </td>
</tr>
<tr align="center">
<td width="40%" valign="top" bgcolor="#0000A0"><input TYPE="button" VALUE="公告栏"

```

```
onClick="lastMessage()"></td>
<td width="30%" bgcolor="#0000A0" valign="top"><input TYPE="text" value="共 8 条"
SIZE="5" name="1"></td>
<td width="30%" bgcolor="#0000A0" valign="top"><input TYPE="button" VALUE="阅 读"
onClick="nextMessage()"></td>
</tr>
</table>
</form>
```

文字动态变化

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT language=JavaScript><!-- Begin
```

```
var speed = 20;
```

```
var cycledelay = 1000;
```

```
var maxsize = 48;
```

```
var x = 0;
```

```
var y = 0;
```

```
var themessage, size;
```

```
var esize = "";
```

```
function initArray() {
```

```
  this.length = initArray.arguments.length;
```

```
  for (var i = 0; i < this.length; i++) {
```

```
    this[i] = initArray.arguments[i];
```

```
  }
```

```
}

var themessage2 = new initArray(

"欢迎访问.....",

"网页之作.....",

"飘蓝工作室向你问好.....!",

"谢谢你的访问....."

);

if(navigator.appName == "Netscape")

document.write('<layer id="wds"></layer><br>');

if (navigator.appVersion.indexOf("MSIE") != -1)

document.write('<span id="wds"></span><br>');

function upwords(){

themessage = themessage2[y];

if (x < maxsize) {

x++;

setTimeout("upwords()",speed);

}

else setTimeout("downwords()",cycledelay);

if(navigator.appName == "Netscape") {

size = "<font point-size="+x+"pt">";

document.wds.document.write(size+"<center>"+themessage+"</center>"+esize);
```

```
document.wds.document.close();

}

if (navigator.appVersion.indexOf("MSIE") != -1){

wds.innerHTML = "<center>"+themessage+"</center>";

wds.style.fontSize=x+'px'

    }

}

function downwords(){

if (x > 1) {

x--;

setTimeout("downwords()",speed);

}

else {

setTimeout("upwords()",cycledelay);

y++;

if (y > themessage2.length - 1) y = 0;

}

if(navigator.appName == "Netscape") {

size = "<font point-size=""+x+"pt">";

document.wds.document.write(size+"<center>"+themessage+"</center>" +size);

document.wds.document.close();

}
```

```
if (navigator.appVersion.indexOf("MSIE") != -1){

wds.innerHTML = "<center>"+themessage+"</center>";

wds.style.fontSize=x+'px'

    }

}

setTimeout("upwords()",speed);

// End -->
```

```
</SCRIPT>
```

文字特殊显示

脚本说明：

把如下代码加入<body>区域中：

```
<script language="JavaScript">
<!--
```

```
IE4    =    navigator.appName    ==    "Microsoft    Internet    Explorer"    &&
parseInt(navigator.appVersion) >= 4;
NS4 = navigator.appName.substring(0,8) == "Netscape" && parseInt(navigator.appVersion) >= 4;
```

```
// checkBrowser() -- Checks whether the browser is new enough for some DynamicMovement ...
```

```
function checkBrowser(){
    if(IE4 || NS4){
        return true;
    }
    return false;
}
```

```
// movableObj() -- Creates a new movable object
```

```
function movableObj(startX, startY, endX, endY, delay, speed, refId){
    this.sX = startX; this.sY = startY; this.eX = endX;
    this.eY = endY;    this.de = delay; this.sp = speed;
    this.ref = refId;
    xL = endX - startX;
    yL = endY - startY;
```

```

with (Math){
    if(abs(xL) > abs(yL)){
        this.xS = (xL > 0)?1:-1;
        this.yS = (yL > 0)?abs(yL / xL):-abs(yL / xL);
        this.howManySteps = abs(xL / speed);
    } else if(abs(yL) > abs(xL)){
        this.yS = (yL > 0)?1:-1;
        this.xS = (xL > 0)?abs(xL / yL):-abs(xL / yL);
        this.howManySteps = abs(yL / speed);
    } else {
        this.yS = (yL > 0)?1:-1;
        this.xS = (xL > 0)?1:-1;
        this.howManySteps = abs(xL / speed);
    }
}
this.startMovement = startMovement;
}

// startMovement() -- starts the movement

function startMovement(){
    if(checkBrowser()){
        if(IE4){
            ref = document.all(this.ref).style;
        } else {
            ref = document[this.ref];
        }
        doDynamicMovement(this.sX, this.sY, this.eX, this.eY, this.de, this.xS, this.yS, ref,
this.sp, this.howManySteps);
    }
}

// doDynamicMovement() -- does the Dynamic Movement

function doDynamicMovement(curX, curY, eX, eY, sp, xS, yS, ref, speed, hS){
    if(Math.floor(hS - 1) != 0){
        hS--;
        curX += xS * speed;
        curY += yS * speed;
        ref.left = Math.round(curX);
        ref.top = Math.round(curY);
        setTimeout("doDynamicMovement(" + curX + ", " + curY + ", " + eX + ", " + eY + ", "
+ sp + ", " + xS + ", " + yS + ", ref, " + speed + ", " + hS + ")", sp);
    } else {

```



```

        setPos(eX, eY, ref);
    }
}

// setPos() -- sets the end position accurately when doDynamicMovement has done its job

function setPos(x, y, ref){
    ref.left = x;
    ref.top = y;
}

// -->
</script>

<table width="600">
    <tr>
        <td><font face="Verdana, Arial"><h3>    </h3>
        <font size="2"><form>
            <div align="center"><center><p><input type="button"
onClick="dynaText.startMovement()"
value="按下去看看"> </p>
            </center></div>
        </form>
        <p>    </font></p>
        <div id="wow"
style="position: absolute; left: -100; top: -100; width: 300;
font-family: Verdana, Arial; font-size: 20pt"><p>欢迎光临南京有线台!
        </font></p>
        </div></td>
    </tr>
</table>
<script language="JavaScript">
<!--

// Here we define the movable object
dynaText = new movableObj(-100,-100,80,180,10,10,"wow");

// -->
</script>

```

文字从旁边出现

脚本说明：

第一步:把如下代码加入<head>区域中:

```

<script LANGUAGE="JavaScript" FCTYPE="mydynamicanimation">
<!--
dynamicanimAttr = "mydynamicanimation"
animateElements = new Array()
currentElement = 0
speed = 0
stepsZoom = 8
stepsWord = 8
stepsFly = 12
stepsSpiral = 16
steps = stepsZoom
step = 0
outString = ""
function mydynAnimation()
{
    var ms = navigator.appVersion.indexOf("MSIE")
    ie4 = (ms>0) && (parseInt(navigator.appVersion.substring(ms+5, ms+6)) >= 4)
    if(!ie4)
    {
        if((navigator.appName == "Netscape") &&
            (parseInt(navigator.appVersion.substring(0, 1)) >= 4))
        {
            for (index=document.layers.length-1; index >= 0; index--)
            {
                layer=document.layers[index]
                if (layer.left==10000)
                    layer.left=0
            }
        }
        return
    }
    for (index=document.all.length-1; index >= document.body.sourceIndex; index--)
    {
        el = document.all[index]
        animation = el.getAttribute(dynamicanimAttr, false)
        if(null != animation)
        {
            if(animation == "dropWord" || animation == "flyTopRightWord" || animation ==
"flyBottomRightWord")
            {
                ih = el.innerHTML
                outString = ""
                i1 = 0
                iend = ih.length

```

```

while(true)
{
    i2 = startWord(ih, i1)
    if(i2 == -1)
        i2 = iend
    outWord(ih, i1, i2, false, "")
    if(i2 == iend)
        break
    i1 = i2
    i2 = endWord(ih, i1)
    if(i2 == -1)
        i2 = iend
    outWord(ih, i1, i2, true, animation)
    if(i2 == iend)
        break
    i1 = i2
}
document.all[index].innerHTML = outString
document.all[index].style.posLeft = 0
document.all[index].setAttribute(dynamicanimAttr, null)
}
if(animation == "zoomIn" || animation == "zoomOut")
{
    ih = el.innerHTML
    outString = "<SPAN " + dynamicanimAttr + "=\"" + animation + "\" style=\"position:
relative; left: 10000px;\">"
    outString += ih
    outString += "</SPAN>"
    document.all[index].innerHTML = outString
    document.all[index].style.posLeft = 0
    document.all[index].setAttribute(dynamicanimAttr, null)
}
}
}
i = 0
for (index=document.body.sourceIndex; index < document.all.length; index++)
{
    el = document.all[index]
    animation = el.getAttribute(dynamicanimAttr, false)
    if (null != animation)
    {
        if(animation == "flyLeft")
        {
            el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth

```

```

    el.style.posTop = 0
  }
  else if(animation == "flyRight")
  {
    el.style.posLeft = 10000-offsetLeft(el)+document.body.offsetWidth
    el.style.posTop = 0
  }
  else if(animation == "flyTop" || animation == "dropWord")
  {
    el.style.posLeft = 0
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
  }
  else if(animation == "flyBottom")
  {
    el.style.posLeft = 0
    el.style.posTop =
document.body.scrollTop-offsetTop(el)+document.body.offsetHeight
  }
  else if(animation == "flyTopLeft")
  {
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
  }
  else if(animation == "flyTopRight" || animation == "flyTopRightWord")
  {
    el.style.posLeft = 10000-offsetLeft(el)+document.body.offsetWidth
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight
  }
  else if(animation == "flyBottomLeft")
  {
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop =
document.body.scrollTop-offsetTop(el)+document.body.offsetHeight
  }
  else if(animation == "flyBottomRight" || animation == "flyBottomRightWord")
  {
    el.style.posLeft = 10000-offsetLeft(el)+document.body.offsetWidth
    el.style.posTop =
document.body.scrollTop-offsetTop(el)+document.body.offsetHeight
  }
  else if(animation == "spiral")
  {
    el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
    el.style.posTop = document.body.scrollTop-offsetTop(el)-el.offsetHeight

```

```

    }
    else if(animation == "zoomIn")
    {
        el.style.posLeft = 10000
        el.style.posTop = 0
    }
    else if(animation == "zoomOut")
    {
        el.style.posLeft = 10000
        el.style.posTop = 0
    }
    else
    {
        el.style.posLeft = 10000-offsetLeft(el)-el.offsetWidth
        el.style.posTop = 0
    }
    el.initLeft = el.style.posLeft
    el.initTop = el.style.posTop
    animateElements[i++] = el
}
}
window.setTimeout("animate();", speed)
}
function offsetLeft(el)
{
    x = el.offsetLeft
    for (e = el.offsetParent; e; e = e.offsetParent)
        x += e.offsetLeft;
    return x
}
function offsetTop(el)
{
    y = el.offsetTop
    for (e = el.offsetParent; e; e = e.offsetParent)
        y += e.offsetTop;
    return y
}
function startWord(ih, i)
{
    for(tag = false; i < ih.length; i++)
    {
        c = ih.charAt(i)
        if(c == '<')
            tag = true
    }
}

```

```

    if(!tag)
        return i
    if(c == '>')
        tag = false
    }
    return -1
}
function endWord(ih, i)
{
    nonSpace = false
    space = false
    while(i < ih.length)
    {
        c = ih.charAt(i)
        if(c != ' ')
            nonSpace = true
        if(nonSpace && c == ' ')
            space = true
        if(c == '<')
            return i
        if(space && c != ' ')
            return i
        i++
    }
    return -1
}
function outWord(ih, i1, i2, dyn, anim)
{
    if(dyn)
        outString += "<SPAN " + dynamicanimAttr + "=\"" + anim + "\" style=\"" + position: relative;
left: 10000;\">"
    outString += ih.substring(i1, i2)
    if(dyn)
        outString += "</SPAN>"
}
function animate()
{
    el = animateElements[currentElement]
    animation = el.getAttribute(dynamicanimAttr, false)
    step++
    if(animation == "spiral")
    {
        steps = stepsSpiral
        v = step/steps
    }
}

```

```

    rf = 1.0 - v
    t = v * 2.0*Math.PI
    rx = Math.max(Math.abs(el.initLeft), 200)
    ry = Math.max(Math.abs(el.initTop), 200)
    el.style.posLeft = Math.ceil(-rf*Math.cos(t)*rx)
    el.style.posTop = Math.ceil(-rf*Math.sin(t)*ry)
  }
  else if(animation == "zoomIn")
  {
    steps = stepsZoom
    el.style.fontSize = Math.ceil(50+50*step/steps) + "%"
    el.style.posLeft = 0
  }
  else if(animation == "zoomOut")
  {
    steps = stepsZoom
    el.style.fontSize = Math.ceil(100+200*(steps-step)/steps) + "%"
    el.style.posLeft = 0
  }
  else
  {
    steps = stepsFly
    if(animation == "dropWord" || animation == "flyTopRightWord" || animation ==
"flyBottomRightWord")
      steps = stepsWord
    dl = el.initLeft / steps
    dt = el.initTop / steps
    el.style.posLeft = el.style.posLeft - dl
    el.style.posTop = el.style.posTop - dt
  }
  if (step >= steps)
  {
    el.style.posLeft = 0
    el.style.posTop = 0
    currentElement++
    step = 0
  }
  if(currentElement < animateElements.length)
    window.setTimeout("animate();", speed)
}
//-->
</script>

```

第二步:把<body>中加入如下代码:

```
<p align="center" mydynamicanimation="flyTopRightWord"
style="position: relative !important; left: 10000 !important"><strong><big><big><font
face="Arial"> 欢 迎 光 临 <a href="Upper1/default.htm"> 怀 柔 网 </a> 谢
谢!</font></big></big></strong></p>
```

第三步:把<body>中内容改为:

```
<body bgcolor="#ffffff" onload="mydynAnimation()">
```

文本从右向左输出

脚本说明:

第一步:把如下代码加入<head>区域中

```
<SCRIPT LANGUAGE="JavaScript1.2">
```

```
<!-- Begin
var l1 = 0; // left of ticker in pixel, or 0 to position relative
var t1 = 0; // top of ticker in pixel, or 0 to position relative
var w1 = 400; // width of ticker in pixel
var ie = document.all ? true : false;
var first = true;
var l2 = l1 + w1;
var l3 = l1 - l2;
var l = l2;
function tickinit() {
if (ie) {
if (l1 == 0 && t1 == 0) {
pos = document.all['tickpos'];
l1 = getLeft(pos);
t1 = getTop(pos);
}
ticktext.style.posTop = t1;
}
else {
if (l1 == 0 && t1 == 0) {
pos = document.anchors['tickpos'];
l1 = pos.x;
t1 = pos.y;
}
document.ticktext.pageY = t1;
```



```

}
l2 = l1 + w1;
l3 = l1 - l2;
l = l2;
setInterval('tick()', 10);
}
function getLeft(l) {
if (l.offsetParent)
return (l.offsetLeft + getLeft(l.offsetParent));
else
return (l.offsetLeft);
}
function getTop(l) {
if (l.offsetParent)
return (l.offsetTop + getTop(l.offsetParent));
else
return (l.offsetTop);
}
function tick() {
l = l - 0.5;
if (l < l3) l = l2;
cl = l1 - l;
cr = l2 - l;
if (ie) {
ticktext.style.posLeft = l;
ticktext.style.posTop = t1;
ticktext.style.clip = "rect(auto "+cr+"px auto "+cl+"px)";
if (first) ticktext.style.visibility = "visible";
}
else {
document.ticktext.pageX = l;
document.ticktext.clip.left = cl;
document.ticktext.clip.right = cr;
if (first) document.ticktext.visibility = "show";
}
first = false;
}
// End -->
</script>

```

第二步:把如下代码加入<body>区域中

```
<a name="tickpos"> </a>
```

```
<div id="ticktext" style="position:absolute;font-family:arial;font-size:14pt;visibility:hidden;">
<nobr>Doesn't this message scroller look great? You can even insert links like this: <a
href="http://www.yahoo.com" target="_blank">yahoo.com</a> Now it repeats.</nobr>
</div>
```

第三步:把<body>中的内容改为:

```
<body bgcolor="#ffffff" OnLoad="tickinit()">
```

消息显示器

脚本说明:

把如下代码加入<body>区域中:

```
<script language="Javascript">
```

```
<!--
```

```
numQuotes=42;
```

```
quoteArray = new Array(numQuotes);
```

```
quoteArray[0]="Great spirits have always encountered violentopposition from mediocre
minds.\" -Albert Einstein";
```

```
quoteArray[0]="男孩不坏女孩不爱。真的是这样的话，那就要看男孩是坏在哪里，而女孩又是谁了。";
```

```
quoteArray[1]="不知从何时开始，到处都流传着一句爱情名言：“男孩不坏女孩不爱！”。
```

```
quoteArray[2]="在瞧了金庸先生的封笔之作《鹿鼎记》后，笔者更是颇有些感触"
```

```
quoteArray[3]="坏男孩该是副什么模样呢？也许就如同《鹿鼎记》中的韦小宝一般吧，一个精灵跳脱的小无赖？"
```

```
quoteArray[4]="他能哄就哄，能骗就骗，侠士嘛说不上，高人嘛更是做不得。"
```

```
quoteArray[5]="但是，小无赖也罢，坏男孩也罢，这种男孩具有一种让女孩子们不能不接受的求爱精神，即“三疯精神”，叫“猎狗、疯狗、赖皮狗”，物色对象时象猎狗，求爱时像疯狗，耗上了像赖皮狗。"
```

```
quoteArray[6]="虽说这提法有些过分偏激之处，却也正点中了要害。如果真的认真按此精神去对付女孩子，恐怕无一幸免了。"
```

```
quoteArray[7]="坏男孩到底用了什么手段那么能招人爱呢？这正如雅俗之分。"
```

```
quoteArray[8]="雅，好象是高人一等的，所谓“阳春白雪”者；俗，好象是低人一等的，所谓“下里巴人”者也。"
```

```
quoteArray[9]="然而高人一等者，“国中属而和者不过数十人”；低人一等者，“国中属而和者数千人”。究竟谁高谁低，不可"
```

```
quoteArray[10]="妄评，各人喜好而已。但毕竟还是俗人多啊！"
```

```
quoteArray[11]="韦小宝就是个纯纯粹粹的俗人，俗得不能再俗了，其实也是世间每一个俗人的影子、劣根。是人都有欲，有欲则必有争，不争才是虚伪的很，那么剩下的就是用何种手段去争了。"
```

```
quoteArray[12]="小宝用的也算是一种方法啊，不论黑猫白猫，只要抓到老鼠就是好猫嘛"
```

```
quoteArray[13]="韦小宝好象还缺了点“英俊”，若是能把这点也加上了，小宝可就是“大众情人”啦！"
```

```
quoteArray[14]="话又说回来，如果让你在英俊却死板的男孩和韦小宝之间做个爱情选择，
```

恐怕你会脱口而出：“选那个可恨又可爱的小宝”呢！”

quoteArray[15]="你瞧，他聪明伶俐，了解人情世故，又会见风使舵，讨女孩的欢心，还深谙处世之道。"

quoteArray[16]="本来么，小宝也不是什么罪大恶极的坏人。"

quoteArray[17]="他这个“坏”，坏得有学问，有原则，有所为而有所不为。"

quoteArray[18]="他可以偷抢拐骗，但那要看是对什么人"

quoteArray[19]="对吴应熊那群卖国贼、四处收刮民脂民膏的人该贪就贪，该拿就拿，何况小宝还懂得钱财乃身外之物，对于天地会和交友的费用他是豪爽大方，丝毫不吝啬，该给就给，该送就送了。"

quoteArray[20]="小宝还很知道讲良心，讲义气，杀小人，宁死也不出卖朋友，这可是做人最基本的准则。"

quoteArray[21]="在对待康熙和陈近南两个对立面时，小宝更是大显神通可算是忠义两全之士了。"

quoteArray[22]="他和康熙可算是总角之交，其间的友谊真挚而坚定，中有地位的悬殊却是牢不可破的。"

quoteArray[23]="因此一涉及到对康熙不利的事，他是绝对不干的，还想主设法地从中作梗。"

quoteArray[24]="对陈近南他也同样够义气，陈近南和天地会是一体性的，对陈近南忠就是对天地会忠。"

quoteArray[25]="当康熙要小宝剿灭天地会时，小宝说出一番道理来：“皇上，他们要来害你，我拼命阻挡，奴才对你是讲义气的。"

quoteArray[26]="皇上要去拿他们，奴才夹在中间，难以做人，只好向你求情，那也是讲义气。"

quoteArray[27]="我拜你为师……那陈近南也是我师父，我如存心害你，那是欺师灭祖。"

quoteArray[28]="我如去害那个师父，也是欺师灭宗……。"

quoteArray[29]="这个道理十分简单，谁都想得出，可又有几人能真正做的到？"

quoteArray[30]="小宝为了这个道理不要高官，不要厚禄，甚至连性命也可以豁出去了，于是康熙虽是恼怒，却也敬重他为人有义。"

quoteArray[31]="旁观者虽瞧你行为话语不耻，却也不得不佩服。"

quoteArray[32]="于是在金庸先生笔下，只要跟小宝作对之人，均无什么好下场，都同风际中一样自取灭亡。"

quoteArray[33]="也许小宝还够不上潇洒，但他在这个世俗社会里为人处事的游刃有余，是谁也比不上的。"

quoteArray[34]="那么，说句真心话，在这世俗社会中，若真的有一个如小宝一样既能赚钱，又会花钱"

quoteArray[35]="会玩会闹会逗你天心，骨子里也讲点良心、义气的俗人，你会不会喜欢他？爱他？"

quoteArray[36]="嘻，“男孩不坏，女孩不爱”嘛！"

quoteArray[37]="小宝为了这个道理不要高官，不要厚禄，甚至连性命也可以豁出去了，于是康熙虽是恼怒，却也敬重他为人有义"

quoteArray[38]="旁观者虽瞧你行为话语不耻，却也不得不佩服。"

quoteArray[39]="于是在金庸先生笔下，只要跟小宝作对之人，均无什么好下场，都同风际中一样自取灭亡。"

quoteArray[40]="那么，说句真心话，在这世俗社会中，若真的有一个如小宝一样既能赚钱，

又会花钱"

quoteArray[41]="小宝为了这个道理不要高官，不要厚禄，甚至连性命也可以豁出去了，于是康熙虽是恼怒，却也敬重他为人有义。"

quoteArray[42]="当康熙要小宝剿灭天地会时，小宝说出一番道理来：“皇上，他们要来害你，我拼命阻挡，奴才对你是讲义气的。”

```
quoteShowing=-1;
```

```
function nextQuote()
{
    // restart at 0 if done
    if (quoteShowing >= numQuotes) quoteShowing=-1;
    quoteShowing++;

    // assign the value in the textbox to the new quote
    document.quoteForm.quoteHere.value = quoteArray[quoteShowing];
}
```

```
function prevQuote()
{
    // restart at end if on 0
    if (quoteShowing <= 0) quoteShowing=numQuotes+1;
    quoteShowing--;

    document.quoteForm.quoteHere.value = quoteArray[quoteShowing];
}
```

```
function randQuote()
{
    // Make sure you don't show the same quote 2x in a row
    prevQuoteShowing = quoteShowing;
    while(quoteShowing == prevQuoteShowing)
        quoteShowing = Math.ceil(Math.random() * numQuotes);

    document.quoteForm.quoteHere.value = quoteArray[quoteShowing];
}
```

```
//!-->
```

```
</script>
```

```

<h1>消息输出框!!</h1>
<form name="quoteForm">
  <textarea wrap="virtual" name="quoteHere" Rows=3 Cols=60>
    消息显示器
  </textarea><br>
  <input type=button value="下一条" onClick="nextQuote();">
  <input type=button value="上一条" onClick="prevQuote();">
  <input type=button value="随机" onclick="randQuote();">
</form>

```

随机跳出信息窗口

脚本说明：

把如下代码加入<body>区域中:

```

<SCRIPT LANGUAGE="JavaScript">
function generateRandomNumber() {
  var tempString = ""
  tempString += Math.random() * 100000
  return tempString.substring(2,3)
}
config='toolbar=no,location=no,directories=no,status=no,menubar=no,width=300,height=150'

config += 'scrollbars=no,resizable=no'
output = window.open ("","outputwindow",config)
output.document.write('<title>Random Useless Fact</title>');
output.document.write('<BODY bgcolor=#000066 text=#cccccc>');
output.document.write('<center><big>Random Useless Fact:</big>');
output.document.write('<hr><br><p>');
if (generateRandomNumber()=="1")
  {output.document.write('Each year more people in the United States are killed from the bite of a
poisonous snake than the bite of a non-poisonous one. ');
  output.document.write('<br><br><br><br><br><br>')}
if (generateRandomNumber()=="2")
  {output.document.write('Each year more women in the Unites States get pregnant than men. ');
  output.document.write('<br><br><br><br><br><br>')}
if (generateRandomNumber()=="3")
  {output.document.write('Flourine (Fl) is the most active metal. ');
  output.document.write('<br><br><br><br><br><br>')}
if (generateRandomNumber()=="4")
  {output.document.write('Marilyn Manson (a.k.a. Brian Warner) was born in 1969. ');
  output.document.write('<br><br><br><br><br><br>')}
if (generateRandomNumber()=="5")
  {output.document.write('I have not entered this fact yet. Please try again. < ' +
generateRandomNumber());
  output.document.write('>');

```

```

        output.document.write('<br><br><br><br><br>');
if (generateRandomNumber()=="6")
    {output.document.write('I have not entered this fact yet. Please try again. < ' +
generateRandomNumber());
    output.document.write('>');
        output.document.write('<br><br><br><br><br>')}
if (generateRandomNumber()=="7")
    {output.document.write('I have not entered this fact yet. Please try again. < ' +
generateRandomNumber());
    output.document.write('>');
        output.document.write('<br><br><br><br><br>')}
if (generateRandomNumber()=="8")
    {output.document.write('I have not entered this fact yet. Please try again. < ' +
generateRandomNumber());
    output.document.write('>');
        output.document.write('<br><br><br><br><br>')}
if (generateRandomNumber()=="9")
    {output.document.write('I have not entered this fact yet. Please try again. < ' +
generateRandomNumber());
    output.document.write('>');
        output.document.write('<br><br><br><br><br>')}
if (generateRandomNumber()=="0")
    {output.document.write('I have not entered this fact yet. Please try again. < ' +
generateRandomNumber());
    output.document.write('>');
        output.document.write('<br><br><br><br><br>');}
else
    {output.document.write("Tungstun (W) has the highest melting point of all metals. That is why
it is used in light bulbs.");
        output.document.write('<br><br><br><br><br>')}

```

</SCRIPT>

输入框各种效果

脚本说明:

把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
<!-- ActiveASCII by Neal Kanodia (please, don't delete this line)
```

```
function createArr(num) { for(var i = 0; i < num; i++) { this[i] = null } }
```

```
function fillArr(tx,me,ti,wa) { this.text = tx; this.method = me.toLowerCase(); this.ticks = ti;
this.wait = wa }
```

```
function block(num,txt,mthod,tcks,wit) { blocks[num] = new fillArr(txt,mthod,tcks,wit) }
```

```

function ms(unt) { var sp = ""; for( var i = 1; i <= unt; i++ ) { sp += " " } return(sp) }
function Activate() { if (cblock == max) { cblock = 0; if (iloop == 0) { loops--; if (loops == 0)
{ meth = "0" } else { meth = blocks[cblock].method } } else { meth = blocks[cblock].method } }
else { meth = blocks[cblock].method }
if (meth == "0") { document.Active.ASCII.value = end }
if (meth == "display") { Tape = blocks[cblock].text; Wait = blocks[cblock].wait; Display() }
if (meth == "display center") { Tape = blocks[cblock].text; Wait = blocks[cblock].wait; half =
Tape.length / 2; DisplayC() }
if (meth == "scroll left") { clen = tlen; Tape = blocks[cblock].text; Ticks =
blocks[cblock].ticks; tTicks = Ticks * 2; ScrollL() }
if (meth == "scroll right") { clen = 0 - blocks[cblock].text.length; Tape = blocks[cblock].text;
Ticks = blocks[cblock].ticks; tTicks = Ticks * 2; ScrollR() }
if (meth == "scroll lc") { clen = 0 - blocks[cblock].text.length; Tape = blocks[cblock].text;
Ticks = blocks[cblock].ticks; Wait = blocks[cblock].wait; tTicks = Ticks * 2; half =
Tape.length / 2; ScrollLC() }
if (meth == "scroll rc") { clen = tlen; Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks;
Wait = blocks[cblock].wait; tTicks = Ticks * 2; half = Tape.length / 2; ScrollRC() }
if (meth == "scroll cl") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; tTicks =
Ticks * 2; half = Tape.length / 2; clen = cent - half; ScrollCL() }
if (meth == "scroll cr") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; tTicks =
Ticks * 2; half = Tape.length / 2; clen = cent - half; ScrollCR() }
if (meth == "slide left") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; Wait =
blocks[cblock].wait; cpos = 0; clet = Tape.charAt(cpos); clen = tlen; cstr = ""; SlideL() }
if (meth == "slide lc") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; Wait =
blocks[cblock].wait; cpos = Tape.length - 1; clet = Tape.charAt(cpos); clen = 0; cstr = "";
half = Tape.length / 2; iba = cent - half; ib = ms(iba); SlideLC() }
if (meth == "slide rc") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; Wait =
blocks[cblock].wait; cpos = 0; clet = Tape.charAt(cpos); cstr = ""; half = Tape.length / 2;
clen = cent + half; fs = ms(cent - half); SlideRC() }
if (meth == "slide cl") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; cpos = 0;
clet = Tape.charAt(cpos); cstr = Tape.substring(1,Tape.length); half = Tape.length / 2; clen =
cent - half; iba = 0; ib = ms(iba); SlideCL() }
if (meth == "slide cr") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; cpos =
Tape.length - 1; clet = Tape.charAt(cpos); cstr = Tape.substring(0,Tape.length - 1); half =
Tape.length / 2; clen = 0; fs = ms(cent - half); SlideCR() }
if (meth == "slip left") { clen = 0; Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks;
SlipL() }
if (meth == "slip right") { clen = 0; Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks;
SlipR() }
if (meth == "slip letter") { Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; cpos =
Tape.length - 1; clet = Tape.charAt(cpos); cstr = Tape.substring(0,Tape.length - 1); clen = 0;
SlipLet() }
if (meth == "split"){ Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; var iii =
Tape.length / 2; if (iii / 2 != Math.ceil(iii / 2)) { Tape = Tape + " " } hstr1 =

```

```

Tape.substring(0,Tape.length/2); hstr2 = Tape.substring(Tape.length/2,Tape.length); tTicks =
Ticks * 2; clen = cent - hstr1.length; iba = 0; ib = ms(iba); Split() }
if (meth == "merge"){ Tape = blocks[cblock].text; Ticks = blocks[cblock].ticks; var iii =
Tape.length / 2; if (iii / 2 != Math.ceil(iii / 2)) { Tape = Tape + " " } hstr1 =
Tape.substring(0,Tape.length/2); hstr2 = Tape.substring(Tape.length/2,Tape.length); tTicks =
Ticks * 2; clen = 0 - hstr1.length; iba = tlen; ib = ms(iba); Wait = blocks[cblock].wait;
Merge() } }
function Display() { document.Active.ASCII.value = Tape; cblock++; timerID =
setTimeout("Activate()",Wait) }
function DisplayC() { var temp = cent - half; ini = ms(temp); document.Active.ASCII.value =
ini + Tape; cblock++; timerID = setTimeout("Activate()",Wait) }
function ScrollL() { if (clen >= 0) { ini = ms(clen); tickered = ini + Tape;
document.Active.ASCII.value = tickered; clen--; timerID = setTimeout("ScrollL()",Ticks) }
else { beg = 0 - clen; if (beg == Tape.length) { document.Active.ASCII.value = ""; cblock++;
timerID = setTimeout("Activate()",Ticks) } else { tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen--; timerID =
setTimeout("ScrollL()",tTicks) } } }
function ScrollR() { if (clen >= 0) { if (clen > tlen) { document.Active.ASCII.value = "";
cblock++; timerID = setTimeout("Activate()",Ticks) } else { ini = ms(clen); tickered = ini +
Tape; document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("ScrollR()",Ticks) } } else { beg = 0 - clen; tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("ScrollR()",tTicks) } } }
function ScrollLC() { if (clen >= 0) { if (cent <= (clen + half)) { cblock++; timerID =
setTimeout("Activate()",Wait) } else { ini = ms(clen); tickered = ini + Tape;
document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("ScrollLC()",Ticks) } } else { beg = 0 - clen; if (cent <= (clen + half)) { cblock++;
timerID = setTimeout("Activate()",Wait) } else { tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("ScrollLC()",tTicks) } } } }
function ScrollRC() { if (clen >= 0) { if (cent >= (clen + half)) { cblock++; timerID =
setTimeout("Activate()",Wait) } else { ini = ms(clen); tickered = ini + Tape;
document.Active.ASCII.value = tickered; clen--; timerID = setTimeout("ScrollRC()",Ticks) } }
else { beg = 0 - clen; if (cent >= (clen + half)) { cblock++; timerID =
setTimeout("Activate()",Wait) } tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen--; timerID =
setTimeout("ScrollRC()",tTicks) } } }
function ScrollCL() { if (clen >= 0) { ini = ms(clen); tickered = ini + Tape;
document.Active.ASCII.value = tickered; clen--; timerID = setTimeout("ScrollCL()",Ticks) }
else { beg = 0 - clen; if (beg >= Tape.length) { document.Active.ASCII.value = ""; cblock++;
timerID = setTimeout("Activate()",Wait) } else { tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen--; timerID =
setTimeout("ScrollCL()",tTicks) } } } }
function ScrollCR() { if (clen >= 0) { if (clen > tlen) { document.Active.ASCII.value = "";

```



```

cblock++; timerID = setTimeout("Activate()",Wait) } else { ini = ms(clen); tickered = ini +
Tape; document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("ScrollCR()",Ticks) } } else { beg = 0 - clen; tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("ScrollCR()",tTicks) } }
function SlideL() { if (clen >= 0) { ini = ms(clen); tickered = cstr + ini + clet;
document.Active.ASCII.value = tickered; clen -= 3; timerID = setTimeout("SlideL()",Ticks) }
else { document.Active.ASCII.value = cstr + clet; cstr = document.Active.ASCII.value; clen =
tlen - cstr.length; cpos++; clet = Tape.charAt(cpos); if (clet == " ") { cstr = cstr + " ";
cpos++; clet = Tape.charAt(cpos) } if (clet == "") { cblock++; timerID =
setTimeout("Activate()",Wait) } else { timerID = setTimeout("SlideL()",Ticks) } } }
function SlideLC() { if (clen <= cent - half) { ini = ms(clen); tickered = ini + clet + ib + cstr;
document.Active.ASCII.value = tickered; clen += 3; iba -= 3; ib = ms(iba); timerID =
setTimeout("SlideLC()",Ticks) } else { iba = cent - half; ini = ms(iba); ib = ms(iba);
document.Active.ASCII.value = ini + clet + cstr; cstr = clet + cstr; clen = 0; cpos--; if
(cpos >= 0) { clet = Tape.charAt(cpos); if (clet == " ") { cstr = " " + cstr; cpos--; clet =
Tape.charAt(cpos) } timerID = setTimeout("SlideLC()",Ticks) } else { cblock++; timerID =
setTimeout("Activate()",Wait) } } }
function SlideRC() { if (clen >= 0) { ini = ms(clen); tickered = fs + cstr + ini + clet;
document.Active.ASCII.value = tickered; clen -= 3; timerID = setTimeout("SlideRC()",Ticks) }
else { clen = cent + half; cstr += clet; document.Active.ASCII.value = fs + cstr; cpos++;
clet = Tape.charAt(cpos); if (clet == " ") { cstr = cstr + " "; cpos++; clet = Tape.charAt(cpos) }
if (clet == "") { document.Active.ASCII.value = fs + Tape; cblock++; timerID =
setTimeout("Activate()",Wait) } else { timerID = setTimeout("SlideRC()",Ticks) } } }
function SlideCL() { if (clen > 0) { ini = ms(clen); tickered = ini + clet + ib + cstr;
document.Active.ASCII.value = tickered; clen -= 3; iba += 3; ib = ms(iba); timerID =
setTimeout("SlideCL()",Ticks) } else { iba = 0; ib = ms(iba); clen = cent - half; ini =
ms(clen); document.Active.ASCII.value = ini + cstr; cstr = cstr.substring(1,Tape.length);
cpos++; clet = Tape.charAt(cpos); if (clet == " ") { cstr = cstr.substring(1,Tape.length);
cpos++; clet = Tape.charAt(cpos) } if (clet == "") { document.Active.ASCII.value = "";
cblock++; timerID = setTimeout("Activate()",Ticks) } else { timerID =
setTimeout("SlideCL()",Ticks) } } }
function SlideCR() { if (clen <= cent + half) { ini = ms(clen); tickered = fs + cstr + ini + clet;
document.Active.ASCII.value = tickered; clen += 3; timerID =
setTimeout("SlideCR()",Ticks) } else { clen = 0; document.Active.ASCII.value = fs + cstr;
cstr = cstr.substring(0,cstr.length - 1); cpos--; half += 1; if (cpos >= 0) {
;
clet = Tape.charAt(cpos); if (clet == " ") { cstr = cstr.substring(0,cstr.length - 1); cpos--; clet
= Tape.charAt(cpos) } timerID = setTimeout("SlideCR()",Ticks) } else { cblock++; timerID =
setTimeout("Activate()",Ticks) } } }
function SlipR() { if (clen >= 0) { if (clen > tlen) { document.Active.ASCII.value = "";
cblock++; timerID = setTimeout("Activate()",Ticks) } else { ini = ms(clen); tickered = ini +
Tape; document.Active.ASCII.value = tickered; clen++; timerID =
setTimeout("SlipR()",Ticks) } } } else { beg = 0 - clen; tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen++; timerID = setTimeout("SlipR()",Ticks) } }

```

```

function SlipL() { if (clen >= 0) { ini = ms(clen); tickered = ini + Tape;
document.Active.ASCII.value = tickered; clen--; timerID = setTimeout("SlipL()",Ticks) } else
{ beg = 0 - clen; if (beg == Tape.length) { document.Active.ASCII.value = ""; cblock++;
timerID = setTimeout("Activate()",Ticks) } else { tickered = Tape.substring(beg,tlen);
document.Active.ASCII.value = tickered; clen--; timerID = setTimeout("SlipL()",Ticks) } } }
function SlipLet() { if (clen < tlen) { ini = ms(clen); tickered = cstr + ini + clet;
document.Active.ASCII.value = tickered; clen += 3; timerID = setTimeout("SlipLet()",Ticks) }
else { clen = 0; cstr = cstr.substring(0,cstr.length - 1); cpos--; if (cpos >= 0) {
;
clet = Tape.charAt(cpos); if (clet == " ") { cstr = cstr.substring(0,cstr.length - 1); cpos--; clet
= Tape.charAt(cpos) } timerID = setTimeout("SlipLet()",Ticks) } else { cblock++; timerID =
setTimeout("Activate()",Ticks) } } }
function Split() { if (clen >= 0) { ini = ms(clen); tickered = ini + hstr1 + ib + hstr2;
document.Active.ASCII.value = tickered; clen--; iba += 2; ib = ms(iba); timerID =
setTimeout("Split()",Ticks) } else { if (clen <= 0 - hstr1.length) { cblock++; timerID =
setTimeout("Activate()",Ticks) } else { beg = 0 - clen; tickered = hstr1.substring(beg,tlen);
document.Active.ASCII.value = tickered + ib + hstr2; clen--; iba += 2; ib = ms(iba);
timerID = setTimeout("Split()",tTicks) } } }
function Merge() { if (clen >= 0) { if (clen > cent - hstr1.length) { tickered = ini + hstr1 + hstr2;
document.Active.ASCII.value = tickered; cblock++; timerID = setTimeout("Activate()",Wait) }
else { ini = ms(clen); tickered = ini + hstr1 + ib + hstr2; document.Active.ASCII.value =
tickered; clen++; iba -= 2; ib = ms(iba); timerID = setTimeout("Merge()",Ticks) } } else
{ beg = 0 - clen; tickered = hstr1.substring(beg,tlen); document.Active.ASCII.value = tickered
+ ib + hstr2; clen++; iba -= 4; ib = ms(iba); timerID = setTimeout("Merge()",tTicks) } }

```

```

////////////////////////////////////

```

```

//# User Vars

```

```

// Number of blocks (see bottom) to be displayed.

```

```

// ***COMMON ERROR***: Make sure to set this value according to the

```

```

// number of blocks (always the last block # + 1)!

```

```

var max = 18

```

```

// Don't change this!

```

```

var blocks = new createArr(max)

```

```

// Length of textbox

```

```

// ***COMMON ERROR: If you change this or the length of the

```

```

// textbox, remember to change the other accordingly.***

```

```

var len = 50

```

```

// Number of time to loop ALL blocks (use 0 for unlimited)

```

```

var loops = 0

```

```

// If you set the number of loops, set the final messege

```

```

var end = 'End of "ActiveASCII" by Neal Kanodia.'

```

```
// Use this format for each string (starting at 0 until 1 less
// than max):
// block(#block,"Text to display","Method",#ticks,#wait)
// example: block(0,"1st block.,"Scroll Left",25,0)
// ***COMMON ERROR***: If you add a block INCREASE MAX BY 1
// ***COMMON ERROR***: If you remove a block DECREASE MAX BY 1
// ***COMMON ERROR***: Check the spelling of your methods!!!
```

```
block(17,"欢迎光临!","display",0,500)
block(18,"欢迎光临!","display center",0,500)
block(2,"欢迎光临!","scroll left",25,0)
block(3,"欢迎光临!","scroll right",25,0)
block(4,"欢迎光临!","scroll lc",25,500)
block(5,"欢迎光临!","scroll rc",25,500)
block(6,"欢迎光临!","scroll cl",25,0)
block(7,"欢迎光临!","scroll cr",25,0)
block(8,"欢迎光临!","slide left",25,500)
block(9,"欢迎光临!","slide lc",25,500)
block(10,"欢迎光临!","slide rc",25,500)
block(11,"欢迎光临!","slide cl",25,0)
block(12,"欢迎光临!","slide cr",25,0)
block(13,"欢迎光临!","slip left",25,0)
block(14,"欢迎光临!","slip right",25,0)
block(15,"欢迎光临!","slip letter",25,0)
block(16,"","display",0,500)
block(0,"欢迎!","merge",25,1000)
block(1,"欢迎!","split",25,0)
```

```
//End User Vars
```

```
////////////////////////////////////
```

```
// Don't change!!!
var tlen = 2.4 * len
var cent = tlen / 2.2
var clen = null
var tickered = null
var ini = null
var iloop = 0
if (loops == 0) {iloop = 1}
var cblock = 0
var timerID = null
var beg = null
var clet = null
var cstr = null
var cpos = null
```

```
var ib = null
var iba = null
var fs = null
var hstr1 = null
var hstr2 = null
<!-- end -->
```

文字从左到右出现

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
var temp
var f = " "
var f = f + "Put your text here."
var speedtogo = 100
```

```
var counter
```

```
function scrollon() {
```

```
    temp = f.substring(0,1);
    f += temp
    f = f.substring(1,f.length);
    document.wow.display.value = f.substring(0,55);
```

```
    counter = setTimeout("scrollon()",speedtogo);
```

```
}
```

```
</script>
```

```
<form name="wow">
```

```
<input type="text" size="50" name="display" value="">
```

```
</form>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="scrollon()>
```

信息逐条出现

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE = "JavaScript">
```

```

<!-- HTML comment to placate non JavaScript capable browsers
var timerDM=null;
var msgCnt = 6;           // 设置信息的数目.
var DisplayTime = 2000;  // 间隔时间
var msgNum = 1;
var Timeshow = DisplayTime;
function araVob() {
}
var DisplayLine = new araVob();
DisplayLine[1] = "你好";
DisplayLine[2] = "欢迎光临";
DisplayLine[3] = "谢谢";
DisplayLine[4] = "要再次来呀";
DisplayLine[5] = "祝你快乐";
DisplayLine[6] = "网页特效";
/*
    只要修改上面的[n]，就可以增加信息数
*/
var msg = DisplayLine[1];

function DisplayMsg() {
    document.msgform.message.value=msg;
    timerDM = setTimeout("DisplayMsg()",Timeshow);
    ChangeMsg();
}

function ChangeMsg() {
    msgNum++;
    if (msgCnt < msgNum) {
        msgNum = 1;}
    msg = DisplayLine[msgNum];
    if (msgNum == 1) {           // change display time
        Timeshow = 3000;       // of a specific message
    }
    else {
        Timeshow = DisplayTime;
    }
}

function quitDisplay() {
    document.msgform.message.value="Alternate!  But don't scroll \"sideways\"!";
}
// -->
</SCRIPT>

```

```

<FORM NAME=default.htm"msgform" ACTION="default.htm">
  <INPUT TYPE="text"
    default.htm default.htm default.htm default.htm SIZE=32
    default.htm default.htm default.htm default.htm NAME="message" default.htm default.htm
    default.htm default.htm default.htm default.htm VALUE="JavaScript (or JScript) Power
needed.">
</FORM>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="DisplayMsg()">
```

选择显示文字方式

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE = "JavaScript">
```

```
<!-- HTML comment to placate non JavaScript capable browsers
```

```

function AraVob() {
}
var ScreenLine = new AraVob();
ScreenLine[1] = "You can display multiple lines of text here,";
ScreenLine[2] = "including \"blank\" lines.";
ScreenLine[3] = " ";
ScreenLine[4] = "Isn't this easier to read than \"sideways\" scrollers?";
ScreenLine[5] = " ";
ScreenLine[6] = "Click on the \"Type/Scroll\" button to switch between....";
ScreenLine[7] = " scrolling the page up with complete lines or,";
ScreenLine[8] = " typing a line and scrolling the page up.";
ScreenLine[9] = " ";
ScreenLine[10] = "Aren't you glad your browser has JavaScript (JScript) power?";
ScreenLine[11] = "Enjoy!....";
/*
To change or add lines, just replace values of or add to ScreenLine[n]
above. Use \" in the message text for quotes and \t for tabs.
*/
var msgNum = 1; // set to first message to display
var msgCnt = 11; // set to number of last ScreenLine to display.
var typeSpeed = 50; // the typing rate in milliseconds (higher number type more slowly)
var lineDelay = 2000 // the delay time at end of line. (unless the line is a single space)
var pagLen = 6; // number of lines per page (usually the number of rows in the

```

```

TEXTAREA)
var delay = typeSpeed;
var timerPS = null;
var linPtr = 0;
var tally = 1;
var msg = " ";
var outMsg = "";
var i = 0;
var typingon = false;

// set up ScreenLines for display
for (x = msgCnt; 1 <= x; x--) {
    ScreenLine[x+pagLen] = ScreenLine[x] + "\r\n";
}
for (x = 1; x <= (pagLen); x++) {
    ScreenLine[x] = " \r\n";
}
msgCnt += pagLen;
msg = ScreenLine[1];
// end setup

function SwitchIt() {
    typingon = !typingon;
}

function DisplayScroll() {
    if (msgNum < pagLen) {
        delay = typeSpeed;
    }
    else {
        delay = lineDelay;
    }
    ChangeMsg();
    outMsg += msg;
    self.document.msgform.msgarea.value = outMsg;
    if (typingon == true) {
        timerPS = setTimeout("DisplayMsg()",delay);
    }
    else {
        clearTimeout(timerPS);
        timerPS = setTimeout("DisplayScroll()",delay);
    }
}

function DisplayMsg() {

```

```

if (msg.length <= i) {
    i = 0;
    ChangeMsg();
}
outMsg += msg.charAt(i);
i++;
if (msg.charAt(i) != "\n" || msg == "\r\n") {
    delay = typeSpeed;
}
else {
    delay = lineDelay;
}
self.document.msgform.msgarea.value = outMsg;
if (typingon == false) {
    timerPS = setTimeout("DisplayScroll()",delay);
}
else {
    clearTimeout(timerPS);
    timerPS = setTimeout("DisplayMsg()",delay);
}
}

```

```

function ChangeMsg() {
    msgNum++;
    if (msgCnt < msgNum) {
        msgNum = 1;
    }
    if (pagLen <= tally) {
        chgPage();
    }
    tally++;
    msg = ScreenLine[msgNum];
}

```

```

function chgPage() {
    if (msgNum < pagLen) {
        linPntr = msgCnt - pagLen + msgNum + 1;
    }
    else {
        linPntr = msgNum - (pagLen - 1);
    }
}

```

```

outMsg = ScreenLine[linPntr];
for (p = 1; p < (pagLen - 1); p++) {

```



```

linPntr++;
if (msgCnt < linPntr) {
    linPntr = 1;
}
outMsg += ScreenLine[linPntr];
}

}

function quitDisplay() {
    self.document.msgform.msgarea.value = "Type a Page for yourself today!";
}
// -->

</SCRIPT>

<FORM NAME =default.htm"msgform" ACTION =default.htm"default.htm">
<TEXTAREA NAME =default.htm"msgarea" COLS = 66 ROWS = 6>
JavaScript (or JScript) Power needed.
</TEXTAREA>
</FORM>
<FORM>
<INPUT TYPE="button"
NAME="button1"
VALUE="逐个显示/逐行显示"
onClick="SwitchIt()">
</FORM>

```

第二步:把如下代码加入<body>区域中
<body bgcolor="#ffffff" onLoad="DisplayMsg()">

文字来回反弹

脚本说明:

第一步:把如下代码加入<body>区域中
<SCRIPT LANGUAGE=JAVASCRIPT>
// Declare all Local Variables Here
Size2 = 42;
Pos2 = Size2;

```

Vel2 = 2;
Dir2 = 2;
Message2="我怕撞";
Size2-=Message2.length;

function Bouncer(){
    Dir2==2 ? Pos2-=Vel2 : Pos2+=Vel2;
    if (Pos2 < 1){
        Dir2=1;
        Pos2=1;
    }
    if (Pos2 > Size2){
        Dir2=2;
        Pos2=Size2;
    }
    Space2 = "";
    for (count=1; count<Pos2; count++){
        Space2+= " ";
    }
    document.PANEL2.Bar2.value = Space2 + Message2;
    setTimeout( 'Bouncer();', 100);
}
</SCRIPT>
<FORM NAME=PANEL2>
<INPUT                               Size=21                               Name=Bar2
Value="*****
*****">
</FORM>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" ONLOAD="Bouncer()">
```

文字逐个出现

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```

var count = -1;
var counter;
var nchar
var speedtogo = 200

```

```

var a = new Array();

a[1] = "网页特效欢迎你的光临";
a[2] = "";

function capswitch() {
    count++
    if(count == 0){
        document.wow.display.value = a[1]
    }
    if(count == 1){
        document.wow.display.value = a[2].substring(0, 1) +
a[1].substring(20, 1)
    }
    if(count > 1){
        a[3] = a[1].substring(0, count - 1) + a[2].substring(count - 1,
count) + a[1].substring(20, count)
        document.wow.display.value = a[3]
    }
    if(count == a[1].length){
        count = -1
    }

        counter    = setTimeout("capswitch()",speedtogo);

}

</script>
<form name="wow">
<input type="text" size="20" name="display" value="">
</form>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onload="capswitch()">
```

电子管显示

脚本说明:

把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

<!--

```
var messages = new Array()
```

```
messages[0] = "welcome to the led sign"
```

```
messages[1] = "i hope you enjoy it!"
```

```
messages[2] = "do not forget to tell..."
```

```
messages[3] = "...your friends about..."
```

```
messages[4] = "javascript planet!"
```

```
// set normal spacing between two characters (no whitespace inbetween)
```

```
var space = 1
```

```
// set height width of each character
```

```
var height = 5
```

```
var width = 3
```

```
// create object of all supported characters in font
```

```
var letters = new letterArray()
```

```
// initialize image variables
```

```
var on = new Image(5, 5)
```

```
var off = new Image(5, 5)
```

```
// set image URLs
```

```
on.src = "ledon.gif"
```

```
off.src = "ledoff.gif"
```

```
// get number of images already layed out in page
```

```
var imageNum = document.images.length
```

```
// set maximum message length in characters
```

```
var boardWidth = 0
```

```
for (var i = 0; i < messages.length; ++i) {
```

```
    var lengthWithNoSpaces = messages[i].split(" ").join("").length
```

```
    var numberOfSpaces = messages[i].length - lengthWithNoSpaces
```

```
    var currentBoardWidth = lengthWithNoSpaces * (width + space) - space + numberOfSpaces
```

```
    * space * 2
```

```
    if (boardWidth < currentBoardWidth)
```

```
        boardWidth = currentBoardWidth
```

```
}
```

```
// sign is currently not running
```

```
var running = false
var timerID = null
```

```
function letterArray() {
  this.a = new Array(height)
  this.a[0] = " * "
  this.a[1] = "* * "
  this.a[2] = "****"
  this.a[3] = "* * "
  this.a[4] = "* * "

  this.b = new Array(height)
  this.b[0] = "*** "
  this.b[1] = "* * "
  this.b[2] = "***"
  this.b[3] = "* * "
  this.b[4] = "***"

  this.c = new Array(height)
  this.c[0] = "****"
  this.c[1] = "*  "
  this.c[2] = "*  "
  this.c[3] = "*  "
  this.c[4] = "****"

  this.d = new Array(height)
  this.d[0] = "*** "
  this.d[1] = "* * "
  this.d[2] = "* * "
  this.d[3] = "* * "
  this.d[4] = "*** "

  this.e = new Array(height)
  this.e[0] = "*** "
  this.e[1] = "*  "
  this.e[2] = "****"
  this.e[3] = "*  "
  this.e[4] = "****"

  this.f = new Array(height)
  this.f[0] = "****"
  this.f[1] = "*  "
  this.f[2] = "****"
  this.f[3] = "*  "
```

```
this.f[4] = "*  "
```

```
this.g = new Array(height)
```

```
this.g[0] = "****"
```

```
this.g[1] = "*  "
```

```
this.g[2] = "****"
```

```
this.g[3] = "* *"
```

```
this.g[4] = "****"
```

```
this.h = new Array(height)
```

```
this.h[0] = "* *"
```

```
this.h[1] = "* *"
```

```
this.h[2] = "****"
```

```
this.h[3] = "* *"
```

```
this.h[4] = "* *"
```

```
this.i = new Array(height)
```

```
this.i[0] = "****"
```

```
this.i[1] = " * "
```

```
this.i[2] = " * "
```

```
this.i[3] = " * "
```

```
this.i[4] = "****"
```

```
this.j = new Array(height)
```

```
this.j[0] = " *"
```

```
this.j[1] = " *"
```

```
this.j[2] = " *"
```

```
this.j[3] = "* *"
```

```
this.j[4] = "****"
```

```
this.k = new Array(height)
```

```
this.k[0] = "* *"
```

```
this.k[1] = "* *"
```

```
this.k[2] = "****"
```

```
this.k[3] = "* *"
```

```
this.k[4] = "* *"
```

```
this.l = new Array(height)
```

```
this.l[0] = "*  "
```

```
this.l[1] = "*  "
```

```
this.l[2] = "*  "
```

```
this.l[3] = "*  "
```

```
this.l[4] = "****"
```

```
this.m = new Array(height)
this.m[0] = "* *"
this.m[1] = "****"
this.m[2] = "****"
this.m[3] = "* *"
this.m[4] = "* *"
```

```
this.n = new Array(height)
this.n[0] = "* *"
this.n[1] = "****"
this.n[2] = "****"
this.n[3] = "****"
this.n[4] = "* *"
```

```
this.o = new Array(height)
this.o[0] = "****"
this.o[1] = "* *"
this.o[2] = "* *"
this.o[3] = "* *"
this.o[4] = "****"
```

```
this.p = new Array(height)
this.p[0] = "*** "
this.p[1] = "* *"
this.p[2] = "*** "
this.p[3] = "*  "
this.p[4] = "*  "
```

```
this.q = new Array(height)
this.q[0] = "****"
this.q[1] = "* *"
this.q[2] = "* *"
this.q[3] = "****"
this.q[4] = "****"
```

```
this.r = new Array(height)
this.r[0] = "*** "
this.r[1] = "* *"
this.r[2] = "*** "
this.r[3] = "* *"
this.r[4] = "* *"
```

```
this.s = new Array(height)
this.s[0] = "****"
```

```
this.s[1] = "*  "  
this.s[2] = "****"  
this.s[3] = " *"  
this.s[4] = "****"
```

```
this.t = new Array(height)  
this.t[0] = "****"  
this.t[1] = " * "  
this.t[2] = " * "  
this.t[3] = " * "  
this.t[4] = " * "
```

```
this.u = new Array(height)  
this.u[0] = "* *"  
this.u[1] = "* *"  
this.u[2] = "* *"  
this.u[3] = "* *"  
this.u[4] = "****"
```

```
this.v = new Array(height)  
this.v[0] = "* *"  
this.v[1] = "* *"  
this.v[2] = "* *"  
this.v[3] = "* *"  
this.v[4] = " * "
```

```
this.w = new Array(height)  
this.w[0] = "* *"  
this.w[1] = "* *"  
this.w[2] = "****"  
this.w[3] = "****"  
this.w[4] = "****"
```

```
this.x = new Array(height)  
this.x[0] = "* *"  
this.x[1] = "* *"  
this.x[2] = " * "  
this.x[3] = "* *"  
this.x[4] = "* *"
```

```
this.y = new Array(height)  
this.y[0] = "* *"  
this.y[1] = "* *"  
this.y[2] = "****"
```



```
this.y[3] = " * "  
this.y[4] = " * "
```

```
this.z = new Array(height)  
this.z[0] = "****"  
this.z[1] = "  *"  
this.z[2] = " *"  
this.z[3] = "*  "  
this.z[4] = "****"
```

```
this['!'] = new Array(height)  
this['!'][0] = " * "  
this['!'][1] = " * "  
this['!'][2] = " * "  
this['!'][3] = "  "  
this['!'][4] = " * "
```

```
this[':'] = new Array(height)  
this[':'][0] = "  "  
this[':'][1] = " * "  
this[':'][2] = "  "  
this[':'][3] = " * "  
this[':'][4] = "  "
```

```
this['.'] = new Array(height)  
this['.'][0] = "  "  
this['.'][1] = "  "  
this['.'][2] = "  "  
this['.'][3] = "  "  
this['.'][4] = " * "
```

```
this['='] = new Array(height)  
this['='][0] = "  "  
this['='][1] = "****"  
this['='][2] = "  "  
this['='][3] = "****"  
this['='][4] = "  "
```

```
this['='] = new Array(height)  
this['='][0] = "  "  
this['='][1] = "****"  
this['='][2] = "  "  
this['='][3] = "****"  
this['='][4] = "  "
```

```
this['+'] = new Array(height)
this['+'][0] = "  "
this['+'][1] = " * "
this['+'][2] = "***"
this['+'][3] = " * "
this['+'][4] = "  "
```

```
this['-'] = new Array(height)
this['-'][0] = "  "
this['-'][1] = "  "
this['-'][2] = "***"
this['-'][3] = "  "
this['-'][4] = "  "
```

```
this['/'] = new Array(height)
this['/'][0] = " *"
this['/'][1] = " *"
this['/'][2] = " * "
this['/'][3] = "*  "
this['/'][4] = "*  "
```

```
this['\\'] = new Array(height)
this['\\'][0] = "*  "
this['\\'][1] = "*  "
this['\\'][2] = " * "
this['\\'][3] = " *"
this['\\'][4] = " *"
```

```
this['\\'] = new Array(height)
this['\\'][0] = "*  "
this['\\'][1] = "*  "
this['\\'][2] = " * "
this['\\'][3] = " *"
this['\\'][4] = " *"
```

```
this['""'] = new Array(height)
this['""'][0] = "* *"
this['""'][1] = "* *"
this['""'][2] = "* *"
this['""'][3] = "  "
this['""'][4] = "  "
```

```
this['""'] = new Array(height)
```

```
this[""][0] = " * "  
this[""][1] = " * "  
this[""][2] = " * "  
this[""][3] = "  "  
this[""][4] = "  "
```

```
this['('] = new Array(height)  
this['('][0] = " *"  
this['('][1] = " * "  
this['('][2] = " * "  
this['('][3] = " * "  
this['('][4] = " *"
```

```
this[')'] = new Array(height)  
this[')'][0] = "*  "  
this[')'][1] = " * "  
this[')'][2] = " * "  
this[')'][3] = " * "  
this[')'][4] = "*  "
```

```
this['*'] = new Array(height)  
this['*'][0] = "  "  
this['*'][1] = "****"  
this['*'][2] = "****"  
this['*'][3] = "****"  
this['*'][4] = "  "
```

```
this['?'] = new Array(height)  
this['?'][0] = "**  "  
this['?'][1] = " *"  
this['?'][2] = " * "  
this['?'][3] = "  "  
this['?'][4] = " * "
```

```
this['0'] = new Array(height)  
this['0'][0] = " * "  
this['0'][1] = "* *"  
this['0'][2] = "* *"  
this['0'][3] = "* *"  
this['0'][4] = " * "
```

```
this['1'] = new Array(height)  
this['1'][0] = " * "  
this['1'][1] = " * "
```

```
this['1'][2] = " * "  
this['1'][3] = " * "  
this['1'][4] = " * "
```

```
this['2'] = new Array(height)  
this['2'][0] = "****"  
this['2'][1] = " *"  
this['2'][2] = "****"  
this['2'][3] = " * "  
this['2'][4] = "****"
```

```
this['3'] = new Array(height)  
this['3'][0] = "****"  
this['3'][1] = " *"  
this['3'][2] = "****"  
this['3'][3] = " *"  
this['3'][4] = "****"
```

```
this['4'] = new Array(height)  
this['4'][0] = "* *"  
this['4'][1] = "* *"  
this['4'][2] = "****"  
this['4'][3] = " *"  
this['4'][4] = " *"
```

```
this['5'] = new Array(height)  
this['5'][0] = "****"  
this['5'][1] = " * "  
this['5'][2] = "****"  
this['5'][3] = " *"  
this['5'][4] = " * "
```

```
this['6'] = new Array(height)  
this['6'][0] = " * * "  
this['6'][1] = " * "  
this['6'][2] = "****"  
this['6'][3] = "* *"  
this['6'][4] = "****"
```

```
this['7'] = new Array(height)  
this['7'][0] = "****"  
this['7'][1] = " *"  
this['7'][2] = " * "  
this['7'][3] = " * "
```

```

this['7'][4] = "*  "

this['8'] = new Array(height)
this['8'][0] = "****"
this['8'][1] = "* *"
this['8'][2] = "****"
this['8'][3] = "* *"
this['8'][4] = "****"

this['9'] = new Array(height)
this['9'][0] = "****"
this['9'][1] = "* *"
this['9'][2] = "****"
this['9'][3] = "  *"
this['9'][4] = "****"

}
function drawBlank() {
    // assign greater than symbol to variable
    var gt = unescape("%3e")
    document.write('<TABLE BORDER=2 CELLPADDING=8' + gt + '<TR' + gt + '<TD
WIDTH=468 BGCOLOR ALIGN="center" VALIGN="center"' + gt)
    // print entire board of off images
    for (var y = 0; y < height; ++y) {
        for (var x = 0; x < boardWidth; ++x) {
            document.write('<IMG SRC="' + off.src + '" HEIGHT=5 WIDTH=5' + gt)
        }
        document.write('<BR' + gt)
    }
    document.write('</TD' + gt + '</TR' + gt + '</TABLE' + gt)
}

function setLight(state, x, y) {
    // set a specific light in sign to on (true) or off (false)
    if (state)
        document.images[computeIndex(x, y)].src = on.src
    else
        document.images[computeIndex(x, y)].src = off.src
}

function drawLetter(letter, startX) {
    // draws a letter at the given x coordinate
    for (var x = 0; x < width; ++x) {
        for (var y = 0; y < height; ++y) {

```

```

        setLight(letters[letter][y].charAt(x) == "*", startX + x, y)
    }
}

```

```

function drawSpace(startX) {
    // create a small space between each two characters
    for (var x = 0; x < space; ++x) {
        for (var y = 0; y < height; ++y) {
            setLight(false, startX + x, y)
        }
    }
}

```

```

function computeIndex(x, y) {
    // compute the document index of an image in the sign, based on the x-y coordinates
    return (y * boardWidth + x) + imageNum
}

```

```

function floodBoard(startX) {
    // set all lights from startX to off
    for (var x = startX; x < boardWidth; ++x) {
        for (var y = 0; y < height; ++y) {
            setLight(false, x, y)
        }
    }
}

```

```

function drawMessage(num) {
    // initialize variable to current message
    var text = messages[num]
    // initialize two counters (j - current character in message, i - current x coordinate)
    var i = 0
    var j = 0
    while (1) {
        if (text.charAt(j) != " ") {
            // draw current letter
            drawLetter(text.charAt(j), i)
            // increment i by the constant width of an image
            i += width
        }
        else {
            // add an extra space (do not advance j yet)
            drawSpace(i)
        }
    }
}

```

```

        i += space
    }
    // if j is less than index of last character
    if (j < text.length - 1) {
        drawSpace(i)
        i += space
    }
    else
        // j is the index of the last character (last character already printed)
        break
        // increment j by one because one letter was printed
        ++j
    }
    // flood the remaining piece of the sign (turn it off)
    floodBoard(i)
    // if message printed this time was not the last one in the array
    if (num < messages.length - 1)
        // val *must* be a global variable for use with the timeout
        val = ++num
    else
        val = 0 // start cycle over again
        // recursive call after waiting 3 seconds (some of the time already passed during
printing)
        timerID = setTimeout("drawMessage(val)", 3000)
    }
    // open form
    document.write('<FORM>')
    // create initial sign (all sign is off)
    drawBlank()

function startSign() {
    // wait 3 seconds and then call function to print first message
    drawMessage(0)
    running = true
}

function stopSign() {
    if(running)
        clearTimeout(timerID)
        running = false
    }
    document.write('<INPUT TYPE="button" VALUE="start" onClick="startSign()">')
    document.write('<INPUT TYPE="button" VALUE="stop" onClick="stopSign();
floodBoard(0)">')

```

```
document.write('</FORM>')
// -->
</SCRIPT>
```

文字循环出现

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT LANGUAGE="JavaScript">
```

```
<!-- escondamos
//texto a mostrarse
var mensaje=" >>> 欢 >>> 迎 >>> 你的 >>> 光临";
mensaje+=" >>> 经 >>> 常 >>> 来 >>> 哟";

//fraccion a mostrarse
var ancho=50;

//rutina de mensaje deslizando
function desliza(){
document.forms[0].panel.value=mensaje.substring(mensaje.length-ancho,mensaje.length);
mensaje=mensaje.substring(mensaje.length-1,mensaje.length)+mensaje;
mensaje=mensaje.substring(0,mensaje.length-1);
setTimeout("desliza()",100);
}

// basta de esconder -->

</SCRIPT>
<form>
<INPUT TYPE="text" NAME="panel" VALUE="" SIZE="50">
</form>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="desliza(); return true;">
```

可调节速度的撞击

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script LANGUAGE="JavaScript">
```



```

var speed=500;
var hellotext="1";
var thetext="";
var started=false;
var step=0;
var times=1;
function welcometext(){
  times--;if(times==0){
    if(started==false){ started=true;
      document.forms[0].message.value=hellotext;
      setTimeout("anim()",1)}thetext=hellotext }
function showformtext(txt){
  thetext=txt;
  setTimeout(welcometext());times++ }
function anim(){ step++;if(step==15){ step=1 }
if(step==1){ document.forms[0].message.value='Ping-Pong* _____|_____ Ping-
Pong'}

if(step==2){ document.forms[0].message.value='Ping-Pong _____|_____ *Pign-
Pong'}

if(step==3){ document.forms[0].message.value='Ping-Pong ____ * _____|_____ Ping-
Pong'}

if(step==4){ document.forms[0].message.value='Ping-Pong _____|_____ * ____ Ping-
Pong'}

if(step==5){ document.forms[0].message.value='Ping-Pong _____ * ____|_____ Ping-
Pong'}

if(step==6){ document.forms[0].message.value='Ping-Pong _____|____ * _____ Ping-
Pong'}

if(step==7){ document.forms[0].message.value='Ping-Pong _____*|_____ Ping-
Pong'}

if(step==8){ document.forms[0].message.value='Ping-Pong _____|* _____ Ping-
Pong'}

if(step==9){ document.forms[0].message.value='Ping-Pong _____| ____ * _____ Ping-
Pong'}

if(step==10){ document.forms[0].message.value='Ping-Pong _____ * ____|_____ Ping
-Pong'}

```

```
if(step==11){ document.forms[0].message.value='Ping-Pong_____|_____ * _____ Ping-
Pong'}
```

```
if(step==12){ document.forms[0].message.value='Ping-Pong_____ * _____|_____ Ping
-Pong'}
```

```
if(step==13){ document.forms[0].message.value='Ping-Pong_____|_____ * _____ Ping
-Pong'}
```

```
if(step==14){ document.forms[0].message.value='Ping-Pong__ * _____|_____ Ping
-Pong'}
```

```
if(step==15){ document.forms[0].message.value='Ping-Pong_____|_____ Ping
-Pong'}
```

```
    setTimeout("anim()",speed)}
```

```
function delay(){if(speed==500){speed=10}else{speed=500}}
```

```
</script>
```

```
<form><INPUT Type="text" Name="message" Size="44"><p>
```

```
<INPUT Type="button" Value="快速/减速" onClick="delay()"></form>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="welcometext()">
```

逐字出现的信息条

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
function makeArray() {
```

```
    this.length = makeArray.arguments.length
```

```
    for (var i = 0; i < this.length; i++)
```

```
        this[i+1] = makeArray.arguments[i]
```

```
}
```

```
var fArray = new makeArray;
```

```
fArray[0]="Message 1 goes here. ";
```

```
fArray[1]="Message 2 goes here. "
```

```
fArray[2]="Message 3 goes here. "
```

```
fArray[3]="Message 4 goes here. "
```

```
var x = 1;
```

```
var y = 0;
```

```
var msg1 = fArray[y];
```

```
function newsFeed() {
```

```
    if (x==msg1.length+1) {
```

```
        for (var z=0; z < 70000; z++);
```

```
        y+=1;
```

```
        if (y > 3) y=0;
```

```
        document.form1.news2.value=' ';
```

```
        msg1 = fArray[y];
```

```
        x=0;
```

```
    }
```

```
    document.form1.news2.value=msg1.substring(0,x);
```

```
    x+=1;
```

```
    setTimeout("newsFeed() ",100);
```

```
}
```

```
</script>
<form name="form1">
<textarea wrap=physical rows=10 cols=25 name="news2">
</textarea>
</form>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="newsFeed()">
```

自由控制文字输入

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT>
```

```
<!-- Activate Cloaking Device
```

```
// used to track position in message
```

```
var i = 0;
```

```
// used to cycle thru messages
```

```
var TextNumber = 0;
```

```
// array of messages
```

```
var TextInput = new Object();
```

```
// used to load manipulate message
```

```
var HelpText="";

// used to load message

var Text = "";

// length of timeout (smaller is faster)

var Speed=50;

// added to end of each message to create a pause

var WaitSpace="          "

// used to position text in ver 2.0

var addPadding="\r\n";

// Each element of TextInput represents a single message.

TextInput[0] = "This is just another method of displaying information to your visitors.";

TextInput[1] = "The routine is based on the T-Banner by Tomer and Yehuda Shiran.";

TextInput[2] = "I've selected the TextArea for display to utilize the wrap-around feature.";
```

```
TextInput[3] = "The messages can be made to cycle manually, check out Tele-Type 1 in Tim's Lab.";
```

```
TextInput[4] = "Though this scheme is not perfect, you have to admit it is different!";
```

```
TextInput[5] = "I've learned that you can reduce flicker by shortening the messages.";
```

```
TextInput[6] = "One may want to add speed adjustment to better match individual machines.";
```

```
TextInput[7] = "Whether practical or not, at least it was fun developing Timothy's Tele-Type Display!";
```

```
TotalTextInput = 7; // (0, 1, 2, 3, 4, 5, 6, 7)
```

```
// Positioning and speed vary between versions.
```

```
var Version = navigator.appVersion;
```

```
if (Version.substring(0, 1)==3)
```

```
{
```

```
Speed=200;
```

```
addPadding="";
```

```
}
```

```
for (var addPause = 0; addPause <= TotalTextInput; addPause++)
```

```
  {TextInput[addPause]=addPadding+TextInput[addPause]+WaitSpace;}
```

```
var TimerId
```

```
var TimerSet=false;
```

```
// Called by the Start button.
```

```
function startMessage()
```

```
{
```

```
  if (!TimerSet)
```

```
  {
```

```
    TimerSet=true;
```

```
    teletype();
```

```
  }
```

```
}
```

```
// Gets and displays character from rollMessage() .
```

```
// Variable Speed controls length of timeout and thus the speed of typing.
```

```
function teletype()
```

```
{
```

```
Text=rollMessage();
```

```
TimerId = setTimeout("teletype()", Speed)
```

```
document.forms[0].elements[0].value=Text;
```

```
}
```

```
// Pulls one character at a time from string and returns (as Text) to function teletype() for displaying.
```

```
function rollMessage ()
```

```
{
```



```
Wait_yn=false;
```

```
i++;
```

```
var CheckSpace = HelpText.substring(i-1, i);
```

```
CheckSpace = "" + CheckSpace;
```

```
if (CheckSpace == " ")
```

```
{i++;}
```

```
if (i >= HelpText.length+1)
```

```
{
```

```
i=0;
```

```
if (TextNumber < TotalTextInput)
```

```
{TextNumber++;}
```

```
else {TextNumber = 0;}
```

```
initMessage();
```

```
}
```

```
Text = HelpText.substring(0, i);
```

```
return (Text);
```

```
}
```

```
// Called from onLoad in BODY tag & resetDisplay().
```

```
function titleDisplay()
```

```
{
```

```
document.forms[0].elements[0].value="\r\n          AutoCycle Tele-Type Display";
```

```
initMessage();
```

```
}
```

```
// Sets Text & HelpText equal to messages for use in rollMessage ().
```

```
function initMessage()
```

```
{
```

```
Text = TextInput[TextNumber]
```

```
HelpText = Text;
```

```
}
```

```
// Called by Stop button.
```

```
function stopMessage()
```

```
{
```

```
    TimerSet=false;
```

```
    clearTimeout (TimerId);
```

```
}
```

```
// Called by Reset button.
```

```
function resetDisplay()
```

```
{
```

```
    TimerSet=false;
```

```
    clearTimeout (TimerId);
```

```
TextNumber=0;
```

```
i=0;
```

```
titleDisplay();
```

```
}
```

```
// Deactivate Cloaking -->
```

```
</SCRIPT>
```

```
<form>
```

```
<TEXTAREA ROWS=2 COLS=55 wrap=yes></TEXTAREA>
```

```
<BR>
```

```
<TABLE BORDER=0 WIDTH=300>
```

```
<TD align="center"><INPUT TYPE="button" VALUE="Start" onClick="startMessage()">
```

```
<TD align="center"><INPUT TYPE="button" VALUE="Reset" onClick="resetDisplay()">
```

```
<TD align="center"><INPUT TYPE="button" VALUE="Stop" onClick="stopMessage()">
```

```
</TABLE>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onLoad="titleDisplay()">
```

一段彩色的文字

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT language="JavaScript">
```

```
var browser = "unknown";
```

```
var version = 0;
```

```
if (navigator.userAgent.indexOf("Opera") >= 0)
    browser = "opera";
else if (navigator.userAgent.indexOf("obot") >= 0)
    browser = "robot";
else if (navigator.appName.indexOf("etscape") >= 0)
    browser = "netscape";
else if (navigator.appName.indexOf("icrosoft") >= 0)
    browser = "msie";

version = parseFloat(navigator.appVersion);
if (isNaN(version)) version = 0;
if ((browser == "msie") && (version == 2)) version = 3;
```

```
// lookup table
var tohex = new Array(256);
var hex = "0123456789ABCDEF";
var count = 0;
for (x=0; x<16; x++) {
    for (y=0; y<16; y++) {
        tohex[count] = hex.charAt(x) + hex.charAt(y);
        count++;
    }
}
```

```
//ColorCode constructor
function ColorCode(hexcode) {
    if (hexcode.length == 7) {
        this.r = parseInt(hexcode.substring(1,3),16);
        this.g = parseInt(hexcode.substring(3,5),16);
        this.b = parseInt(hexcode.substring(5,7),16);
    }
    else if (hexcode.length == 6) {
        this.r = parseInt(hexcode.substring(0,2),16);
        this.g = parseInt(hexcode.substring(2,4),16);
        this.b = parseInt(hexcode.substring(4,6),16);
    }
    else {
        this.r = this.g = this.b = 0;
        alert("Error: ColorCode constructor failed");
    }
    if (isNaN(this.r)||isNaN(this.g)||isNaN(this.b))
        alert("Error: ColorCode constructor failed");
}
```

```

}

// ColorList constructor
function ColorList(hexcodes) {
  var i = 0;
  var c = 0;
  this.codes = new Array(Math.round(hexcodes.length/7));
  while (i < hexcodes.length) {
    if (isNaN(parseInt(hexcodes.substring(i,i+6),16))) ++i;
    else {
      this.codes[c] = new ColorCode(hexcodes.substring(i,i+6));
      i += 7;
      ++c;
    }
  }
  this.len = c;
}

function interpolate (x1, y1, x3, y3, x2) {
  if (x3 == x1) return y1
  else return (x2-x1)*(y3-y1)/(x3-x1) + y1
}

// x=index of letter, y=number of letters, z=number of colors
function lowcolorindex (x, y, z) {
  if (y == 1) return 0
  else return Math.floor( (x*(z-1))/(y-1) )
}

function hicolorindex (x, y, z, low) {
  if ( low*(y-1) == x*(z-1) ) return low
  else if (y == 1) return 0
  else return Math.floor( (x*(z-1))/(y-1) + 1 )
}

function gradient (thetext,thecolors) {
  if (((browser == "netscape")||(browser == "msie")||(browser == "opera"))&&(version>=3.0)) {
    var colors = new ColorList(thecolors);
    var numcolors = colors.len;
    var numchars = thetext.length;
    var rr = 0;
    var gg = 0;
    var bb = 0;
    var lci = 0; //lower color index

```

```

var hci = 0; //high color index
for (i=0; i<numchars; ++i) {
    lci = lowcolorindex(i, numchars, numcolors);
    hci = hicolorindex(i, numchars, numcolors, lci);
    rr = Math.round(interpolate( lci/(numcolors-1), colors.codes[lci].r, hci/(numcolors-1),
colors.codes[hci].r, i/(numchars-1)));
    gg = Math.round(interpolate( lci/(numcolors-1), colors.codes[lci].g, hci/(numcolors-1),
colors.codes[hci].g, i/(numchars-1)));
    bb = Math.round(interpolate( lci/(numcolors-1), colors.codes[lci].b, hci/(numcolors-1),
colors.codes[hci].b, i/(numchars-1)));
    if (browser == "opera") {
        rr = 255 - rr;
        gg = 255 - gg;
        bb = 255 - bb;
    }
    document.write(thetext.charAt(i).fontcolor(tohex[rr]+tohex[gg]+tohex[bb]));
}
}
else document.write(thetext); // unrecognized browser, better not to attempt anything fancy
}

```

```

</SCRIPT>
<SCRIPT language="JavaScript">
gradient("always wanted to be a genius?", "FF0000 FFFFFFFF 0000FF");
document.write('<BR>');
gradient("...well...do it, in...", "444444 DDDDDD 444444");
document.write('<BR><FONT size=+1><TT><B>');
gradient("snazzy, eyecatching, gradient colors!", "FF8888 FFFF88 88FF88 88FFFF 8888FF
FF88FF");
document.write('</B></TT></FONT><BR><FONT size=2>');
gradient("but uhm, just be careful not to overdo it", "884488 444488 448888 448844 888844
884444");
document.write("</FONT><BR>");
</SCRIPT>

```

可调节的输出形式

脚本说明:

第一步:把如下代码加入<body>区域中

```
<SCRIPT>
```

```
var msg = "javascript 欢迎你的光临!!!"
```

```
var x = ""
```

```
num = 1
```

```
toggle = 1
```

```
tt = 1
```

```
OOK = 0
```

```
timval = 60
```

```
var tval = ""
```

```
function switcha() {
```

```
    if (document.myform.dowhat.value == "Start/Stop" )
```

```
        tval = "Forward/Backward"
```

```
    if (document.myform.dowhat.value == "Forward/Backward")
```

```
        tval = "Fast/Slow"
```

```
    if (document.myform.dowhat.value == "Fast/Slow")
```

```
        tval = "Start/Stop"
```

```
    document.myform.dowhat.value = tval
```

```
}
```

```
function switcha2() {
```

```
    if (document.myform.dowhat.value == "Start/Stop" ) toggla()
```

```
    if (document.myform.dowhat.value == "Forward/Backward" ) csd()
```

```
    if (document.myform.dowhat.value == "Fast/Slow" ) fasl()
```

```
}
```

```
function fasl() { timval = (timval==60 ? 150 : 60) }
```



```
function csd() {  
  
    tt = ( tt==1 ? 0 : 1)  
  
}  
  
function scroll() {  
  
    if (tt==1)  
  
        if (num <= msg.length)  
  
            OOK = 1  
  
        if (tt==0)  
  
            if (num >= 0)  
  
                OOK = 1  
  
  
  
        if ( OOK == 1)  
  
        {  
  
        OOK = 0  
  
        x = msg.substring(0,num)  
  
        document.myform.scroll.value = x  
  
        num = ( tt==1 ? num+1 : num-1 )  
  
        }  
  
        else  
  
        {  
  
        x = ""  
  
        document.myform.scroll.value = ""
```

```

num = (tt==1 ? 0 : msg.length)

}

if (toggle == 1)

setTimeout("scroll()", timval)

}

function toggla() {

toggle = (toggle == 1 ? 0 : 1)

if (toggle == 1) scroll()

}

</SCRIPT>
<FORM NAME="myform">
<INPUT TYPE="text" NAME="scroll" SIZE={msg.length + 2}; ><br>
<INPUT TYPE="button" VALUE="Do It" onClick="switcha2()">
<INPUT TYPE="text" NAME="dowhat" SIZE = 10 VALUE = "Start/Stop">
<INPUT TYPE="button" VALUE="next" onClick="switcha()" >
</FORM>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onload=scroll(>
```

文字同时输出

脚本说明:

第一步:把如下代码加入<body>区域中

```

<form NAME="SearchForm">
</form>
<Script language="javascript">

```

```
var m = "Wanna see two lines scroll in a funky way?"
```

```
var a = ""
```

```
i=0
```

```
s=0
```

```
function checkspace () {
```

```
    if(m.substring(i-1,i) == " ") {
```

```
        if(s == 0) {
```

```
            s = 1;
```

```
        }
```

```
    } else {
```

```
        s = 0;
```

```
    }
```

```
  }
```

```
}
```

```
function scrollit() {
```

```
    i++
```

```
    if(i > m.length) {
```

```
        i = 1
```

```
    }
```

```
    checkspace()
```

```
    a = m.substring(0,i)
```

```

document.forms[1].elements[s].value = a

setTimeout("scrollit()",100)

}

</script>
<form name="msg">
<input type="text" size=50 name="mesg1"><br>
<input type="text" size=50 name="mesg2">
</form>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onload=scrollit(>
```

调节文字移动形式

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```

var u=0
var v=0
var f = Math.PI/180
var txt="-----"
u=0
var text1 = "=> 欢迎你 <=---"
var text2 = "=> javascript <=---"
var text = text1
var cpt=19
var t=0
var z=0
function maketab(pas) {
    for (var i=0; i<180; i++) {
        sinus = Math.round(Math.sin(i*f)*100);
        this[i] = sinus;
    }
}
var tb = new maketab()

function change() {

```

```

    cpt++
    if (cpt==20) {
        if (t==0) {
            text = text1
            t=1;
        }
        else {
            text = text2
            t=0;
        }
        cpt=0;
    }
}

function move(z) {

    if (u>180) {u=0}
    if (v>180) {v=0}
    change()
    if (z==0) {
        u+=2
        document.forms[0].elements[0].value = txt.substring(0,tb[u]) + text
    }
    if (z==1) {
        v+=2
        window.status = txt.substring(0,tb[v]) + text
    }
    if (z==2) {
        u+=2
        v+=2
        document.forms[0].elements[0].value = txt.substring(0,tb[u]) + text
        window.status = txt.substring(0,tb[v]) + text
    }

    setTimeout ("move(z)",150); //设置字符移动速度
}

</script>
<form name="msg">
    <p><input type="text" size="79" name="mesg"> </p>
    </small></font></small></p>

    <p><input type="text" size="37" name="message" value="在这里输入">
    </small></font></small>

```

```

<input type="text" size="37" name="message2" value="也可在这里输入">
</small></font></small><br>
<input type="button" name="newmsg" value="自己创建文字"
onclick="text1=form.message.value; text2=form.message2.value;">
</small></font></small></p>

<p><input type="button" size="79" name="winstatus" value="状态栏显示" onclick="z=1">
</small></font></small>
<input type="button" size="79" name="txtarea" value="文本框显示" onclick="z=0">
</small></font></small>
</small></font></small>
<input type="button" size="79" name="both" value="状态栏和文本框都显示"
onclick="z=2">
</small></font></small></p>
</form>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onload=move(0)>
```

文字飘动输出

脚本说明:

把如下代码加入<body>区域中

```

<SCRIPT LANGUAGE=JAVASCRIPT>

var ltext="超级 javascript 欢迎你的光临!!!" /*the message*/

var spc=10 /*spacing*/

var speed=50 /*speed in milliseconds*/

var times=2 /*number of times to run each style*/

/* DISPLAY DIMENTIONS */

var rows=5 /*number of textarea rows*/

var cols=60 /*number of textarea coloums*/

```

```
/* ADVANCED OPTIONS */
```

```
var addstopbutton=true /*add optional stop button? ture=yes false=no*/
```

```
var stopbuttonvalue="                STOP                " /* Text For Stop  
Button */
```

```
var startvalue="                START                " /* When Stop Button  
Clicked Button Value=? */
```

```
/* END OF OPTIONS */
```

```
var len=spc*2;var text=ltext;var i;
```

```
var stop=false;var stopped;
```

```
for (i=0;i<spc;i++){text=text+" " }
```

```
function array(n) {
```

```
    this.length = n
```

```
    for (i=1; i <= n; i++){this[i] ="";}
```

```
    return this }
```

```
document.writeln('<FORM NAME="F">')
```

```
document.writeln('<TEXTAREA    ROWS='+rows+'    COLS='+cols+'    NAME="D"  
WRAP=SOFT<>/TEXTAREA>')
```

```
if      (addstopbutton){ document.writeln('<BR><INPUT    TYPE=BUTTON  
VALUE="'+stopbuttonvalue+' " ONCLICK="stopstart()" NAME=SS>')}
```

```
document.writeln('</FORM>')
```

```

var l=text.length

var ll=ltext.length;

var lb=new array(l)

var lr=new array(spc*2+1)

var lg=new array(ll)

var lk=new array(ll)

lb[0]=text;

lb[1]=text;

for (j=1;j<l;j++){

    for (i=1;i<=l;i++){

        lb[j]=lb[j]+lb[j-1].charAt(i);if(i==l){lb[j]=lb[j]+lb[j-1].charAt(0)

        }

    }}

lr[0]=ltext;

lr[spc*2]=ltext;

for (i=1;i<=spc;i++){

    lr[i]=" "+lr[i-1]

}

for (i=spc*2-1;i>=spc+1;i--){

    lr[i]=" "+lr[i+1]

```



```
}
```

```
lg[0]=ltext;
```

```
var ll=ltext.length;
```

```
for (j=1;j<ll;j++){
```

```
    for (i=lg[j-1].length-2;i>=0;i--){
```

```
        lg[j]=lg[j-1].charAt(i)+lg[j];
```

```
    }
```

```
lk[ll]=ltext;
```

```
for (j=ll-1;j>=0;j--){
```

```
    for (i=1;i<=l;i++){
```

```
        lk[j]=lk[j]+lk[j+1].charAt(i);
```

```
    }
```

```
var lge="";var lbe="";var rle="";
```

```
for (i=0;i<rows;i++){
```

```
    lge=lge+lg[i]+unescape('%0D%0A')}
```

```
for (i=0;i<rows;i++){
```

```
    lbe=lbe+lb[l-i]+unescape('%0D%0A')}
```

```
for (i=1;i<=rows;i++){
```

```
    rle=rle+lr[spc*2-i]+unescape('%0D%0A')}
```

```
var c=1;
```

```
var i=ll;
```

```
var j=0;
```

```
var f=0;
```

```
function lgf(){
```

```
if(stop===false){
```

```
if(i>ll){j=0;i=i-2};
```

```
if(i==0&& j==0){c++;j=1};
```

```
if(j!=0){ document.F.D.value=lg[i]+unescape('%0D%0A')+document.F.D.value;i++ }
```

```
if(j==0){ document.F.D.value=lg[i]+unescape('%0D%0A')+document.F.D.value;i-- }
```

```
if(c<=times){ setTimeout("lgf()",speed) }else{ document.F.D.value=lge;i=0;j=0;c=0;t() }
```

```
}
```

```
}
```

```
function t(){
```

```
if(stop===false){
```

```
if(i>l){i=1};
```

```
document.F.D.value=lb[i]+unescape('%0D%0A')+document.F.D.value;i++;j++
```

```
if(j<=l*times){ setTimeout("t()",speed) }else{ document.F.D.value=lbe;i=0;j=0;rl() }
```

```
}
```

```
}
```

```
function rl(){
```

```
if (stop==false){
```

```
if(i>=spc*2){i=0};
```

```
document.F.D.value=lr[i]+unescape('%0D%0A')+document.F.D.value;
```

```
i++;j++;
```

```
if(j<len*times){setTimeout("rl()",speed)}else{ document.F.D.value=rle;i=ll-1;j=0;trans() }
```

```
}}
```

```
function trans(){
```

```
if(stop==false){
```

```
document.F.D.value=lk[i]+unescape('%0D%0A')+document.F.D.value;i--;
```

```
if(i!=1){setTimeout("trans()",speed)}else{i=ll;lzf() }
```

```
}}
```

```
function stopstart(){
```

```
stopped=stop;
```

```
if(stopped==false){ stop=true;document.F.SS.value=startvalue }
```

```
if(stopped==true){ stop=false;document.F.SS.value=stopbuttonvalue;document.F.D.value="";i=11;  
j=0;c=0;lzf() }
```

```
}
```

```
if (rows>spc||rows>ll){alert("ERROR!\nrows can NOT be more that spaces or message length!!!!\ndont ask why thats just the way it is.")}
```

```
if (spc+ll>cols){alert("ERROR!\nncols(coloums) can NOT be less that the message length + spacing length")}
```

```
if (rows<=spc&&rows<=ll&&spc+ll<=cols){lgf()}
```

```
</SCRIPT>
```

各种形式文字输出

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language=javascript>
```

```
//Change the following 4 messages to your liking.
```

```
var txt = "欢迎你的光临"
```

```
var txt2 = "I love javascript"
```

```
var txt3 = "记得要经常来呀"
```

```
var txt4 = "谢谢你的光临"
```

```
//Make sure that "def" is longer than your longest message
```

```
var def = "_____"
```

```
//Don't change any of the following
```

```
var end = txt4.length
```

```
var end2 = end / 2
```

```
var close = end2
```

```
var close2 = end2
```

```
var close3 = end
```

```
var max2 = txt3.length
```

```
var mid = max2 / 2
```

```
var max = txt2.length
```

```
var msg
var msg2
var msg3
var msg4
var msg5
var msg6
var word = 0
var word2 = txt.length
var scroll = 0
var door = max
var blink = 0
var blink2 = 20
var stay = 0
var timestay
var time
var time2
var doortime
var timeblink
var timescroll
var timeblink2
var timeclose
```

```
function Type() {
  if (word <= txt.length) { word++;
  msg = txt.substring(0, word);
  document.form1.text.value = msg
  time = setTimeout("Type()", 100) }
  else { word = 0;
  clearTimeout(time);
  Stay() }
}
```

```
function Stay() {
  if (stay==0) { document.form1.text.value = txt;
  stay = 1;
  timestay = setTimeout("Stay()", 1000) }
  else if (stay==1) { document.form1.text.value = txt;
  stay = 0;
  clearTimeout(timestay);
  Erase() }
}
```

```
function Close() {
  if(close2 <= end) {
```

```

close -= 1;
close2++;
close3 -= 2;
msg6 = txt4.substring(close, end2) + def.substring(0, close3) + txt4.substring(end2, close2);
document.form1.text.value = msg6;
timeclose = setTimeout("Close()", 100)
}
else { clearTimeout(timeclose);
close = end2;
close2 = end2;
close3 = end;
Stay2() }
}

```

```

function Stay2() {
    if (stay==0) { document.form1.text.value = txt4;
    stay = 1;
    timestay = setTimeout("Stay2()", 1300) }
    else if (stay==1) { document.form1.text.value = txt4;
    stay = 0;
    clearTimeout(timestay);
    Doors() }
}

```

```

function Erase() {
    if (word2 <= txt.length && word2 > 0) { word2 -= 1;
    msg2 = txt.substring(0, word2)
    document.form1.text.value = msg2
    time2 = setTimeout("Erase()", 20)}
    else { word2 = txt.length;
    clearTimeout(time2);
    Close() }
}

```

```

function Doors() {
    if (door >= 0) {
    door -= 1;
    msg3 = txt2.substring(door, max)
    document.form1.text.value = msg3
    doortime = setTimeout("Doors()", 100)
    }
    else { door = max;
    clearTimeout(doortime);
}

```

```
    Blink() }  
}
```

```
function Blink() {  
    if (blink==0) { document.form1.text.value = txt2;  
        blink = 1;  
        timeblink = setTimeout("Blink()", 200) }  
    else if (blink==1) { document.form1.text.value = "";  
        blink = 2 ;  
        timeblink = setTimeout("Blink()", 200) }  
    else if (blink==2) { document.form1.text.value = txt2;  
        blink = 3;  
        timeblink = setTimeout("Blink()", 200) }  
    else if (blink==3) { document.form1.text.value = "";  
        blink = 4;  
        timeblink = setTimeout("Blink()", 200) }  
    else if (blink==4) { document.form1.text.value = txt2;  
        blink = 5;  
        timeblink = setTimeout("Blink()", 200) }  
    else if (blink==5) { document.form1.text.value = "";  
        blink = 0;  
        clearTimeout(timeblink);  
        Scroll() }  
}
```

```
function Scroll() {  
    if(scroll <= txt2.length) { msg4 = txt2.substring(scroll, txt2.length);  
        document.form1.text.value = msg4;  
        scroll++;  
        timescroll = setTimeout("Scroll()", 100)  
    }  
    else { clearTimeout(timescroll);  
        scroll = 0  
        Blink2() }  
}
```

```
function Blink2() {  
    if (blink2==20) { msg5 = txt3;  
        document.form1.text.value = msg5;  
        blink2 = 0;  
        timeblink2 = setTimeout("Blink2()", 800) }  
    else if (blink2==0) { msg5 = txt3.substring(0, mid) + def.substring(0, mid);
```

```

document.form1.text.value = msg5;
blink2 = 1;
timeblink2 = setTimeout("Blink2()", 300) }
else if (blink2==1) { msg5 = def.substring(0, mid) + txt3.substring(mid, max2);
document.form1.text.value = msg5;
blink2 = 2 ;
timeblink2 = setTimeout("Blink2()", 300) }
else if (blink2==2) { msg5 = txt3.substring(0, mid) + def.substring(0, mid);
document.form1.text.value = msg5;
blink2 = 3;
timeblink2 = setTimeout("Blink2()", 300) }
else if (blink2==3) { msg5 = def.substring(0, mid) + txt3.substring(mid, max2);
document.form1.text.value =msg5;
blink2 = 4;
timeblink2 = setTimeout("Blink2()", 300) }
else if (blink2==4) { msg5 = txt3.substring(0, mid) + def.substring(0, mid);
document.form1.text.value = msg5;
blink2 = 5;
timeblink2 = setTimeout("Blink2()", 300) }
else if (blink2==5) { msg5 = def.substring(0, mid) + txt3.substring(mid, max2);
document.form1.text.value = msg5;
blink2 = 6;
timeblink2 = setTimeout("Blink2()", 300) }
else if (blink2==6) { document.form1.text.value = txt3;
blink2 = 20;
clearTimeout(timeblink2);
Type() }
}

```

</script>

<form name=form1><input type=text name=text size=32,0></form>

第二步:把如下代码加入<body>区域中

<body bgcolor="#ffffff" onload="Type()">

文字逐个闪烁

脚本说明：

把如下代码加入<body>区域中:

```
<script language="JavaScript">
```

```
<!-- Begin
```

```
text = "欢迎光临网页制作特效站"; //显示的文字
```

```
color1 = "blue"; //文字的颜色
```

```
color2 = "red"; //转换的颜色
```



```

fontsize = "6"; //字体大小
speed = 100; //转换速度 (1000 = 1 秒)
i = 0;
if (navigator.appName == "Netscape") {
document.write("<layer id=a visibility=show></layer><br><br><br>");
}
else {
document.write("<div id=a></div>");
}
function changeCharColor() {
if (navigator.appName == "Netscape") {
document.a.document.write("<center><font face=arial size =" + fontsize + "><font color=" +
color1 +
">");
for (var j = 0; j < text.length; j++) {
if(j == i) {
document.a.document.write("<font face=arial color=" + color2 + ">" + Text.charAt(i) +
"</font>");
}
else {
document.a.document.write(text.charAt(j));
}
}
document.a.document.write('</font></font></center>');
document.a.document.close();
}
if (navigator.appName == "Microsoft Internet Explorer") {
str = "<center><font face=arial size=" + fontsize + "><font color=" + color1 + ">";
for (var j = 0; j < text.length; j++) {
if(j == i) {
str += "<font face=arial color=" + color2 + ">" + text.charAt(i) + "</font>";
}
else {
str += text.charAt(j);
}
}
str += "</font></font></center>";
a.innerHTML = str;
}
(i == text.length) ? i=0 : i++;
}
setInterval("changeCharColor()", speed);
// End -->
</script>

```


脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language=javascript>
var layers =document.layers,style=document.all,both=layers||style,idme=908601;
if(layers){layerRef='document.layers';styleRef="};if(style){layerRef='document.all';styleRef =
'.style';}
function writeOnText(obj,str){
if(layers)with(document[obj]){ document.open();document.write(str);document.close();}
if(style)eval(obj+'.innerHTML=str');   }
var dispStr=new Array("欢迎光临 javascript 特效站!!!");
var overMe=0;
function txtTyper(str,idx,idObj,spObj,clr1,clr2,delay,plysnd){
var tmp0=tmp1="",skip=100;
if (both && idx<=str.length) {
if (str.charAt(idx)=='<'){ while(str.charAt(idx)!='>') idx++;idx++;}
if (str.charAt(idx)=='&''&&str.charAt(idx+1)!=' '){ while (str.charAt(idx)!=';')idx++;idx++;}
tmp0 = str.slice(0,idx);
tmp1 = str.charAt(idx++);
if (overMe==0 && plysnd==1){
if (navigator.plugins[0]){
if(navigator.plugins["LiveAudio"][0].type=="audio/basic"           &&
navigator.javaEnabled()){ document.embeds
[0].stop();
setTimeout(" document.embeds[0].play(false)",100);}
} else if (document.all){
ding.Stop();
setTimeout("ding.Run()",100);}
overMe=1;}else overMe=0;
writeOnText(idObj, "<span class="+spObj+"><font color='"+clr1+"'>"+tmp0+"</font><font
color='"+clr2
+">"+tmp1+"</font></span>");
setTimeout("txtTyper('"+str+"', "+idx+", '"+idObj+"', '"+spObj+"', '"+clr1+"', '"+clr2+"',
"+delay+" ,"+plysnd+")",delay);}}
function init(){txtTyper(dispStr[0], 0, 'ttl0', 'ttl1', 'red', '#99FF33', 300, 0);}
</script>

<DIV class=ttl1 id=ttl0></DIV>
```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onload=init(>
```

点击改变文字

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT LANGUAGE="JAVASCRIPT">
```

```
n = (document.layers) ? 1:0
ie = (document.all) ? 1:0
function change_content(divname, newtext) {
    if (n) {
        document.layers[divname].document.write(newtext)
        document.layers[divname].document.close()
    }
    if (ie) document.all[divname].innerHTML = newtext
}
```

```
</SCRIPT>
```

```
<A HREF="default.htm" onClick="change_content('layer1', 'This is the new text!')">Change the
current text to "This is the new text!"</A><BR>
```

```
<DIV ID="layer1" STYLE="position:absolute; top:100; left:200; visibility:visible">
```

```
This is a layer called "layer1"<BR>
```

```
</DIV>
```

文字段任意移动

脚本说明：

把如下代码加入<body>区域中：

```
<SCRIPT LANGUAGE="JAVASCRIPT">
```

```
n = (document.layers) ? 1:0
ie = (document.all) ? 1:0
function move(newleft, newtop) {
    if (n) {
        document.layer1.left = newleft;
        document.layer1.top = newtop;
    }
    if (ie) {
        layer1.style.left = newleft;
        layer1.style.top = newtop;
    }
}
function moveby(left, top) {
    if (n) {
        document.layer1.left = document.layer1.left + left;
        document.layer1.top = document.layer1.top + top;
    }
    if (ie) {
```

```

        layer1.style.left= layer1.style.pixelLeft + left;
        layer1.style.top = layer1.style.pixelTop + top;
    }
}

</SCRIPT>
<A HREF="default.htm" onClick="move(300,300)">Move(300,300)</A><BR>
<A HREF="default.htm" onClick="move(300,100)">Move(300,100)</A><BR>
<A HREF="default.htm" onClick="move(100,300)">Move(100,300)</A><BR>
<A HREF="default.htm" onClick="moveby(20,20)">Moveby(20,20)</A><BR>
<A HREF="default.htm" onClick="moveby(10,20)">Moveby(10,20)</A><BR>
<A HREF="default.htm" onClick="moveby(20,-10)">Moveby(20,-10)</A><BR>
<DIV ID="layer1" STYLE="position:absolute; top:100; left:200; visibility:visible">
This is a layer called "layer1"<BR>
</DIV>

```

文字连续闪烁

脚本说明:

第一步:把如下代码加入<body>区域中

```

<script language="JAVASCRIPT">
    colors2 = new Array(6);
    colors2[0]="#000000";
    colors2[1]="#333300";
    colors2[2]="#665500";
    colors2[3]="#997700";
    colors2[4]="#CC9900";
    colors2[5]="#FFCC00";

    var i=0;
    function fLi2() {
        line2.style.visibility = "visible";
        if (i<6) {
            line2.style.color = colors2[i];
            i++;
            timerID2 = setTimeout( "fLi2()", 16);
        }
        else {
            i=0;
            line2.style.visibility="hidden";
            TimerID2=setTimeout("fLi2()",1000);
        }
    }
</script>

```

```

<div id=line2 style="container:positioned; position:relative; width=50%; height=10%;
left=10%;
font-family=Arial; font-size=35px; line-height=28px; color=black; visibility=hidden;">
JavaScript Planet
</div>

```

第二步:把如下代码加入<body>区域中

```

<body bgcolor="#ffffff" onload="TimerID2=setTimeout('fLi2()',500)"
onunload="clearTimeout(TimerID2)">

```

点击出现链接

脚本说明：

把如下代码加入<body>区域中:

```

<div id=Out0 style="position:relative; left:20; top:+15px; width:90%;" >
  <span id=Out1 class=Outline style="hand: hand; "></span><b id=Out1 class=Outline
style="cursor: hand; ">Click here for some cool links</b>
  <div id=Out1details style="display:None; position:relative; left:12;">
    <U>Not a link</u>
  <P>
  <u>Not a link</u>
  <P>
    <U>Not a link</u>
  <P>
  <u>Not a link</u>
  <P>    <U>Not a link</u>
  <P>
  <u>Not a link</u>
  <P>    <U>Not a link</u>
  <P>
  <u>Not a link</u>
  <P>    <U>Not a link</u>
  <P>
  <u>Not a link</u>
  <P>
</div>
</div>
<script language=JavaScript>

```

```
function clickHandler() {
```

```

var targetId, srcElement, targetElement;
srcElement = window.event.srcElement;
if (srcElement.className == "Outline") {
    targetId = srcElement.id + "details";
    targetElement = document.all(targetId);
    if (targetElement.style.display == "none") {
        targetElement.style.display = "";
    } else {
        targetElement.style.display = "none";
    }
}
}
}

```

```
document.onclick = clickHandler;
```

```
</script>
```

状态栏条

脚本说明：

第一步:把如下代码加入<body>区域中:

```
<STYLE>
```

```

.conts {visibility:hidden}
.tab {
    border-top:solid thin #E0E0E0;
        border-right:solid thin gray;
        border-left:solid thin #E0E0E0;
        font-family:Verdana;
        font-size:10pt;
        text-align:center;
        font-weight:normal}

```

```

.selTab {
    border-left:solid thin white;
        border-top:solid thin white;
        border-right:solid thin black;
        font-weight:bold;
        text-align:center}

```

```
</STYLE>
```

```
<SCRIPT LANGUAGE=JavaScript>
```

```
//a public function that the container uses to pass in values for the labels
```

```
function public_Labels(label1, label2, label3, label4, label5, label6, label7){
```

```
    t1.innerText = label1;
```

```

        t2.innerText = label2;
        t3.innerText = label3;
        t4.innerText = label4;
        t5.innerText = label5;
        t6.innerText = label6;
        t7.innerText = label7;
    }

    //a public function that the container uses to pass in values for the card containers
    function public_Contents(contents1, contents2, contents3, contents4, contents5, contents6,
    contents7){

        t1Contents.innerHTML = contents1;
        t2Contents.innerHTML = contents2;
        t3Contents.innerHTML = contents3;
        t4Contents.innerHTML = contents4;
        t5Contents.innerHTML = contents5;
        t6Contents.innerHTML = contents6;
        t7Contents.innerHTML = contents7;

        init();
    }

    //sets the default display to tab 1
    function init(){
        tabContents.innerHTML = t1Contents.innerHTML;
    }

    //this is the tab switching function
    var currentTab;
    var tabBase;
    var firstFlag = true;

    function changeTabs(){

        if(firstFlag == true){
            currentTab = t1;
            tabBase = t1base;
            firstFlag = false;
        }

        if(window.event.srcElement.className == "tab"){

```



```

currentTab.className = "tab";

tabBase.style.backgroundColor = "white";

currentTab = window.event.srcElement;

tabBaseID = currentTab.id + "base";

tabContentID = currentTab.id + "Contents";

tabBase = document.all(tabBaseID);

tabContent = document.all(tabContentID);

currentTab.className = "selTab";

tabBase.style.backgroundColor = "";

tabContents.innerHTML = tabContent.innerHTML;

    }
}

</SCRIPT>

<DIV STYLE="position:absolute; top:40; height:350; width:500; left:25; border:none thin gray">

<TABLE STYLE="width:100%; height:250" CELLPADDING=0 CELLSPACING=0>
  <TR>
    <TD ID=t1 CLASS=selTab HEIGHT=25>tab 1</TD>
    <TD ID=t2 CLASS=tab>tab 2</TD>
    <TD ID=t3 CLASS=tab>tab 3</TD>
    <TD ID=t4 CLASS=tab>tab 4</TD>
    <TD ID=t5 CLASS=tab>tab 5</TD>
    <TD ID=t6 CLASS=tab>tab 6</TD>
    <TD ID=t7 CLASS=tab>tab 7</TD>
  </TR>
  <TR>
    <TD ID=t1base STYLE="height:2; border-left:solid thin white"></TD>
    <TD ID=t2base STYLE="height:2; background-color:white"></TD>
    <TD ID=t3base STYLE="height:2; background-color:white"></TD>

```

```

        <TD ID=t4base STYLE="height:2; background-color:white"></TD>
        <TD ID=t5base STYLE="height:2; background-color:white"></TD>
        <TD ID=t6base STYLE="height:2; background-color:white"></TD>
        <TD ID=t7base STYLE="height:2; background-color:white;
border-right:solid thin white"></TD>
    </TR>

    <TR>
        <TD HEIGHT="*" COLSPAN=7 ID=tabContents
STYLE=" border-left:solid thin white;
border-bottom:solid thin white;
border-right:solid thin white">sample contents</TD>
    </TR>
</TABLE>
</DIV>

```

```

<DIV CLASS=conts ID=t1Contents>This text is on tab one</DIV>
<DIV CLASS=conts ID=t2Contents>This text is on tab two</DIV>
<DIV CLASS=conts ID=t3Contents>This text is on tab three</DIV>
<DIV CLASS=conts ID=t4Contents>This text is on tab four</DIV>
<DIV CLASS=conts ID=t5Contents>This text is on tab five</DIV>
<DIV CLASS=conts ID=t6Contents>This text is on tab six</DIV>
<DIV CLASS=conts ID=t7Contents>This text is on tab seven</DIV>

```

第二步:把<body>中的内容改为 :

```
<body bgcolor="#ffffff" onload=init() onclick=changeTabs(>
```

链接在右面打开

脚本说明 :

把如下代码加入<body>区域中:

```

<SCRIPT>
function _init(){
    for(var i=0;i<document.all.length;i++){
        if(document.all[i].getAttribute("menu")){

```

```

        var attrs = _eat_attr(document.all[i].getAttribute("menu"));
        var tree = new Array();
        var src = document.all.item(attrs["src"]).innerText; // get the config info from
the contents of the designated source element
        src = _strip(src); // remove whitespace informatin
        tree = _compile(tree,src); // turn it into a multilevel array

// at this time, associate the element the
// menu is attached to with the created menuing elements
        var menuId = _menus.length;
        document.all[i].menuId = menuId;
        document.all[i].onmouseover = _rootmouseover;
        document.all[i].onmouseout = _rootmouseout;

// get and preset designer preferences
        var attrs = _eat_attr(document.all[i].getAttribute("menu"));
        attrs["border-width"] = (attrs["border-width"]!=null?attrs["border-width"]:1);
        attrs["border-color"] =
(attribs["border-color"]!=null?attribs["border-color"]:"black");
        attrs["background"] =
(attribs["background"]!=null?attribs["background"]:"white");
        attrs["highlight"] = (attrs["highlight"]!=null?attrs["highlight"]:"#DCDCDC");
        attrs["font-size"] = (attrs["font-size"]!=null?attrs["font-size"]:"normal");
        attrs["font-family"] = (attrs["font-family"]!=null?attrs["font-family"]:"");
        attrs["font-color"] = (attrs["font-color"]!=null?attrs["font-color"]:"");
        attrs["icon-color"] = (attrs["icon-color"]!=null?attrs["icon-color"]:"black");
        attrs["arrow"] = (attrs["arrow"]!=null?attrs["arrow"]:true);
        attrs["showrow"] = (attrs["showrow"]!=null?attrs["showrow"]:true);
        attrs["height"] = (attrs["height"]!=null?attrs["height"]:22);
        attrs["width"] = (attrs["width"]!=null?attrs["width"]:150);
        attrs["arrow-offset"] =
(attribs["arrow-offset"]!=null?Number(attrs["arrow-offset"]):135);
        attrs["menu-offset"] =
(attribs["menu-offset"]!=null?Number(attrs["menu-offset"]):1);
        attrs["menu-topoffset"] =
(attribs["menu-topoffset"]!=null?Number(attrs["menu-topoffset"]):0);
        attrs["wait"] = (attrs["wait"]!=null?Number(attrs["wait"]):500);
        document.all[i].attrs = attrs;

// now, create all of the needed elements for this menu
        _create(document.all[i],tree);
    }
}
}

```

```

window.onload = _init;
////////////////////////////////////

////////////////////////////////////
//// takes a position and a string,
//// returns the position of the next unpaired "]" character
function _pair(after,str){
    while(1){
        var nextA = str.indexOf("[",after + 1);
        var nextB = str.indexOf("]",after + 1);
        if(nextA == -1){
            return nextB;
        }
        if(nextA > nextB){
            return nextB;
        }
        after = _pair(nextA,str);
    }
}

////////////////////////////////////
//// transforms raw text input into a multilevel array
//// returns an array based on the string input
function _compile(ary,str){
    while(1){ // keep circling and eating the str

        // when the str is empty, return the built array
        if(str.length == 0){
            return ary;
        }

        // is there any more sub-arrays?
        var nextA = str.indexOf("[");
        if(nextA == -1){
            var go = str;
            var spawn = "";
            str = "";
        }else{
            var go = str.substring(0,nextA);
            var spawn = str.substring(str.indexOf("[") + 1,_pair(str.indexOf("["),str))
            str = str.substring(_pair(str.indexOf("["),str) + 1,str.length);
        }
    }
}

```


`_menus[menuId] = thismenu; // save a reference to the element object in a global array for later use`

```
thismenu.menuId = menuId; // tell the element object where it is in the global array
thismenu.close = _close; // assign a close function to it
thismenu.menuParent = null; // initialize some variables to null
thismenu.menuChild = null;
thismenu.highlightBG = e.attrs["highlight"];
thismenu.normalBG = e.attrs["background"];
thismenu.menuOffset = e.attrs["menu-offset"];
thismenu.menuTopoffset = e.attrs["menu-topoffset"];
thismenu.waitDelay = e.attrs["wait"];
var prevBottom = 0; // initialize where the option elements should start drawing
```

`// create a span element for every option`

```
for(var i=0;i<ary.length;i++){
  str = '<SPAN ID="_link_' // assign a unique name
    + menuId
    + '_'
    + i
    + " STYLE="position:absolute;top:'
    + prevBottom // position it correctly
    + ';left:0;height:'
    + e.attrs["height"]
    + ';overflow:hidden;width:'
    + e.attrs["width"]
    + ';background:'
    + e.attrs["background"]
    + ';border-width:'
    + e.attrs["border-width"]
    + ';border-style:solid;border-color:'
    + e.attrs["border-color"]
    + ';';
  if(e.attrs["showrow"]!=true && i != 0){
    str += 'border-top-width:0;';
  }
  str += 'text-align:left;font-size:'
    + e.attrs["font-size"]
    + ';padding-left:4;">';
  if(ary[i].icon!=null){
    str += '<SPAN STYLE="font-family:webdings;color:'
      + e.attrs["icon-color"]
      + "'>&#
      + ary[i].icon
      + '</SPAN> ';
  }
}
```

```

    }
    str += '<A HREF='
        + ary[i].url
        + ' TITLE='
        + ary[i].desc
        + ' STYLE="font-family:'
        + e.attrs["font-family"]
        + ';color:'
        + e.attrs["font-color"]
        + ';padding-left:3;">'
        + ary[i].name // fill in the content/name
        + '</A>';
    if(ary[i].length > 0 && e.attrs["arrow"]){
        str += '<SPAN STYLE="font-family:webdings;position:absolute;top:0;left:'
            + e.attrs["arrow-offset"]
            + ';width:'
            + (e.attrs["width"] - e.attrs["arrow-offset"])
            + ';overflow:hidden;color:'
            + e.attrs["icon-color"]
            + ">4</SPAN>";
    }
    str += '</SPAN>';
    thismenu.insertAdjacentHTML("BeforeEnd",str); // insert it inside the menu element
    thisoption = document.all.item('_link_' + menuId + '_' + i);
    thisoption.menuId = menuId; // save some references and initialize some variables
    thisoption.onmouseover = _optionmouseover;
    thisoption.onmouseout = _optionmouseout;
    prevBottom = thisoption.style.pixelTop + (e.attrs["height"] - e.attrs["border-width"]);
    // where should the next one draw?
    if(ary[i].length > 0){ // uhoh, if there is a submenu here, better draw it!
        thisoption.menuChild=_menus.length; // tell this option that it has a child
        _create(e,ary[i]);
    }
}
thismenu.style.pixelHeight = prevBottom; // set the height on the menu element
}
////////////////////////////////////

////////////////////////////////////
////////////////////////////////////
//// All the following are used on the "fly"

```

```

//// as needed during the documents life
////
////

var _menus = new Array(); // global array of menus
var _currentMenu = null; // temporary storage of the current and current root menu elements
var _rootMenu = null;
var _rootKludge = null;
var _zIndex = 1;

////////////////////////////////////
//// show the menu for this object
function _rootmouseover(){
    var e = window.event.srcElement;
    if(_rootMenu != null){
        _menus[_rootMenu].close();
    }
    _rootMenu = e.menuId; // store a temporary reference
    _rootKludge = e.menuId;
    var attrs = _eat_attr(e.getAttribute("menu")); // initialize its position based on the config
    _menus[e.menuId].style.pixelTop = attrs["top"];
    _menus[e.menuId].style.pixelLeft = attrs["left"];
    _menus[e.menuId].style.visibility = "visible";
    _menus[e.menuId].style.zIndex = _zIndex++;
}
////////////////////////////////////

////////////////////////////////////
//// if the mouse leaves the main element,
//// try to close the displayed menu
function _rootmouseout(){
    _rootKludge = null;
    window.setTimeout("if(_rootKludge != " + _rootMenu + "){_menus[" + _rootMenu +
"].close();}",_menus[_rootMenu].waitDelay);
}
////////////////////////////////////

////////////////////////////////////
//// nifty little IMPORTANT recursive function that
//// returns true only if the id to check
//// is in the heritage of the current menu!

```



```

function _heritage(menu,check){
    if(_menus[menu].menuId == check){
        return true;
    }else{
        // if I have a parent, check it, otherwise the answer is no
        if(_menus[menu].menuParent != null){
            return _heritage(_menus[menu].menuParent,check);
        }else{
            return false;
        }
    }
}
}
////////////////////////////////////

////////////////////////////////////

//// associated with every menu element object,
//// close this menu unless it is still active
function _close(){
    if(_currentMenu != null){
        if(_heritage(_currentMenu,this.menuId)){
            return;
        }
    }
    if(this.menuChild != null){
        _menus[this.menuChild].close();
    }
    this.style.visibility = "hidden";
    this.menuChild = null;
    this.menuParent = null;
}
}
////////////////////////////////////

////////////////////////////////////

//// when the mouse passes over an option
function _optionmouseover(){
    // some ugly kludges to reduce flashing when the mouse passes through a subelement of the
option
    if(window.event.srcElement.menuId==null    &&    window.event.fromElement.id    ==
window.event.srcElement.offsetParent.id){
        return;
    }
    if(window.event.fromElement.offsetParent!=null){

```

```

        if(window.event.fromElement.menuId==null    &&    window.event.srcElement.id    ==
window.event.fromElement.offsetParent.id){
            return;
        }
    }
    if(window.event.srcElement.menuId==null){
        var e = window.event.srcElement.offsetParent;
    }else{
        var e = window.event.srcElement;
    }
    e.style.background = _menus[e.menuId].highlightBG;    // highlight it
    _currentMenu = e.menuId;    // reset the current menu
    if(_menus[_currentMenu].menuChild != null){    // close any previous children
        _menus[_menus[_currentMenu].menuChild].close();
    }
    if(e.menuChild!=null){    // if this option has a submenu, display it
        _menus[_currentMenu].menuChild = e.menuChild;    // tell the menu it has a child
        _menus[e.menuChild].menuParent = _currentMenu;    // tell the child it has a parent
        _menus[e.menuChild].style.pixelTop    =    _menus[_currentMenu].style.pixelTop    +
e.style.pixelTop + _menus[_currentMenu].menuTopoffset;
        _menus[e.menuChild].style.pixelLeft    =    _menus[_currentMenu].style.pixelLeft    +
_menus[_currentMenu].style.pixelWidth + _menus[_currentMenu].menuOffset;
        _menus[e.menuChild].style.visibility = "visible";
        _menus[e.menuChild].style.zIndex = _zIndex++;
    }
}
}
//////////

//////////
//// when the mouse leaves the option
function _optionmouseout(){
    // some ugly kludges to reduce flashing when the mouse passes through a subelement of the
option
    if(window.event.srcElement.menuId==null    &&    window.event.toElement.id    ==
window.event.srcElement.offsetParent.id){
        return;
    }
    if(window.event.toElement.offsetParent!=null){
        if(window.event.toElement.menuId==null    &&    window.event.srcElement.id    ==
window.event.toElement.offsetParent.id){
            return;
        }
    }
}
}

```

```

if(window.event.srcElement.menuId==null){
    var e = window.event.srcElement.offsetParent;
}else{
    var e = window.event.srcElement;
}
e.style.background = _menus[e.menuId].normalBG;        // unhighlight it
var to = window.event.toElement.menuId;                // greener pasture?
if(to!=null){ // leaving to a menu element
    if(to!=e.menuId){ // not this menu
        _menus[_currentMenu].close();
    }else{ // this menu, but hide any existing children
        if(_menus[e.menuId].menuChild!=null){
            _menus[_menus[e.menuId].menuChild].close();
        }
    }
}else{ // wait a bit, and close the whole menu
    window.setTimeout("_menus[_rootMenu].close()",_menus[_rootMenu].waitDelay);
}
_currentMenu = null;
}

```

```

function _eat_attrib(str){
    var chunks = new Array();
    var all = new Array();

    chunks=str.split(";");

    for(var i=0;i<chunks.length;i++){
        var tmpA = new Array();
        tmpA=chunks[i].split(":");
        all[tmpA[0]]=tmpA[1];
    }
    return all;
}

```

```

function _strip(str){
    var A = new Array();

    A = str.split("\t");
    str = A.join("");

    A = str.split("\n");
    str = A.join("");
}

```

```
A = str.split("\r");
str = A.join("");
```

```
return str;
}
```

```
//////////
```

```
</SCRIPT>
```

```
<a href="default.htm" menu="top:60;left:200;src:menusrc;">Start</a>
```

```
<div id="menusrc" style="display:none;">
```

```
Yahoo!http://www.yahoo.com!Just a simple link to yahoo.;
```

```
Microsoft!http://www.microsoft.com!Go ahead and visit Microsoft's Home Page;
```

```
[
```

```
Internet Explorer!http://www.microsoft.com/ie!Microsoft Internet Explorer;
```

```
Internet Information Server!http://www.microsoft.com/iis!Ver 4 is VERY powerful;
```

```
]
```

```
W3C!http://www.w3.org!The 'source' :);
```

```
</div>
```

文字胡乱跳动

脚本说明:

第一步:把如下代码加入<body>区域中

```
<script language="JavaScript">
```

```
function nextSize(i,incMethod,textLength)
```

```
{
```

```
if (incMethod == 1) return (72*Math.abs( Math.sin(i/(textLength/3.14))) );
```

```
if (incMethod == 2) return (255*Math.abs( Math.cos(i/(textLength/3.14))));
```

```
}
```

```
function sizeCycle(text,method,dis)
```

```
{
```

```
output = "";
```

```
for (i = 0; i < text.length; i++)
```

```
{
```

```
size = parseInt(nextSize(i +dis,method,text.length));
```

```
output += "<font style='font-size: "+ size +"pt'" +text.substring(i,i+1)+ "</font>";
```

```
}
```

```
theDiv.innerHTML = output;
```

```
}
```

```
function doWave(n)
```

```

{
    theText = "JavaScript";
    sizeCycle(theText,1,n);
    if (n > theText.length) {n=0}
    setTimeout("doWave(" + (n+1) + ")", 50);
}
</script>
<div ID="theDiv" align="center">

</div>

```

第二步:把如下代码加入<body>区域中

```
<body bgcolor="#ffffff" onload=doWave(0);>
```

按钮驱动文字闪烁

脚本说明:

第一步:把如下代码加入<body>区域中

```

<SCRIPT LANGUAGE="JavaScript">
var x=9;
var strobe="on"
if (navigator.appName == "Netscape") {
visShow="show";
visHide="hide";
docStyle="document.";
styleDoc="";
}
else {
visHide="hidden";
visShow="visible";
docStyle="";
styleDoc=".style";
}
</SCRIPT>
<SCRIPT LANGUAGE="JavaScript">
function hide1() {
eval(docStyle+ 'object1' + styleDoc + '.visibility=' + visHide);
}
function hide2() {
eval(docStyle+ 'object2' + styleDoc + '.visibility=' + visHide);
}
function hide3() {
eval(docStyle+ 'object3' + styleDoc + '.visibility=' + visHide);
}

```

```
}
function hide4() {
eval(docStyle+ 'object4' + styleDoc + '.visibility=' + visHide);
}
function hide5() {
eval(docStyle+ 'object5' + styleDoc + '.visibility=' + visHide);
}
function hide6() {
eval(docStyle+ 'object6' + styleDoc + '.visibility=' + visHide);
}
function hide7() {
eval(docStyle+ 'object7' + styleDoc + '.visibility=' + visHide);
}
function hide8() {
eval(docStyle+ 'object8' + styleDoc + '.visibility=' + visHide);
}
function hide9() {
eval(docStyle+ 'object9' + styleDoc + '.visibility=' + visHide);
}
function hide10() {
eval(docStyle+ 'object10' + styleDoc + '.visibility=' + visHide);
}
function show1() {
eval(docStyle+ 'object1' + styleDoc + '.visibility=' + visShow);
hide2(),hide3());
}
function show2() {
eval(docStyle+ 'object2' + styleDoc + '.visibility=' + visShow);
hide1(),hide3());
}
function show3() {
eval(docStyle+ 'object3' + styleDoc + '.visibility=' + visShow);
hide2(),hide4());
}
function show4() {
eval(docStyle+ 'object4' + styleDoc + '.visibility=' + visShow);
hide3(),hide5());
}
function show5() {
eval(docStyle+ 'object5' + styleDoc + '.visibility=' + visShow);
hide4(),hide6());
}
function show6() {
eval(docStyle+ 'object6' + styleDoc + '.visibility=' + visShow);
```

```

hide5(),hide7());
}
function show7() {
eval(docStyle+ 'object7' + styleDoc + '.visibility=' + visShow);
hide6(),hide8());
}
function show8() {
eval(docStyle+ 'object8' + styleDoc + '.visibility=' + visShow);
hide7(),hide9());
}
function show9() {
eval(docStyle+ 'object9' + styleDoc + '.visibility=' + visShow);
hide8(),hide10());
}
function show10() {
eval(docStyle+ 'object10' + styleDoc + '.visibility=' + visShow);
hide9());
}
function strobe1() {
x+=1;
eval("show" + x + "()");
if (x<10) setTimeout("strobe1()", 75);
else if (strobe=="on") strobe2());
}
function strobe2() {
x-=1;
eval("show" + x + "()");
if (x>1) setTimeout("strobe2()", 75);
else strobe1());
}
function strobeOn() {
x=9;
strobe="on";
strobe1());
}
function strobeOff() {
strobe="off";
}
</SCRIPT>
<div id="vis" style="position:absolute; visibility:show; left:175px; top:280px; z-index:1">
<table cellpadding=2 border=1><tr>
<td><center><b>Strobe:</b></center></font></a></td>
<td><a href="javascript:strobeOn()">
<font color="#000000"><center>on</center></font></a></td>

```

```
<td><a href="javascript:strobeOff()">
<font color="#000000"><center>off</center></font></a></td>
</tr></table></div>
```

```
<div id="object1" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=#eaffff width=175 height=50><td><center><b><font
color="#F9F9F9">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object2" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#ECECEC">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object3" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#D5D5D5">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object4" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#C0C0C0">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object5" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#b0b0b0">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object6" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#939393">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object7" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#808080">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object8" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#6b6b6b">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object9" style="position:absolute; visibility:hide; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#424242">JavaScript Planet</font></b></center></td></table>
</div>
```

```
<div id="object10" style="position:absolute; visibility:show; left:175px; top:300px; z-index:1">
<table border=1 bgcolor=eaffff width=175 height=50><td><center><b><font
color="#000000">JavaScript Planet</font></b></center></td></table>
</div><P>
```


</CENTER>

文字向左移动

脚本说明：

把如下代码加入<body>区域中：

```
<script language="JavaScript1.2">
//设置 marquee 的宽度 (in pixels)
var marqueeWidth=400
//设置 marquee 的高度 (in pixels, 该参数只适用于 NS)
var marqueeHeight=20
//设置 marquee 滚动的速度(数值大速度快)
var speed=4
//设置 marquee 显示内容，使用标准的 HTML 语法。
var marqueeContents='<strong><big>欢迎光临<a href="http://www.javascript2000.com">网页制
作特效</a> javascript 的精彩世界 </big></strong></font>'
if (document.all)
document.write('<marquee                                scrollAmount='+speed+'
style="width:'+marqueeWidth+'">'+marqueeContents+'</marquee>')
function regenerate(){
window.location.reload()
}
function regenerate2(){
if (document.layers){
setTimeout("window.onresize=regenerate",450)
intializemarquee()
}
}
function intializemarquee(){
document.cmarquee01.document.cmarquee02.document.write('<nobr>'+marqueeContents+'</nobr
>')
document.cmarquee01.document.cmarquee02.document.close()
theLength=document.cmarquee01.document.cmarquee02.document.width
scrollit()
}
function scrollit(){
if (document.cmarquee01.document.cmarquee02.left>=theLength*(-1)){
document.cmarquee01.document.cmarquee02.left-=speed
setTimeout("scrollit()",100)
}
else{
document.cmarquee01.document.cmarquee02.left=marqueeWidth
scrollit()
}
}
}
```

```
window.onload=regenerate2
</script>
<ilayer width={marqueewidth}; height={marqueeheight}; name="cmarquee01">
<layer name="cmarquee02"></layer>
</ilayer>
```

文字弯曲变形

脚本说明：

把如下代码加入<body>区域中：

```
<span style="position:relative; width:200; height:50;
filter:wave(Add=0,Freq=5,LightStrength=10,Phase=1,Strength=3)"><p>
<font color="#FF0000"> 欢迎光临 javascript 网页制作特效站，请多提意
见!!!</font></p></span>
```

双重输入文字 复制不了 综合字符集

脚本说明：

把如下代码加入 <body>区域中：

```
<SCRIPT LANGUAGE="JavaScript">
```

```
function freecol(brtspc,bgcolor)
{
    table("cellspacing='0' cellpadding='0' bgcolor='"+bgcolor+"'");
    tr();
        td("width='"+brtspc+"'");
        td("/");
    tr("/");
    table("/");
}
```

```
function table(strg)
{
    if (strg != "/")
        document.write("<table "+anf repl(strg)+">");
    else
        document.write("</table>");
}
```

```
function tr(strg)
{
```

```

        if (strg != "/" )
            document.write("<tr "+anf repl(strg)+">");
        else
            document.write("</tr>");
    }

function td(strg)
{
    if (strg != "/" )
        document.write("<td "+anf repl(strg)+">");
    else
        document.write("</td>");
}

function th(strg)
{
    if (strg != "/" )
        document.write("<th "+anf repl(strg)+">");
    else
        document.write("</th>");
}

// interpreting ' as " in
a string
function anf repl(strg)
{
    var i;
    var outstring= "";

    if (!strg)
        strg = "";

    for (i=0; i<strg.length; i++)
    {
        if(strg.charCodeAt(i)==39)
            outstring = outstring + chr(34);
        else
            outstring = outstring + strg.charAt(i);
    }
    return outstring;
}

function chr(asciwert)
{
    return String.fromCharCode(asciwert);
}

```

```

}

function dec2hex(dec)
{
    var result;
    var i,j;

    hexChars = "0123456789ABCDEF";
    i = dec % 16;
    j = (dec - i) / 16;
    result = hexChars.charAt(j) + hexChars.charAt(i);
    return result;
}

// Main programm: Sorry 4 the jurble but its hard to combine the structure of the
// program
// and the structure of the tables.

function outtest(which)
{
    var i,j;
    var actwert,hexwert,buchst;

    if (which == false)
        var brtchar = htmchar;
    else
        var brtchar = jschar;

    document.write(anf repl("<font      size='+1'><b>ASCII      Table      of:
"+font+ "</b></font><br>"));

    table("border='0' cellspacing='0' cellpadding='0' bgcolor='"+bgcolor+"'");
    tr();
        td();
            freecol(brtspc,bgcolor);
        td("/");

    for (i=0 ; i<spalt ; i++)
    {
        td();
            table("cellspacing='0' cellpadding='0' bgcolor='"+bgcolor+"'
border='0'      bordercolor='Silver'      bordercolorlight='Silver'
bordercolordark='Silver'");

```

```

        tr();
            th("width='"+(brtdec+2)+"' align='CENTER'");
                document.write("Dec");
            th("/");
            th("width='"+(brthex+2)+"' align='CENTER'");
                document.write("Hex");
            th("/");
            th("<th width='"+(brtchar+2)+"' align='CENTER'");
                document.write("Chr");
        tr("/");
        table("/");
    td("/");
    td();
        freecol(brtspc,bgcolor);
    td("/");
    }
tr("/");

    for (i=0 ; i<Math.ceil(max/spalt) ; i++)
    {
tr();
    td();
        freecol(brtspc,bgcolor);
    td("/");

        for (j=0 ; j<spalt ; j++)
        {
            if (Math.floor((i*spalt+j)/((max+1)/100)) <= 100)
                status = "Building Table: " +
Math.floor((i*spalt+j)/((max+1)/100)) + "%";
            actwert=j*Math.ceil(max/spalt)+i;
            hexwert=dec2hex(actwert);
            if (which == false)
                buchst="&#" + actwert + ";";
            else
                buchst=chr(actwert);
            if (actwert > 255)
                actwert=hexwert=buchst="";

        td();
        table("cellspacing='0' cellpadding='0' bgcolor='White'
border='1'");

```

```

        tr();
        td("width='"+brtdec+"' align='CENTER'");
            document.write(" "+actwert);
        td("/");
        td("width='"+brthex+"' align='CENTER'");
            document.write(" "+hexwert);
        td("/");
        th("width='"+brtchar+"' align='CENTER'");
            document.write(anf repl("<font
face=' "+font+" '>"));
            document.write(" "+buchst);
            document.write("</font>");

```

```

        th("/");
        tr("/");
        table("/");
        td("/");
        td();
            freecol(brtspc,bgcolor);
        td("/");
        }
    tr("/");
    }
    status = "Viewing Table: Please wait."
    table("/");
    }

```

</SCRIPT>

<SCRIPT LANGUAGE="JavaScript">

```

    var spalt = 6;                // number of columns
    var max = 256;                // maximum ascii value
    var brtdec = 40;              // width of DEC column
    var brthex = 30;              // width of HEX column
    var brtspc= 15;                // width of the space between the
columns
    var bgcolor = "silver";        // colour of the spaces
    var htmchar = 60;              // width of C-R
column-HTML-Version (CANCEL Button)
    var jschar = 40;                // width of C-R column-JS-Version
(CK Button)

```

```
var font = "罗马字符 " // Font of the ASCII character

outtest(confirm("确定 :\t字符将用 javascript解释 .\n取消 :\t字符将用 HTML
来解释 . "));
```

```
</SCRIPT>
```

```
</CENTER>
```

```
<SCRIPT LANGUAGE="JavaScript">
```

```
status = "Table ready";
```

```
</SCRIPT>
```

文字从小变大

脚本说明：

第一步 把如下代码加入 <body>区域中

```
<style type="text/css">
```

```
body
```

```
{
background-color:#FFFFFF;
font-family: Arial;
font-size:10pt;
}
```

```
</style>
```

```
<script>
```

```
text=new Array('www','njcatv','net','怀柔网')
```

```
var numText=4
```

```
color=new Array('#000000','#2F2F2F','#4F4F4F','#7F7F7F','#408080')
```

```
var numColors=5
```

```
var endSize=70
```

```

var Zspeed=30

var Cspeed=200

var font='Arial Black'

var hide=false

var size=10

var gonum=0

var ie, n;

if (document.all) {

    n=0

    ie=1

    zoomText='document.all.zoom.innerText=text[num]'

    zoomSize='document.all.zoom.style.fontSize=size'

    closeIt=""

    fadeColor="document.all.zoom.style.color=color[num]"

}

if (document.layers) {

    n=1; ie=0

    zoomText=""

    zoomSize="document.zoom.document.write('<p align=\"center\"
style=\"font-family: '+font+'; font-size: '+size+'px;
color: '+color[0]+'\">'+text[num]+'</p>')"

    closeIt="document.zoom.document.close()"

    fadeColor="document.zoom.document.write('<p align=\"center\"

```



```
style=\"font-family: '+font+'; font-size: '+endSize+'px;
color: '+color[num]+'\">'+text[numText-1]+'</p>' )"
```

```
}
```

```
function zoom(num, fn){
```

```
    if (size<endSize){
```

```
        eval (zoomText)
```

```
        eval (zoomSize)
```

```
        eval (closeIt)
```

```
        size+=5;
```

```
        setTimeout ("zoom("+num+", '"+fn+"' )", Zspeed)
```

```
    }else{
```

```
        eval (fn);
```

```
    }
```

```
}
```

```
function fadeIt(num){
```

```
    if (num<numColors){
```

```
        eval (fadeColor)
```

```
        eval (closeIt)
```

```
        num+=1;
```

```
        setTimeout ("fadeIt("+num+")", Cspeed)
```

```
    }else{
```

```
        hideIt()
```

```
    }  
}  
  
function hideIt(){  
    if(hide){  
        if(ie)document.all.zoom.style.visibility="hidden"  
        if(n)document.layers.zoom.visibility="hidden"  
    }  
}  
  
function init(){  
    if(ie){  
        document.all.zoom.style.color=color[0]  
        document.all.zoom.style.fontFamily=font  
    }  
    if(ie || n) go(0)  
}  
  
function go(num){  
    gonum+=1  
    size=10  
    if(num<numText){  
        zoom(num, 'go('+gonum+')')  
    }else{  
    }
```

```

        fadeIt(0)
    }
}

</script>
<div id="zoom" align="center" style="position:absolute; top:150">

```

导航菜单类

树形菜单 (一)

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<script language="JavaScript1.2">
scores = new Array(20);var numTotal=0;NS4 = (document.layers) ? 1 : 0;IE4 =
(document.all) ? 1 : 0;ver4 = (NS4 || IE4) ? 1 : 0;if (ver4) { with (document)
{
write("<STYLE TYPE='text/css'>");
if (NS4)
write(".parent {position:absolute; visibility:visible}");
write(".child {position:absolute; visibility:visible}");
write(".regular {position:absolute; visibility:visible}") } else
{
write(".child {display:none}") }
write("</STYLE>"); }}function getIndex(el) { ind = null; for (i=0;
i<document.layers.length; i++) { whichEl = document.layers[i]; if
(whichEl.id == el) { ind = i; break; } }
return ind;}function arrange() { nextY = document.layers[firstInd].pageY
+document.layers[firstInd].document.height; for (i=firstInd+1;
i<document.layers.length; i++) { whichEl = document.layers[i]; if
(whichEl.visibility != "hide") { whichEl.pageY = nextY;
nextY += whichEl.document.height; } }}function initIt(){ if (!ver4)
return; if (NS4) { for (i=0; i<document.layers.length; i++)
{
whichEl = document.layers[i];
if
(whichEl.id.indexOf("Child") != -1) whichEl.visibility = "hide"; }
arrange(); } else { divColl = document.all.tags("DIV"); for
(i=0; i<divColl.length; i++) { whichEl = divColl(i); if
(whichEl.className == "child") whichEl.style.display =
"none"; } }}function expandIt(el) { if (!ver4) return; if (IE4)
{
whichEl1 = eval(el + "Child"); for(i=1;i<=numTotal;i++){
whichEl = eval(scores[i] + "Child"); if(whichEl!=whichEl1) {
whichEl.style.display = "none"; } } whichEl1 =
eval(el + "Child"); if (whichEl1.style.display == "none")
{
whichEl1.style.display = "block"; } else
{
whichEl1.style.display = "none"; } } else

```

```

{      whichEl = eval("document." + el + "Child");
  for(i=1;i<=numTotal;i++){      whichEl = eval("document." + scores[i] +
"Child");      if(whichEl!=whichEl1) {      whichEl.visibility =
"hide";      }      }      if (whichEl.visibility = "hide")
{      whichEl.visibility = "show";      }      else
{      whichEl.visibility="hide";      }      arrange();  }}onload
= initIt;
</script>

```

第二步 把如下代码加入 <body>区域中

```

<div id='KB1Parent' class='parent'><a href="default.htm" onClick="expandIt('KB1');
return false">
<IMG SRC='plus.gif' BORDER=0> 时间日期类 </a></div><div id='KB1Child'
class='parent'>
<a href='time1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>任意位置显示
时钟 </a><br>
<a href='time2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>倒计时代码生
成器 </a><br>
<a href='time3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>八种风格时间
显示 </a><br>
<a href='time4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>显示登陆时间
</a><br>
<a href='time5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>日历生成器
</a><br>
<a href='time6.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>退出显示访问
时间 </a><br>
<a href='time7.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>一款特酷的时
钟 </a><br>
<a href='time8.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>全中文日期显
示 </a></div>
<div id='KB2Parent' class='parent'><a href="default.htm" onClick="expandIt('KB2');
return false">
<IMG SRC='plus.gif' BORDER=0> 页面导航类 </a></div><div id='KB2Child'
class='child'>
<a href='dao1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>显示站点信息
导航 </a><br>
<a href='dao2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>任意显示导航
信息 </a><br>
<a href='dao3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>动态导航脚本
</a><br>
<a href='dao4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>下拉式导航菜
单 </a><br>

```

[
](dao5.htm)

[
](dao6.htm)

[
](dao7.htm)

[
](dao8.htm)

[
](dao9.htm)

[
](dao10.htm)

[](dao11.htm)

</div>

<div id='KB3Parent' class='parent'>

 页面背景类 </div><div id='KB3Child' class='child'>

[
](back1.htm)

[
](back2.htm)

[
](back3.htm)

[
](back4.htm)

[
](back5.htm)

[
](back6.htm)

[
](back7.htm)

[
](back8.htm)

[</div>](back9.htm)

<div id='KB4Parent' class='parent'>

 页面特效类 </div><div id='KB4Child' class='child'>

[
](ye1.htm)

字

 滚动显示的
LOGO

 文本自动滚屏

 控制别人输入字
数

 文本上下弹跳

 特酷消隐字体

 文本框栏目介
绍

 旋转变换文字

 特酷的文本输
出

 页面自动滚屏
效果

 炽热的文字特
效

 鼠标响应文字
变色
</div>
<div id='KB5Parent' class='parent'><a href="default.htm" onClick="expandIt('KB5');
return false">
 图形图 象 类 </div><div id='KB5Child'
class='child'>
 禁止图片
下载

 图片隐现
效果

 随机显示
图片

 图片变形
扭曲

 雪 景

 图片渐渐
出现

 相片选择
器

 图形循环
渐显


```
<a href='picture10.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>图形左右  
晃动 </a><br>  
<a href='picture11.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>图形选择  
脚本 </a><br>  
<a href='picture12.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>图片翻滚  
导航 </a><br>  
<a href='picture13.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>图片翻滚  
导航 </a>  
</div>  
<div id='KB6Parent' class='parent'><a href="default.htm" onClick="expandIt('KB6');  
return false">  
<IMG SRC='plus.gif' BORDER=0> 按钮特效类 </a></div><div id='KB6Child'  
class='child'>  
<a href='an2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>跑马灯式链接说  
明 </a><br>  
<a href='an3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>窗口打开关闭  
</a><br>  
<a href='an4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>浮动的链接说明  
</a><br>  
<a href='an5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>链接处变换色彩  
</a><br>  
<a href='an6.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>变换链接色和底  
色 </a><br>  
<a href='an7.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>按顺序点击链接  
</a></div>  
<div id='KB7Parent' class='parent'><a href="default.htm" onClick="expandIt('KB7');  
return false">  
<IMG SRC='plus.gif' BORDER=0> 鼠标事件类 </a></div><div id='KB7Child'  
class='child'>  
<a href='shu1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>图片跟随鼠标  
</a><br>  
<a href='shu2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>鼠标响应新页  
面 </a><br>  
<a href='shu3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>禁用鼠标左右  
键 </a><br>  
<a href='shu4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>鼠标控制窗口  
开关 </a><br>  
<a href='picture6.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>鼠标点击  
效果 </a><br>  
<a href='shu5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>禁用右键自动  
导航 </a><br>  
<a href='shu6.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>鼠标激活警告  
框 </a>  
</div>
```

```
<div id='KB8Parent' class='parent'><a href="default.htm" onClick="expandIt('KB8');
return false">
<IMG SRC='plus.gif' BORDER=0>Cookie 脚本 </a></div><div id='KB8Child'
class='child'>
<a href='cook1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>随登陆次数变
提示 </a><br>
<a href='cook2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>集成
Cookies</a><br>
<a href='cook3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>使窗口仅弹出
一次 </a><br>
<a href='cook4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>签名提示程序
</a><br>
<a href='cook5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>记录上次登录
时间 </a><br>
<a href='cook6.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>自由控制打开
窗口 </a><br>
<a href='cook7.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>记录页面修改
时间 </a><br>
<a href='cook8.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>检测 IE去过
站点 </a><br>
<a href='cook9.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>离开时显示信
息 </a><br>
<a href='cook10.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>弹出窗口自
动关闭 </a><br>
<a href='cook11.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>离开页面弹
出窗口 </a><br>
<a href='cook12.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>进入时显示
信息 </a></div>
<div id='KB9Parent' class='parent'><a href="default.htm" onClick="expandIt('KB9');
return false">
<IMG SRC='plus.gif' BORDER=0> 文本特效类 </a></div><div id='KB9Child'
class='child'>
<a href='text1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>随机信息显示
</a><br>
<a href='text2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>随机文本链接
</a><br>
<a href='text3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>所有链接不停
变色 </a><br>
<a href='text4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>鼠标经过文字
变色 </a><br>
<a href='text5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>随日期变换文
本 </a><br>
<a href='ye9.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字颜色渐变脚
本 </a><br>
```



```
<a href='ye5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文本自动输出
</a></div>
<div id='KB10Parent' class='parent'><a href="default.htm"
onClick="expandIt('KB10'); return false">
<IMG SRC='plus.gif' BORDER=0> 状态栏特效 </a></div><div id='KB10Child'
class='child'>
<a href='ye8.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>状态栏跑马灯脚
本 </a><br>
<a href='zhuang1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字从右弹
出 </a><br>
<a href='zhuang2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字从左依
次弹出 </a><br>
<a href='zhuang3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字从右到
左移动 </a><br>
<a href='zhuang4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字快速依
次弹出 </a><br>
<a href='zhuang5.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字组合弹
出 </a><br>
<a href='zhuang6.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>文字不停闪
烁 </a><br>
<a href='zhuang7.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>状态栏显示
链接 </a><br>
<a href='time9.htm' target='_blank'> <IMG SRC='blank.gif' BORDER=0>title 显示日
期 </a><br>
<a href='zhuang8.htm' target='_blank'> <IMG SRC='blank.gif' BORDER=0>title 变化
弹出 </a></div>
<div id='KB11Parent' class='parent'><a href="default.htm"
onClick="expandIt('KB11'); return false">
<IMG SRC='plus.gif' BORDER=0>密 码 类 </a></div><div id='KB11Child'
class='child'>
<a href='password1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>控制他人
进入页面 </a><br>
<a href='password3.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>用来实现
会员制度 </a><br>
<a href='password4.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>密码保护
相应页面 </a><br><a href='password5.htm' target='_target'> <IMG SRC='blank.gif'
BORDER=0>自己编制密码表 </a></div>
<div id='KB12Parent' class='parent'><a href="default.htm"
onClick="expandIt('KB12'); return false">
<IMG SRC='plus.gif' BORDER=0>综 合 类 </a></div><div id='KB12Child'
class='child'>
<a href='zh1.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>加密页面源代码
</a><br>
<a href='zh2.htm' target='_target'> <IMG SRC='blank.gif' BORDER=0>访问时间限制
```

```

</a><br>
<a href='zh3.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>给页面加“热键”
</a><br>
<a href='zh4.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>两个脚本同时调用
</a><br>
<a href='zh5.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>浏览器毁灭者
</a><br>
<a href='zh6.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>文本中首字母大写
</a><br>
<a href='zh7.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>查看某网址源代码
</a><br>
<a href='zh8.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>文本中首字母大写
</a><br>
<a href='zh9.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>加快图片显示
</a><br>
<a href='zh10.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>综合的搜索引擎
</a><br>
<a href='zh11.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>搜索引擎登记
</a><br>
<a href='zh12.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>下载记时器脚本
</a>
</div>
<div id='KB13Parent' class='parent'><a href="default.htm"
onClick="expandIt('KB13'); return false">
<IMG SRC='plus.gif' BORDER=0> 游 戏 类 </a></div><div id='KB13Child'
class='child'>
<a href='you1.htm' target='_target'><IMG SRC='blank.gif' BORDER=0>一款流行游戏
</a></div>

```

```

<SCRIPT>numTotal=14;scores[1]='KB1';scores[2]='KB1';scores[3]='KB2';scores[4]='
KB3';scores[5]='KB4';scores[6]='KB5';scores[7]='KB6';scores[8]='KB7';scores[9]=
'KB8';scores[10]='KB9';scores[11]='KB10';scores[12]='KB11';scores[13]='KB12';sc
ores[14]='KB13';</SCRIPT>

```

树形菜单 (二)

脚本说明：

第一步 把如下代码加入 <head>区域中

```

<SCRIPT LANGUAGE="JavaScript">
<!--
var bv=parseInt(navigator.appVersion);
var NS4=(document.layers) ? true : false;
var IE4=((document.all)&&(bv>=4))?true:false;
var ver4 = (NS4 || IE4) ? true : false;

```

```

function expandIt(){return}
function expandAll(){return}
function nmmsg(){self.status="";}

if(ver4){
    document.write("<SCR"+"IPT
                                                                LANGUAGE=\"JavaScript\"
SRC=\"\rsmenu.js\"></SCR"+"IPT>");
}
//-->
</SCRIPT>

```

第二步 把如下代码加入 <body>区域中

```

<span class="label"></span><br>
<!------- begin OUTLINE ----->
<!--上方全部展开 /关闭 -->
<A HREF="default.htm" onClick="expandAll(false); return false"><IMG NAME="inEx"
SRC="bullet-plus.gif" WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开或关闭全部菜单 "><FONT
STYLE="font-size: 9pt">展开 /关闭全部 </FONT></A>
<!-- <BLOCKQUOTE> -->

```

<!-- 第一级父菜单 -->

```

<DIV ID="elOneParent" CLASS=parent style="margin-left: 0.1px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=101><tr><td class=label>
<A HREF="default.htm" style="color:#FFFF00; text-decoration:none;"
onClick="expandIt('elOne'); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开全部菜单 "> 主菜单一
</a></td></tr></table>
</DIV>

```

<!-- 第一级子菜单 -->

```

<DIV ID="elOneChild" CLASS=child style="margin-left: 0.5px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=96>
<tr><td>
    <A HREF="1.htm" target="data">连接页面 1</A><BR>
</td></tr><tr><td>
    <A HREF="2.htm" target="data">连接页面 2</A><BR>
</td></tr><tr><td>
    <A HREF="3.htm" target="data">连接页面 3</A><BR>
</td></tr><tr>
    <td height="12"> <A HREF="4.htm" target="data">连接页面 4</A> </td>
</tr></table>
</DIV>

```

<!-- 第二级父菜单 -->

```

<DIV ID="elTwoParent" CLASS=parent style="margin-left: 0.1px">

```

```
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=101><tr><td class=label>
<A HREF="default.htm" style="color:#FFFF00; text-decoration:none;"
onClick="expandIt('elTwo'); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开全部菜单 "> 主菜单二
</a></td></tr></table>
</DIV>
```

```
<!-- 第二级子菜单 -->
<DIV ID="elTwoChild" CLASS=child style="margin-left: 0.5px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=96>
<tr><td>
<A HREF="1.htm" target="data">连接页面 1</A><BR>
</td></tr><tr><td>
<A HREF="2.htm" target="data">连接页面 2</A><BR>
</td></tr><tr><td>
<A HREF="3.htm" target="data">连接页面 3</A><BR>
</td></tr><tr><td>
<A HREF="4.htm" target="data">连接页面 4</A>
</td></tr></table>
</DIV>
```

```
<!-- 第三级父菜单 -->
<DIV ID="elThreeParent" CLASS=parent style="margin-left: 0.1px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=101><tr><td class=label>
<A HREF="default.htm" style="color:#FFFF00; text-decoration:none;"
onClick="expandIt('elThree'); return false"><IMG NAME="inEx"
SRC="bullet-plus.gif" WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开全部菜单 "> 主菜单三
</a></td></tr></table>
</DIV>
```

```
<!-- 第三级子菜单 -->
<DIV ID="elThreeChild" CLASS=child style="margin-left: 0.5px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=96>
<tr><td>
<A HREF="1.htm" target="data">连接页面 1</A><BR>
</td></tr><tr><td>
<A HREF="2.htm" target="data">连接页面 2</A><BR>
</td></tr><tr><td>
<A HREF="3.htm" target="data">连接页面 3</A><BR>
</td></tr><tr><td>
<A HREF="4.htm" target="data">连接页面 4</A>
</td></tr></table>
</DIV>
```

```
<!-- 第四级父菜单 -->
<DIV ID="elFourParent" CLASS=parent style="margin-left: 0.1px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=101><tr><td class=label>
<A HREF="default.htm" style="color:#FFFF00; text-decoration:none;"
onClick="expandIt('elFour'); return false"><IMGNAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开全部菜单 "> 主菜单四
</a></td></tr></table>
</DIV>
```

```
<!-- 第四级子菜单 -->
<DIV ID="elFourChild" CLASS=child style="margin-left: 0.5px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=96>
<tr><td>
<A HREF="1.htm" target="data">连接页面 1</A><BR>
</td></tr><tr><td>
<A HREF="2.htm" target="data">连接页面 2</A><BR>
</td></tr><tr><td>
<A HREF="3.htm" target="data">连接页面 3</A><BR>
</td></tr><tr><td>
<A HREF="4.htm" target="data">连接页面 4</A>
</td></tr></table>
</DIV>
```

```
<!-- 第五级父菜单 -->
<DIV ID="elFiveParent" CLASS=parent style="margin-left: 0.1px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=101><tr><td class=label>
<A HREF="default.htm" style="color:#FFFF00; text-decoration:none;"
onClick="expandIt('elFive'); return false"><IMGNAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开全部菜单 "> 主菜单五
</a></td></tr></table>
</DIV>
```

```
<!-- 第五级子菜单 -->
<DIV ID="elFiveChild" CLASS=child style="margin-left: 0.5px">
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=96>
<tr><td>
<A HREF="1.htm" target="data">连接页面 1</A><BR>
</td></tr><tr><td>
<A HREF="2.htm" target="data">连接页面 2</A><BR>
</td></tr><tr><td>
<A HREF="3.htm" target="data">连接页面 3</A><BR>
</td></tr><tr><td>
<A HREF="4.htm" target="data">连接页面 4</A>
</td></tr></table>
```

```
</DIV>
```

```
<!-- 第六级父菜单 -->
```

```
<DIV ID="eISixParent" CLASS=parent style="margin-left: 0.1px">
```

```
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=101><tr><td class=label>
```

```
<A HREF="default.htm" style="color:#FFFF00; text-decoration:none;"  
onClick="expandIt('eISix'); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"  
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开全部菜单 "> 主菜单六
```

```
</a></td></tr></table>
```

```
</DIV>
```

```
<!-- 第六级子菜单 -->
```

```
<DIV ID="eISixChild" CLASS=child style="margin-left: 0.5px">
```

```
<TABLE BORDER=1 CELLSPACING=0 CELLPADDING=0 WIDTH=96>
```

```
<tr><td>
```

```
<A HREF="1.htm" target="data">连接页面 1</A><BR>
```

```
</td></tr><tr><td>
```

```
<A HREF="2.htm" target="data">连接页面 2</A><BR>
```

```
</td></tr><tr><td>
```

```
<A HREF="3.htm" target="data">连接页面 3</A><BR>
```

```
</td></tr><tr><td>
```

```
<A HREF="4.htm" target="data">连接页面 4</A>
```

```
</td></tr></table>
```

```
</DIV>
```

```
<!-- </BLOCKQUOTE> -->
```

```
<!--下方全部展开 /关闭 -->
```

```
<DIV ID="eIExpParent" CLASS=regular> <A HREF="default.htm"  
onClick="expandAll(true); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"  
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开 /关闭全部 ">展开 /关闭全部 </A> </DIV>
```

```
<!------- end OUTLINE ----->
```

```
<br>
```

```
<SCRIPT LANGUAGE="JavaScript1.2">
```

```
<!--
```

```
if(NS4){
```

```
    firstEl = "eIOneParent";
```

```
    firstInd = getIndex(firstEl);
```

```
    showAll();
```

```
    arrange();
```

```
}
```

```
//-->
```

</SCRIPT>

树形菜单 (三)

脚本说明：

第一步 把如下代码加入 <head>区域中

```
<SCRIPT LANGUAGE="JavaScript">
<!--
var bv=parseInt(navigator.appVersion);
var NS4=(document.layers) ? true : false;
var IE4=((document.all)&&(bv>=4))?true:false;
var ver4 = (NS4 || IE4) ? true : false;

function expandIt(){return}
function expandAll(){return}
function nmsg(){self.status="";}

if(ver4){
    document.write("<SCR"+"IPT
LANGUAGE=\"JavaScript\"
SRC=\"rsmenu1.js\"></SCR"+"IPT>");
}
//-->
</SCRIPT>
```

第二步 把如下代码加入 <body>区域中

```
<!------- begin OUTLINE -----> <A HREF="default.htm"
onClick="expandAll(false); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开 /关闭全部" >
<FONT COLOR="#008000">全部菜单 </FONT></A> <!-- <span style="background: #00FFFF;
color: black">展开 /关闭全部 </span> -->
<!-- <BLOCKQUOTE> --> <!-- 第一级父菜单 -->
<DIV ID="e1OneParent" CLASS=parent style="margin-left: 0.5em">
<A HREF="default.htm" style="color:#0000FF; text-decoration:none;"
onClick="expandIt('e1One'); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0>主菜单一 </A>
</DIV>

<!-- 第一级子菜单 -->
<DIV ID="e1OneChild" CLASS=child style="margin-left: 1em">
<A HREF="1.htm" target="data">子页面一 </A><BR>
<A HREF="2.htm" target="data">子页面二 </A><BR>
<A HREF="3.htm" target="data">子页面三 </A><BR>
<A HREF="4.htm" target="data">子页面四 </A>
</DIV>
```

```
<!-- 第二级父菜单 -->
<DIV ID="eITwoParent" CLASS=parent style="margin-left: 0.5em">
<A HREF="default.htm" style="color:#0000FF; text-decoration:none;"
onClick="expandIt('eITwo'); return false"><IMG NAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0>主菜单二 </A>
</DIV>
```

```
<!-- 第二级子菜单 -->
<DIV ID="eITwoChild" CLASS=child style="margin-left: 1em">
<A HREF="1.htm" target="data">子页面一 </A><BR>
<A HREF="2.htm" target="data">子页面二 </A><BR>
<A HREF="3.htm" target="data">子页面三 </A><BR>
<A HREF="4.htm" target="data">子页面四 </A>
</DIV>
```

```
<!-- 第三级父菜单 -->
<DIV ID="eIThreeParent" CLASS=parent style="margin-left: 0.5em">
<A HREF="default.htm" style="color:#0000FF; text-decoration:none;"
onClick="expandIt('eIThree'); return false"><IMG NAME="inEx"
SRC="bullet-plus.gif" WIDTH=9 HEIGHT=9 BORDER=0>主菜单三 </A>
</DIV>
```

```
<!-- 第三级子菜单 -->
<DIV ID="eIThreeChild" CLASS=child style="margin-left: 1em">
<A HREF="1.htm" target="data">子页面一 </A><BR>
<A HREF="2.htm" target="data">子页面二 </A><BR>
<A HREF="3.htm" target="data">子页面三 </A><BR>
<A HREF="4.htm" target="data">子页面四 </A>
</DIV>
```

```
<!-- 第四级父菜单 -->
<DIV ID="eIFourParent" CLASS=parent style="margin-left: 0.5em">
<A HREF="default.htm" style="color:#0000FF; text-decoration:none;"
onClick="expandIt('eIFour'); return false"><IMGNAME="inEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0>主菜单四 </A>
</DIV>
```

```
<!-- 第四级子菜单 -->
<DIV ID="eIFourChild" CLASS=child style="margin-left: 1em">
<A HREF="1.htm" target="data">子页面一 </A><BR>
<A HREF="2.htm" target="data">子页面二 </A><BR>
<A HREF="3.htm" target="data">子页面三 </A><BR>
```



```
<A HREF="4.htm" target="data">子页面四 </A>
</DIV>
```

```
<!-- 第五级父菜单 -->
<DIV ID="elFiveParent" CLASS=parent style="margin-left: 0.5em">
<A HREF="default.htm" style="color:#0000FF; text-decoration:none;"
onClick="expandIt('elFive'); return false"><IMG NAME="irEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0>主菜单五 </A>
</DIV>
```

```
<!-- 第五级子菜单 -->
<DIV ID="elFiveChild" CLASS=child style="margin-left: 1em">
<A HREF="1.htm" target="data">子页面一 </A><BR>
<A HREF="2.htm" target="data">子页面二 </A><BR>
<A HREF="3.htm" target="data">子页面三 </A><BR>
<A HREF="4.htm" target="data">子页面四 </A>
</DIV>
```

```
<!-- </BLOCKQUOTE> -->
```

```
<DIV ID="elExpParent" CLASS=regular> <A HREF="default.htm"
onClick="expandAll(true); return false"><IMG NAME="irEx" SRC="bullet-plus.gif"
WIDTH=9 HEIGHT=9 BORDER=0 ALT="展开 /关闭全部 ">
<FONT COLOR="#008000">全部菜单 </FONT></A> </DIV>
```

```
<!------- end OUTLINE ----->
```

```
<SCRIPT LANGUAGE="JavaScript1.2">
<!--
if(NS4){
firstEl = "elOneParent";
firstInd = getIndex(firstEl);
showAll();
arrange();
}
//-->
</SCRIPT>
```

页面搜索类

站内搜索脚本 (一)

脚本说明：

第一步：把如下代码加入 <body>区域中

```
<script language="JavaScript">
<!--
// 下面是负责搜索的页面的全路径或相对路径
var search_html_url = "searchsource.htm";

function searchPage() {
if ((document.searchpage.keyword.value.length == 0)
|| (document.searchpage.keyword.value == " ")) {
alert("请填写关键字!");
} else {
sel = document.searchpage.and_or.selectedIndex;
location.href = search_html_url + "?"
+ escape(document.searchpage.keyword.value)
+ (sel==0?"&and":(sel==2?"&exact":"&or"));
}
return false;
}

document.write('<form name="searchpage" onSubmit="return searchPage()">'
+ '请填写关键字：<input type="text" size=22 name="keyword"> '
+ '<input type="button" value="Search" onClick="searchPage()"><br>'
+ '<select name="and_or" size=1><option>关键字与搜索 <option>关键字或搜索 '
+ '<option>关键字异或搜索 </select></form>');
// -->
</script>
```

第二步：新建 searchsource.htm其内容为

```
<!-- 代码开始 -->
<form NAME="database">
<input type="hidden" name="list"
value="http://www.hrw.cn-怀柔网网站 |njcatv 怀柔网 网页特效 影音空间 新闻
javascript java applet 健康之桥 ^为广大南京市民提供全方位的信息和帮助
*http://www.sina.com.cn-最全的中文新闻发部站点 |sina 新浪 新闻 super 王志东 聊天
室 ^国内最大的新闻网站!*http://www.163.net-最大的综合中文网站 |163 netease 网易
丁磊 新闻 yeah 126 娱乐 freemail 聊天室 ^最大的综合中文网站 ,为你提供全方位的各种
信息,是你上网的好去处!*http://www.sohu.com最大的中文引擎搜索站点 |sohu search
搜索 引擎 张朝阳 聊天室 ^最大的中文引擎搜索站点,是你上网查找资料的最好去
处!*http://www.sohu.com最大的中文引擎搜索站点 |sohu search 搜索 引擎 张朝阳 聊
天室 ^最大的中文引擎搜索站点,是你上网查找资料的最好去处!*http://www.sohu.com最
大的中文引擎搜索站点 |sohu search 搜索 引擎 张朝阳 聊天室 ^最大的中文引擎搜索站
点,是你上网查找资料的最好去处!*http://www.sohu.com最大的中文引擎搜索站点 |sohu
```

search 搜索 引擎 张朝阳 聊天室 ^最大的中文引擎搜索站点,是你上网查找资料的最好去处!*http://www.sohu.com最大的中文引擎搜索站点 |sohu search 搜索 引擎 张朝阳 聊天室 ^最大的中文引擎搜索站点,是你上网查找资料的最好去处!*http://www.sohu.com最大的中文引擎搜索站点 |sohu search 搜索 引擎 张朝阳 聊天室 ^最大的中文引擎搜索站点,是你上网查找资料的最好去处!">

</form>

<!-- 以下代码不要变动 -->

<script language="JavaScript">

<!--

```
function Page(url,title,keywords,description) {
while ((url.length > 0) && (url.charAt(0) == " ")) {
url = url.substring(1,url.length);
}
this.url = url;
while ((title.length > 0) && (title.charAt(0) == " ")) {
title = title.substring(1,title.length);
}
this.title = title;
this.keywords = keywords;
this.description = description;
return this;
}
function Database() {
var pos = 0;
while ((pos1 = amorphous.indexOf("~",pos)) != -1) {
pos2 = amorphous.indexOf("|",pos1+1);
pos3 = amorphous.indexOf("^",pos2+1);
pos4 = amorphous.indexOf("*",pos3+1);
if ((pos2 != -1)
&& (pos2 < pos3) && (pos3 < pos4)
&& (pos4 <= amorphous.indexOf("*",pos))) {
this[database_length++] = new Page(amorphous.substring(pos,pos1),
amorphous.substring(pos1+1,pos2),
amorphous.substring(pos2+1,pos3),
amorphous.substring(pos3+1,pos4));
pos = pos4+1;
} else { // error reading amorphous database
if (pos+30 <= amorphous.length)
alert('Error reading in amorphous database around "'
+ amorphous.substring(pos,pos+30) + '"');
pos = amorphous.indexOf("*",pos) + 1;
}
}
return this;
```

```

}
function search(str) {
menu_length = 0;
temp = new Object();
temp_length = 0;
words_length = 0;
words = new Object();
pos = 0;
while ((pos = str.indexOf(" ")) != -1
&& and_search != "exact") {
words[words_length] = str.substring(0,pos);
if (words[words_length].length > 0)
words_length++;
if (str.length == 1)
str="";
else
str = str.substring(pos+1,str.length);
}
if (str.length > 0)
words[words_length++] = str;
for (q=0;q<words_length;q++) {
temp_length = 0;
str = words[q].toLowerCase();
len = (and_search=="and"&&q>0?menu_length:database_length);
for (n=0; n<len; n++) {
if (and_search=="and"&&q>0) {
combo = (menu[n].title + " " + menu[n].description
+ " " + menu[n].keywords).toLowerCase();
} else {
combo = (database[n].title + " " + database[n].description
+ " " + database[n].keywords).toLowerCase();
}
if (combo.indexOf(str) != -1) // found
temp[temp_length++] = (and_search=="and"&&q>0?menu[n]:database[n]);
}
if (and_search!="and" && q>0) {
added = 0;
for (i=0;i<temp_length;i++) {
duplicate = false;
for (j=0;j<menu_length&&!duplicate;j++) {
if (menu[j] == temp[i]) {
duplicate = true;
}
}
}
}
}
}

```

```

if (!duplicate)
menu[menu_length+(added++)] = temp[i];
}
menu_length += added;
} else {
for(h=0;h<temp_length;h++)
menu[h] = temp[h];
menu_length = temp_length;
}
}
}
function entry() {
if ((document.entryform.keyword.value.length == 0)
|| (document.entryform.keyword.value == " ")) {
alert("你必须填写关键字!");
return false;
}
and_search = (document.entryform.and_or.selectedIndex == 0?"and":"or");
if (document.entryform.and_or.selectedIndex == 2)
and_search = "exact";
location.href = location.pathname + "?"
+ escape(document.entryform.keyword.value)
+ (and_search != "or"?"&"+and_search:"");
return false;
}
function red\brd(str) {
for(r=0; r<words_length; r++) {
pos = -3;
word = words[r].toLowerCase();
while ((pos = str.toLowerCase().indexOf(word,pos+3)) != -1) {
val = pos+word.length;
str = str.substring(0,pos) + "*"
+ str.substring(pos,val) + "|"
+ str.substring(val,str.length);
}
}
pos = -16;
while ((pos = str.toLowerCase().indexOf("*",pos+16)) != -1)
str = str.substring(0,pos) + "<font color=red>"
+ str.substring(pos+1,str.length);
pos = -7;
while ((pos = str.toLowerCase().indexOf("|",pos+7)) != -1)
str = str.substring(0,pos) + "</font>"
+ str.substring(pos+1,str.length);

```

```

return str;
}

var amorphous = document.database.list.value;
temp_str = amorphous.substring(amorphous.length-2,amorphous.length);
if (temp_str.indexOf("*") == -1)
amorphous += "* ";
else
amorphous += " "; // amorphous database must have characters after last asterisk

database_length = 0; // Netscape 2 fix
var database = new Database(); // read in from amorphous database

menu_length = 0; // Netscape 2 fix
var menu = new Object();

string = "";
and_search = "or";
if (location.search.length > 1) {
string = unescape(location.search.substring(1,location.search.length));
pos = 0;
while ((pos = string.indexOf("'",pos)) != -1) {
string = string.substring(0,pos) + '\\\'' + string.substring(pos+1,string.length);
pos += 2;
}
if (string.substring(string.length-4,string.length) == "&and") {
string = string.substring(0,string.length-4);
and_search = "and";
} else if (string.substring(string.length-6,string.length) == "&exact") {
string = string.substring(0,string.length-6);
and_search = "exact";
} else if (string.substring(string.length-3,string.length) == "&or") {
string = string.substring(0,string.length-3);
and_search = "or";
}
search(string);
}
document.write('<form name="entryform" onSubmit="return entry()">'
+'Search for:<input type="text" size=22 '
+'name="keyword" value="'+string+' "> '
+'<input type="button" value="Search" onClick="entry()"><br><select name="and_or"
,
+'size=1<option'+(and_search=="and"? " selected":"" )+'>Search All word '
+'(AND)<option'+(and_search=="or"? " selected":"" )+'>Search any word '

```

```

+'(OR)<option'+(and_search=="exact"? " selected":"" )+'>Exact '
+'word</select></form><br>');
if (location.search.length > 1)
document.write( '查询结果 :<br><br>\n');

for (n=0; n<menu_length; n++)
document.write('<a href="'+menu[n].url+'">'+menu[n].title
+'</a><br>'+red\brd(menu[n].description)+'<br>Keywords: '
+red\brd(menu[n].keywords)+'<br><br>\n');
if ((menu_length == 0) && (location.search.length > 1))
document.write( '对不起 :你查询的关键字 "' +string+' 没有发现 !\n');
// -->
</script>

```

站内搜索脚本 (二)

脚本说明：

把如下代码加入 <body>区域中

```

<script language="javascript">
var key = "";

```

```

function makeEntry (){
this.Date = "";
this.Name="";
this.URL = "";
this.Desc = "";
this.Category = "";
return this;
}

```

```

function makeArray(n) {
this.length = n;
for (var k = 1; k <= n; k++) {
this[k] = "";
}
return this;
}

```

```

function makeLinks(size) {
this.length = size;
for (var r=1; r<= size; r++) {
this[r] = new makeEntry();
this[r].Date = datesArray[r];
this[r].Name = namesArray[r];
}
}

```

```
this[r].URL = urlsArray[r];
this[r].Desc = descArray[r];
}
return this;
}
```

```
var linksize=0
```

```
datesArray = new makeArray(linksize);
namesArray = new makeArray(linksize);
urlsArray = new makeArray(linksize);
descArray = new makeArray(linksize);
```

```
var arraycount=0
```

```
arraycount += 1
datesArray[arraycount] = "5/30/2000"
urlsArray[arraycount] = "http://www.163.net"
namesArray[arraycount] = "网易"
descArray[arraycount] = "163 netease yeah 126 chinese "
//alert(arraycount)
```

```
arraycount += 1
datesArray[arraycount] = "5/30/2000 "
urlsArray[arraycount] = "http://www.sina.com.cn"
namesArray[arraycount] = "新浪网"
descArray[arraycount] = "sina net chat chatting news super"
//alert(arraycount)
```

```
arraycount += 1
datesArray[arraycount] = "5/30/2000 "
urlsArray[arraycount] = "http://www.sohu.com"
namesArray[arraycount] = "搜狐"
descArray[arraycount] = "sohu net chat news "
//alert(arraycount)
```

```
linksize = arraycount;
```

```
// ----end data -----
```

```
function showAll(linkobj) {
```



```

for (var s=1; s<= linkobj.length; s++) {
showLink(linkobj,s);
}
}

function showLink (links, index) {
//document.write("<table border>");
document.write("<tr><td>" + links[index].Date + "</td>");
document.write("<td><a href=" + links[index].URL + ">" + links[index].Name +
"</a></td>");
document.write("<td>" + links[index].Desc + "</td></tr>");
//document.write("</table>");
}

function searchLinks(links, keyword){
document.write("搜寻结果 : " +keyword + "<br>");

document.write("<table border>");
for (var q=1; q<=links.length; q++) {
//document.write(q+".")
if (links[q].URL.indexOf(keyword) != -1){
// document.write("Search Results for keyword: "+keyword+ "<br>" +links[q].Name
+"<p>")
//document.write("搜寻结果 : "+keyword+ "<br>" );
showLink(links,q);
continue;
}
if (links[q].Desc.indexOf(keyword) != -1) {
showLink(links,q);
continue;
}
if (links[q].Date.indexOf(keyword) != -1) {
showLink(links,q);
continue;
}
if (links[q].Name.indexOf(keyword) != -1) {
showLink(links,q);
continue;
}
}
}
document.write("</table>");
}

```

```

// final stuff
// the main program ---

jsi = new makeLinks(linksize);
document.write("<title>站内查询 </title>");
searchLinks(jsi, prompt("输入查询关键字:", "输入查询关键字:"));
document.write("<hr>");
document.write("按 <b>search again</b>再次查询 <hr>");
document.write("<form><input type=button onClick='history.go(0)' value='Search Again'></form>");

// show all the links
//document.write("<table border>");
//showAll(jsi);
//document.write("</table>");

</script>

```

站内搜索脚本 (三)

脚本说明：

第一步：把如下代码加入 <body>区域中

```

<script language="javascript">
    var key = "";
    function makeEntry () {
        this.Name="";
        this.URL = "";
        this.Desc = "";
        this.Category = "";
        this.Target = "";
        return this;
    }

    function makeArray(n) {
        this.length = n;
        for (var k = 1; k <= n; k++) {
            this[k] = "";
        }
        return this;
    }

    function makeLinks(size) {
        this.length = size;
        for (var r=1; r<= size; r++) {
            this[r] = new

```

```

makeEntry();
namesArray[r];
urlsArray[r];
descArray[r];
categoryArray[r];
targetArray[r];

this[r].Name =
this[r].URL =
this[r].Desc =
this[r].Category =
this[r].Target =

}
return this;
}

```

```
var linksize=0
```

```

datesArray = new makeArray(linksize);
namesArray = new makeArray(linksize);
urlsArray = new makeArray(linksize);
descArray = new makeArray(linksize);
categoryArray = new makeArray(linksize);
targetArray = new makeArray(linksize);

```

```
var arraycount=0
```

```
<!-- 数据库部分由此开始 -->
```

```

arraycount += 1
urlsArray[arraycount] = "http://java2000.126.com"
namesArray[arraycount] = "java脚本资源站 Chinese-GB"
descArray[arraycount] = "java, javascript, scripts, applet, html, dhtml,activex,
midi, search, downloads, 脚本, free, 免费资源"
categoryArray[arraycount] = "最酷的 java脚本资源站,大量详细的 java源代码和实例说
明!"
targetArray[arraycount] = "target=_blank"

```

```

arraycount += 1
urlsArray[arraycount] = "http://members.aol.com/MASTER54X/Anime.html"
namesArray[arraycount] = "Anime Master"
descArray[arraycount] = "animemaster, anime, project a-ko, vampire hunter D, tenchi
muyo, bubblegumcrisis, sailormoon, sailormoon, gunsmit cats, slayers, all purpose
cultural cat girl nuku nuku, plastic little, devil hunter yohko, iria: zeiram the

```

animation, iria, rama 1/2, rama, fist of the north star, multimedia, galleries, pic galleries, picture gallery, image gallery, image galleries"
categoryArray[arraycount] = "Multimedia, Image galleries for project a-ko, vampire hunter D, tenchi muyo, bubblegum crisis, sailormoon, gunsmith cats, slayers, all purpose cultural cat girl nuku nuku, plastic little, devil hunter yohko, iria: zeiran the animation, rama 1/2, and fist of the north star."
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://www.geocities.com/Tokyo/Towers/6508/"
namesArray[arraycount] = "The Anime Shrine"
descArray[arraycount] = "the anime shrine, anime shrine, anime, the anime shrine, anime shrine, manga, saintseiya, fushigi yuugi, fushigi yuugi, evangelion, neon genesis evangelion, eva, rama, rama 1/2"
categoryArray[arraycount] = "this is a fairly large site with large image galleries from many dif animes, many links, gives out awards, has 3 voting shrines, also sub-Shrines for Fushigi Yuugi, SaintSeiya, Evangelion, and Rama 1/2. And much more! Must see!"
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://home.taegu.net/~virus/"
namesArray[arraycount] = "Evangelion Site"
descArray[arraycount] = "evangelion site, anime, evangelion, neon genesis, neon genesis evangelion, eva, neon, genesis"
categoryArray[arraycount] = "This site is about evangelion, but available in Korean only..."
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://animeonline.org/"
namesArray[arraycount] = "The Animeonline Network"
descArray[arraycount] = "the animeonline network, anime, animecca, news, information, anime magazine, magazine, zine, e-zine"
categoryArray[arraycount] = "Your Online Anime Magazine!"
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://www.visi.com/~vdgaijin/gaijin.html"
namesArray[arraycount] = "Psychommu Gaijin Anime E-zine"
descArray[arraycount] = "psychommu gaijin anime e-zine, anime, music, links, news, information, e-zine, zine"
categoryArray[arraycount] = "Our aim is to provide you with news and information on some of the coolest aspects of Anime. Old and new! So come on in and enjoy!"

```

targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://the.animearchive.org/"
namesArray[arraycount] = "Ultimate Animanga Archive"
descArray[arraycount] = "ultimate animanga archive, anime, manga, images, pictures,
image gallery, midi, image galleries, music, chat, information, descriptions, info"
categoryArray[arraycount] = "Searchable page of images, info, and descriptions of
anime OAVs and series."
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://otakuworld.com/"
namesArray[arraycount] = "Otaku World"
descArray[arraycount] = "otaku world, anime, manga, desktop themes, anime themes,
search engine, link database, web rings, web ring"
categoryArray[arraycount] = "One of the largest multimedia anime sources on the
web!"
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://www.usagi.com"
namesArray[arraycount] = "Usagi.com"
descArray[arraycount] = "usagi.com, anime, manga, links, link, database, tenchi,
tenchi myo, download, multimedia"
categoryArray[arraycount] = "Your guide to the online anime community!"
targetArray[arraycount] = "target=_blank"

arraycount += 1
urlsArray[arraycount] = "http://www.si.hhs.nl/~v962343/home.html"
namesArray[arraycount] = "Richie's Place"
descArray[arraycount] = "richie's place, anime, manga, pictures, pics, movies,
links, gif animations, animation, hentai, java, link"
categoryArray[arraycount] = "Richie's Place! Over 30 pages! with a picture gallery,
movies, gif animations, games, java and more."
targetArray[arraycount] = "target=_blank"

linksize = arraycount;

// --- 数据库结束 -----
// --- 以下是输出结果检索结果的页面代码 ----

function searchLinks(links, keyword){
    document.write("<BODY  fontsize='2'  BGCOLOR='#000000'  TEXT='#ffffff'

```

```

LINK='#ccffcc' \LINK='#ffffff'>")
    document.write(" 搜索关键字结果 : <strong>" +keyword
+ "</strong><br><br>");
    for (var q=1; q<=links.length; q++) {

        if (links[q].URL.toLowerCase().indexOf(keyword) != -1){
            document.write("<a href=" + links[q].URL + " " + links[q].Target + ">" +
links[q].Name + "</a> - ");

            document.write( links[q].Category + "<br><br>");
            continue;
        }
        if (links[q].Desc.toLowerCase().indexOf(keyword) != -1) {
            document.write("<a href=" + links[q].URL + " " + links[q].Target + ">" +
links[q].Name + "</a> - ");

            document.write( links[q].Category + "<br><br>");
            continue;
        }
        if (links[q].Name.toLowerCase().indexOf(keyword) != -1) {
            document.write("<a href=" + links[q].URL + " " + links[q].Target + ">" +
links[q].Name + "</a> - ");

            document.write( links[q].Category + "<br><br>");
            continue;
        }
    }

}

```

```

</script>
<font size="5" color="#FF0000">站内搜索引擎 <br>
</font><font color="#FF0000"> <font color="#000000">测试：输入关键字 "java"
或中文字符 "免费 " 查询。 </font></font> </div>
<p align=Center>
<form name="form">
    <div align="center">
        <p>查询关键字：
            <input type="text" size=20 name="search">
            <input type="button" name="submit" value=" 开始 查 询 "
onClick="validate_form()" class="pt9">
            <input type="reset" name="reset" value="清除 " class="pt9">

```

```
<br>
</p>
```

```
</div>
</form>
<!-- 以下是合法性检测 -->
<script>
function validate_form() {
```

```
txt = document.fom.search.value;
if (txt.indexOf(".") != -1){
    alert("Search is invalid! Contains a '.'"); return;}
if (txt.indexOf(",") != -1){
    alert("Search is invalid! Contains a ','"); return;}
if (txt.indexOf("@") != -1){
    alert("Search is invalid! Contains a '@'"); return;}
if (txt.indexOf("!") != -1){
    alert("Search is invalid! Contains a '!'); return;}
if (txt.indexOf("#") != -1){
    alert("Search is invalid! Contains a '#'"); return;}
if (txt.indexOf("$") != -1){
    alert("Search is invalid! Contains a '$'"); return;}
if (txt.indexOf("%") != -1){
    alert("Search is invalid! Contains a '%'"); return;}
if (txt.indexOf("^") != -1){
    alert("Search is invalid! Contains a '^'"); return;}
if (txt.indexOf("&") != -1){
    alert("Search is invalid! Contains a '&'"); return;}
if (txt.indexOf("*") != -1){
    alert("Search is invalid! Contains a '*'"); return;}
if (txt.indexOf("(") != -1){
    alert("Search is invalid! Contains a '('"); return;}
if (txt.indexOf(")") != -1){
    alert("Search is invalid! Contains a ')'"); return;}
if (txt.indexOf("[") != -1){
    alert("Search is invalid! Contains a '['"); return;}
if (txt.indexOf("]") != -1){
    alert("Search is invalid! Contains a ']'"); return;}
if (txt.indexOf(";") != -1){
    alert("Search is invalid! Contains a ';'"); return;}
if (txt.indexOf(":") != -1){
    alert("Search is invalid! Contains a ':'"); return;}
if (txt.indexOf("<") != -1){
    alert("Search is invalid! Contains a '<'"); return;}
```

```

if (txt.indexOf(">") != -1){
    alert("Search is invalid! Contains a '>''"); return;}
if (txt.indexOf("?") != -1){
    alert("Search is invalid! Contains a '?''"); return;}
if (txt.indexOf("-") != -1){
    alert("Search is invalid! Contains a '-''"); return;}
if (txt.indexOf("=") != -1){
    alert("Search is invalid! Contains a '='''"); return;}
if (txt.indexOf("+") != -1){
    alert("Search is invalid! Contains a '+''"); return;}
else {
    jsi = new makeLinks(linksize);
    searchLinks(jsi, txt);
document.write("<hr>");
document.write("<a href='searchabledb2.htm'>返回检索页 </a><br><br> ");
//将 searchabledb2.htm替换为检索页的 URL, 以便访问者返回检索页。
}

}
</script>

```

站内搜索脚本 (四)

脚本说明：

第一步：把如下代码加入 <body>区域中

```

<form name="database">
    <input
        type="hidden"
        name="list"
        value='http://www.webcrawler.com-Webcrawler|keywords for first file go here
separated by spaces^A great search engine from the makers of
ACL!*http://java2000.126.com-java2000 collections|java javascript search html
download cgi perl dhtml games activex 下载 脚本 ^coolest java and javascript
collections for internet surfers to enhance web
page!*http://www.javagoodies.com/~javagoodies|ActiveX ASP C/C++ CGI Databases
java javascript^coolest javagoodies!*>
</form>
<p>
    <script language="JavaScript">
<!--
version = 1.0;
// -->
</script>
    <script language="JavaScript1.1">
<!--
version = 1.1;

```



```

// -->
</script>
  <script language="JavaScript">
<!--
// When set to true, searching for "fun*y" matches in the string "fun sky".
// (it will also match the string "fun and here is some long dummy text for you"
// which is obviously not what they were looking for, so we suggest you set
// match_across_word_boundaries to false)
// When set to false, the * operator will not match across word boundaries so
// the above example will not match.
match_across_word_boundaries = false; // false is suggested strongly

```

```

// ***** NO NEED TO MODIFY ANYTHING BELOW THIS POINT *****

```

```

function Page(url,title,keywords) {
  while ((url.length > 0) && (url.charAt(0) == " ")) {
    url = url.substring(1,url.length);
  }
  this.url = url;
  while ((title.length > 0) && (title.charAt(0) == " ")) {
    title = title.substring(1,title.length);
  }
  this.title = title;
  this.keywords = keywords;
  return this;
}

function Database() {
  var pos = 0;
  while ((pos1 = amorphous.indexOf("~",pos)) != -1) {
    pos2 = amorphous.indexOf("|",pos1+1);
    pos3 = amorphous.indexOf("*",pos2+1);
    if ((pos2 != -1)
    && (pos2 < pos3) && (pos3 <= amorphous.indexOf("*",pos))) {
      this[database_length++] = new Page(amorphous.substring(pos,pos1),
      amorphous.substring(pos1+1,pos2),
      amorphous.substring(pos2+1,pos3));
      pos = pos3+1;
    } else { // error reading amorphous database
      if (pos+30 <= amorphous.length)
        alert('Error reading in amorphous database around "'
        + amorphous.substring(pos,pos+30) + '"');
      pos = amorphous.indexOf("*",pos) + 1;
    }
  }
}

```

```

    }
    return this;
}
var array = new Object();
array_length = 0; // Netscape 2 fix
var position = new Object();
position_length = 0; // Netscape 2 fix
function pattern(str) {
    array_length = position_length = 0;
    while ((str.length > 1) && (str.charAt(0) == "*")) {
        str = str.substring(1,str.length);
    }
    while ((str.length > 1) && (str.charAt(str.length-1) == "*")) {
        str = str.substring(0,str.length-1);
    }
    if (str == "")
        return "(true)";
    if (str.indexOf("*") == -1) {
        array[array_length++] = str;
        pat = "(combo.indexOf(array[0]) != -1)";
    } else {
        left = right = 0;
        pat2 = "";
        pat = "(((position[0] = combo.indexOf(array[0])) != -1)";
        while ((right = str.indexOf("*",left)) != -1) {
            array[array_length++] = str.substring(left,right);
            pat += " && (position["+(position_length)+"] < (position["
                ++position_length)+"] = combo.indexOf(array["+(array_length)
+"],position["+(position_length-1)+"]+array["+(array_length-1)+"].length"+"))"
;
            if (!match_across_word_boundaries)
                pat2 = " && (no_back_up = ((back_up_pos += combo.substring("
                    +temp_pos = back_up_pos = position["
                    +(position_length-1)+"]+array["+(array_length-1)+"].length,position["
                    + (position_length) + "]).lastIndexOf(' ')) < temp_pos))" + pat2;
            left = right+1;
        }
        array[array_length++] = str.substring(left,str.length);
        pat += pat2+"";
    }
    return pat;
}
function search(str) {

```

```

menu_length = 0;
temp = new Object();
temp_length = 0;
words_length = 0;
words = new Object();
pos = 0;
while ((pos = str.indexOf(" ")) != -1
&& and_search != "exact") {
    words[words_length] = str.substring(0,pos);
    if (words[words_length].length > 0)
        words_length++;
    if (str.length == 1)
        str="";
    else
        str = str.substring(pos+1,str.length);
}
if (str.length > 0)
    words[words_length++] = str;
for (q=0;q<words_length;q++) {
    temp_length = 0;
    str = words[q].toLowerCase();
    pattern_string = pattern(str);
    start_pos = back_up_pos = 0;
    len = (and_search=="and" && q>0?menu_length:database_length);
    for (n=0; n<len; n++) {
        no_back_up = true;
        position_length = 0;
        if (and_search=="and" && q>0) {
            carbo = (menu[n].title + " " + menu[n].keywords).toLowerCase();
        } else {
            carbo = (database[n].title + " " + database[n].keywords).toLowerCase();
        }
        carbo = carbo.substring(start_pos,carbo.length);
        if (eval(pattern_string)) { // found
            temp[temp_length++] = (and_search=="and" && q>0?menu[n]:database[n]);
            start_pos = 0;
        } else if (!no_back_up) { // try pattern again in new spot
            n--;
            start_pos += back_up_pos+1;
        } else { // not found
            start_pos = 0;
        }
    }
}
if (and_search!="and" && q>0) {

```

```

added = 0;
for (i=0;i<temp_length;i++) {
    duplicate = false;
    for (j=0;j<menu_length&&!duplicate;j++) {
        if (menu[j] == temp[i]) {
            duplicate = true;
        }
    }
    if (!duplicate)
        menu[menu_length+(added++)] = temp[i];
}
menu_length += added;
} else {
    for(h=0;h<temp_length;h++)
        menu[h] = temp[h];
    menu_length = temp_length;
}
}
}
function entry() {
    if ((document.entryform.keyword.value.length == 0)
    || (document.entryform.keyword.value == " ")) {
        alert("First you must enter a keyword to search for.");
        return false;
    }
    and_search = (document.entryform.and_or.selectedIndex == 0?"and":"or");
    if (document.entryform.and_or.selectedIndex == 2)
        and_search = "exact";
    if (version >= 1.1) {
        search(document.entryform.keyword.value);
        if (menu_length == 0)
            menu[menu_length++] = new Page("", "Not found!", "");
        document.display.found.options.length = menu_length;
        for (n=0; n<menu_length; n++) {
            if (menu[n].title.length <= 50)
                document.display.found.options[n].text = menu[n].title;
            else
                document.display.found.options[n].text = menu[n].title.substring(0,50);
            document.display.found.options[n].value = menu[n].url;
        }
    }
} else {
    location.href = location.pathname + "?"
    + escape(document.entryform.keyword.value)
    + (and_search != "or"?"&"+and_search:"");
}

```

```

    }
    return false;
}
function go_there() {
    sel = document.display.found.selectedIndex;
    if ((sel != -1) && (document.display.found.options[sel].value.length > 0))
        location.href = document.display.found.options[sel].value;
}

var amorphous = document.database.list.value;
temp_str = amorphous.substring(amorphous.length-2,amorphous.length);
if (temp_str.indexOf("*") == -1)
    amorphous += "* ";
else
    amorphous += " "; // amorphous database must have characters after last asterisk

database_length = 0; // Netscape 2 fix
var database = new Database(); // read in from amorphous database

menu_length = 0; // Netscape 2 fix
var menu = new Object();

string = "";
and_search = "or";
if (location.search.length > 1) {
    string = unescape(location.search.substring(1,location.search.length));
    pos = 0;
    while ((pos = string.indexOf("'",pos)) != -1) {
        string = string.substring(0,pos) + "\\'" +
string.substring(pos+1,string.length);
        pos += 2;
    }
    if (string.substring(string.length-4,string.length) == "&and") {
        string = string.substring(0,string.length-4);
        and_search = "and";
    } else if (string.substring(string.length-6,string.length) == "&exact") {
        string = string.substring(0,string.length-6);
        and_search = "exact";
    } else if (string.substring(string.length-3,string.length) == "&or") {
        string = string.substring(0,string.length-3);
        and_search = "or";
    }
}
search(string);
}

```

```

document.write('<form name="entryform" class="pt9" onSubmit="return entry()"'
+'Search for: <input type="text" type="pt9" size=15 name="keyword"
value="'+string+' "> '
+'<input type="button" class="pt9" value="Search" onClick="entry()"><br><select
name="and_or" '
+'size=1><option'+(and_search=="and"?" selected":"" )+'>AND查询 '
+'(AND)<option'+(and_search=="or"?" selected":"" )+'>OR查询 '
+'(OR)<option'+(and_search=="exact"?" selected":"" )+'>完全 '
+'匹配 </select><br>"可以使用通配符 </form><br>'
+'<form name="display"><select name="found" size=5>\n');
for (n=0; n<menu_length; n++)
document.write('<option value="'+menu[n].url+' ">'+menu[n].title+'\n');
if ((menu_length == 0) && (location.search.length <= 1))
document.write('<option value="" class="pt9">Enter a search keyword above\n');
else if ((menu_length == 0) && (location.search.length > 1))
document.write('<option value="">关键字 "'
+location.search.substring(1, location.search.length)+'没有发现!\n');
document.write('</select><br><input
type="button"
class="pt9"
onClick="go_there()" '
+'value=" Go There "></form>');
// -->
</script>

```

站内搜索脚本 (五)

脚本说明：

第一步：把如下代码加入 <body>区域中

```

<SCRIPT LANGUAGE="JavaScript">

<!-- Hide Script from Old Browsers

Keyword = new Object();

Descrip = new Object();

Address = new Object();

// Keyword[0] = n (where n is the number of keywords which can be searched

Keyword[0] = 5 /对应查询组的数量；

```

Keyword[1] = "javascript"

Descrip[1] = "最全的 javascript资源站 - javascript2000.com"

Address[1] = "http://www.javascript2000.com"

Keyword[2] = "javascript"

Descrip[2] = "很好的 javascript站点 "

Address[2] = "http://www.cnlot.com/ "

Keyword[3] = "javascript"

Descrip[3] = "java神捕 "

Address[3] = "http://pcafei.3322.net/ "

Keyword[4] = "javascript"

Descrip[4] = "精彩天地 "

Address[4] = "http://dempy.3322.net/ "

Keyword[5] = "javascript"

Descrip[5] = "国外最大的 javascript资源站 "

Address[5] = "http://www.javascript.com/ "

function checkDatabase() {

```

var Found = false

var Item = document.forms[0].searchfor.value.toLowerCase();

stats='toolbar=no,location=no,directories=no,status=no,menubar=no,
stats += 'scrollbars=yes,resizable=yes'

MsgBox = window.open ("", "msgWindow", stats)

MsgBox.document.write("<head><title>查询结果 </title></head>");

MsgBox.document.write ("<BODY BGCOLOR=#ffffff TEXT=#000000 LINK=#000080
VLINK=#800040 ALINK=#FF0000><CENTER>查询结果 </CENTER>")

MsgBox.document.write ("For the keyword: "+Item+"<R>");

for (var i=1; i <= Keyword[0]; i++) {

if(Item = Keyword[i]) {

Found = true;

MsgBox.document.write (Descrip[i]+"<BR><A HREF="+Address[i]+>Click Here To
View</A><br>")

}

}

if(!Found)

MsgBox.document.write ("没有发现与该关键词有关的条目。 ")

MsgBox.document.write ("<H6>Enjoy it!<BR><A
HREF=http://java2000.126.com>http://java2000.126.com</A></H6>")

MsgBox.document.write ("<FORM class='pt9'><CENTER>")

MsgBox.document.write ("<INPUT type='button' value='关闭查询窗口 ' onClick =

```



```
'self.close()')>")  
  
MsgBox.document.write ("</CENTER></FORM>") }  
  
// -->  
  
</SCRIPT>
```

如下代码生成查询表单界面：

```
<form name="form1">  
  
<u>请输入查询关键词 :</u><br>  
  
<input type="text" name="searchfor" value="" size=20>  
  
<input type="button" value="查询 " onClick="checkDatabase()" name="button">  
  
<br>  
  
<!-- End Of File -->  
  
<font color="#FF0000">输入小写字符 </font>  
  
<p>  
  
</form>
```

站内搜索脚本 (六)

脚本说明：

第一步：把如下代码加入 <body>区域中

```
<script language = "JavaScript">  
    var key = "";  
    function makeEntry ()  
    {  
        this.Name="";
```

```

        this.URL = "";
        this.Desc = "";
        return this;
    }

    function makeArray(n)
    {
        this.length = n;
        for (var k = 1; k <= n; k++)
        {
            this[k] = "";
        }
        return this;
    }

    function makeLinks(size)
    {
        this.length = size;
        for (var r=1; r<= size; r++)
        {
            this[r] = new makeEntry();
            this[r].Name = namesArray[r];
            this[r].URL = urlsArray[r];
            this[r].Desc = descArray[r];
        }
        return this;
    }

```

```
var linksize=0;
```

```

namesArray = new makeArray(linksize);
urlsArray = new makeArray(linksize);
descArray = new makeArray(linksize);

```

```
var arraycount=0;
```

```
<!-- 以下是数据库部分，随意添加和删除 -->
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://nettrain.163.net/java/navigation/newscript.htm"
```

```
namesArray[arraycount] = "网际快车 Java脚本资源站 "
```

```

descArray[arraycount] = "java javascript applet games activex asp cgi databases
search media dw2 midi music menu html dhtml intranet internet scripts games perl
downloads password cookies free graphics freescrpts calander dw2 flash plugins 脚

```

本 密码保护页 脚本 免费资源 主页制作技巧 下载 搜索引擎 表单递交 插件 教学 动态
页面 图形图象 多媒体 "

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/desktop/adc120.html "  
namesArray[arraycount] = "Advanced Disk Catalog v1.20 beta 1"  
descArray[arraycount] = "Catalog your disks, folders and files"
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/tools/azpr.html "  
namesArray[arraycount] = "Advanced ZIP Password Recovery v0.91a"  
descArray[arraycount] = "Recover lost password for encrypted ZIP file"
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/games/AdvMith.html "  
namesArray[arraycount] = "Adventures With Chickens 2.01"  
descArray[arraycount] = "A Christian Windows-95 Arcade/Adventure Game"
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/games/INW58FUL.html "  
namesArray[arraycount] = "Alien Invasion 1.0"  
descArray[arraycount] = "Action Game for players with disabilities"
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/games/ayatze22.html "  
namesArray[arraycount] = "All In One Yahtzee v2.2"  
descArray[arraycount] = "Advanced yahtzee game with 5 variations."
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/games/atris_10.html "  
namesArray[arraycount] = "Alphatris v1.0"  
descArray[arraycount] = "Arcade style word game for windows 95"
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/inet/ang32setup.html "  
namesArray[arraycount] = "Amigo! v2.2 "  
descArray[arraycount] = "Internet Enabled, Free Form PIM"
```

```
arraycount += 1  
urlsArray[arraycount] = "http://www.win-shareware.com/games/32anbj12.html "  
namesArray[arraycount] = "Animated Blackjack v1.2"  
descArray[arraycount] = "A realistic game with great graphics.."
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/games/95ani12.html "  
namesArray[arraycount] = "Animated Slots v1.2"  
descArray[arraycount] = "A fun 5 wheel slot machine with great graphics.."
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/inet/pie184.html "  
namesArray[arraycount] = "ApplePie Pro HTML Editor 1.8.4"  
descArray[arraycount] = "Tag highlighting, JavaScript, Homepage Wizard"
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/tools/apackmk1.html "  
namesArray[arraycount] = "arclab Packager MK1 1.2.0.61"  
descArray[arraycount] = "Split one or more files into packages"
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/games/bbsetup.html "  
namesArray[arraycount] = "BrainsBreaker 2.1"  
descArray[arraycount] = "Create and play jigsaw puzzles in Windows95"
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/business/bs1sb.html "  
namesArray[arraycount] = "BS1 Small Business v1.1"  
descArray[arraycount] = "Bill customers, pay vendors, and manage accounting"
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/games/bubble97.html "  
namesArray[arraycount] = "Bubble Puzzle 97 v1.1g"  
descArray[arraycount] = "Bubble Puzzle 97 from Correg. Bust-a-move clone."
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/business/bfsnf216.html "  
namesArray[arraycount] = "Budget for Success Win95 v2.16"  
descArray[arraycount] = "Budget databases, mortgages, investment planner."
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/program/bc10.html "  
namesArray[arraycount] = "Bug Collector 1.0"  
descArray[arraycount] = "Manage feature requests and problem reports easier."
```

```
arraycount += 1
```

```
urlsArray[arraycount] = "http://www.win-shareware.com/games/bzzz_1_01.html "  
namesArray[arraycount] = "Bzzz! 1.01"  
descArray[arraycount] = "Win95 Game Control a frog to catch flies."
```

```
arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/inet/cachekill.html"
namesArray[arraycount] = "Cache Killer Pro 1.4"
descArray[arraycount] = "Clean up Internet Cache folders"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/business/cal9107b.html"
namesArray[arraycount] = "Calendar+ v1.07.00"
descArray[arraycount] = "Appointment scheduler and to do minder"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/business/cb32.html"
namesArray[arraycount] = "Calendar Builder v2.2b"
descArray[arraycount] = "Quickly and easily make your own custom calendars."

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/multi/cdm160.html"
namesArray[arraycount] = "CDMaster v1.6"
descArray[arraycount] = "CDPlayer w/Dubbing and Picture Attachment"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/inet/cgixpert.html"
namesArray[arraycount] = "CGI Expert 3.03"
descArray[arraycount] = "CGI/ISAPI/NSAPI component suite for Delphi and C++"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/tools/clox_5.html"
namesArray[arraycount] = "CLOX v1.3"
descArray[arraycount] = "Gives you world times on your desktop"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/desktop/snow_wi.html"
namesArray[arraycount] = "D2G Snow screen saver v1.00"
descArray[arraycount] = "Displays snow falling on a starry night w/snowman."

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/inet/dbQuickPage.html"
namesArray[arraycount] = "dbQuickPage 1.1"
descArray[arraycount] = "Database to HTML conversion for the Web."

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/misc/trim21.html"
namesArray[arraycount] = "Final Trim v2.1"
descArray[arraycount] = "A Win95 WMI Submarine Multimedia Publication"
```

```

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/inet/np25.html "
namesArray[arraycount] = "NetPopup 2.51"
descArray[arraycount] = "Messaging tool for Networks"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/inet/mong144.html "
namesArray[arraycount] = "NewsMonger Search Agent 1.44"
descArray[arraycount] = "Automatically monitor newsgroups for keywords"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/tools/notebk32.html "
namesArray[arraycount] = "Notebook v5.1"
descArray[arraycount] = "Large file text editor."

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/commun/nprsv15.html "
namesArray[arraycount] = "NotePager 1.5"
descArray[arraycount] = "An easy to use alphanumeric paging software"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/multi/ntrack10.html "
namesArray[arraycount] = "n-Track v1.5.2"
descArray[arraycount] = "An audio/MIDI shareware multitrack recorder"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/business/sd20.html "
namesArray[arraycount] = "SecurDesk! 2.0"
descArray[arraycount] = "Security environment and utilities for Win 95/NT"

arraycount += 1
urlsArray[arraycount] = "http://www.win-shareware.com/desktop/yapla16.html "
namesArray[arraycount] = "Yapla V1.6"
descArray[arraycount] = "YAPLA - Yet Another Program Launcher"

linksize = arraycount;

function searchLinks(links, keyword, hits, diw)
{
    var resultcount=0;
<!-- 如下是生成查询结果显示页面 外观自己可以修改相应代码即可! -->
    document.write('<HTML>');
    document.write('<BODY BGCOLOR=#000000 TEXT=white LINK=yellow VLINK=yellow

```

```

ALINK=yellow>');
    document.write('<CENTER><TABLE BORDER=3 CELLSPACING=0 CELLPADDING=3
BGCOLOR=\ "#ff0000\">TR<TD><CENTER><TABLE BORDER=1 CELLSPACING=0 CELLPADDING=3
BGCOLOR=\ "#42526B\">TR<TD>');
    document.write("<CENTER><font color=red>Results for keywords:
</font><font size=5 color=yellow>" +keyword + "</font></CENTER>");

document.write('</TD></TR></TABLE></CENTER></TD></TR></TABLE></CENTER><P>');
    document.write('<OL>');
    for (var q=1; q<=links.length; q++)
    {
        if (links[q].URL.toLowerCase().indexOf(dirw) != -1)
        {
            if (links[q].Desc.toLowerCase().indexOf(keyword) != -1)
            {
                resultcount += 1;
                if (resultcount > hits)
                {
                    break;
                }
            }
            else
            {
                document.write("<LI>");
                document.write("<a href=\"\" + links[q].URL + \"\">" +
links[q].Name + "</a>");
                document.write(" -" + links[q].Desc + "<br>");
                continue;
            }
        }
        if (links[q].Name.toLowerCase().indexOf(keyword) != -1)
        {
            resultcount += 1;
            if (resultcount > hits)
            {
                break;
            }
        }
        else
        {
            document.write("<LI>");
            document.write("<a href=\"\" + links[q].URL + \"\">" +
links[q].Name + "</a>");
            document.write(" -" + links[q].Desc + "<br>");
            continue;
        }
    }
}

```

```

    }
  }
}

}

</script>
<script>
<!-- 如下是表单合法性检查 主要是避免一些非法字符的查询! -->
function validate_fom()
{
  txt = document.fom.search.value;
  newindex = document.fom.nurhits.selectedIndex;
  dahits = document.fom.nurhits[newindex].value;
  newindexb = document.fom.whichdir.selectedIndex;
  dadir = document.fom.whichdir[newindexb].value;
  if (txt.indexOf(".") != -1){
    alert("Search is invalid! Contains a '.'"); return;}
  if (txt.indexOf(",") != -1){
    alert("Search is invalid! Contains a ','"); return;}
  if (txt.indexOf("@") != -1){
    alert("Search is invalid! Contains a '@'"); return;}
  if (txt.indexOf("!") != -1){
    alert("Search is invalid! Contains a '!'); return;}
  if (txt.indexOf("#") != -1){
    alert("Search is invalid! Contains a '#'"); return;}
  if (txt.indexOf("$") != -1){
    alert("Search is invalid! Contains a '$'"); return;}
  if (txt.indexOf("%") != -1){
    alert("Search is invalid! Contains a '%'"); return;}
  if (txt.indexOf("^") != -1){
    alert("Search is invalid! Contains a '^'"); return;}
  if (txt.indexOf("&") != -1){
    alert("Search is invalid! Contains a '&'"); return;}
  if (txt.indexOf("*") != -1){
    alert("Search is invalid! Contains a '*'"); return;}
  if (txt.indexOf("(") != -1){
    alert("Search is invalid! Contains a '('"); return;}
  if (txt.indexOf(")") != -1){
    alert("Search is invalid! Contains a ')'"); return;}
  if (txt.indexOf("[") != -1){
    alert("Search is invalid! Contains a '['"); return;}
  if (txt.indexOf("]") != -1){
    alert("Search is invalid! Contains a ']'"); return;}
}

```



```

if (txt.indexOf(";") != -1){
    alert("Search is invalid! Contains a ';'"); return;}
if (txt.indexOf(":") != -1){
    alert("Search is invalid! Contains a ':'"); return;}
if (txt.indexOf("<") != -1){
    alert("Search is invalid! Contains a '<'"); return;}
if (txt.indexOf(">") != -1){
    alert("Search is invalid! Contains a '>'"); return;}
if (txt.indexOf("?") != -1){
    alert("Search is invalid! Contains a '?'"); return;}
if (txt.indexOf("=") != -1){
    alert("Search is invalid! Contains a '='"); return;}
if (txt.indexOf("+") != -1){
    alert("Search is invalid! Contains a '+'"); return;}
else
    {
        jsi = new makeLinks(linksize);
        searchLinks(jsi, txt, dahits, dadir);
        document.write('</OL>');
        document.write('<font color=red>..... 查 询 结 果 结
束 .....</font><P>');
        document.write('<hr>');
        document.write('</body></html>');
    }
}
</script>

```

```

<table width=59% border=1 cellpadding=0 cellspacing=0 align=center valign=top>
<tr>
<td width=100% align=left bgcolor=#42526B height="232">
<form name="form">
<center>
<font color="yellow"> </font>
</center>
<center>
<font color="yellow">关键字 (小写字符, 支持中文): </font> <font
color="yellow"><b>
<input name="search" type=text size="20">
</b> </font>
</center>
<font color="yellow"><b><br>
</b> </font>
<center>

```

```

        <font color="#FFFF00">返回记录数 : </font> <font color="yellow"><font
face="Arial, Helvetica, sans-serif">
        <select name="numhits" size="1">
            <option selected value="25">25
            <option value="50">50
            <option value="75">75
            <option value="100">100
            <option value="150">150
            <option value="200">200
        </select>
        </font> 检 索 分 类 <font face="Arial, Helvetica, sans-serif">
</font><b><font size=3><font size=3>
        <select size=1 name="whichdir" class="pt9">
            <option selected value="http">ALL
            <option value="java">javaScript
            <option value="business">Business
            <option value="commun">Communications
            <option value="desktop">Desktop
            <option value="educate">Education
            <option value="games">Games
            <option value="graphics">Graphics
            <option value="hobby">Hobby
            <option value="homeuse">Home Use
            <option value="inet">Internet
            <option value="multi">Multimedia
            <option value="program">Programming
            <option value="tools">System Tools
        </select>
        </font></font> </b> </font>
</center>
<font color="yellow"><b><font size=3><font size=3> <br>
<br>
</font></font></b></font><font color=yellow size=3><font color=yellow
size=3>
<center>
    <font color="yellow"><b>
        <input type="button" name="submit" value="Search"
onClick="validate_form()">
        <input type="reset" name="reset" value=" Clear ">
        </b> </font>
    </center>
</font></font>
</form>

```

内部搜索脚本

脚本说明：

把如下代码加入 <body>区域中：

```
<script LANGUAGE="JavaScript1.1">

<!--

    var tname= new Array ();
// -----
// Enter DATA HERE !!
// -----
    tname[0]="Yahoo;www.yahoo.com";
    tname[1]="Infoseek;www.infoseek.com";
    tname[2]="Lycos;www.lycos.com";
    tname[3]="WebCrawler;www.webcrawler.com";
    tname[4]="Trovator;trovator.combios.es";
    tname[5]="BME;biwe.cesat.es";
    tname[6]="Ole;www.ole.es";
    tname[7]="Fantastico;www.fantastico.com";
    tname[8]="SQL;www.sol.es";
    tname[9]="donde;donde.uji.es";
    tname[10]="Telepolis;www.telepolis.com";
    tname[11]="El Cano;www.elcano.com";
// -----

function QuickSort (vec) {
// -----
// Algoritmo QuickSort 1.0 vs. JavaScript
// Guillermo BT
// -----
    orderedVec= Ordenar (vec,0,vec.length-1);
    return orderedVec
}

function Order (vec,iz,de) {
// -----
// Order (subfuncion de QuickSort)
// PARAMETERS (IN):
// *vec*      : vector to Order (Array object)
// *iz*       : lower bound (typically 0)
// *de*       : upper bound (typically array.length-1)
```

```

//
// OUT: returns the ordered vector (lexicographic order)
// -----
var i=iz;
var j=de;
var x= vec[Math.round((iz+de)/ 2)];
while (i<=j) {
  while (vec[i]<x) {i++};
  while (vec[j]>x) {j--};
  if (i<=j) {
    var w= vec[i];
    vec[i]= vec[j];
    vec[j]= w;
    i++;
    j--;
  }
}
if (iz<j) Order(vec, iz, j);
if (i<de) Order(vec, i, de);
return vec;
}

function Vector2URL (elem, separation) {
  var cArray= elem.split(separation);
  var url="<a href=http://"+cArray[1]+">";
  //alert (url);
  v.document.write ("<li>", cArray[0].fontcolor('red'));
  v.document.write (" has ", url, "web</a> page<br>");
}

function ShowEntries (vec) {
  v= window.open ('jv_sor2b.html', 'ventana',
'scrollbars=1,width=400,height=220');
  v.document.write ("<b>Available entries:</b><br><ul>");
  var i = 0;
  n=vec.length;
  if (n != 0) {
    while (i<n) {
      Vector2URL(vec[i], ';');
      i++
    }
  }
  v.document.write ("</ul>");
  v.document.write ("<form><input type=button value=Close

```

```
onClick='self.close()></form>");  
}
```

```
function Manage (vector) {  
  if (vector.length==0) {  
    alert ("No entries were found!");  
  }  
  else {  
    alert ("Let's do it!");  
    ShowEntries (vector);  
  }  
}
```

```
function Search (strng, vector) {  
  // -----  
  // Search 1.0-EN vs. JavaScript  
  // Guillermo BT  
  // -----  
  // IN:  
  // *strng* : string to search  
  // *vector* : Array object whose elements have the format:  
  //           "<name>;<web_page_URL>"  
  //  
  // OUT:  
  // returns an Array with those elements whose <name> field  
  // contains the *strng* string (substrings are allowed too)  
  //  
  // -----  
  var i=0; var j=0;  
  var array2= new Array();  
  while (i<(vector.length)) {  
    var cArray= vector[i].split(';');  
    nStr=new String (cArray[0]);  
    idx=nStr.toLowerCase().indexOf(strng);  
    if (idx != -1) {  
      array2[j]= vector[i];  
      j++  
    }  
    i++  
  }  
  return array2  
}  
  
// -->
```

```
</script>
```

```
<FORM name=fomSearch>
```

```
<table border=2 bordercolor=blue cellpadding=3 cellspacing=4>
```

```
<!-- FIRST ARROW -->
```

```
<tr bgcolor=yellow>
```

```
  <th colspan=2>Access to data:
```

```
<!-- SECOND ARROW -->
```

```
<tr align=center>
```

```
  <td bgcolor=lightgreen><b>order</b>
```

```
  <td>
```

```
    <input type=button value="Chronological" name=botMbstrar  
      onClick="ShowEntries(tname)">
```

```
    <input type=button value="Alphabetical" name=botOrder  
      onClick="tname.sort(); ShowEntries(tname)">
```

```
<!-- THIRD ARROW -->
```

```
<tr align=center>
```

```
  <td bgcolor=lightgreen><b>Search</b>
```

```
  <td>
```

```
    <input type=text size=20 name=who value=""><br>
```

```
    <input type=button value="similar words" name=botSearch  
      onClick="
```

```
      if (this.fom.who.value=='') {  
        alert ('You must enter something to search!')
```

```
      }
```

```
      else {
```

```
        valor=Search(this.fom.who.value.toLowerCase(), tname);
```

```
        Manage (valor)
```

```
      }">
```

```
</table>
```

```
</FORM>
```